

Package ‘REDCapR’

April 22, 2020

Title Interaction Between R and REDCap

Description Encapsulates functions to streamline calls from R to the REDCap API. REDCap (Research Electronic Data CAPture) is a web application for building and managing online surveys and databases developed at Vanderbilt University. The Application Programming Interface (API) offers an avenue to access and modify data programmatically, improving the capacity for literate and reproducible programming.

Version 0.11.0

URL <https://github.com/OuhscBbmc/REDCapR>, <http://ouhsc.edu/bbmc/>,
<http://project-redcap.org>

BugReports <https://github.com/OuhscBbmc/REDCapR/issues>

Depends R(>= 3.0.0)

Imports checkmate (>= 2.0), dplyr (>= 0.8.0), httr (>= 1.4.0),
magrittr (>= 1.5), methods, readr (>= 1.3.1), rlang (>= 0.4),
tibble (>= 2.0), tidyr (>= 1.0)

Suggests covr (>= 3.4), DBI (>= 1.1), kableExtra (>= 1.0), knitr (>= 1.18),
odbc (>= 1.1.1), rmarkdown (>= 2.0), sessioninfo (>= 1.1.1), testthat (>= 2.0)

License GPL-2

LazyData TRUE

VignetteBuilder knitr

Encoding UTF-8

RoxygenNote 7.1.0

NeedsCompilation no

Author Will Beasley [aut, cre] (<<https://orcid.org/0000-0002-5613-5006>>),
David Bard [ctb],
Thomas Wilson [ctb],
John J Aponte [ctb],
Rollie Parrish [ctb],
Benjamin Nutter [ctb],
Andrew Peters [ctb],

Hao Zhu [ctb] (<<https://orcid.org/0000-0002-3386-6076>>),
 Felix Torres [ctb],
 Philip Chase [ctb]

Maintainer Will Beasley <wibeasley@hotmail.com>

Repository CRAN

Date/Publication 2020-04-22 00:10:02 UTC

R topics documented:

REDCapR-package	3
collapse_vector	4
constant	4
create_batch_glossary	6
kernel_api	8
metadata_utilities	9
redcap_column_sanitize	11
redcap_download_file_oneshot	12
redcap_download_instrument	14
redcap_metadata_read	17
redcap_metadata_write	18
redcap_next_free_record_name	20
redcap_project	22
redcap_read	23
redcap_read_oneshot	27
redcap_read_oneshot_eav	30
redcap_survey_link_export_oneshot	33
redcap_upload_file_oneshot	35
redcap_users_export	37
redcap_variables	38
redcap_version	39
redcap_write	40
redcap_write_oneshot	42
replace_nas_with_explicit	44
retrieve_credential	45
sanitize_token	47
validate	48

Index

50

REDCapR-package *R utilities for interacting with a REDCap data system* <http://www.project-redcap.org/>

Description

Comprehensive documentation is also available at <https://ouhscbbmc.github.io/REDCapR/>.

Much of this package has been developed to support the needs of the following projects. We appreciate the support.

- *OUHSC CCAN Independent Evaluation of the State of Oklahoma Competitive Maternal, Infant, and Early Childhood Home Visiting (MIECHV) Project*. [HRSA/ACF D89MC23154](#). David Bard, PI, OUHSC; 2011-2015.
- *Independent Evaluation of the State of OK MIECHV Evidence Based Home Visitation Project*, NIH-sponsored collaboration with [OSDH](#). David Bard, PI, OUHSC; 2015-2017.
- *OSDH ParentPRO Pilot Evaluation*, federally-sponsored collaboration with [OSDH](#). David Bard, PI, OUHSC; 2015-2017.
- *Title IV-E Waiver Project*, [HRSA/MCHB](#)-sponsored collaboration with [OKDHS](#); David Bard, PI, OUHSC; 2014-2017.
- *Integrative Analysis of Longitudinal Studies of Aging (IALSA)*, sponsored by [NIH 5P01AG043362](#). Scott Hofer, PI, University of Victoria; Will Beasley, PI of site-award, OUHSC; 2013-2018.
- *Oklahoma Shared Clinical and Translational Resources*, sponsored by [NIH NIGMS; U54 GM104938](#). Judith A. James, PI, OUHSC; 2013-2018.
- Additional Institutional Support from OUHSC [Dept of Pediatrics](#); 2013-2017.

Note

The release version is available through [CRAN](#) by running `install.packages('REDCapR')`. The most recent development version is available through [GitHub](#) by running `remotes::install_github('OuhscBbmc/REDCapR')` (make sure [remotes](#) is already installed). If you're having trouble with the package, please install the development version. If this doesn't solve your problem, please create a [new issue](#), or email Will.

See REDCapR's advanced vignette for information and examples for overriding the default SSL options.

Examples

```
## Not run:
# Install/update REDCapR with the release version from CRAN.
install.packages('REDCapR')

# Install/update REDCapR with the development version from GitHub
# install.packages("remotes") # Uncomment if `remotes` isn't installed already.
remotes::install_github('OuhscBbmc/REDCapR')

## End(Not run)
```

collapse_vector	<i>Collapse a vector of values into a single string when necessary</i>
-----------------	--

Description

REDCap's API frequently specifies a series of values separated by commas. In the R world, it's easier to keep these values as separate elements in a vector. This functions squashes them together in a single character element (presumably right before the return value is passed to the API)

Usage

```
collapse_vector(elements, collapsed)
```

Arguments

elements	An array of values. Can be NULL. Required.
collapsed	A single character element, where the values are separated by commas. Can be NULL. Required.

Value

A single character element, where the values are separated by commas. Can be blank. (*i.e.*, "").

Author(s)

Will Beasley

Examples

```
library(REDCapR) #Load the package into the current R session.
REDCapR::collapse_vector(elements=NULL, collapsed=NULL)
REDCapR::collapse_vector(elements=letters, collapsed=NULL)
REDCapR::collapse_vector(elements=NULL, collapsed="4,5,6")
```

constant	<i>Collection of REDCap-specific constants</i>
----------	--

Description

Collection of constants defined by the REDCap developers.

Usage

```
constant(name)
```

Arguments

name Name of constant. Required character.

Details**Form Completeness**

The current constants relate to the 'complete' variable at the end of each form.

- form_incomplete: 0L (*i.e.*, an integer)
- form_unverified: 1L
- form_complete: 2L

Export Rights

See https://your-server/redcap/api/help/?content=exp_users.

- data_export_rights_no_access : 0L
- data_export_rights_deidentified : 1L
- data_export_rights_full : 2L

Form Rights

See https://your-server/redcap/api/help/?content=exp_users. The order of these digits may be unexpected.

- form_rights_no_access : 0L
- form_rights_readonly : 2L
- form_rights_edit_form : 1L
- form_rights_edit_survey : 3L

Access Rights

See https://your-server/redcap/api/help/?content=exp_users.

- access_no : 0L
- access_yes : 1L

To add more, please for and edit [constant.R](#) on GitHub and submit a pull request. For instructions, please see [Editing files in another user's repository # nolint](#) in the GitHub documentation.

Value

The constant's value. Currently all are single integers, but that could be expanded in the future.

Author(s)

Will Beasley

Examples

```

REDCapR::constant("form_incomplete") # Returns 0L
REDCapR::constant("form_unverified") # Returns 1L
REDCapR::constant("form_complete" ) # Returns 2L

REDCapR::constant("data_export_rights_no_access" ) # Returns 0L
REDCapR::constant("data_export_rights_deidentified") # Returns 1L
REDCapR::constant("data_export_rights_full" ) # Returns 2L

REDCapR::constant("form_rights_no_access") # Returns 0L
REDCapR::constant("form_rights_readonly" ) # Returns 2L --Notice the order
REDCapR::constant("form_rights_edit_form") # Returns 1L
REDCapR::constant("form_rights_edit_survey") # Returns 3L

REDCapR::constant("access_no" ) # Returns 0L
REDCapR::constant("access_yes") # Returns 1L

REDCapR::constant(c(
  "form_complete",
  "form_complete",
  "form_incomplete"
)) # Returns c(2L, 2L, 0L)
REDCapR::constant(c(
  "form_rights_no_access",
  "form_rights_readonly",
  "form_rights_edit_form",
  "form_rights_edit_survey"
)) # Returns c(0L, 2L, 1L, 3L)

constant_to_form_completion( c(0, 2, 1, 2, NA))
constant_to_form_rights( c(0, 2, 1, 2, NA))
constant_to_export_rights( c(0, 2, 1, 3, NA))
constant_to_access( c(0, 1, 1, 0, NA))

## Not run:
# The following line returns an error:
# Assertion on 'name' failed: Must be a subset of
# {'form_complete','form_incomplete','form_unverified'},
# but is {'bad-name'}.

REDCapR::constant("bad-name") # Returns an error

REDCapR::constant(c("form_complete", "bad-name")) # Returns an error

## End(Not run)

```

create_batch_glossary *Creates a dataset that help batching long-running read and writes*

Description

The function returns a `base::data.frame()` that other functions use to separate long-running read and write REDCap calls into multiple, smaller REDCap calls. The goal is to (1) reduce the chance of time-outs, and (2) introduce little breaks between batches so that the server isn't continually tied up.

Usage

```
create_batch_glossary(row_count, batch_size)
```

Arguments

<code>row_count</code>	The number records in the large dataset, before it's split.
<code>batch_size</code>	The maximum number of subject records a single batch should contain.

Details

This function can also assist splitting and saving a large `base::data.frame()` to disk as smaller files (such as a `.csv`). The padded columns allow the OS to sort the batches/files in sequential order.

Value

Currently, a `base::data.frame()` is returned with the following columns,

- `id`: an integer that uniquely identifies the batch, starting at 1.
- `start_index`: the index of the first row in the batch. `integer`.
- `stop_index`: the index of the last row in the batch. `integer`.
- `id_pretty`: a character representation of `id`, but padded with zeros.
- `start_index_pretty`: a character representation of `start_index`, but padded with zeros.
- `stop_index_pretty`: a character representation of `stop_index`, but padded with zeros.
- `label`: a character concatenation of `id_pretty`, `start_index_pretty`, and `stop_index_pretty`.

Author(s)

Will Beasley

See Also

See `redcap_read()` for a function that uses `create_batch_glossary`.

Examples

```
REDCapR::create_batch_glossary(100, 50)
REDCapR::create_batch_glossary(100, 25)
REDCapR::create_batch_glossary(100, 3)
d <- data.frame(
  record_id = 1:100,
  iv        = sample(x=4, size=100, replace=TRUE),
```

```

    dv          = rnorm(n=100)
  )
  REDCapR::create_batch_glossary(nrow(d), batch_size=40)

```

kernel_api

REDCapR internal function for calling the REDCap API

Description

This function is used by other functions to read and write values.

Usage

```

kernel_api(
  redcap_uri,
  post_body,
  config_options,
  encoding = "UTF-8",
  content_type = "text/csv"
)

```

Arguments

redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
post_body	List of contents expected by the REDCap API. Required.
config_options	A list of options to pass to POST method in the <code>httr</code> package. See the details below. Optional.
encoding	The encoding value passed to <code>httr::content()</code> . Defaults to 'UTF-8'.
content_type	The MIME value passed to <code>httr::content()</code> . Defaults to 'text/csv'.

Details

If the API call is unsuccessful, a value of `base::package_version("0.0.0")` will be returned. This ensures that the function will always return an object of class `base::package_version`. It guarantees the value can always be used in `utils::compareVersion()`.

Value

A `utils::packageVersion`.

Examples

```

config_options <- NULL
uri           <- "https://bbmc.ouhsc.edu/redcap/api/"
token        <- "9A81268476645C4E5F03428B8AC3AA7B"
post_body    <- list(
  token      = token,
  content    = 'project',
  format     = 'csv'
)
kernel <- REDCapR::kernel_api(uri, post_body, config_options)

# Consume the results in a few different ways.
kernel$result
read.csv(text=kernel$raw_text, stringsAsFactors=FALSE)
as.list(read.csv(text=kernel$raw_text, stringsAsFactors=FALSE))

```

metadata_utilities	<i>Manipulate and interpret the metadata of a REDCap project</i>
--------------------	--

Description

A collection of functions that assists handling REDCap project metadata.

Usage

```

regex_named_captures(pattern, text, perl = TRUE)

checkbox_choices(select_choices)

```

Arguments

pattern	The regular expression pattern. Required.
text	The text to apply the regex against. Required.
perl	Indicates if perl-compatible regexps should be used. Default is TRUE. Optional.
select_choices	The text containing the choices that should be parsed to determine the id and label values. Required.

Details

The `regex_named_captures()` function is general, and not specific to REDCap; it accepts any arbitrary regular expression. It returns a `base::data.frame()` with as many columns as named matches.

The `checkbox_choices()` function is specialized, and accommodates the "select choices" for a *single* REDCap checkbox group (where multiple boxes can be selected). It returns a `base::data.frame()` with two columns, one for the numeric id and one for the text label.

Value

Currently, a `base::data.frame()` is returned a row for each match, and a column for each *named* group within a match. For the `retrieve_checkbox_choices()` function, the columns will be.

- `id`: The numeric value assigned to each choice (in the data dictionary).
- `label`: The label assigned to each choice (in the data dictionary).

Author(s)

Will Beasley

References

See the official documentation for permissible characters in a checkbox label. *I'm bluffing here, because I don't know where this is located. If you know, please tell me.*

Examples

```
# The weird ranges are to avoid the pipe character;
# PCRE doesn't support character negation.
pattern_boxes <- "(?<=\\A| \\| )(?<id>\\d{1,}), (?<label>[\\x20-\\x7B\\x7D-\\x7E]{1,})(?= \\| |\\Z)"

choices_1 <- paste0(
  "1, American Indian/Alaska Native | ",
  "2, Asian | ",
  "3, Native Hawaiian or Other Pacific Islander | ",
  "4, Black or African American | ",
  "5, White | ",
  "6, Unknown / Not Reported")

# This calls the general function, and requires the correct regex pattern.
REDCapR::regex_named_captures(pattern=pattern_boxes, text=choices_1)

# This function is designed specifically for the checkbox values.
REDCapR::checkbox_choices(select_choices=choices_1)

## Not run:
uri <- "https://bbmc.ouhsc.edu/redcap/api/"
token <- "9A81268476645C4E5F03428B8AC3AA7B"

ds_metadata <- redcap_metadata_read(redcap_uri=uri, token=token)$data
choices_2 <- ds_metadata[ds_metadata$field_name=="race", "select_choices_or_calculations"]

REDCapR::regex_named_captures(pattern=pattern_boxes, text=choices_2)

## End(Not run)

path_3 <- system.file(package="REDCapR", "test-data/project-simple/simple-metadata.csv")
ds_metadata_3 <- read.csv(path_3, stringsAsFactors=FALSE)
choices_3 <- ds_metadata_3[ds_metadata_3$field_name=="race", "select_choices_or_calculations"]
REDCapR::regex_named_captures(pattern=pattern_boxes, text=choices_3)
```

`redcap_column_sanitize`*Sanitize to adhere to REDCap character encoding requirements*

Description

Replace non-ASCII characters with legal characters that won't cause problems when writing to a REDCap project.

Usage

```
redcap_column_sanitize(  
  d,  
  column_names = colnames(d),  
  encoding_initial = "latin1",  
  substitution_character = "?"  
)
```

Arguments

<code>d</code>	The <code>base::data.frame()</code> containing the dataset used to update the REDCap project. Required.
<code>column_names</code>	An array of character values indicating the names of the variables to sanitize. Optional.
<code>encoding_initial</code>	An array of character values indicating the names of the variables to sanitize. Optional.
<code>substitution_character</code>	The character value that replaces characters that were unable to be appropriately matched.

Details

Letters like an accented 'A' are replaced with a plain 'A'.

This is a thin wrapper around `base::iconv()`. The ASCII//TRANSLIT option does the actual transliteration work. As of R 3.1.0, the OSes use similar, but different, versions to convert the characters. Be aware of this in case you notice OS-dependent differences.

Value

A `base::data.frame()` with same columns, but whose character values have been sanitized.

Author(s)

Will Beasley

Examples

```
# Typical examples are not shown because they require non-ASCII encoding,
# which makes the package documentation less portable.

dirty <- data.frame(
  id      = 1:3,
  names   = c("Ekstr\xfb8m", "J\xfb6reskog", "bi\xbfdchen Z\xfbcrcher")
)

REDCapR::redcap_column_sanitize(dirty)
```

```
redcap_download_file_oneshot
```

Download a file from a REDCap project record

Description

This function uses REDCap's API to download a file.

Usage

```
redcap_download_file_oneshot(
  file_name = NULL,
  directory = NULL,
  overwrite = FALSE,
  redcap_uri,
  token,
  record,
  field,
  event = "",
  repeat_instrument = NULL,
  repeat_instance = NULL,
  verbose = TRUE,
  config_options = NULL
)
```

Arguments

<code>file_name</code>	The name of the file where the downloaded file is saved. If empty the original name of the file will be used and saved in the default directory. Optional.
<code>directory</code>	The directory where the file is saved. By default current directory. Optional
<code>overwrite</code>	Boolean value indicating if existing files should be overwritten. Optional
<code>redcap_uri</code>	The URI (uniform resource identifier) of the REDCap project. Required.
<code>token</code>	The user-specific string that serves as the password for a project. Required.
<code>record</code>	The record ID where the file is to be imported. Required

field	The name of the field where the file is saved in REDCap. Required
event	The name of the event where the file is saved in REDCap. Optional
repeat_instrument	The name of the instrument that is repeating for a given event. Optional
repeat_instance	(only for projects with repeating instruments/events) The repeat instance number of the repeating event (if longitudinal) or the repeating instrument (if classic or longitudinal). Default value is '1'. Optional
verbose	A boolean value indicating if messages should be printed to the R console during the operation. Optional.
config_options	A list of options to pass to <code>httr::POST()</code> method in the 'httr' package. See the details below. Optional.

Details

Currently, the function doesn't modify any variable types to conform to REDCap's supported variables. See `validate_for_write()` for a helper function that checks for some common important conflicts.

Value

Currently, a list is returned with the following elements,

- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The [http status code](#) of the operation.
- `outcome_message`: A human readable string indicating the operation's outcome.
- `records_affected_count`: The number of records inserted or updated.
- `affected_ids`: The subject IDs of the inserted or updated records.
- `elapsed_seconds`: The duration of the function.
- `raw_text`: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the `raw_text` is returned as an empty string to save RAM.
- `file_name`: The name of the file persisted to disk. This is useful if the name stored in REDCap is used (which is the default).

Author(s)

Will Beasley, John J. Aponte

References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

Examples

```

## Not run:
uri    <- "https://bbmc.ouhsc.edu/redcap/api/"
token  <- "D70F9ACD1EDD6F151C6EA78683944E98" #pid=213
record <- 1
field  <- "mugshot"
# event <- "" # only for longitudinal projects

result_1 <- REDCapR::redcap_download_file_oneshot(
  record      = record,
  field       = field,
  redcap_uri  = uri,
  token       = token
)
base::unlink("mugshot-1.jpg")

(full_name <- base::tempfile(pattern="mugshot", fileext=".jpg"))
result_2 <- REDCapR::redcap_download_file_oneshot(
  file_name   = full_name,
  record      = record,
  field       = field,
  redcap_uri  = uri,
  token       = token
)
base::unlink(full_name)

(relative_name <- "ssss.jpg")
result_3 <- REDCapR::redcap_download_file_oneshot(
  file_name   = relative_name,
  record      = record,
  field       = field,
  redcap_uri  = uri,
  token       = token
)
base::unlink(relative_name)

## End(Not run)

```

redcap_download_instrument

Download REDCap Instruments

Description

Download instruments as a pdf, with or without responses.

Usage

```
redcap_download_instrument(
```

```

file_name = NULL,
directory = NULL,
overwrite = FALSE,
redcap_uri,
token,
record = character(0),
instrument = "",
event = "",
verbose = TRUE,
config_options = NULL
)

```

Arguments

file_name	The name of the file where the downloaded pdf is saved. Optional.
directory	The directory where the file is saved. By default current directory. Optional.
overwrite	Boolean value indicating if existing files should be overwritten. Optional.
redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
record	The record ID of the instrument(s). If empty, the responses are blank. Optional.
instrument	The instrument(s) to download. If empty, all instruments are returned. Optional.
event	The unique event name. For a longitudinal project, if record is not blank and event is blank, it will return data for all events from that record. If record is not blank and event is not blank, it will return data only for the specified event from that record. Optional.
verbose	A boolean value indicating if messages should be printed to the R console during the operation. Optional.
config_options	A list of options to pass to <code>httr::POST()</code> method in the 'httr' package. See the details below. Optional.

Details

Currently, the function doesn't modify any variable types to conform to REDCap's supported variables. See `validate_for_write()` for a helper function that checks for some common important conflicts.

Value

Currently, a list is returned with the following elements,

- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The [http status code](#) of the operation.
- `outcome_message`: A human readable string indicating the operation's outcome.
- `record_id`: The `record_id` of the instrument.
- `elapsed_seconds`: The duration of the function.

- `raw_text`: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the `raw_text` is returned as an empty string to save RAM.
- `file_name`: The name of the file persisted to disk. This is useful if the name stored in REDCap is used (which is the default).

Author(s)

Will Beasley

References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

Examples

```
## Not run:
uri    <- "https://bbmc.ouhsc.edu/redcap/api/"
token  <- "D70F9ACD1EDD6F151C6EA78683944E98" #pid=213
# event <- "" # only for longitudinal projects

(full_name <- base::temp(pattern="instruments-all-records-all", fileext=".pdf"))
result_1  <- REDCapR::redcap_download_instrument(
  file_name    = full_name,
  redcap_uri   = uri,
  token        = token
)
base::unlink(full_name)

(full_name <- base::tempfile(pattern="instruments-all-record-1-", fileext=".pdf"))
result_2  <- REDCapR::redcap_download_instrument(
  record       = 5,
  file_name    = full_name,
  redcap_uri   = uri,
  token        = token
)
base::unlink(full_name)
(full_name <- base::tempfile(pattern="instrument-1-record-1-", fileext=".pdf"))
result_3  <- REDCapR::redcap_download_instrument(
  record       = 5,
  instrument   = "health",
  file_name    = full_name,
  redcap_uri   = uri,
  token        = token
)
base::unlink(full_name)

## End(Not run)
```

redcap_metadata_read *Export the metadata of a REDCap project*

Description

Export the metadata (as a data dictionary) of a REDCap project as a `base::data.frame()`. Each row in the data dictionary corresponds to one field in the project's dataset.

Usage

```
redcap_metadata_read(
  redcap_uri,
  token,
  forms = NULL,
  forms_collapsed = "",
  fields = NULL,
  fields_collapsed = "",
  verbose = TRUE,
  config_options = NULL
)
```

Arguments

redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
forms	An array, where each element corresponds to the REDCap form of the desired fields. Optional.
forms_collapsed	A single string, where the desired forms are separated by commas. Optional.
fields	An array, where each element corresponds to a desired project field. Optional.
fields_collapsed	A single string, where the desired field names are separated by commas. Optional.
verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information (<i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
config_options	A list of options to pass to POST method in the <code>httr</code> package. See the details in <code>redcap_read_oneshot()</code> . Optional.

Details

Specifically, it internally uses multiple calls to `redcap_read_oneshot()` to select and return data. Initially, only primary key is queried through the REDCap API. The long list is then subsetted into partitions, whose sizes are determined by the `batch_size` parameter. REDCap is then queried for all variables of the subset's subjects. This is repeated for each subset, before returning a unified `base::data.frame()`.

The function allows a delay between calls, which allows the server to attend to other users' requests.

Value

Currently, a list is returned with the following elements:

- `data`: An R `base::data.frame()` of the desired records and columns.
- `success`: A boolean value indicating if the operation was apparently successful.
- `status_codes`: A collection of [http status codes](#), separated by semicolons. There is one code for each batch attempted.
- `outcome_messages`: A collection of human readable strings indicating the operations' semicolons. There is one code for each batch attempted. In an unsuccessful operation, it should contain diagnostic information.
- `forms_collapsed`: The desired records IDs, collapsed into a single string, separated by commas.
- `fields_collapsed`: The desired field names, collapsed into a single string, separated by commas.
- `elapsed_seconds`: The duration of the function.

Author(s)

Will Beasley

References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

Examples

```
## Not run:
uri   <- "https://bbmc.ouhsc.edu/redcap/api/"
token <- "9A81268476645C4E5F03428B8AC3AA7B"
REDCapR::redcap_metadata_read(redcap_uri=uri, token=token)

## End(Not run)
```

`redcap_metadata_write` *Import metadata of a REDCap project*

Description

Import metadata (*i.e.*, data dictionary) into a project. Because of this method's destructive nature, it works for only projects in Development status.

Usage

```
redcap_metadata_write(  
  ds,  
  redcap_uri,  
  token,  
  verbose = TRUE,  
  config_options = NULL  
)
```

Arguments

ds	The <code>base::data.frame()</code> to be imported into the REDCap project. Required.
redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information (<i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
config_options	A list of options to pass to <code>httr::POST()</code> method in the 'httr' package. See the details in <code>redcap_read_oneshot()</code> Optional.

Value

Currently, a list is returned with the following elements:

- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The `http status code` of the operation.
- `outcome_message`: A human readable string indicating the operation's outcome.
- `field_count`: Number of fields imported.
- `elapsed_seconds`: The duration of the function.
- `raw_text`: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the `raw_text` is returned as an empty string to save RAM.

Author(s)

Will Beasley

References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki. If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

Examples

```
## Not run:
# Please don't run this example without changing the token to
# point to your server. It could interfere with our testing suite.
uri      <- "https://bbmc.ouhsc.edu/redcap/api/"
token    <- "457C24AB91B7FCF5B1A7DA67E70E24C7"

# Read in the dictionary in R's memory from a csv file.
ds_to_write <-
  readr::read_csv(
    file = system.file(
      "test-data/project-simple/simple-metadata.csv",
      package = "REDCapR"
    ),
    col_types = readr::cols(.default = readr::col_character())
  )
ds_to_write

# Import the dictionary into the REDCap project
REDCapR::redcap_metadata_write(
  ds      = ds_to_write,
  redcap_uri = uri,
  token    = token
)

## End(Not run)
```

redcap_next_free_record_name

Determine free available record ID

Description

Determines the next available record ID.

Usage

```
redcap_next_free_record_name(
  redcap_uri,
  token,
  verbose = TRUE,
  config_options = NULL
)
```

Arguments

redcap_uri The URI (uniform resource identifier) of the REDCap project. Required.

token	The user-specific string that serves as the password for a project. Required.
verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information (<i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
config_options	A list of options to pass to POST method in the <code>httr</code> package. See the details below. Optional.

Details

If the API call is unsuccessful, a value of `character(0)` will be returned (*i.e.*, an empty vector). This ensures that a the function will always return an object of class `base::character`.

Value

a `base::character` vector of either length 1 (if successful) or length 0 (if not successful).

Note

Documentation in REDCap 8.4.0

To be used by projects with record auto-numbering enabled, this method exports the next potential record ID for a project. It generates the next record name by determining the current maximum numerical record ID and then incrementing it by one.

Note: This method does not create a new record, but merely determines what the next record name would be.

If using Data Access Groups (DAGs) in the project, this method accounts for the special formatting of the record name for users in DAGs (*e.g.*, DAG-ID); in this case, it only assigns the next value for ID for all numbers inside a DAG. For example, if a DAG has a corresponding DAG number of 223 wherein records 223-1 and 223-2 already exist, then the next record will be 223-3 if the API user belongs to the DAG that has DAG number 223. (The DAG number is auto-assigned by REDCap for each DAG when the DAG is first created.)

When generating a new record name in a DAG, the method considers all records in the entire project when determining the maximum record ID, including those that might have been originally created in that DAG but then later reassigned to another DAG.

Note: This method functions the same even for projects that do not have record auto-numbering enabled.

Examples

```
uri      <- "https://bbmc.ouhsc.edu/redcap/api/"
token    <- "9A81268476645C4E5F03428B8AC3AA7B"
# Returns 6
REDCapR::redcap_next_free_record_name(redcap_uri = uri, token = token)
```

redcap_project	<i>A Reference Class to make later calls to REDCap more convenient</i>
----------------	--

Description

This Reference Class represents a REDCap project. Once some values are set that are specific to a REDCap project (such as the URI and token), later calls are less verbose (such as reading and writing data).

Fields

`redcap_uri` The URI (uniform resource identifier) of the REDCap project. Required.
`token` token The user-specific string that serves as the password for a project. Required.

Methods

`read(batch_size = 100L, interbatch_delay = 0, records = NULL, records_collapsed = "", fields = NULL, field`
 Exports records from a REDCap project.
`write(ds_to_write, batch_size = 100L, interbatch_delay = 0, continue_on_error = FALSE, verbose = TRUE, co`
 Imports records to a REDCap project.

Examples

```
uri    <- "https://bbmc.ouhsc.edu/redcap/api/"
token  <- "D70F9ACD1EDD6F151C6EA78683944E98"
## Not run:
project <- REDCapR::redcap_project$new(redcap_uri=uri, token=token)
ds_all  <- project$read()

# Demonstrate how repeated calls are more concise when the token and
# url aren't always passed.
ds_skinny <- project$read(fields=c("record_id", "sex", "height"))$data

ids_of_males    <- ds_skinny$record_id[ds_skinny$sex==1]
ids_of_shorties <- ds_skinny$record_id[ds_skinny$height < 40]

ds_males        <- project$read(records=ids_of_males, batch_size=2)$data
ds_shorties     <- project$read(records=ids_of_shorties)$data

#Switch the Genders
sex_original    <- ds_skinny$sex
ds_skinny$sex   <- (1 - ds_skinny$sex)
project$write(ds_skinny)

#Switch the Genders back
ds_skinny$sex   <- sex_original
project$write(ds_skinny)

## End(Not run)
```

redcap_read	<i>Read records from a REDCap project in subsets, and stacks them together before returning a dataset</i>
-------------	---

Description

From an external perspective, this function is similar to `redcap_read_oneshot()`. The internals differ in that `redcap_read` retrieves subsets of the data, and then combines them before returning (among other objects) a single `base::data.frame()`. This function can be more appropriate than `redcap_read_oneshot()` when returning large datasets that could tie up the server.

Usage

```
redcap_read(
  batch_size = 100L,
  interbatch_delay = 0.5,
  continue_on_error = FALSE,
  redcap_uri,
  token,
  records = NULL,
  records_collapsed = "",
  fields = NULL,
  fields_collapsed = "",
  forms = NULL,
  forms_collapsed = "",
  events = NULL,
  events_collapsed = "",
  raw_or_label = "raw",
  raw_or_label_headers = "raw",
  export_checkbox_label = FALSE,
  export_survey_fields = FALSE,
  export_data_access_groups = FALSE,
  filter_logic = "",
  col_types = NULL,
  guess_type = TRUE,
  guess_max = NULL,
  verbose = TRUE,
  config_options = NULL,
  id_position = 1L
)
```

Arguments

`batch_size` The maximum number of subject records a single batch should contain. The default is 100.

`interbatch_delay` The number of seconds the function will wait before requesting a new subset from REDCap. The default is 0.5 seconds.

<code>continue_on_error</code>	If an error occurs while reading, should records in subsequent batches be attempted. The default is <code>FALSE</code> , which prevents subsequent batches from running. Required.
<code>redcap_uri</code>	The URI (uniform resource identifier) of the REDCap project. Required.
<code>token</code>	The user-specific string that serves as the password for a project. Required.
<code>records</code>	An array, where each element corresponds to the ID of a desired record. Optional.
<code>records_collapsed</code>	A single string, where the desired ID values are separated by commas. Optional.
<code>fields</code>	An array, where each element corresponds to a desired project field. Optional.
<code>fields_collapsed</code>	A single string, where the desired field names are separated by commas. Optional.
<code>forms</code>	An array, where each element corresponds to a desired project form. Optional.
<code>forms_collapsed</code>	A single string, where the desired form names are separated by commas. Optional.
<code>events</code>	An array, where each element corresponds to a desired project event. Optional.
<code>events_collapsed</code>	A single string, where the desired event names are separated by commas. Optional.
<code>raw_or_label</code>	A string (either <code>'raw'</code> or <code>'label'</code>) that specifies whether to export the raw coded values or the labels for the options of multiple choice fields. Default is <code>'raw'</code> .
<code>raw_or_label_headers</code>	A string (either <code>'raw'</code> or <code>'label'</code>) that specifies for the CSV headers whether to export the variable/field names (<code>raw</code>) or the field labels (<code>label</code>). Default is <code>'raw'</code> .
<code>export_checkbox_label</code>	specifies the format of checkbox field values specifically when exporting the data as labels. If <code>raw_or_label</code> is <code>'label'</code> and <code>export_checkbox_label</code> is <code>TRUE</code> , the values will be the text displayed to the users. Otherwise, the values will be <code>0/1</code> .
<code>export_survey_fields</code>	A boolean that specifies whether to export the survey identifier field (e.g., <code>'redcap_survey_identifier'</code>) or survey timestamp fields (e.g., <code>instrument+'_timestamp'</code>).
<code>export_data_access_groups</code>	A boolean value that specifies whether or not to export the <code>redcap_data_access_group</code> field when data access groups are utilized in the project. Default is <code>FALSE</code> . See the details below.
<code>filter_logic</code>	String of logic text (e.g., <code>[gender] = 'male'</code>) for filtering the data to be returned by this API method, in which the API will only return the records (or record-events, if a longitudinal project) where the logic evaluates as <code>TRUE</code> . An blank/empty string returns all records.
<code>col_types</code>	A <code>readr::cols()</code> object passed internally to <code>readr::read_csv()</code> . Optional.

guess_type	A boolean value indicating if all columns should be returned as character. If true, <code>readr::read_csv()</code> guesses the intended data type for each column.
guess_max	Deprecated.
verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information (<i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
config_options	A list of options to pass to POST method in the <code>httr</code> package. See the details in <code>redcap_read_oneshot()</code> Optional.
id_position	The column position of the variable that unique identifies the subject (typically <code>record_id</code>). This defaults to the first variable in the dataset.

Details

Specifically, it internally uses multiple calls to `redcap_read_oneshot()` to select and return data. Initially, only the primary key is queried through the REDCap API. The long list is then subsetted into batches, whose sizes are determined by the `batch_size` parameter. REDCap is then queried for all variables of the subset's subjects. This is repeated for each subset, before returning a unified `base::data.frame()`.

The function allows a delay between calls, which allows the server to attend to other users' requests (such as the users entering data in a browser). In other words, a delay between batches does not bog down the webserver when exporting/importing a large dataset.

A second benefit is less RAM is required on the webserver. Because each batch is smaller than the entire dataset, the webserver tackles more manageably sized objects in memory. Consider batching if you encounter the error

```
ERROR: REDCap ran out of server memory. The request cannot be processed.  
Please try importing/exporting a smaller amount of data.
```

For `redcap_read()` to function properly, the user must have Export permissions for the 'Full Data Set'. Users with only 'De-Identified' export privileges can still use `redcap_read_oneshot`. To grant the appropriate permissions:

- go to 'User Rights' in the REDCap project site,
- select the desired user, and then select 'Edit User Privileges',
- in the 'Data Exports' radio buttons, select 'Full Data Set'.

Value

Currently, a list is returned with the following elements:

- `data`: An R `base::data.frame()` of the desired records and columns.
- `success`: A boolean value indicating if the operation was apparently successful.
- `status_codes`: A collection of [http status codes](#), separated by semicolons. There is one code for each batch attempted.
- `outcome_messages`: A collection of human readable strings indicating the operations' semicolons. There is one code for each batch attempted. In an unsuccessful operation, it should contain diagnostic information.

- `records_collapsed`: The desired records IDs, collapsed into a single string, separated by commas.
- `fields_collapsed`: The desired field names, collapsed into a single string, separated by commas.
- `filter_logic`: The filter statement passed as an argument.
- `elapsed_seconds`: The duration of the function.

Author(s)

Will Beasley

References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

Examples

```
## Not run:
uri    <- "https://bbmc.ouhsc.edu/redcap/api/"
token  <- "9A81268476645C4E5F03428B8AC3AA7B"
REDCapR::redcap_read(batch_size=2, redcap_uri=uri, token=token)$data

# Specify the column types.
col_types <- readr::cols(
  record_id = readr::col_integer(),
  race___1  = readr::col_logical(),
  race___2  = readr::col_logical(),
  race___3  = readr::col_logical(),
  race___4  = readr::col_logical(),
  race___5  = readr::col_logical(),
  race___6  = readr::col_logical()
)
REDCapR::redcap_read(
  redcap_uri = uri,
  token      = token,
  col_types  = col_types,
  batch_size = 2
)$data

## End(Not run)
```

redcap_read_oneshot *Read/Export records from a REDCap project*

Description

This function uses REDCap's API to select and return data.

Usage

```
redcap_read_oneshot(  
    redcap_uri,  
    token,  
    records = NULL,  
    records_collapsed = "",  
    fields = NULL,  
    fields_collapsed = "",  
    forms = NULL,  
    forms_collapsed = "",  
    events = NULL,  
    events_collapsed = "",  
    raw_or_label = "raw",  
    raw_or_label_headers = "raw",  
    export_checkbox_label = FALSE,  
    export_survey_fields = FALSE,  
    export_data_access_groups = FALSE,  
    filter_logic = "",  
    col_types = NULL,  
    guess_type = TRUE,  
    guess_max = 1000L,  
    verbose = TRUE,  
    config_options = NULL  
)
```

Arguments

redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
records	An array, where each element corresponds to the ID of a desired record. Optional.
records_collapsed	A single string, where the desired ID values are separated by commas. Optional.
fields	An array, where each element corresponds to a desired project field. Optional.
fields_collapsed	A single string, where the desired field names are separated by commas. Optional.
forms	An array, where each element corresponds to a desired project form. Optional.

forms_collapsed	A single string, where the desired form names are separated by commas. Optional.
events	An array, where each element corresponds to a desired project event. Optional.
events_collapsed	A single string, where the desired event names are separated by commas. Optional.
raw_or_label	A string (either 'raw' or 'label') that specifies whether to export the raw coded values or the labels for the options of multiple choice fields. Default is 'raw'.
raw_or_label_headers	A string (either 'raw' or 'label' that specifies for the CSV headers whether to export the variable/field names (raw) or the field labels (label). Default is 'raw'.
export_checkbox_label	specifies the format of checkbox field values specifically when exporting the data as labels. If raw_or_label is 'label' and export_checkbox_label is TRUE, the values will be the text displayed to the users. Otherwise, the values will be 0/1.
export_survey_fields	A boolean that specifies whether to export the survey identifier field (e.g., 'redcap_survey_identifier') or survey timestamp fields (e.g., instrument+'_timestamp')
export_data_access_groups	A boolean value that specifies whether or not to export the redcap_data_access_group field when data access groups are utilized in the project. Default is FALSE. See the details below.
filter_logic	String of logic text (e.g., [gender] = 'male') for filtering the data to be returned by this API method, in which the API will only return the records (or record-events, if a longitudinal project) where the logic evaluates as TRUE. An blank/empty string returns all records.
col_types	A <code>readr::cols()</code> object passed internally to <code>readr::read_csv()</code> . Optional.
guess_type	A boolean value indicating if all columns should be returned as character. If false, <code>readr::read_csv()</code> guesses the intended data type for each column. Ignored if col_types is not null.
guess_max	A positive integer passed to <code>readr::read_csv()</code> that specifies the maximum number of records to use for guessing column types.
verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information (e.g. PHI), so turn this off if the output might be visible somewhere public. Optional.
config_options	A list of options to pass to POST method in the <code>httr</code> package. See the details below. Optional.

Details

The full list of configuration options accepted by the `httr` package is viewable by executing `httr::httr_options()`. The `httr` package and documentation is available at <https://cran.r-project.org/package=httr>.

If you do not pass in this `export_data_access_groups` value, it will default to `FALSE`. The following is from the API help page for version 5.2.3: This flag is only viable if the user whose token is being used to make the API request is *not* in a data access group. If the user is in a group, then this flag will revert to its default value.

Value

Currently, a list is returned with the following elements:

- `data`: An R `base::data.frame()` of the desired records and columns.
- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The `http status code` of the operation.
- `outcome_message`: A human readable string indicating the operation's outcome.
- `records_collapsed`: The desired records IDs, collapsed into a single string, separated by commas.
- `fields_collapsed`: The desired field names, collapsed into a single string, separated by commas.
- `filter_logic`: The filter statement passed as an argument.
- `elapsed_seconds`: The duration of the function.
- `raw_text`: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the `raw_text` is returned as an empty string to save RAM.

Author(s)

Will Beasley

References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

Examples

```
## Not run:
uri      <- "https://bbmc.ouhsc.edu/redcap/api/"
token    <- "9A81268476645C4E5F03428B8AC3AA7B"

#Return all records and all variables.
ds <- REDCapR::redcap_read_oneShot(redcap_uri=uri, token=token)$data

#Return only records with IDs of 1 and 3
desired_records_v1 <- c(1, 3)
ds_some_rows_v1 <- REDCapR::redcap_read_oneShot(
  redcap_uri = uri,
  token      = token,
  records    = desired_records_v1
```

```

)$data

#Return only the fields record_id, name_first, and age
desired_fields_v1 <- c("record_id", "name_first", "age")
ds_some_fields_v1 <- REDCapR::redcap_read_oneshot(
  redcap_uri = uri,
  token      = token,
  fields     = desired_fields_v1
)$data

# Specify the column types.
col_types <- readr::cols(
  record_id = readr::col_integer(),
  race___1  = readr::col_logical(),
  race___2  = readr::col_logical(),
  race___3  = readr::col_logical(),
  race___4  = readr::col_logical(),
  race___5  = readr::col_logical(),
  race___6  = readr::col_logical()
)
ds_col_types <- REDCapR::redcap_read_oneshot(
  redcap_uri = uri,
  token      = token,
  col_types  = col_types
)$data

## End(Not run)

```

redcap_read_oneshot_eav

Read/Export records from a REDCap project –still in development

Description

This function uses REDCap's API to select and return data. This function is still in development.

Usage

```

redcap_read_oneshot_eav(
  redcap_uri,
  token,
  records = NULL,
  records_collapsed = "",
  fields = NULL,
  fields_collapsed = "",
  forms = NULL,
  forms_collapsed = "",

```

```

events = NULL,
events_collapsed = "",
raw_or_label = "raw",
raw_or_label_headers = "raw",
export_data_access_groups = FALSE,
filter_logic = "",
verbose = TRUE,
config_options = NULL
)

```

Arguments

redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
records	An array, where each element corresponds to the ID of a desired record. Optional.
records_collapsed	A single string, where the desired ID values are separated by commas. Optional.
fields	An array, where each element corresponds to a desired project field. Optional.
fields_collapsed	A single string, where the desired field names are separated by commas. Optional.
forms	An array, where each element corresponds to a desired project field. Optional.
forms_collapsed	A single string, where the desired form names are separated by commas. Optional.
events	An array, where each element corresponds to a desired project event. Optional.
events_collapsed	A single string, where the desired event names are separated by commas. Optional.
raw_or_label	A string (either 'raw' or 'label' that specifies whether to export the raw coded values or the labels for the options of multiple choice fields. Default is 'raw'.
raw_or_label_headers	A string (either 'raw' or 'label' that specifies for the CSV headers whether to export the variable/field names (raw) or the field labels (label). Default is 'raw'.
export_data_access_groups	A boolean value that specifies whether or not to export the redcap_data_access_group field when data access groups are utilized in the project. Default is FALSE. See the details below.
filter_logic	String of logic text (e.g., [gender] = 'male') for filtering the data to be returned by this API method, in which the API will only return the records (or record-events, if a longitudinal project) where the logic evaluates as TRUE. An blank/empty string returns all records.
verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information (e.g. PHI), so turn this off if the output might be visible somewhere public. Optional.

`config_options` A list of options to pass to POST method in the `httr` package. See the details below. Optional.

Details

The full list of configuration options accepted by the `httr` package is viewable by executing `httr::httr_options()`. The `httr` package and documentation is available at <https://cran.r-project.org/package=httr>.

If you do not pass in this `export_data_access_groups` value, it will default to `FALSE`. The following is from the API help page for version 5.2.3: This flag is only viable if the user whose token is being used to make the API request is *not* in a data access group. If the user is in a group, then this flag will revert to its default value.

As of REDCap 6.14.3, this field is not exported in the EAV API call.

Value

Currently, a list is returned with the following elements:

- `data`: An R `base::data.frame()` of the desired records and columns.
- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The `http status code` of the operation.
- `outcome_message`: A human readable string indicating the operation's outcome.
- `records_collapsed`: The desired records IDs, collapsed into a single string, separated by commas.
- `fields_collapsed`: The desired field names, collapsed into a single string, separated by commas.
- `filter_logic`: The filter statement passed as an argument.
- `elapsed_seconds`: The duration of the function.
- `raw_text`: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the `raw_text` is returned as an empty string to save RAM.

Author(s)

Will Beasley

References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

Examples

```
## Not run:
uri    <- "https://bbmc.ouhsc.edu/redcap/api/"
token  <- "9A81268476645C4E5F03428B8AC3AA7B"
```



```

#Return all records and all variables.
ds <- REDCapR::redcap_read_oneshot_eav(redcap_uri=uri, token=token)$data

#Return only records with IDs of 1 and 3
desired_records_v1 <- c(1, 3)
ds_some_rows_v1 <- REDCapR::redcap_read_oneshot_eav(
  redcap_uri = uri,
  token      = token,
  records    = desired_records_v1
)$data

#Return only the fields record_id, name_first, and age
desired_fields_v1 <- c("record_id", "name_first", "age")
ds_some_fields_v1 <- redcap_read_oneshot_eav(
  redcap_uri = uri,
  token      = token,
  fields     = desired_fields_v1
)$data

## End(Not run)

```

redcap_survey_link_export_oneshot

Download a file from a REDCap project record

Description

This function uses REDCap's API to download a file.

Usage

```

redcap_survey_link_export_oneshot(
  redcap_uri,
  token,
  record,
  instrument,
  event = "",
  verbose = TRUE,
  config_options = NULL
)

```

Arguments

redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
record	The record ID where the file is to be imported. Required
instrument	The name of the instrument associated with the survey link. Required
event	The name of the event where the file is saved in REDCap. Optional

verbose	A boolean value indicating if messages should be printed to the R console during the operation. Optional.
config_options	A list of options to pass to <code>httr::POST()</code> method in the 'httr' package. See the details below. Optional.

Details

Currently, the function doesn't modify any variable types to conform to REDCap's supported variables. See `validate_for_write()` for a helper function that checks for some common important conflicts.

Permissions Required To use this method, you must have API Export privileges in the project. (As stated in the 9.0.0 documentation.)

Value

Currently, a list is returned with the following elements,

- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The [http status code](#) of the operation.
- `outcome_message`: A human readable string indicating the operation's outcome.
- `records_affected_count`: The number of records inserted or updated.
- `affected_ids`: The subject IDs of the inserted or updated records.
- `elapsed_seconds`: The duration of the function.
- `raw_text`: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the `raw_text` is returned as an empty string to save RAM.
- `file_name`: The name of the file persisted to disk. This is useful if the name stored in REDCap is used (which is the default).

Author(s)

Will Beasley

References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

Examples

```
## Not run:
uri    <- "https://bbmc.ouhsc.edu/redcap/api/"
token  <- "8FA9A6BDAE2C0B5DD3CB472DD8E8918C" #pid=817
record <- 1
instrument <- "participant_morale_questionnaire"
# event <- "" # only for longitudinal projects
```

```

result <- REDCapR::redcap_survey_link_export_one_shot(
  record      = record,
  instrument  = instrument,
  redcap_uri  = uri,
  token       = token
)
result$survey_link

## End(Not run)

```

redcap_upload_file_one_shot

Upload a file into to a REDCap project record

Description

This function uses REDCap's API to upload a file.

Usage

```

redcap_upload_file_one_shot(
  file_name,
  record,
  redcap_uri,
  token,
  field,
  event = "",
  verbose = TRUE,
  config_options = NULL
)

```

Arguments

file_name	The name of the relative or full file to be uploaded into the REDCap project. Required.
record	The record ID where the file is to be imported. Required
redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
field	The name of the field where the file is saved in REDCap. Required
event	The name of the event where the file is saved in REDCap. Optional
verbose	A boolean value indicating if messages should be printed to the R console during the operation. Optional.
config_options	A list of options to pass to POST method in the httr package. See the details below. Optional.

Details

Currently, the function doesn't modify any variable types to conform to REDCap's supported variables. See `validate_for_write()` for a helper function that checks for some common important conflicts.

Value

Currently, a list is returned with the following elements:

- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The [http status code](#) of the operation.
- `outcome_message`: A human readable string indicating the operation's outcome.
- `records_affected_count`: The number of records inserted or updated.
- `affected_ids`: The subject IDs of the inserted or updated records.
- `elapsed_seconds`: The duration of the function.
- `raw_text`: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the `raw_text` is returned as an empty string to save RAM.

Author(s)

Will Beasley, John J. Aponte

References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (ie, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/456/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

Examples

```
## Not run:
# Define some constants
uri    <- "https://bbmc.ouhsc.edu/redcap/api/"
token  <- "D70F9ACD1EDD6F151C6EA78683944E98" # The simple project -pid 213
field  <- "mugshot"
event  <- "" # only for longitudinal events

#Upload a single image file.
record <- 1
file_path <- system.file("test-data/mugshot-1.jpg", package="REDCapR")

REDCapR::redcap_upload_file_oneshot(
  file_name = file_path,
  record    = record,
  field     = field,
  redcap_uri = redcap_uri,
  token     = token
)
```

```

#Upload a collection of five images.
records    <- 1:5
file_paths <- system.file(
  paste0("test-data/mugshot-", records, ".jpg"),
  package="REDCapR"
)

for (i in seq_along(records)) {
  record    <- records[i]
  file_path <- file_paths[i]
  REDCapR::redcap_upload_file_oneshot(
    file_name = file_path,
    record    = record,
    field     = field,
    redcap_uri = redcap_uri,
    token     = token
  )
}

## End(Not run)

```

redcap_users_export *List authorized users*

Description

List users authorized for a project.

Usage

```
redcap_users_export(redcap_uri, token, verbose = TRUE, config_options = NULL)
```

Arguments

redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information (<i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
config_options	A list of options to pass to POST method in the <code>httr</code> package. See the details below. Optional.

Value

a `utils::packageDescription`.

Note**Documentation in REDCap 8.4.0**

This method allows you to export the list of users for a project, including their user privileges and also email address, first name, and last name.

Note: If the user has been assigned to a user role, it will return the user with the role's defined privileges.

Examples

```
uri      <- "https://bbmc.ouhsc.edu/redcap/api/"
token    <- "06DEFB601F9B46847DAA9DF0CFA951B4"
result   <- REDCapR::redcap_users_export(redcap_uri=uri, token=token)
result$data_user
result$data_user_form
```

redcap_variables *Enumerate the exported variables*

Description

This function calls the 'exportFieldNames' function of the REDCap API.

Usage

```
redcap_variables(redcap_uri, token, verbose = TRUE, config_options = NULL)
```

Arguments

redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information (<i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
config_options	A list of options to pass to POST method in the <code>httr</code> package. See the details below. Optional.

Details

The full list of configuration options accepted by the `httr` package is viewable by executing `httr::httr_options()`. The `httr` package and documentation is available at <https://cran.r-project.org/package=httr>.

As of REDCap version 6.14.2, three variable types are *not* returned in this call: calculated, file, and descriptive. All variables returned are writable/uploadable.

Value

Currently, a list is returned with the following elements,

- data: An R `base::data.frame()` where each row represents one column in the REDCap dataset.
- success: A boolean value indicating if the operation was apparently successful.
- status_code: The `http status code` of the operation.
- outcome_message: A human readable string indicating the operation's outcome.
- elapsed_seconds: The duration of the function.
- raw_text: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the raw_text is returned as an empty string to save RAM.

Author(s)

Will Beasley

References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

Examples

```
## Not run:
uri      <- "https://bbmc.ouhsc.edu/redcap/api/"
token    <- "9A81268476645C4E5F03428B8AC3AA7B"
ds_variable <- REDCapR::redcap_variables(redcap_uri=uri, token=token)$data

## End(Not run)
```

redcap_version	<i>Determine version of REDCap instance</i>
----------------	---

Description

This function uses REDCap's API to query its version.

Usage

```
redcap_version(redcap_uri, token, verbose = TRUE, config_options = NULL)
```

Arguments

redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information (<i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
config_options	A list of options to pass to POST method in the <code>httr</code> package. See the details below. Optional.

Details

If the API call is unsuccessful, a value of `base::package_version("0.0.0")` will be returned. This ensures that the function will always return an object of class `base::numeric_version`. It guarantees the value can always be used in `utils::compareVersion()`.

Value

a `utils::packageDescription`

Examples

```
uri      <- "https://bbmc.ouhsc.edu/redcap/api/"
token    <- "9A81268476645C4E5F03428B8AC3AA7B"
REDCapR::redcap_version(redcap_uri = uri, token = token)
```

redcap_write

Write/Import records to a REDCap project

Description

This function uses REDCap's APIs to select and return data.

Usage

```
redcap_write(
  ds_to_write,
  batch_size = 100L,
  interbatch_delay = 0.5,
  continue_on_error = FALSE,
  redcap_uri,
  token,
  verbose = TRUE,
  config_options = NULL
)
```


Arguments

<code>ds_to_write</code>	The <code>base::data.frame()</code> to be imported into the REDCap project. Required.
<code>batch_size</code>	The maximum number of subject records a single batch should contain. The default is 100.
<code>interbatch_delay</code>	The number of seconds the function will wait before requesting a new subset from REDCap. The default is 0.5 seconds.
<code>continue_on_error</code>	If an error occurs while writing, should records in subsequent batches be attempted. The default is FALSE, which prevents subsequent batches from running. Required.
<code>redcap_uri</code>	The URI (uniform resource identifier) of the REDCap project. Required.
<code>token</code>	The user-specific string that serves as the password for a project. Required.
<code>verbose</code>	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information (<i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
<code>config_options</code>	A list of options to pass to POST method in the <code>httr</code> package. See the details in <code>redcap_read_oneshot()</code> . Optional.

Details

Currently, the function doesn't modify any variable types to conform to REDCap's supported variables. See `validate_for_write()` for a helper function that checks for some common important conflicts.

For `redcap_write` to function properly, the user must have Export permissions for the 'Full Data Set'. Users with only 'De-Identified' export privileges can still use `redcap_write_oneshot()`. To grant the appropriate permissions:

- go to 'User Rights' in the REDCap project site,
- select the desired user, and then select 'Edit User Privileges',
- in the 'Data Exports' radio buttons, select 'Full Data Set'.

Value

Currently, a list is returned with the following elements:

- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The `http status code` of the operation.
- `outcome_message`: A human readable string indicating the operation's outcome.
- `records_affected_count`: The number of records inserted or updated.
- `affected_ids`: The subject IDs of the inserted or updated records.
- `elapsed_seconds`: The duration of the function.

Author(s)

Will Beasley

References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

Examples

```
## Not run:
#Define some constants
uri      <- "https://bbmc.ouhsc.edu/redcap/api/"
token    <- "D70F9ACD1EDD6F151C6EA78683944E98"

# Read the dataset for the first time.
result_read1 <- REDCapR::redcap_read_oneshot(redcap_uri=uri, token=token)
ds1          <- result_read1$data
ds1$telephone

# Manipulate a field in the dataset in a VALID way
ds1$telephone <- paste0("(405) 321-000", seq_len(nrow(ds1)))

ds1 <- ds1[1:3, ]
ds1$age <- NULL; ds1$bmi <- NULL #Drop the calculated fields before writing.
result_write <- REDCapR::redcap_write(ds=ds1, redcap_uri=uri, token=token)

# Read the dataset for the second time.
result_read2 <- REDCapR::redcap_read_oneshot(redcap_uri=uri, token=token)
ds2          <- result_read2$data
ds2$telephone

# Manipulate a field in the dataset in an INVALID way. A US exchange can't be '111'.
ds1$telephone <- paste0("(405) 321-000", seq_len(nrow(ds1)))

# This next line will throw an error.
result_write <- REDCapR::redcap_write(ds=ds1, redcap_uri=uri, token=token)
result_write$raw_text

## End(Not run)
```

redcap_write_oneshot *Write/Import records to a REDCap project*

Description

This function uses REDCap's API to select and return data.

Usage

```
redcap_write_one_shot(  
  ds,  
  redcap_uri,  
  token,  
  verbose = TRUE,  
  config_options = NULL  
)
```

Arguments

<code>ds</code>	The <code>base::data.frame()</code> to be imported into the REDCap project. Required.
<code>redcap_uri</code>	The URI (uniform resource identifier) of the REDCap project. Required.
<code>token</code>	The user-specific string that serves as the password for a project. Required.
<code>verbose</code>	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information (<i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
<code>config_options</code>	A list of options to pass to <code>httr::POST()</code> method in the 'httr' package. See the details in <code>redcap_read_one_shot()</code> Optional.

Details

Currently, the function doesn't modify any variable types to conform to REDCap's supported variables. See `validate_for_write()` for a helper function that checks for some common important conflicts.

Value

Currently, a list is returned with the following elements:

- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The `http status code` of the operation.
- `outcome_message`: A human readable string indicating the operation's outcome.
- `records_affected_count`: The number of records inserted or updated.
- `affected_ids`: The subject IDs of the inserted or updated records.
- `elapsed_seconds`: The duration of the function.
- `raw_text`: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the `raw_text` is returned as an empty string to save RAM.

Author(s)

Will Beasley

References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

Examples

```
## Not run:
#Define some constants
uri          <- "https://bbmc.ouhsc.edu/redcap/api/"
token        <- "D70F9ACD1EDD6F151C6EA78683944E98"

# Read the dataset for the first time.
result_read1 <- REDCapR::redcap_read_onehot(redcap_uri=uri, token=token)
ds1          <- result_read1$data
ds1$telephone

# Manipulate a field in the dataset in a VALID way
ds1$telephone <- paste0("(405) 321-000", seq_len(nrow(ds1)))

ds1 <- ds1[1:3, ]
ds1$sage      <- NULL; ds1$bmi <- NULL #Drop the calculated fields before writing.
result_write  <- REDCapR::redcap_write_onehot(ds=ds1, redcap_uri=uri, token=token)

# Read the dataset for the second time.
result_read2 <- REDCapR::redcap_read_onehot(redcap_uri=uri, token=token)
ds2          <- result_read2$data
ds2$telephone

# Manipulate a field in the dataset in an INVALID way. A US exchange can't be '111'.
ds1$telephone <- paste0("(405) 321-000", seq_len(nrow(ds1)))

# This next line will throw an error.
result_write  <- REDCapR::redcap_write_onehot(ds=ds1, redcap_uri=uri, token=token)
result_write$raw_text

## End(Not run)
```

replace_nas_with_explicit

Create explicit factor level for missing values

Description

Missing values are converted to a factor level. This explicit assignment can reduce the chances that missing values are inadvertently ignored. It also allows the presence of a missing to become a predictor in models.

Usage

```
replace_nas_with_explicit(  
  scores,  
  new_na_label = "Unknown",  
  create_factor = FALSE,  
  add_unknown_level = FALSE  
)
```

Arguments

scores	An array of values, ideally either factor or character. Required
new_na_label	The factor label assigned to the missing value. Defaults to Unknown.
create_factor	Converts scores into a factor, if it isn't one already. Defaults to FALSE.
add_unknown_level	Should a new factor level be created? (Specify TRUE if it already exists.) Defaults to FALSE.

Value

An array of values, where the NA values are now a factor level, with the label specified by the new_na_label value.

Note

The create_factor parameter is respected only if scores isn't already a factor. Otherwise, levels without any values would be lost.

A stop error will be thrown if the operation fails to convert all the NA values.

Author(s)

Will Beasley

Examples

```
library(REDCapR) #Load the package into the current R session.
```

retrieve_credential	<i>Read a token and other credentials from a (non-REDCap) database or file</i>
---------------------	--

Description

These functions are not essential to calling the REDCap API, but instead are functions that help manage tokens securely.

Usage

```

retrieve_credential_local(
  path_credential,
  project_id,
  check_url          = TRUE,
  check_username     = FALSE,
  check_token_pattern = TRUE
)
retrieve_credential_mssql(
  project_id,
  instance,
  dsn,
  channel = NULL
)

```

Arguments

path_credential	The file path to the CSV containing the credentials. Required.
project_id	The ID assigned to the project withing REDCap. This allows the user to store tokens to multiple REDCap projects in one file. Required
check_url	A logical value indicates if the url in the credential file should be checked to have approximately the correct form. Defaults to TRUE.
check_username	A logical value indicates if the username in the credential file should be checked against the username returned by R. Defaults to FALSE.
check_token_pattern	A logical value indicates if the token in the credential file is a 32-character hexadecimal string. Defaults to FALSE.
instance	The casual name associated with the REDCap instance on campus. This allows one credential system to accommodate multiple instances on campus. Required
dsn	A DSN on the local machine that points to the desired MSSQL database. Required.
channel	An <i>optional</i> connection handle as returned by <code>DBI::dbConnect()</code> . See Details below. Optional.

Details

If the database elements are created with the script provided in package's 'Security Database' vignette, the default values will work.

Value

A list of the following elements:

- redcap_uri: The URI of the REDCap Server.
- username: Username.

- `project_id`: The ID assigned to the project withing REDCap.
- `token`: The token to pass to the REDCap server
- `comment`: An optional string.

Note

Although we strongly encourage storing all the tokens on a central server (*e.g.*, see the `retrieve_credential_mssql()` function and the "SecurityDatabase" vignette), there are times when this approach is not feasible and the token must be stored locally. Please contact us if your institution is using something other than SQL Server, and would like help adapting this approach to your infrastructure.

Author(s)

Will Beasley

Examples

```
# ---- Local File Example -----
path <- system.file("misc/example.credentials", package = "REDCapR")
(p1 <- REDCapR::retrieve_credential_local(path, 153L))
(p2 <- REDCapR::retrieve_credential_local(path, 212L))
```

sanitize_token	<i>Validate and sanitize the user's REDCap token</i>
----------------	--

Description

Verifies the token is nonmissing and conforms to the legal pattern of a 32-character hexadecimal value. Trailing line endings are removed.

Usage

```
sanitize_token(token)
```

Arguments

token	The REDCap token. Required.
-------	-----------------------------

Value

The token, without a terminal newline character.

Note

Contact your institution's REDCap administrator for more information about your project-specific token.

Author(s)

Hao Zhu, Benjamin Nutter, Will Beasley

Examples

```
secret_token_1 <- "12345678901234567890123456ABCDEF"
secret_token_2 <- "12345678901234567890123456ABCDEF\n"
REDCapR::sanitize_token(secret_token_1)
REDCapR::sanitize_token(secret_token_2)
```

validate	<i>Inspect a dataset to anticipate problems before writing to a REDCap project</i>
----------	--

Description

This set of functions inspect a `base::data.frame()` to anticipate problems before writing with REDCap's API.

Usage

```
validate_for_write( d )

validate_no_logical( data_types, stop_on_error )

validate_field_names( field_names, stop_on_error = FALSE )

validate_field_names_collapsed( field_names_collapsed, stop_on_error = FALSE )
```

Arguments

data_types	The data types of the <code>base::data.frame()</code> corresponding to the REDCap project.
stop_on_error	If TRUE, an error is thrown for violations. Otherwise, a dataset summarizing the problems is returned.
d	The <code>base::data.frame()</code> containing the dataset used to update the REDCap project.
field_names	The names of the fields/variables in the REDCap project. Each field is an individual element in the character vector.
field_names_collapsed	The names of the fields/variables in the REDCap project. All fields are combined in a single vector element, separated by commas.

Details

All functions listed in the Usage section above inspect a specific aspect of the dataset. The `validate_for_write()` function executes all these individual validation checks. It allows the client to check everything with one call.

Currently it verifies that the dataset

- does not contain **logical** values (because REDCap typically wants 0/1 values instead of FALSE/TRUE).
- starts with a lowercase letter, and subsequent optional characters are a sequence of (a) lowercase letters, (b) digits 0-9, and/or (c) underscores. (The exact regex is `^[a-z][0-9a-z_]*$`.)

If you encounter additional types of problems when attempting to write to REDCap, please tell us by creating a **new issue**, and we'll incorporate a new validation check into this function.

Value

A `tibble::tibble()`, where each potential violation is a row. The two columns are:

- `field_name`: The name of the `base::data.frame()` that might cause problems during the upload.
- `field_index`: The position of the field. (For example, a value of '1' indicates the first column, while a '3' indicates the third column.)
- `concern`: A description of the problem potentially caused by the field.
- `suggestion`: A *potential* solution to the concern.

Author(s)

Will Beasley

References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

Examples

```
d <- data.frame(
  record_id      = 1:4,
  flag_logical   = c(TRUE, TRUE, FALSE, TRUE),
  flag_Uppercase = c(4, 6, 8, 2)
)
REDCapR::validate_for_write(d = d)
```

Index

`base::character`, 21
`base::data.frame()`, 7, 9–11, 17–19, 23, 25, 29, 32, 39, 41, 43, 48, 49
`base::iconv()`, 11
`base::numeric_version`, 40
`base::package_version`, 8

`checkbox_choices` (`metadata_utilities`), 9
`checkbox_choices()`, 9
`collapse_vector`, 4
`constant`, 4
`constant_to_access` (`constant`), 4
`constant_to_export_rights` (`constant`), 4
`constant_to_form_completion` (`constant`), 4
`constant_to_form_rights` (`constant`), 4
`create_batch_glossary`, 6

`DBI::dbConnect()`, 46

`httr::content()`, 8
`httr::httr_options()`, 28, 32, 38
`httr::POST()`, 13, 15, 19, 34, 43

`kernel_api`, 8

`metadata_utilities`, 9

`readr::cols()`, 24, 28
`readr::read_csv()`, 24, 25, 28
`redcap_column_sanitize`, 11
`redcap_download_file_oneshot`, 12
`redcap_download_instrument`, 14
`redcap_metadata_read`, 17
`redcap_metadata_write`, 18
`redcap_next_free_record_name`, 20
`redcap_project`, 22
`redcap_read`, 23
`redcap_read()`, 7, 25
`redcap_read_oneshot`, 27
`redcap_read_oneshot()`, 17, 19, 23, 25, 41, 43
`redcap_read_oneshot_eav`, 30
`redcap_survey_link_export_oneshot`, 33
`redcap_upload_file_oneshot`, 35
`redcap_users_export`, 37
`redcap_variables`, 38
`redcap_version`, 39
`redcap_write`, 40
`redcap_write_oneshot`, 42
`redcap_write_oneshot()`, 41
`REDCapR` (`REDCapR-package`), 3
`REDCapR-package`, 3
`regex_named_captures` (`metadata_utilities`), 9
`regex_named_captures()`, 9
`replace_nas_with_explicit`, 44
`retrieve_credential`, 45
`retrieve_credential_local` (`retrieve_credential`), 45
`retrieve_credential_mssql` (`retrieve_credential`), 45

`sanitize_token`, 47

`tibble::tibble()`, 49

`utils::compareVersion()`, 8, 40
`utils::packageDescription`, 37, 40
`utils::packageVersion`, 8

`validate`, 48
`validate_field_names` (`validate`), 48
`validate_field_names_collapsed` (`validate`), 48
`validate_for_write` (`validate`), 48
`validate_for_write()`, 13, 15, 34, 36, 41, 43, 49
`validate_no_logical` (`validate`), 48