

Package ‘ROracle’

November 10, 2021

Version 1.3-1.1

Date 2016-10-05

Author Denis Mukhin, David A. James and Jake Luciani

Maintainer Rajendra S. Pingte <rajendra.pingte@oracle.com>

Title OCI Based Oracle Database Interface for R

Description Oracle Database interface (DBI) driver for R.
This is a DBI-compliant Oracle driver based on the OCI.

SystemRequirements Oracle Instant Client or Oracle Database Client

LazyLoad yes

Depends methods, DBI (>= 0.2-5)

Imports utils

License LGPL

URL <http://www.oracle.com>

Collate dbi.R oci.R zzz.R

NeedsCompilation yes

Repository CRAN

Date/Publication 2021-11-10 12:22:19 UTC

R topics documented:

dbCommit-methods	2
dbConnect-methods	3
dbDriver-methods	8
dbGetInfo-methods	10
dbListConnections-methods	17
dbReadTable-methods	18
dbSendQuery-methods	27
ExtDriver-class	30
fetch-methods	31
Oracle	32

OraConnection-class	35
OraDriver-class	37
OraResult-class	38
summary-methods	39

Index	41
--------------	-----------

dbCommit-methods	<i>DBMS Transaction Management</i>
------------------	------------------------------------

Description

Commits or roll backs the current transaction in an Oracle connection

Usage

```
## S4 method for signature 'OraConnection'
dbCommit(conn, ...)
## S4 method for signature 'OraConnection'
dbRollback(conn, ...)
```

Arguments

conn	a OraConnection object, as produced by the function dbConnect
...	currently unused.

Details

dbCommit implementation saves all changes done on that connection. Changes can not be undone once saved permanently.

dbRollback implementation undo all chnages done after last savepoint.

Side Effects

dbCommit saves changes permanently.

dbRollback undo all changes done after last save point.

References

For the Oracle Database documentaion see <http://www.oracle.com/technetwork/indexes/documentation/index.html>.

See Also

[Oracle](#), [dbConnect](#), [dbSendQuery](#), [dbGetQuery](#), [fetch](#), [dbCommit](#), [dbGetInfo](#), [dbReadTable](#).

Examples

```
## Not run:
drv <- dbDriver("Oracle")
con <- dbConnect(drv, "scott", "tiger")
dbReadTable(con, "EMP")
rs <- dbSendQuery(con, "delete from emp where deptno = 10")
dbReadTable(con, "EMP")
if(dbGetInfo(rs, what = "rowsAffected") > 1)
{
  warning("dubious deletion -- rolling back transaction")
  dbRollback(con)
}
dbReadTable(con, "EMP")

## End(Not run)
```

dbConnect-methods

Create a Connection Object to an Oracle DBMS

Description

These methods are straightforward implementations of the corresponding generic functions.

Usage

```
## S4 method for signature 'OraDriver'
dbConnect(drv, username = "", password = "", dbname = "", prefetch = FALSE,
          bulk_read = 1000L, bulk_write = 1000L, stmt_cache = 0L,
          external_credentials = FALSE, sysdba = FALSE, ...)
## S4 method for signature 'ExtDriver'
dbConnect(drv, prefetch = FALSE, bulk_read = 1000L,
          bulk_write = 1000L, stmt_cache = 0L,
          external_credentials = FALSE, sysdba = FALSE, ...)
## S4 method for signature 'OraConnection'
dbDisconnect(conn, ...)
```

Arguments

drv	An object of class OraDriver or ExtDriver.
conn	An OraConnection object as produced by dbConnect.
username	A character string specifying a user name.
password	A character string specifying a password.
dbname	A character string specifying a connect identifier (for more information refer to Chapter 8, Configuring Naming Methods, of Oracle Database Net Services Administrator's Guide). This is the same as part of the SQL*Plus connect string that follows the '@' sign. If you are using Oracle Wallet to store username

and password, then this string should be the connect string used to create the wallet mapping (for more information, refer to Configuring Clients to Use the External Password Store in Chapter 3 of Oracle Database Security Guide). Connect identifiers for an Oracle TimesTen IMDB instance are supported via the OCI tnsnames or easy connect naming methods. For additional information on TimesTen connections for OCI see chapter 3, TimesTen Support for OCI, of TimesTen In-Memory C Developer's Guide. Examples below show various ways to specify the connect identifier.

prefetch	A logical value indicating TRUE or FALSE. When set to TRUE, ROracle will use OCI prefetch buffers to retrieve additional data from the server thus saving memory required in RODBI/ROOCI by allocating a single row buffer to fetch the data from OCI. Using prefetch results in a fetch call for every row. By default, prefetch is FALSE and array fetch is used to retrieve the data from the server.
bulk_read	An integer value indicating the number of rows to fetch at a time. The default value is 1000L. When the prefetch option is selected, memory is allocated for prefetch buffers and OCI will fetch that many rows at a time. When prefetch is not used (the default), memory is allocated in RODBI/ROOCI define buffers. Setting this to a large value will result in more memory allocated based on the number of columns in the select list and the types of columns. For a column of type character, define buffers are allocated using the maximum width times the NLS maximum width. Applications should adjust this value based on the query result and a larger value will benefit queries that return a large result. An application can tune this value as needed.
bulk_write	An integer value indicating the number of rows to insert, update or delete at a time. The default value is 1000L. When the bulk_write value is given in argument, memory is allocated for buffers and OCI will write that many rows at a time. When bulk_write argument is not given, the default value 1000 is used to allocate memory for the bind buffers. Setting this to a large value will result in more memory allocated based on the number of columns in the insert list and the types of columns.
stmt_cache	An integer value indicating the number of statements to cache. It means that cursors are ready to be used without the need to parse the statements again. The default value is 0L. If stmt_cache value is greater than 0L then prefetch value must be set to TRUE.
external_credentials	A logical value indicating TRUE or FALSE. When set to TRUE, ROracle will begin OCI session authenticated with external credentials on the connection. The default value is FALSE.
sysdba	A logical value indicating TRUE or FALSE. When set to TRUE, ROracle will begin OCI session with SYSDBA privileges on the connection. The default value is FALSE.
...	Currently unused.

Details

dbConnect This connection object is used to execute operations on the database.

When `prefetch` is set to `TRUE`, it allows the use of the OCI prefetch buffer to retrieve additional data from the server.

The `bulk_read` argument is used to set an integer value indicating the number of rows to fetch at a time.

The `bulk_write` argument is used to set an integer value indicating the number of rows to write at a time.

The `stmt_cache` argument is used to enable or disable the statement caching feature. Its value specifies the statement cache size.

The `external_credentials` argument is used to begin OCI session authenticated with external credentials on the connection.

The `sysdba` argument is used to begin OCI session with SYSDBA privileges on the connection.

When establishing a connection with an `ExtDriver` driver, none of the arguments specifying credentials are used. A connection in this mode is a singleton object, that is, all calls to `dbConnect` return the same connection object.

dbDisconnect This implementation disconnects the connection between R and the database server. It frees all resources used by the connection object. It frees all result sets associated with this connection object.

Value

`dbConnect` An object `OraConnection` whose class extends `DBIConnection`. This object is used to execute SQL queries on the database.

`dbDisconnect` A logical value indicating whether the operation succeeded or not.

Side Effects

dbConnect Establishes a connection between R and an Oracle Database server.

dbDisconnect Frees resources used by the connection object.

References

For the Oracle Database documentation see <http://www.oracle.com/technetwork/indexes/documentation/index.html>.

See Also

[Oracle](#), [dbConnect](#), [dbSendQuery](#), [dbGetQuery](#), [fetch](#), [dbCommit](#), [dbGetInfo](#), [dbReadTable](#).

Examples

```
## Not run:
## Create an Oracle Database instance and create one connection on the
## same machine.
drv <- dbDriver("Oracle")

## Use username/password authentication.
con <- dbConnect(drv, username = "scott", password = "tiger")
```

```

## Run a SQL statement by creating first a resultSet object.
rs <- dbSendQuery(con, "select * from emp where deptno = 10")

## We now fetch records from the resultSet into a data.frame.
data <- fetch(rs)      ## extract all rows
dim(data)

## End(Not run)
## Not run:
## Create an Oracle Database instance and create one connection to a
## remote database using the SID in the connect string.
drv <- dbDriver("Oracle")

## Refer to Oracle Database Net Services Administrator's Guide for
## details on connect string specification.
host <- "myhost"
port <- 1521
sid <- "mysid"
connect.string <- paste(
  "(DESCRIPTION=",
  "(ADDRESS=(PROTOCOL=tcp)(HOST=", host, ")(PORT=", port, "))",
  "(CONNECT_DATA=(SID=", sid, "))", sep = "")

## Use username/password authentication.
con <- dbConnect(drv, username = "scott", password = "tiger",
  dbname = connect.string)

## Run a SQL statement by creating first a resultSet object.
rs <- dbSendQuery(con, "select * from emp where deptno = 10")

## We now fetch records from the resultSet into a data.frame.
data <- fetch(rs)      ## extract all rows
dim(data)

## End(Not run)
## Not run:
## Create an Oracle Database instance and create one connection to a
## remote database using the service name.
drv <- dbDriver("Oracle")

## Refer to Oracle Database Net Services Administrator's Guide for
## details on connect string specification.

host <- "myhost"
port <- 1521
svc <- "mydb.example.com"
connect.string <- paste(
  "(DESCRIPTION=",
  "(ADDRESS=(PROTOCOL=tcp)(HOST=", host, ")(PORT=", port, "))",
  "(CONNECT_DATA=(SERVICE_NAME=", svc, "))", sep = "")
## Use username/password authentication.
con <- dbConnect(drv, username = "scott", password = "tiger",

```

```
        dbname = connect.string)

## Run a SQL statement by creating first a resultSet object.
rs <- dbSendQuery(con, "select * from emp where deptno = 10")

## We now fetch records from the resultSet into a data.frame.
data <- fetch(rs)      ## extract all rows
dim(data)

## End(Not run)
## Not run:
## Create an Oracle Database instance and create one connection.
drv <- dbDriver("Oracle")

## Use Oracle Wallet authentication.
con <- dbConnect(drv, username = "", password = "",
  dbname = "<wallet_connect_string>")

## Run a SQL statement by creating first a resultSet object.
rs <- dbSendQuery(con, "select * from emp where deptno = 10")

## We now fetch records from the resultSet into a data.frame.
data <- fetch(rs)      ## extract all rows
dim(data)

## End(Not run)
## Not run:
## Create an Oracle Database instance and create one connection.
drv <- dbDriver("Oracle")

## Connect to a TimesTen IMDB instance using the easy connect
## naming method where SampleDb is a direct driver TimesTen DSN.
con <- dbConnect(drv, username = "scott", password = "tiger",
  dbname = "localhost/SampleDb:timesten_direct")

## Run a SQL statement by creating first a resultSet object.
rs <- dbSendQuery(con, "select * from dual")

## We now fetch records from the resultSet into a data.frame.
data <- fetch(rs)      ## extract all rows
dim(data)

## End(Not run)
## Not run:
## Connect to an extproc (this assumes that the driver has already
## been initialized in the embedded R code by passing an external
## pointer representing the extproc context).
con <- dbConnect(Extproc())

## Run a SQL statement by creating first a resultSet object.
rs <- dbSendQuery(con, "select * from dual")

## We now fetch records from the resultSet into a data.frame.
```

```

data <- fetch(rs)      ## extract all rows
dim(data)

## End(Not run)
## Not run:
## Create an Oracle Database instance and create one connection.
drv <- dbDriver("Oracle")

## Create connection with SYSDBA privileges.
con <- dbConnect(drv, username ="scott", password="tiger",
                 sysdba = TRUE)

## Run a SQL statement by creating first a resultSet object.
rs <- dbSendQuery(con, "select * from emp where deptno = 10")

## We now fetch records from the resultSet into a data.frame.
data <- fetch(rs)      ## extract all rows
dim(data)

## End(Not run)
## Not run:
## Create an Oracle Database instance and create one connection.
drv <- dbDriver("Oracle")

## Use OS authentication as an example of external authentication
## Make sure that databse user exist to allow an OS authentication

## Create connection authenticated with external credentials.
con <- dbConnect(drv, username = "", password="",
                 external_credentials = TRUE)

## Above dbConnect() used OS credentials to connect with database.

## Run a SQL statement by creating first a resultSet object.
rs <- dbSendQuery(con, "select * from emp where deptno = 10")

## We now fetch records from the resultSet into a data.frame.
data <- fetch(rs)      ## extract all rows
dim(data)

## End(Not run)

```

dbDriver-methods

Oracle Implementation of the Database Interface (DBI) Classes and Drivers

Description

Oracle driver initialization and closing.

Usage

```
## S4 method for signature 'OraDriver'
dbUnloadDriver(drv, ...)
## S4 method for signature 'ExtDriver'
dbUnloadDriver(drv, ...)
```

Arguments

`drv` An object that inherits from `OraDriver` or `ExtDriver` as created by `dbDriver`.

`...` Any other arguments to pass to the driver `drvName`.

Details

dbDriver This object is a singleton, that is, subsequent invocations of `dbDriver` return the same initialized object.

This implementation allows you to connect to multiple host servers and run multiple connections on each server simultaneously.

When `interruptible` is set to `TRUE`, it allows for interrupting long-running queries on the server by executing the query in a thread. Main thread checks for Ctrl-C and issues OCI-Break/OCIReset to cancel the operation on the server. By default, `interruptible` is `FALSE`.

When `unicode_as_utf8` is set to `FALSE`, `NCHAR`, `NVARCHAR` and `NCLOB` data is fetched using the character set specified by the `NLS_LANG` setting. By default, `unicode_as_utf8` is set to `TRUE`.

When `ora.attributes` is set to `TRUE`, the result set from `dbGetQuery` and `fetch` contains DBMS-specific attributes like `ora.encoding`, `ora.type`, and `ora.maxlength` for the corresponding column.

dbUnloadDriver This implementation removes communication links between the R client and the database. It frees all connections and all result sets associated with those connection objects.

Value

`dbDriver` An object `OraDriver` or `ExtDriver` whose class extends `DBIDriver`. This object is used to create connections, using the function `dbConnect`, to one or more Oracle Database engines.

`dbUnloadDriver` Free all resources occupied by the driver object.

Side Effects

dbDriver The R client part of the database communication is initialized, but note that connecting to the database engine needs to be done through calls to `dbConnect`.

dbUnloadDriver Remove the communication link between the R client and the database.

References

For Oracle Database documentation, see <http://www.oracle.com/technetwork/indexes/documentation/index.html>.

See Also

[Oracle](#), [dbConnect](#), [dbSendQuery](#), [dbGetQuery](#), [fetch](#), [dbCommit](#), [dbGetInfo](#), [dbListTables](#), [dbReadTable](#).

Examples

```
## Not run:
# first load the library
library("ROracle")

# create an Oracle instance
drv <- dbDriver("Oracle")

con <- dbConnect(drv, "scott", "tiger")
dbListTables(con)

# fetch all results from the emp table
res <- dbGetQuery(con, "select * from emp")

# dbSendQuery can be used to fetch data in chunks
# as well as all of data at once
res <- dbSendQuery(con, "select * from emp")

# fetch all results
fetch(res)

# or a chunk at a time
fetch(res, n = 5)

# describing the schema for the emp table using dbGetInfo
dbGetInfo(res, what = 'fields')

# clear the result
dbClearResult(res)

# disconnect from the database
dbDisconnect(con)

# free the driver object
dbUnloadDriver(drv)

## End(Not run)
```

dbGetInfo-methods

Database interface Metadata

Description

These methods are straight-forward implementations of the corresponding generic functions.

Usage

```
## S4 method for signature 'OraDriver'
dbGetInfo(dbObj, ...)
## S4 method for signature 'ExtDriver'
dbGetInfo(dbObj, ...)
## S4 method for signature 'OraConnection'
dbGetInfo(dbObj, what, ...)
## S4 method for signature 'OraResult'
dbGetInfo(dbObj, what, ...)
## S4 method for signature 'OraResult'
dbGetStatement(res, ...)
## S4 method for signature 'OraResult'
dbGetRowCount(res, ...)
## S4 method for signature 'OraResult'
dbGetRowsAffected(res, ...)
## S4 method for signature 'OraResult'
dbColumnInfo(res, ...)
## S4 method for signature 'OraResult'
dbHasCompleted(res)
```

Arguments

dbObj	Any object that implements some functionality in the R interface to databases (a driver, a connection, or a result set).
what	A character string specifying an element of the output list.
res	An OraResult.
...	Currently unused.

Details

Table, schema, and column names are case sensitive, for example, table names ABC and abc are not the same. All database schema object names should not include double quotes as they are enclosed in double quotes when the corresponding SQL statement is generated.

The **ROracle** method dbGetInfo provides following details about the driver object:

- `\$driverName` The name of the driver, "Oracle (OCI)"
- `\$driverVersion` The version of the ROracle driver used
- `\$clientVersion` The version of the Oracle Client library used
- `\$conTotal` The number of connections instantiated by the driver
- `\$conOpen` The number of connections open currently
- `\$interruptible` TRUE when a long-running query can be interrupted
- `\$unicode_as_utf8` TRUE when character data is to be fetched in UTF8 encoded format
- `\$ora_attributes` TRUE when each column in a result set data frame has corresponding Oracle DBMS attributes

- `\$connections` Information about each connection currently open, see `dbGetInfo` of connection object for details

The **ROracle** method `dbGetInfo` provides following the details about the connection object:

- `\$username` The name of the user on this connection
- `\$dbname` The connect alias or the connect string used
- `\$serverVersion` The version of the Oracle Database server
- `\$serverType` The value "Oracle RDBMS"
- `\$resTotal` The number of result sets on this connection
- `\$resOpen` The number of result sets open on this connection
- `\$prefetch` TRUE when prefetch mechanism is used to fetch data
- `\$bulk_read` The number of rows to fetch at a time from DBMS
- `\$bulk_write` The number of rows to write at a time to DBMS
- `\$stmt_cache` TRUE when the statement cache is used
- `\$results` Information about each result set currently open, see `dbGetInfo` of result set for details

The **ROracle** method `dbGetInfo` provides the following details about the result set object:

- `\$statement` SQL statement used to produce the result set object
- `\$isSelect` TRUE when a select statement is specified
- `\$rowsAffected` The number of rows affected by DML statement
- `\$rowCount` The number of rows in result set currently
- `\$completed` TRUE if there are no more rows in the result set
- `\$prefetch` TRUE when the prefetch mechanism used to fetch data
- `\$bulk_read` The number of rows to fetch at a time from DBMS
- `\$bulk_write` The number of rows to write at a time to DBMS
- `\$fields` Information about each column in the the result set, see `dbColumnInfo` for details

The **ROracle** method `dbColumnInfo` provides following details about each column in the result set:

- `\$name` The name of the column
- `\$sclass` The R type of the object containing the data returned by the Oracle RDBMS
- `\$type` The type of column as created in Oracle RDBMS
- `\$len` Length of VARCHAR, CHAR and RAW column type in Oracle RDBMS. All other columns will have NA.
- `\$precision` The precision of number column
- `\$scale` The scale of number column
- `\$nullOK` TRUE when a NULL value can be present in the column

The example below shows the driver, connection, result set, and column information for a table containing:

```
create table foo(  
  a number(21),  
  b number,  
  c char(20),  
  d varchar(300),  
  e binary_double,  
  f binary_float,  
  g clob,  
  h blob,  
  i bfile,  
  j date,  
  m timestamp,  
  n timestamp with time zone,  
  o timestamp with local time zone,  
  r interval day to second,  
  s raw(234)  
);
```

```
library(ROracle)  
Loading required package: DBI  
> # instantiate ROracle driver object  
> drv <- Oracle()  
> con <- dbConnect(drv, "scott", "tiger")  
> rs <- dbSendQuery(con, "select * from foo")  
> dbGetInfo(drv)  
$driverName  
[1] "Oracle (OCI)"  
  
$driverVersion  
[1] "1.1-12"  
  
$clientVersion  
[1] "11.2.0.4.0"  
  
$conTotal  
[1] 1  
  
$conOpen  
[1] 1  
  
$interruptible  
[1] FALSE  
  
$unicode_as_utf8  
[1] TRUE  
  
$ora_attributes  
[1] TRUE
```

```
$connections
$connections[[1]]
User name:          scott
Connect string:
Server version:    11.2.0.4.0
Server type:       Oracle RDBMS
Results processed: 1
OCI prefetch:     FALSE
Bulk read:         1000
Bulk write:        1000
Statement cache size: 0
Open results:      1
```

```
> dbGetInfo(con)
```

```
$username
[1] "scott"
```

```
$dbname
[1] ""
```

```
$serverVersion
[1] "11.2.0.4.0"
```

```
$serverType
[1] "Oracle RDBMS"
```

```
$resTotal
[1] 1
```

```
$resOpen
[1] 1
```

```
$prefetch
[1] FALSE
```

```
$bulk_read
[1] 1000
```

```
$bulk_write
[1] 1000
```

```
$stmt_cache
[1] 0
```

```
$results
$results[[1]]
```

```

Statement:      select * from foo
Rows affected:  0
Row count:     0
Select statement: TRUE
Statement completed: FALSE
OCI prefetch:  FALSE
Bulk read:     1000
Bulk write:    1000

```

```

> dbGetInfo(rs)
$statement
[1] "select * from foo"

```

```

$isSelect
[1] TRUE

```

```

$rowsAffected
[1] 0

```

```

$rowCount
[1] 0

```

```

$completed
[1] FALSE

```

```

$prefetch
[1] FALSE

```

```

$bulk_read
[1] 1000

```

```

$bulk_write
[1] 1000

```

```

$fields
  name  Sclass          type len precision scale nullOK
1    A  numeric      NUMBER  NA      21      0    TRUE
2    B  numeric      NUMBER  NA       0     -127    TRUE
3    C character      CHAR    20       0       0    TRUE
4    D character     VARCHAR2 300      0       0    TRUE
5    E  numeric     BINARY_DOUBLE  NA       0       0    TRUE
6    F  numeric     BINARY_FLOAT  NA       0       0    TRUE
7    G character      CLOB    NA       0       0    TRUE
8    H    raw          BLOB    NA       0       0    TRUE
9    I    raw          BFILE   NA       0       0    TRUE
10   J  POSIXct      DATE    NA       0       0    TRUE
11   M  POSIXct     TIMESTAMP  NA       0       6    TRUE

```

12	N	POSIXct	TIMESTAMP WITH TIME ZONE	NA	0	6	TRUE
13	O	POSIXct	TIMESTAMP WITH LOCAL TIME ZONE	NA	0	6	TRUE
14	R	difftime	INTERVAL DAY TO SECOND	NA	2	6	TRUE
15	S	raw		RAW 234	0	0	TRUE

Value

Information about driver, connection or a result set object.

References

For the Oracle Database documentaion see <http://www.oracle.com/technetwork/indexes/documentation/index.html>.

See Also

[Oracle](#), [dbDriver](#), [dbConnect](#), [dbSendQuery](#), [dbGetQuery](#), [fetch](#), [dbCommit](#), [dbGetInfo](#), [dbListTables](#), [dbReadTable](#).

Examples

```
## Not run:
drv <- dbDriver("Oracle")
con <- dbConnect(drv, "scott", "tiger")

rs <- dbSendQuery(con, "select * from emp")

# Get the SQL statement for the result set object rs
dbGetStatement(rs)

# Are there any more rows in result set?
dbHasCompleted(rs)

# Information about columns in result set rs object
dbColumnInfo(rs)

# DBIDriver info
names(dbGetInfo(drv))

# DBIConnection info
names(dbGetInfo(con))

# DBIResult info
names(dbGetInfo(rs))

## End(Not run)
```

dbListConnections-methods

List items from Oracle objects

Description

These methods are straight-forward implementations of the corresponding generic functions.

Usage

```
## S4 method for signature 'OraDriver'  
dbListConnections(drv, ...)  
## S4 method for signature 'ExtDriver'  
dbListConnections(drv, ...)  
## S4 method for signature 'OraConnection'  
dbListResults(conn, ...)
```

Arguments

drv	an OraDriver or ExtDriver.
conn	an OraConnection.
...	currently unused.

Details

dbListConnections implementation return a list of all associated connections. It shows information about all associated connections.

dbListResults implementation return a list of all associated result sets. It shows information about all associated result sets.

Value

dbListConnections	A list of all connections associated with driver.
dbListResults	A list of all result sets associated with connection.

References

For the Oracle Database documentaion see <http://www.oracle.com/technetwork/indexes/documentation/index.html>.

See Also

[Oracle](#), [dbGetInfo](#), [dbColumnInfo](#), [dbDriver](#), [dbConnect](#), [dbSendQuery](#)

Examples

```
## Not run:
drv <- dbDriver("Oracle")
con1 <- dbConnect(drv, "scott", "tiger")
res1 <- dbSendQuery(con1, "select * from emp where deptno = 10")
res2 <- dbSendQuery(con1, "select * from emp where deptno = 20")
con2 <- dbConnect(drv, "scott", "tiger")
res3 <- dbSendQuery(con2, "select * from dept")

## get all active statements
for(con in dbListConnections(drv))
  for (res in dbListResults(con))
    print(dbGetStatement(res))

## End(Not run)
```

dbReadTable-methods *Convenience Functions for Manipulating DBMS Tables*

Description

These functions mimic their R counterparts except that they generate code that gets remotely executed in a database engine: get, assign, exists, remove, objects, and names.

Usage

```
## S4 method for signature 'OraConnection,character'
dbReadTable(conn, name, schema = NULL, row.names = NULL, ...)
## S4 method for signature 'OraConnection,character,data.frame'
dbWriteTable(conn, name, value, row.names = FALSE, overwrite = FALSE,
             append = FALSE, ora.number = TRUE, schema = NULL, date = FALSE, ...)
## S4 method for signature 'OraConnection,character'
dbExistsTable(conn, name, schema = NULL, ...)
## S4 method for signature 'OraConnection,character'
dbRemoveTable(conn, name, purge = FALSE, schema = NULL, ...)
## S4 method for signature 'OraConnection'
dbListTables(conn, schema = NULL, all = FALSE, full = FALSE, ...)
## S4 method for signature 'OraConnection,character'
dbListFields(conn, name, schema = NULL, ...)
```

Arguments

conn	An OraConnection database connection object.
name	A case-sensitive character string specifying a table name.
schema	A case-sensitive character string specifying a schema name (or a vector of character strings for dbListTables).

date	A boolean flag to indicate whether to use date or DateTimep. By default, Date-Time will be used instead of timestamp.
row.names	In the case of dbReadTable, this argument can be a string, an index or a logical vector specifying the column in the DBMS table to be used as row.names in the output data.frame (a NULL specifies that no column should be used as row.names in the output). The default is NULL. In the case of dbWriteTable, this argument should be a logical value specifying whether the row.names should be output to the output DBMS table; if TRUE, an extra column whose name is "row.names" will be added to the output. The default is FALSE.
value	A data.frame containing the data to write to a table. (See Details section for supported column types.)
overwrite	A logical value specifying whether to overwrite an existing table or not. The default is FALSE.
append	A logical value specifying whether to append to an existing table in the DBMS. The default is FALSE.
ora.number	A logical value specifying whether to create a table with Oracle NUMBER or BINARY_DOUBLE columns while writing numeric data. Specify TRUE to create a table with Oracle NUMBER values or specify FALSE to create a table with Oracle BINARY_DOUBLE values. The default value is TRUE. Specify FALSE if one or more of the numeric data values are NaN.
purge	A logical value specifying whether to add the PURGE option to the SQL DROP TABLE statement.
all	A logical value specifying whether to look at all schemas.
full	A logical value specifying whether to generate schema names. When argument all is TRUE, the output is a vector containing schema names followed by the table names. Using matrix(..., ncol = 2) on the output produces a matrix where each row corresponds to a table and the columns represent the schema names and table names respectively.
...	currently unused.

Details

Table, schema, and column names are case sensitive, e.g., table names ABC and abc are not the same. All database schema object names should not include double quotes as they are enclosed in double quotes when the corresponding SQL statement is generated.

The following attributes are used for mapping BLOB, CLOB, NCLOB, NCHAR, VARCHAR2, NVARCHAR2, CHAR, TIMESTAMP WITH TIME ZONE and TIMESTAMP WITH LOCAL TIME ZONE columns correctly in dbWriteTable: 1) Attribute Name: ora.type This attribute indicates the type of the underlying column and can be "CLOB", "BLOB", "CHAR", "VARCHAR2", or "RAW". The user can specify TIMESTAMP, DATE, TIMESTAMP WITH TIME ZONE or any other column types supported by Oracle Database. Oracle does not parse the value; it is validated by the database. The user can provide one of the following values for ora.type: CLOB, BLOB, CHAR, TIMESTAMP WITH TIME ZONE, TIMESTAMP WITH LOCAL TIME ZONE and fractional_seconds_precision. 2) Attribute Name: ora.encoding When UTF-8 is specified,

the database uses NCLOB, NCHAR or NVARCHAR based on `ora.type`. 3) Attribute Name: `ora.maxLength` One can specify the maximum length of CHAR, VARCHAR, NCHAR, NVARCHAR2, or RAW columns. For other data types, `ora.maxLength` does not apply and is ignored. The following default values are used for certain data types when `ora.maxLength` is not specified. CHAR 2000 NCHAR 1000 VARCHAR2 4000 NVARCHAR2 2000 RAW 2000 4) Attribute Name: `ora.fractional_seconds_precision` One can specify the fractional part of the SECOND date-time field of TIMESTAMP, TIMESTAMP WITH TIME ZONE and TIMESTAMP WITH LOCAL TIME ZONE columns. It can be a number in the range 0 to 9. The default value is 6.

ROracle methods such as `dbReadTable`, `dbGetQuery`, `fetch`, and `dbWriteTable` use the following mapping between R and Oracle data types:

- logical and integer map to Oracle INTEGER
- numeric maps to Oracle NUMBER if argument `ora.number` is TRUE or Oracle BINARY_DOUBLE if FALSE
- character maps to Oracle CLOB if attribute `ora.type` is "CLOB" or Oracle NCLOB if attribute `ora.type` is "CLOB" and `ora.encoding` is "UTF-8" or Oracle CHAR(`ora.maxLength`) if attribute `ora.type` is "CHAR" or Oracle NCHAR(`ora.maxLength`) if attribute `ora.type` is "CHAR" and `ora.encoding` is "UTF-8" or Oracle NVARCHAR2(`ora.maxLength`) if attribute `ora.encoding` is "UTF-8" or Oracle VARCHAR2(`ora.maxLength`)
- Date and POSIXct map to Oracle DATE **ROracle** - the ROracle package R - the R application
- POSIXct maps to Oracle TIMESTAMP WITH TIME ZONE(`ora.fractional_seconds_precision`) if attribute `ora.type` is "TIMESTAMP WITH TIME ZONE" or Oracle TIMESTAMP WITH LOCAL TIME ZONE(`ora.fractional_seconds_precision`) if attribute `ora.type` is "TIMESTAMP WITH LOCAL TIME ZONE" or Oracle TIMESTAMP(`ora.fractional_seconds_precision`) and if Date is FALSE
- difftime maps to Oracle INTERVAL DAY TO SECOND
- list of raw vectors map to Oracle BLOB if attribute `ora.type` is "BLOB" or Oracle RAW(`ora.maxLength`)
- other R types such as factor are converted to character

ROracle returns values from database columns that are of data type: date, time stamp, time stamp with time zone and time stamp with local time zone data types in R's POSIXct format. POSIXct refers to a time that is internally stored as the number of seconds since the start of 1970 in UTC. Number of seconds are exchanged from R and ROracle driver in floating point double format. In POSIXct representation R uses the TZ environment variable or maps the OS time zone environment variable to its own, therefore the date will be displayed in this time zone format.

One can insert data into columns of the four data types listed above using a string with the correct format or POSIXct representation. String data is passed to the database directly and ROracle relies on database to convert it to date time representation. ROracle driver converts the POSIXct representation to a string representation using the format "%Y-%m-%d %H:%M:%OS6" in a data frame that is used for DML operations. Data in this format corresponds to NLS_TIMESTAMP_TZ_FORMAT "YYYY-MM-DD HH24:MI:SSXFF" and is converted to SQLT_TIMESTAMP_LTZ to be bound to the Oracle database. An intermediate class "datetime" is created that represents character data to the ROracle driver internally.

Columns having a date and time stamp data type are fetched by ROracle using the SQLT_TIMESTAMP data type. Columns having a time stamp with time zone or a time stamp with local time zone data types are fetched using SQLT_TIMESTAMP_LTZ data type. Columns of data type time stamp with

local time zone undergo conversion to the session time zone that the R application runs in, therefore setting the time zone environment TZ in R will affect the data values in this column. ROracle driver maps the TZ environment variable to the session time zone and issues an alter DDL to set the session time zone when the connection is made to the database.

To fetch data from columns with a timestamp with time zone or a timestamp with local time zone, the client and server must have the same time zone data file else an error will be reported.

When these data types are selected from the database, they are converted to string representation using the NLS_TIMESTAMP_TZ_FORMAT "YYYY-MM-DD HH24:MI:SSXFF" that corresponds to "%Y-%m-%d %H:%M:%OS6" in R. An intermediate class "datetime" is created to represent this character data in ROracle driver. ROracle driver then converts it to POSIXct using the as.POSIXct() function. An R application sees the data in POSIXct form in the data frame.

R session time zone:

R has the concept of a time zone in which the R engine operates. The time zone can be set to a string such as 'PST8PDT', 'America/Los_Angeles' and so on. These strings are self-explanatory and specify the time zone in which the session is operating.

The R session time zone can be set in one of two ways:

1. By entering the following on the Linux or Unix command line before starting R:

```
setenv TZ = America/Los_Angeles on Linux/UNIX
```

NOTE: Do not use this option on Windows as it does not allow one to set Oracle compatible timezone names for the environment variable TZ.
2. By entering the following at the R prompt:

```
Sys.setenv(TZ = "PST8PDT")
```

We recommend using the option 2 as the R script works without any porting issues on Linux/Unix as well as Windows. Option 2 also allows you to specify Oracle compatible timezone names even on Windows.

The R session time zone determines the time zone for all POSIXct time zone unqualified date-time types. It is also the time zone to which all qualified date-time types are converted when they are displayed by R.

The following example demonstrates this.

```
Sys.setenv(TZ = "PST8PDT")
dt <- c(as.POSIXct("2010/3/13", tz = "PST8PDT"),
        as.POSIXct("2010/3/13 3:47:30.123456", tz = "PST8PDT"),
        as.POSIXct("2010/3/22", tz = "PST8PDT"),
        as.POSIXct("2010/3/22 7:02:30", tz = "PST8PDT"),
        as.POSIXct("2010/3/13"),
        as.POSIXct("2010/3/13 3:47:30.123456"),
        as.POSIXct("2010/3/22"),
        as.POSIXct("2010/3/22 7:02:30"))
dt
[1] "2010-03-13 00:00:00.000000 PST" "2010-03-13 03:47:30.123456 PST"
[3] "2010-03-22 00:00:00.000000 PDT" "2010-03-22 07:02:30.000000 PDT"
[5] "2010-03-13 00:00:00.000000 PST" "2010-03-13 03:47:30.123456 PST"
```

```
[7] "2010-03-22 00:00:00.000000 PDT" "2010-03-22 07:02:30.000000 PDT"
```

Note that the unqualified timestamps are also assumed to be in the R's session time zone when they are displayed by R. Of course, R is also smart enough to make the determination of whether the time falls into PST or PDT based on when US Daylight savings begins, and displays PST or PDT accordingly.

The following example makes this more obvious.

```
> Sys.setenv(TZ = "EST5EDT")
> dt <- c(as.POSIXct("2010/3/13", tz = "PST8PDT"),
+        as.POSIXct("2010/3/13 3:47:30.123456", tz = "PST8PDT"),
+        as.POSIXct("2010/3/22", tz = "PST8PDT"),
+        as.POSIXct("2010/3/22 7:02:30", tz = "PST8PDT"),
+        as.POSIXct("2010/3/13"),
+        as.POSIXct("2010/3/13 3:47:30.123456"),
+        as.POSIXct("2010/3/22"),
+        as.POSIXct("2010/3/22 7:02:30"))
> dt
[1] "2010-03-13 03:00:00.000000 EST" "2010-03-13 06:47:30.123456 EST"
[3] "2010-03-22 03:00:00.000000 EDT" "2010-03-22 10:02:30.000000 EDT"
[5] "2010-03-13 00:00:00.000000 EST" "2010-03-13 03:47:30.123456 EST"
[7] "2010-03-22 00:00:00.000000 EDT" "2010-03-22 07:02:30.000000 EDT"
```

Note that all the time zone unqualified timestamps are assumed to be in the session time zone. However, even the time zone qualified timestamps are converted to session time zone and displayed. Note that all the values are displayed by R in the R session's time zone (with the timezone name also modified to EST or EDT to account for daylight savings as applicable). Refer to Date-Time Classes at <http://stat.ethz.ch/R-manual/R-devel/library/base/html/DateTimeClasses.html> and timezones at:

<http://stat.ethz.ch/R-manual/R-devel/library/base/html/timezones.html> for details on how R handles dates and times and time zones)

Let's take an example where we use a longer time zone name (often referred to as an 'Olson Name') as opposed to an abbreviation.

```
> Sys.setenv(TZ = "America/Los_Angeles")
> dt <- c(as.POSIXct("2010/3/13", tz = "PST8PDT"),
+        as.POSIXct("2010/3/13 3:47:30.123456", tz = "PST8PDT"),
+        as.POSIXct("2010/3/22", tz = "PST8PDT"),
+        as.POSIXct("2010/3/22 7:02:30", tz = "PST8PDT"),
+        as.POSIXct("2010/3/13"),
+        as.POSIXct("2010/3/13 3:47:30.123456"),
+        as.POSIXct("2010/3/22"),
+        as.POSIXct("2010/3/22 7:02:30"))
> dt
[1] "2010-03-13 00:00:00.000000 PST" "2010-03-13 03:47:30.123456 PST"
```

```
[3] "2010-03-22 00:00:00.000000 PDT" "2010-03-22 07:02:30.000000 PDT"
[5] "2010-03-13 00:00:00.000000 PST" "2010-03-13 03:47:30.123456 PST"
[7] "2010-03-22 00:00:00.000000 PDT" "2010-03-22 07:02:30.000000 PDT"
```

Note that in such a case, R doesn't use the long name when the values are displayed, but instead still displays the values using the abbreviations "PST" and "PDT". This is significant because Oracle doesn't necessarily like these abbreviations. For example, an Oracle database doesn't recognize "PDT" as a valid time zone. See "R Time zone and Oracle session time zone" for details on valid time zones.

The example below shows the effect of changing the time zone in R environment:

```
R> Sys.timezone()
[1] "PST8PDT"
# Selecting data and displaying it
res <- dbGetQuery(con, selStr)
R> res[,1]
[1] 1 2 3 4 5 6
R> res[,2]
[1] "2012-06-05 00:00:00 PDT" "2012-01-05 07:15:02 PST"
    "2012-01-05 00:00:00 PST" "2011-01-05 00:00:00 PST"
[5] "2013-01-05 00:00:00 PST" "2020-01-05 00:00:00 PST"
R> res[,3]
[1] "2012-06-05 00:00:00 PDT" "2012-01-05 07:15:03 PST"
    "2012-01-05 00:00:00 PST" "2011-01-05 00:00:00 PST"
[5] "2013-01-05 00:00:00 PST" "2020-01-05 00:00:00 PST"
R> res[,4]
[1] "2012-06-05 00:00:00 PDT" "2012-01-05 07:15:03 PST"
    "2012-01-05 00:00:00 PST" "2011-01-05 00:00:00 PST"
[5] "2013-01-05 00:00:00 PST" "2020-01-05 00:00:00 PST"
R> res[,5]
[1] "2012-06-05 00:00:00 PDT" "2012-01-05 07:15:03 PST"
    "2012-01-05 00:00:00 PST" "2011-01-05 00:00:00 PST"
[5] "2013-01-05 00:00:00 PST" "2020-01-05 00:00:00 PST"
R> Sys.setenv(TZ='EST5EDT')
R> res[,1]
[1] 1 2 3 4 5 6
R> res[,2]
[1] "2012-06-05 03:00:00 EDT" "2012-01-05 10:15:02 EST"
    "2012-01-05 03:00:00 EST" "2011-01-05 03:00:00 EST"
[5] "2013-01-05 03:00:00 EST" "2020-01-05 03:00:00 EST"
R> res[,3]
[1] "2012-06-05 03:00:00 EDT" "2012-01-05 10:15:03 EST"
    "2012-01-05 03:00:00 EST" "2011-01-05 03:00:00 EST"
[5] "2013-01-05 03:00:00 EST" "2020-01-05 03:00:00 EST"
R> res[,4]
[1] "2012-06-05 03:00:00 EDT" "2012-01-05 10:15:03 EST"
    "2012-01-05 03:00:00 EST" "2011-01-05 03:00:00 EST"
```

```
[5] "2013-01-05 03:00:00 EST" "2020-01-05 03:00:00 EST"
R> res[,5]
[1] "2012-06-05 03:00:00 EDT" "2012-01-05 10:15:03 EST"
    "2012-01-05 03:00:00 EST" "2011-01-05 03:00:00 EST"
[5] "2013-01-05 03:00:00 EST" "2020-01-05 03:00:00 EST"
```

Also `dbWriteTable` always auto commits a current transaction as well as the data it inserts, i.e. it acts as a DDL statement even if appends rows to an already existing table.

Value

A data frame in the case of `dbReadTable`; a vector in the case of `dbListTables` and `dbListFields`; a logical in the case of `dbExistsTable` indicating whether the table exists; otherwise TRUE when the operation was successful or an exception.

References

For the Oracle Database documentation see <http://www.oracle.com/technetwork/indexes/documentation/index.html>. For Datetime Data Types and Time Zone Support in Oracle see http://docs.oracle.com/cd/E11882_01/server.112/e10729/ch4datetime.htm.

See Also

[Oracle](#), [dbDriver](#), [dbConnect](#), [dbSendQuery](#), [dbGetQuery](#), [fetch](#), [dbCommit](#), [dbGetInfo](#).

Examples

```
## Not run:
con <- dbConnect(Oracle(), "scott", "tiger")
if (dbExistsTable(con, "FOO", "SCOTT"))
  dbRemoveTable(con, "FOO")

foo <- dbReadTable(con, "EMP")
row.names(foo) <- foo$EMPNO
foo <- foo[,-1]

dbWriteTable(con, "FOO", foo, row.names = TRUE)
dbWriteTable(con, "FOO", foo, row.names = TRUE, overwrite = TRUE)
dbReadTable(con, "FOO", row.names = 1)

dbGetQuery(con, "delete from foo")
dbWriteTable(con, "FOO", foo, row.names = TRUE, append = TRUE)
dbReadTable(con, "FOO", row.names = 1)
dbRemoveTable(con, "FOO")

dbListTables(con)
dbListFields(con, "EMP")

if (dbExistsTable(con, "RORACLE_TEST", "SCOTT"))
  dbRemoveTable(con, "RORACLE_TEST")

# Example of POSIXct usage.
```

```

# A table is created using:
createTab <- "create table RORACLE_TEST(row_num number, id1 date,
      id2 timestamp, id3 timestamp with time zone,
      id4 timestamp with local time zone )"

dbGetQuery(con, createTab)
# Insert statement.
insStr <- "insert into RORACLE_TEST values(:1, :2, :3, :4, :5)";

# Select statement.
selStr <- "select * from RORACLE_TEST";

# Insert time stamp without time values in POSIXct form.
x <- 1;
y <- "2012-06-05";
y <- as.POSIXct(y);
dbGetQuery(con, insStr, data.frame(x, y, y, y, y));

# Insert date & times stamp with time values in POSIXct form.
x <- 2;
y <- "2012-01-05 07:15:02";
y <- as.POSIXct(y);
z <- "2012-01-05 07:15:03.123";
z <- as.POSIXct(z);
dbGetQuery(con, insStr, data.frame(x, y, z, z, z));

# Insert list of date objects in POSIXct form.
x <- c(3, 4, 5, 6);
y <- c('2012-01-05', '2011-01-05', '2013-01-05', '2020-01-05');
y <- as.POSIXct(y);
dbGetQuery(con, insStr, data.frame(x, y, y, y, y));

dbCommit (con)

# Selecting data and displaying it.
res <- dbGetQuery(con, selStr)
res[,1]
res[,2]
res[,3]
res[,4]
res[,5]

# insert data in Date format
a<-as.Date("2014-01-01")
dbWriteTable(con, 'TEMP', data.frame(a), date = TRUE)

# using attribute to map NCHAR, CLOB, BLOB, NCLOB columns correctly in
# dbWriteTable
str1 <- paste(letters, collapse="")
lstr1 <- paste(rep(str1, 200), collapse="")
raw.lst <- vector("list",1)
lraw.lst <- vector("list",1)
raw.lst[[1L]] <- charToRaw(str1)

```

```

lraw.lst[[1L]] <- rep(charToRaw(str1), 200)
a <- as.POSIXct("2014-01-01 14:12:09.0194733")
b <- as.POSIXct("2014-01-01 14:12:09.01947")
test.df <- data.frame(char=str1, nchar=str1, varchar=str1, clob=lstr1,
                      nclob=lstr1, stringsAsFactors=FALSE)
test.df$raw.typ <- raw.lst
test.df$blob <- lraw.lst
test.df$char_max <- str1
test.df$raw_max.typ <- raw.lst
test.df$nvchar <- str1
test.df$nvchar_max <- str1
test.df$date_tz <- a
test.df$date_ltz <- b

# adding attributes
attr(test.df$clob, "ora.type") <- "CLOB"
attr(test.df$blob, "ora.type") <- "BLOB"
attr(test.df$nclob, "ora.type") <- "CLOB"
attr(test.df$nclob, "ora.encoding") <- "UTF-8"
attr(test.df$char_max, "ora.maxlength") <- 3000
attr(test.df$raw_max.typ, "ora.maxlength") <- 1000
attr(test.df$nvchar, "ora.encoding") <- "UTF-8"
attr(test.df$nvchar_max, "ora.encoding") <- "UTF-8"
attr(test.df$nvchar_max, "ora.maxlength") <- 1500
attr(test.df$char, "ora.type") <- "CHAR"
attr(test.df$date_tz, "ora.type") <- "timestamp with time zone"
attr(test.df$date_ltz, "ora.type") <- "timestamp with local time zone"
attr(test.df$nchar, "ora.type") <- "CHAR"
attr(test.df$nchar, "ora.encoding") <- "UTF-8"
attr(test.df$date_tz, "ora.fractional_seconds_precision") <- 9
R> # displaying the data frame
R> test.df
char                nchar
1 abcdefghijklmnopqrstuvwxyz abcdefghijklmnopqrstuvwxyz
varchar
1 abcdefghijklmnopqrstuvwxyz
clob
1 abcdefghijklmnopqrstuvwxyz...
nclob
1 abcdefghijklmnopqrstuvwxyz...
raw.typ
1 61, 62, 63, 64, 65, 66, 67, 68, 69, 6a, 6b, 6c, 6d, 6e, 6f, 70, 71, 72, 73,
  74, 75, 76, 77, 78, 79, 7a
blob
1 61, 62, 63, 64, 65, 66, 67, 68, 69, 6a, 6b, 6c, 6d, 6e, 6f, 70, 71, 72, 73,
  74, 75, 76, 77, 78, 79, 7a,...
char_max
1 abcdefghijklmnopqrstuvwxyz
raw_max.typ
1 61, 62, 63, 64, 65, 66, 67, 68, 69, 6a, 6b, 6c, 6d, 6e, 6f, 70, 71, 72, 73,
  74, 75, 76, 77, 78, 79, 7a
nvchar                nvchar_max
1 abcdefghijklmnopqrstuvwxyz abcdefghijklmnopqrstuvwxyz

```

```

date_tz          date_tz
1 2014-01-01 14:12:09.019473 2014-01-01 14:12:09.01946

  dbWriteTable(con, name="TEST_TAB", value=test.df)
  res <- dbReadTable(con, name="TEST_TAB")
R> res
char
1 abcdefghijklmnopqrstuvwxyz
nchar
1 abcdefghijklmnopqrstuvwxyz
varchar
1 abcdefghijklmnopqrstuvwxyz
clob
1 abcdefghijklmnopqrstuvwxyz...
nclob
1 abcdefghijklmnopqrstuvwxyz...
raw.typ
1 61, 62, 63, 64, 65, 66, 67, 68, 69, 6a, 6b, 6c, 6d, 6e, 6f, 70, 71, 72, 73,
  74, 75, 76, 77, 78, 79, 7a
blob
1 61, 62, 63, 64, 65, 66, 67, 68, 69, 6a, 6b, 6c, 6d, 6e, 6f, 70, 71, 72, 73,
  74, 75, 76, 77, 78, 79, 7a,...
char_max
1 abcdefghijklmnopqrstuvwxyz
raw_max.typ
1 61, 62, 63, 64, 65, 66, 67, 68, 69, 6a, 6b, 6c, 6d, 6e, 6f, 70, 71, 72, 73,
  74, 75, 76, 77, 78, 79, 7a
nvchar          nvchar_max
1 abcdefghijklmnopqrstuvwxyz abcdefghijklmnopqrstuvwxyz
date_tz          date_tz
1 2014-01-01 14:12:09.019473 2014-01-01 14:12:09.01946

## End(Not run)
## Not run:
df <- data.frame(A=c(0,1,NaN,4), B=c(NA, 2,3,NaN))
con <- dbConnect(Oracle(), "scott", "tiger")
dbWriteTable(con,"TEST", df, row.names = FALSE, ora.number=FALSE)

## End(Not run)

```

dbSendQuery-methods *Execute a Statement on a Given Database Connection*

Description

These methods are straight-forward implementations of the corresponding generic functions except for the execute method, which is an ROracle specific DBI extension.

Usage

```

## S4 method for signature 'OraConnection,character'
dbSendQuery(conn, statement, data = NULL,
             prefetch = FALSE, bulk_read = 1000L, bulk_write = 1000L, ...)
## S4 method for signature 'OraConnection,character'
dbGetQuery(conn, statement, data = NULL,
            prefetch = FALSE, bulk_read = 1000L, bulk_write = 1000L, ...)
## S4 method for signature 'OraConnection,character'
oracleProc(conn, statement, data = NULL,
            prefetch = FALSE, bulk_read = 1000L, bulk_write = 1000L, ...)
## S4 method for signature 'OraResult'
dbClearResult(res, ...)
## S4 method for signature 'OraConnection'
dbGetException(conn, ...)

execute(res, ...)
## S4 method for signature 'OraResult'
execute(res, data = NULL, ...)

```

Arguments

conn	An OraConnection object.
statement	A character vector of length 1 with the SQL statement.
res	An OraResult object.
data	A data.frame specifying bind data
prefetch	A logical value that specifies whether ROracle uses prefetch buffers or an array fetch to retrieve data from the server. If TRUE, then ROracle uses OCI prefetch buffers to retrieve additional data from the server thus saving the memory required in RODBI/ROOCI by allocating a single row buffer to fetch the data from OCI. Using prefetch results in a fetch call for every row. If FALSE (the default), then ROracle uses an array fetch to retrieve the data.
bulk_read	An integer value indicating the number of rows to fetch at a time. The default value is 1000L. When the prefetch option is selected, memory is allocated for prefetch buffers and OCI fetches the specified number of rows at a time. When prefetch is not used, which is the default, memory is allocated in RODBI/ROOCI define buffers. Setting this to a large value results in more memory being allocated based on the number of columns in the select list and the types of columns. For a column of type character, define buffers are allocated using the maximum width times the NLS maximum width. An application should adjust this value based on the query result. A larger value benefits queries that return a large result. The application can tune this value as needed.
bulk_write	An integer value indicating the number of rows to write at a time. The default value is 1000L. When a bulk_write value is specified, memory is allocated for buffers and OCI writes that many rows at a time. If the bulk_write argument is not used, then the default value is used to allocate memory for the bind buffers. Setting bulk_write to a large value results in more memory being allocated based on the number of columns in the insert list and the types of columns.

... Currently unused.

Details

dbGetQuery This function executes a query statement and fetches the result data from the database. It should not be used for calling PL/SQL queries.

dbSendQuery This function executes a query statement and returns a result set to the application. The application can then perform operations on the result set. It should not be used for calling PL/SQL queries.

oracleProc This function executes a PL/SQL stored procedure or function query statement and returns the result.

dbClearResult This function frees resources used by result set.

dbGetException This function retrieves error information.

execute This function executes the specified query statement.

Value

dbSendQuery An OraResult object whose class extends DBIResult. This object is used to fetch data from a database, using the function fetch.

Side Effects

dbGetQuery Query statement is executed and data is fetched from database.

dbSendQuery Query statement is executed, but data needs to be fetched through calls to [fetch](#).

oracleProc PL/SQL stored procedure or function query statement is executed and result is returned.

dbClearResult Resources acquired by the result set are freed.

dbGetException Error information is retrieved and then cleaned from the driver.

execute Query statement is executed.

References

For the Oracle Database documentation see <http://www.oracle.com/technetwork/indexes/documentation/index.html>.

See Also

[Oracle](#), [dbDriver](#), [dbConnect](#), [fetch](#), [dbCommit](#), [dbGetInfo](#), [dbReadTable](#).

Examples

```
## Not run:
drv <- dbDriver("Oracle")
con <- dbConnect(drv, "scott", "tiger")
res <- dbSendQuery(con, "select * from emp where deptno = :1",
                  data = data.frame(deptno = 10))
data <- fetch(res, n = -1)
```

```

res2 <- dbSendQuery(con, "select * from emp where deptno = :1",
                    data1 <- data.frame(deptno = 10), prefetch=TRUE,
                    bulk_read=2L)
data1 <- fetch(res2, n = -1)
data1

res3 <- dbSendQuery(con, "select * from emp where deptno = :1",
                    data2 <- data.frame(deptno = 10), bulk_read=10L)
data2 <- fetch(res3, n = -1)
data2

res4 <- dbSendQuery(con, "select * from emp where deptno = :1",
                    data3 <- data.frame(deptno = 10), bulk_write=10L)
data3 <- fetch(res4, n = -1)
data3

res5 <- dbSendQuery(con, "select * from emp where ename = :1",
                    data4 <- data.frame(ename = 'SMITH'))
data4 <- fetch(res5, n = -1)
data4

## End(Not run)

```

ExtDriver-class

Class ExtDriver

Description

An Oracle extproc driver class implementing the R database interface (DBI) API.

Generators

The main generators are [dbDriver](#) and [Extproc](#).

Extends

Class "DBIDriver", directly. Class "DBIObject", by class "DBIDriver", distance 2.

Methods

dbConnect signature(drv = "ExtDriver"): ...
dbGetInfo signature(dbObj = "ExtDriver"): ...
dbListConnections signature(drv = "ExtDriver"): ...
dbUnloadDriver signature(drv = "ExtDriver"): ...
summary signature(object = "ExtDriver"): ...
show signature(object = "ExtDriver")

See Also

DBI classes: [OraConnection-class](#) [OraResult-class](#)

Examples

```
## Not run:  
con <- dbConnect(Extproc())  
  
## End(Not run)
```

fetch-methods

Fetch records from a previously executed query

Description

This method is a straight-forward implementation of the corresponding generic function.

Usage

```
## S4 method for signature 'OraResult'  
fetch(res, n = -1, ...)
```

Arguments

<code>res</code>	an <code>OraResult</code> object.
<code>n</code>	maximum number of records to retrieve per fetch. Use <code>n = -1</code> to retrieve all pending records.
<code>...</code>	currently unused.

Details

The `ROracle` implementations retrieves only `n` records, and if `n` is missing it returns all records.

Value

number of records fetched from database.

References

For the Oracle Database documentaion see <http://www.oracle.com/technetwork/indexes/documentation/index.html>.

See Also

[Oracle](#), [dbConnect](#), [dbSendQuery](#), [dbGetQuery](#), [dbClearResult](#), [dbCommit](#), [dbGetInfo](#), [dbReadTable](#).

Examples

```
## Not run:
drv <- dbDriver("Oracle")
con <- dbConnect(drv, "scott", "tiger")
res <- dbSendQuery(con, "select * from emp")

# we now fetch the first 10 records from the resultSet into a data.frame
data1 <- fetch(res, n = 10)
dim(data1)

dbHasCompleted(res)

# let's get all remaining records
data2 <- fetch(res, n = -1)

## End(Not run)
```

Oracle

Instantiate an Oracle client from the current R session

Description

This function creates and initializes an Oracle client from the current R session. It returns an object that allows you to connect to one or more Oracle servers.

Usage

```
Oracle(interruptible = FALSE, unicode_as_utf8 = TRUE,
       ora.attributes = FALSE)
Extproc(extproc.ctx = NULL)
```

Arguments

`interruptible` A logical indicating whether to allow user interrupts on long-running queries.

`extproc.ctx` An external pointer wrapping extproc context.

`unicode_as_utf8` A logical indicating whether to fetch NCHAR, NVARCHAR and NCLOB data encoded in UTF8.

`ora.attributes` A logical indicating whether to include the attributes `ora.encoding`, `ora.type`, and `ora.maxlength` in the data frames returned by `dbGetQuery` and `fetch`.

Details

This object is a singleton, that is, on subsequent invocations it returns the same initialized object.

This implementation allows you to connect to multiple host servers and run multiple connections on each server simultaneously.

When `interruptible` is set to `TRUE`, it allows for interrupting long-running queries on the server by executing the query in a thread. Main thread checks for Ctrl-C and issues `OCIBreak/OCIReset` to cancel the operation on the server. By default `interruptible` is `FALSE`.

When `unicode_as_utf8` is set to `FALSE`, `NCHAR`, `NVARCHAR` and `NCLOB` data is fetched using the character set using the `NLS_LANG` setting. By default `unicode_as_utf8` is set to `TRUE`.

When `ora.attributes` is set to `TRUE` attributes `ora.encoding`, `ora.type` and `ora.maxlength` are added in result data frame returned from `dbGetQuery` and `fetch`. It should be used with `dbWriteTable` to create the same data types as in the Oracle DBMS as fetched from the source table.

Value

An object of class `OraDriver` for Oracle or `ExtDriver` for `Extproc` whose class extends `DBIDriver`. This object is used to create connections, using the function `dbConnect`, to one or more Oracle database engines.

Side Effects

The R client part of the database communication is initialized, but note that connecting to the database engine needs to be done through calls to `dbConnect`.

Oracle user authentication

In order to establish a connection to an Oracle server users need to provide a user name, a password, and possibly a connect identifier (for more information refer to chapter 8 (Configuring Naming Methods) of Oracle Database Net Services Administrator's Guide). This is the same as the part of the SQL*Plus connect string that follows the '@' sign.

Connections to an Oracle TimesTen IMDB instance are established using the OCI tnsnames or easy connect naming methods. For additional information on TimesTen connections for OCI see chapter 3 (TimesTen Support for Oracle Call Interface) of the Oracle TimesTen In-Memory C Developer's Guide.

Transactions

The current implementation directly supports transaction commits and rollbacks on a connection-wide basis through calls to `dbCommit` and `dbRollback`. Save points are not yet directly implemented, but you may be able to define them and rollback to them through calls to dynamic SQL with `dbGetQuery`.

Notice that Oracle (and ANSI/ISO compliant DBMS) transactions are implicitly started when data definition SQL statements are executed (create table, etc.), which helper functions like `dbWriteTable` may execute behind the scenes. You may want or need to commit or roll back your work before issuing any of these helper functions.

References

For Oracle Database documentation, see <http://docs.oracle.com/en/database/>.

Author(s)

David A. James and Denis Mukhin

See Also

On database managers:

[dbDriver](#) [dbUnloadDriver](#) [dbListConnections](#)

On connections:

[dbConnect](#) [dbDisconnect](#) [dbSendQuery](#) [dbGetQuery](#) [dbGetException](#) [dbListResults](#)

Convenience methods: [dbListTables](#) [dbReadTable](#) [dbWriteTable](#) [dbExistsTable](#) [dbRemoveTable](#)
[dbListFields](#)

On transaction management:

[dbCommit](#) [dbRollback](#)

On queries and result objects:

[fetch](#) [dbClearResult](#) [dbColumnInfo](#) [dbGetStatement](#) [dbHasCompleted](#) [dbGetRowsAffected](#)
[dbGetRowCount](#)

On meta-data:

[show summary](#) [dbGetInfo](#)

Examples

```
## Not run:
## create a Oracle instance and create one connection.
ora <- Oracle()          ## or dbDriver("Oracle")
con <- dbConnect(ora, username = "scott", password = "tiger",
                 dbname = "inst1")

## if you are connecting to a local database
con <- dbConnect(ora, username = "scott", password = "tiger")

## execute a statement and fetch its output in chunks of no more
## than 5000 rows at a time
rs <- dbSendQuery(con, "select * from emp where deptno = 10")
while (!dbHasCompleted(rs)) {
  df <- fetch(rs, n = 5000)
  ## process df
}
dbClearResult(rs)      ## done with this query

## execute and fetch a statement with bind data
df <- dbGetQuery(con, "select * from emp where deptno = :1",
                 data = data.frame(deptno = 10))

## create a copy of emp table
dbGetQuery(con, "create table foo as select * from emp")

## execute and bind an INSERT statement
my.data = data.frame(empno = c(8001, 8002), ename = c('MUKHIN', 'ABOYOUN'))
more.data = data.frame(empno = c(8003), ename = c('JAMES'))
rs <- dbSendQuery(con, "insert into foo (empno, ename) values (:1, :2)",
                 data = my.data)
```

```

## execute with more data
execute(rs, data = more.data)
dbClearResult(rs)      ## done with this query

## ok, everything looks fine
dbCommit(con)

## a concise description of the driver
summary(ora)

## done with this connection
dbDisconnect(con)

## End(Not run)

```

OraConnection-class *Class OraConnection*

Description

An Oracle connection class implementing the R database interface (DBI) API.

Generators

The method [dbConnect](#) is the main generator.

Extends

Class "DBIConnection", directly. Class "DBIObject", by class "DBIConnection", distance 2.

Methods

```

dbDisconnect signature(conn = "OraConnection"): ...
dbSendQuery signature(conn = "OraConnection", statement = "character", prefetch = FALSE, bulk_read
= 1000L, bulk_write = 1000L): ...
dbGetQuery signature(conn = "OraConnection", statement = "character", prefetch = FALSE, bulk_read
= 1000L, bulk_write = 1000L): ...
dbGetException signature(conn = "OraConnection"): ...
dbListResults signature(conn = "OraConnection"): ...
dbListTables signature(conn = "OraConnection"): ...
dbReadTable signature(conn = "OraConnection", name = "character"): ...
dbWriteTable signature(conn = "OraConnection", name = "character", value = "data.frame"): ...
...
dbExistsTable signature(conn = "OraConnection", name = "character"): ...
dbRemoveTable signature(conn = "OraConnection", name = "character"): ...
dbListFields signature(conn = "OraConnection", name = "character"): ...

```

```

dbCommit signature(conn = "OraConnection"): ...
dbRollback signature(conn = "OraConnection"): ...
dbGetInfo signature(dbObj = "OraConnection"): ...
summary signature(object = "OraConnection"): ...
show signature(object = "OraConnection")

```

See Also

DBI classes: [OraDriver-class](#) [OraConnection-class](#) [OraResult-class](#)

Examples

```

## Not run:
ora <- dbDriver("Oracle")
## connecting without a connect string
con <- dbConnect(ora, "scott", "tiger")

## connecting with a connection string with SID
host <- "myhost"
port <- 1521
sid <- "mysid"
connect.string <- paste(
  "(DESCRIPTION=",
  "(ADDRESS=(PROTOCOL=tcp)(HOST=", host, ")(PORT=", port, "))",
  "(CONNECT_DATA=(SID=", sid, ")))", sep = "")

## use username/password authentication
con <- dbConnect(drv, username = "scott", password = "tiger",
  dbname = connect.string)

## connecting with a connection string with service name
host <- "myhost"
port <- 1521
svc <- "mydb.example.com"
connect.string <- paste(
  "(DESCRIPTION=",
  "(ADDRESS=(PROTOCOL=tcp)(HOST=", host, ")(PORT=", port, "))",
  "(CONNECT_DATA=(SERVICE_NAME=", svc, ")))", sep = "")
## use username/password authentication
con <- dbConnect(drv, username = "scott", password = "tiger",
  dbname = connect.string)

## Please refer to "Oracle Database Net Services Administrator's Guide", which
## has the topic "Connect Identifier and Connect Descriptor Syntax
## Characteristics"

dbListTables(con)

## End(Not run)

```

OraDriver-class	<i>Class OraDriver</i>
-----------------	------------------------

Description

An Oracle driver class implementing the R database interface (DBI) API.

Generators

The main generators are [dbDriver](#) and [Oracle](#).

Extends

Class "DBIDriver", directly. Class "DBIObject", by class "DBIDriver", distance 2.

Methods

dbConnect signature(drv = "OraDriver"): ...
dbGetInfo signature(dbObj = "OraDriver"): ...
dbListConnections signature(drv = "OraDriver"): ...
dbUnloadDriver signature(drv = "OraDriver"): ...
summary signature(object = "OraDriver"): ...
show signature(object = "OraDriver")

See Also

DBI classes: [OraConnection-class](#) [OraResult-class](#)

Examples

```
## Not run:  
# first load the library  
library("ROracle")  
ora <- dbDriver("Oracle")  
con <- dbConnect(ora, "scott", "tiger")  
  
## End(Not run)
```

OraResult-class	Class <i>OraResult</i>
-----------------	------------------------

Description

An Oracle query results class. This class encapsulates the result of a SQL statement.

Generators

The main generator is [dbSendQuery](#).

Extends

Class "DBIResult", directly. Class "DBIObject", by class "DBIResult", distance 2.

Methods

dbClearResult signature(res = "OraResult"): ...
dbColumnInfo signature(res = "OraResult"): ...
dbGetInfo signature(dbObj = "OraResult"): ...
dbGetStatement signature(res = "OraResult"): ...
dbGetRowCount signature(res = "OraResult"): ...
dbGetRowsAffected signature(res = "OraResult"): ...
dbHasCompleted signature(res = "OraResult"): ...
fetch signature(res = "OraResult", n = "numeric"): ...
fetch signature(res = "OraResult", n = "missing"): ...
execute signature(res = "OraResult"): ...
summary signature(object = "OraResult"): ...
show signature(object = "OraResult")

See Also

DBI classes: [OraDriver-class](#) [OraConnection-class](#) [OraResult-class](#)

Examples

```
## Not run:
ora <- dbDriver("Oracle")
con <- dbConnect(ora, "scott", "tiger")
res <- dbSendQuery(con, "select * from emp")
fetch(res, n = 2)
fetch(res)
dbColumnInfo(res)
dbClearResult(res)

## End(Not run)
```

summary-methods	<i>Summarize an Oracle object</i>
-----------------	-----------------------------------

Description

These methods are straight-forward implementations of the corresponding generic functions.

Usage

```
## S4 method for signature 'OraDriver'  
summary(object, ...)  
## S4 method for signature 'ExtDriver'  
summary(object, ...)  
## S4 method for signature 'OraConnection'  
summary(object, ...)  
## S4 method for signature 'OraResult'  
summary(object, ...)
```

Arguments

object	a driver, connection or result set object.
...	currently unused.

Value

description of object.

References

For the Oracle Database documentaion see <http://www.oracle.com/technetwork/indexes/documentation/index.html>.

See Also

[Oracle](#), [dbConnect](#), [dbSendQuery](#), [dbGetQuery](#), [dbClearResult](#), [dbCommit](#), [dbGetInfo](#), [dbGetInfo](#).

Examples

```
## Not run:  
drv <- dbDriver("Oracle")  
con <- dbConnect(drv, "scott", "tiger")  
res <- dbSendQuery(con, "select * from emp")  
  
summary(drv)  
summary(con)  
summary(res)  
show(drv)  
show(con)
```

```
    show(res)  
## End(Not run)
```

Index

* classes

ExtDriver-class, 30
OraConnection-class, 35
OraDriver-class, 37
OraResult-class, 38

* database

dbCommit-methods, 2
dbConnect-methods, 3
dbDriver-methods, 8
dbGetInfo-methods, 10
dbListConnections-methods, 17
dbReadTable-methods, 18
dbSendQuery-methods, 27
ExtDriver-class, 30
fetch-methods, 31
Oracle, 32
OraConnection-class, 35
OraDriver-class, 37
OraResult-class, 38
summary-methods, 39

* interface

dbCommit-methods, 2
dbConnect-methods, 3
dbDriver-methods, 8
dbGetInfo-methods, 10
dbListConnections-methods, 17
dbReadTable-methods, 18
dbSendQuery-methods, 27
ExtDriver-class, 30
fetch-methods, 31
Oracle, 32
OraConnection-class, 35
OraDriver-class, 37
OraResult-class, 38
summary-methods, 39

* methods

dbCommit-methods, 2
dbConnect-methods, 3
dbDriver-methods, 8

dbGetInfo-methods, 10
dbListConnections-methods, 17
dbReadTable-methods, 18
dbSendQuery-methods, 27
fetch-methods, 31
summary-methods, 39

dbClearResult, 31, 34, 39
dbClearResult (dbSendQuery-methods), 27
dbClearResult, OraResult-method
(dbSendQuery-methods), 27
dbColumnInfo, 17, 34
dbColumnInfo (dbGetInfo-methods), 10
dbColumnInfo, OraResult-method
(dbGetInfo-methods), 10
dbCommit, 2, 5, 10, 16, 24, 29, 31, 33, 34, 39
dbCommit (dbCommit-methods), 2
dbCommit, OraConnection-method
(dbCommit-methods), 2
dbCommit-methods, 2
dbConnect, 2, 5, 9, 10, 16, 17, 24, 29, 31,
33–35, 39
dbConnect (dbConnect-methods), 3
dbConnect, ExtDriver-method
(dbConnect-methods), 3
dbConnect, OraDriver-method
(dbConnect-methods), 3
dbConnect-methods, 3
dbDisconnect, 34
dbDisconnect (dbConnect-methods), 3
dbDisconnect, OraConnection-method
(dbConnect-methods), 3
dbDriver, 16, 17, 24, 29, 30, 34, 37
dbDriver-methods, 8
dbExistsTable, 34
dbExistsTable (dbReadTable-methods), 18
dbExistsTable, OraConnection, character-method
(dbReadTable-methods), 18
dbGetException, 34
dbGetException (dbSendQuery-methods), 27

- dbGetException, OraConnection-method
(dbSendQuery-methods), 27
- dbGetInfo, 2, 5, 10, 16, 17, 24, 29, 31, 34, 39
- dbGetInfo (dbGetInfo-methods), 10
- dbGetInfo, ExtDriver-method
(dbGetInfo-methods), 10
- dbGetInfo, OraConnection-method
(dbGetInfo-methods), 10
- dbGetInfo, OraDriver-method
(dbGetInfo-methods), 10
- dbGetInfo, OraResult-method
(dbGetInfo-methods), 10
- dbGetInfo-methods, 10
- dbGetQuery, 2, 5, 10, 16, 24, 31, 33, 34, 39
- dbGetQuery (dbSendQuery-methods), 27
- dbGetQuery, OraConnection, character-method
(dbSendQuery-methods), 27
- dbGetRowCount, 34
- dbGetRowCount (dbGetInfo-methods), 10
- dbGetRowCount, OraResult-method
(dbGetInfo-methods), 10
- dbGetRowsAffected, 34
- dbGetRowsAffected (dbGetInfo-methods),
10
- dbGetRowsAffected, OraResult-method
(dbGetInfo-methods), 10
- dbGetStatement, 34
- dbGetStatement (dbGetInfo-methods), 10
- dbGetStatement, OraResult-method
(dbGetInfo-methods), 10
- dbHasCompleted, 34
- dbHasCompleted (dbGetInfo-methods), 10
- dbHasCompleted, OraResult-method
(dbGetInfo-methods), 10
- dbListConnections, 34
- dbListConnections
(dbListConnections-methods), 17
- dbListConnections, ExtDriver-method
(dbListConnections-methods), 17
- dbListConnections, OraDriver-method
(dbListConnections-methods), 17
- dbListConnections-methods, 17
- dbListFields, 34
- dbListFields (dbReadTable-methods), 18
- dbListFields, OraConnection, character-method
(dbReadTable-methods), 18
- dbListResults, 34
- dbListResults
(dbListConnections-methods), 17
- dbListResults, OraConnection-method
(dbListConnections-methods), 17
- dbListTables, 10, 16, 34
- dbListTables (dbReadTable-methods), 18
- dbListTables, OraConnection-method
(dbReadTable-methods), 18
- dbReadTable, 2, 5, 10, 16, 29, 31, 34
- dbReadTable (dbReadTable-methods), 18
- dbReadTable, OraConnection, character-method
(dbReadTable-methods), 18
- dbReadTable-methods, 18
- dbRemoveTable, 34
- dbRemoveTable (dbReadTable-methods), 18
- dbRemoveTable, OraConnection, character-method
(dbReadTable-methods), 18
- dbRollback, 33, 34
- dbRollback (dbCommit-methods), 2
- dbRollback, OraConnection-method
(dbCommit-methods), 2
- dbSendQuery, 2, 5, 10, 16, 17, 24, 31, 34, 38,
39
- dbSendQuery (dbSendQuery-methods), 27
- dbSendQuery, OraConnection, character-method
(dbSendQuery-methods), 27
- dbSendQuery-methods, 27
- dbUnloadDriver, 34
- dbUnloadDriver (dbDriver-methods), 8
- dbUnloadDriver, ExtDriver-method
(dbDriver-methods), 8
- dbUnloadDriver, OraDriver-method
(dbDriver-methods), 8
- dbWriteTable, 33, 34
- dbWriteTable (dbReadTable-methods), 18
- dbWriteTable, OraConnection, character, data.frame-method
(dbReadTable-methods), 18
- execute (dbSendQuery-methods), 27
- execute, OraResult-method
(dbSendQuery-methods), 27
- ExtDriver-class, 30
- Extproc, 30
- Extproc (Oracle), 32
- fetch, 2, 5, 10, 16, 24, 29, 34
- fetch (fetch-methods), 31
- fetch, OraResult-method (fetch-methods),
31
- fetch-methods, 31

Oracle, [2](#), [5](#), [10](#), [16](#), [17](#), [24](#), [29](#), [31](#), [32](#), [37](#), [39](#)
oracleProc (dbSendQuery-methods), [27](#)
oracleProc, OraConnection, character-method
 (dbSendQuery-methods), [27](#)
OraConnection-class, [35](#)
OraDriver-class, [37](#)
OraResult-class, [38](#)

show, [34](#)
show, ExtDriver-method
 (summary-methods), [39](#)
show, OraConnection-method
 (summary-methods), [39](#)
show, OraDriver-method
 (summary-methods), [39](#)
show, OraResult-method
 (summary-methods), [39](#)
summary, [34](#)
summary, ExtDriver-method
 (summary-methods), [39](#)
summary, OraConnection-method
 (summary-methods), [39](#)
summary, OraDriver-method
 (summary-methods), [39](#)
summary, OraResult-method
 (summary-methods), [39](#)
summary-methods, [39](#)