

# Package ‘adass’

November 18, 2021

**Type** Package

**Title** Adaptive Smoothing Spline (AdaSS) Estimator for the Function-on-Function Linear Regression

**Version** 1.0.0

**Description** Implements the adaptive smoothing spline estimator for the function-on-function linear regression model described in Centofanti et al. (2020) <[arXiv:2011.12036](https://arxiv.org/abs/2011.12036)>.

**License** GPL-3

**Encoding** UTF-8

**Imports** fda, parallel, matrixcalc, SparseM, mvtnorm, Rfast, plot3D

**URL** <https://github.com/unina-sfere/adass>

**BugReports** <https://github.com/unina-sfere/adass>

**SystemRequirements** GNU make

**Suggests** knitr, rmarkdown, testthat

**RoxygenNote** 7.1.1

**NeedsCompilation** no

**Author** Fabio Centofanti [cre, aut],  
Antonio Lepore [aut],  
Alessandra Menafoglio [aut],  
Biagio Palumbo [aut],  
Simone Vantini [aut]

**Maintainer** Fabio Centofanti <[fabio.centofanti@unina.it](mailto:fabio.centofanti@unina.it)>

**Repository** CRAN

**Date/Publication** 2021-11-18 14:40:05 UTC

## R topics documented:

adass-package . . . . .	2
adass.fr . . . . .	3
adass.fr_eaass . . . . .	5
plot.adass . . . . .	7
simulate_data . . . . .	8

**Index****9**


---

<b>adass-package</b>	<i>Adaptive smoothing spline estimator for the function-on-function linear regression model</i>
----------------------	---

---

**Description**

Implements the adaptive smoothing spline estimator for the function-on-function linear regression model described in Centofanti et al. (2020) <arXiv:2011.12036>.

**Details**

Package:	adass
Type:	Package
Version:	1.0.0
Date:	2021-11-16
License:	GPL-3

**Author(s)**

Fabio Centofanti, Antonio Lepore, Alessandra Menafoglio, Biagio Palumbo, Simone Vantini

**References**

Centofanti, F., Lepore, A., Menafoglio, A., Palumbo, B., Vantini, S. (2020). Adaptive Smoothing Spline Estimator for the Function-on-Function Linear Regression Model. *arXiv preprint arXiv:2011.12036*.

**See Also**

[adass.fr](#), [adass.fr\\_eaass](#)

**Examples**

```
library(adass)
data<-simulate_data("Scenario HAT",n_obs=100)
X_fd=data$X_fd
Y_fd=data$Y_fd
basis_s <- fda::create.bspline.basis(c(0,1),nbasis = 10,norder = 4)
basis_t <- fda::create.bspline.basis(c(0,1),nbasis = 10,norder = 4)
mod_smooth <-adass.fr(Y_fd,X_fd,basis_s = basis_s,basis_t = basis_t,tun_par=c(10^-6,10^-6,0,0,0,0))
grid_s<-seq(0,1,length.out = 10)
grid_t<-seq(0,1,length.out = 10)
beta_der_eval_s<-fda::eval.bifd(grid_s,grid_t,mod_smooth$Beta_hat_fd,sLfdoj = 2)
```

```

beta_der_eval_t<-fdas::eval.bifd(grid_s,grid_t,mod_smooth$Beta_hat_fd,tLfdobj = 2)
mod_adsm<-adass.fr_eaass(Y_fd,X_fd,basis_s,basis_t,
                           beta_ders=beta_der_eval_s, beta_dert=beta_der_eval_t,
                           rand_search_par=list(c(-8,4),c(-8,4),c(0,0.1),c(0,4),c(0,0.1),c(0,4)),
                           grid_eval_ders=grid_s, grid_eval_dert=grid_t,
                           popul_size = 2,ncores=1,iter_num=1)

mod_opt <-adass.fr(Y_fd, X_fd, basis_s = basis_s, basis_t = basis_t,
                     tun_par=mod_adsm$tun_par,beta_ders = beta_der_eval_s,
                     beta_dert = beta_der_eval_t,grid_eval_ders=grid_s,grid_eval_dert=grid_t )
plot(mod_opt)

```

**adass.fr**

*Adaptive smoothing spline estimator for the function-on-function linear regression model*

**Description**

The adaptive smoothing spline (AdaSS) estimator for the function-on-function linear regression proposed in Centofanti et al., 2020.

**Usage**

```

adass.fr(
  Y_fd,
  X_fd,
  basis_s,
  basis_t,
  beta_ders = NULL,
  beta_dert = NULL,
  grid_eval_ders = NULL,
  grid_eval_dert = NULL,
  tun_par = c(lambda_s = 10^4, lambda_t = 10^4, delta_s = 0, gamma_s = 1, delta_t = 0,
             delta_t = 1),
  CV = FALSE,
  K = 10,
  X_fd_test = NULL,
  Y_fd_test = NULL
)

```

**Arguments**

- |                |   |
|----------------|---|
| <b>Y_fd</b>    | An object of class fd corresponding to the response functions.  |
| <b>X_fd</b>    | An object of class fd corresponding to the covariate functions. |
| <b>basis_s</b> | B-splines basis along the s-direction of class basisfd.         |
| <b>basis_t</b> | B-splines basis along the t-direction of class basisfd.         |

<code>beta_ders</code>	Initial estimate of the partial derivative of the coefficient function along the s-direction. Either a matrix or a class basisfd object. If NULL no adaptive penalty is used along the s-direction.
<code>beta_dert</code>	Initial estimate of the partial derivative of the coefficient function along the t-direction. Either a matrix or a class basisfd object. If NULL no adaptive penalty is used along the t-direction.
<code>grid_eval_ders</code>	Grid of evaluation of the partial derivatives along the s-direction.
<code>grid_eval_dert</code>	Grid of evaluation of the partial derivatives along the t-direction.
<code>tun_par</code>	Vector of tuning parameters.
<code>CV</code>	If TRUE the K-fold cross-validation prediction error is calculated. Default is FALSE. If <code>X_fd_test</code> and <code>Y_fd_test</code> are both provided the prediction error on the test set is calculated in place of the cross-validation prediction error when <code>CV</code> is TRUE.
<code>K</code>	Number of folds. Default is 10.
<code>X_fd_test</code>	Test set covariate functions. Default is NULL.
<code>Y_fd_test</code>	Test set response functions. Default is NULL.

### Value

A list containing the following arguments:

- `B`: The basis coefficients matrix estimate of the coefficient function.
- `Beta_hat_fd`: The coefficient function estimate of class bifd.
- `alpha`: The intercept function estimate.
- `tun_par`: Vector of tuning parameters.
- `CV`: Estimated prediction error.
- `CV_sd`: Standard error of the estimated prediction error.
- `Y_fd`: The response functions.
- `X_fd`: The covariate functions.

### References

Centofanti, F., Lepore, A., Menafoglio, A., Palumbo, B., Vantini, S. (2020). Adaptive Smoothing Spline Estimator for the Function-on-Function Linear Regression Model. *arXiv preprint arXiv:2011.12036*.

### See Also

[adass.fr\\_eaass](#)

### Examples

```
library(adass)
data<-simulate_data("Scenario HAT",n_obs=100)
X_fd=data$X_fd
Y_fd=data$Y_fd
```

```

basis_s <- fda::create.bspline.basis(c(0,1),nbasis = 10,norder = 4)
basis_t <- fda::create.bspline.basis(c(0,1),nbasis = 10,norder = 4)
mod_smooth <-adass.fr(Y_fd,X_fd,basis_s = basis_s,basis_t = basis_t,tun_par=c(10^-6,10^-6,0,0,0,0))
grid_s<-seq(0,1,length.out = 10)
grid_t<-seq(0,1,length.out = 10)
beta_der_eval_s<-fda::eval.bifd(grid_s,grid_t,mod_smooth$Beta_hat_fd,sLfobj = 2)
beta_der_eval_t<-fda::eval.bifd(grid_s,grid_t,mod_smooth$Beta_hat_fd,tLfobj = 2)
mod_adass <-adass.fr(Y_fd, X_fd, basis_s = basis_s, basis_t = basis_t,
                      tun_par=c(10^-6,10^-6,0,1,0,1),beta_ders = beta_der_eval_s,
                      beta_dert = beta_der_eval_t,grid_eval_ders=grid_s,grid_eval_dert=grid_t )

```

adass.fr\_eaass

*Evolutionary algorithm for the adaptive smoothing spline estimator (EAASS).*

## Description

EAASS algorithm to choose the tuning parameters for the AdaSS estimator (Centofanti et al., 2020).

## Usage

```

adass.fr_eaass(
  Y_fd,
  X_fd,
  basis_s,
  basis_t,
  beta_ders = NULL,
  beta_dert = NULL,
  grid_eval_ders = NULL,
  grid_eval_dert = NULL,
  rand_search_par = list(c(-4, 4), c(-4, 4), c(0, 1, 5, 10, 15), c(0, 1, 2, 3, 4), c(0,
    1, 5, 10, 15), c(0, 1, 2, 3, 4)),
  popul_size = 12,
  iter_num = 10,
  r = 0.2,
  pert_vec = c(0.8, 1.2),
  X_fd_test = NULL,
  Y_fd_test = NULL,
  progress = TRUE,
  ncores = 1,
  K = 10
)

```

## Arguments

- |      |   |
|------|---|
| Y_fd | An object of class fd corresponding to the response functions.  |
| X_fd | An object of class fd corresponding to the covariate functions. |

<b>basis_s</b>	B-splines basis along the s-direction of class basisfd.
<b>basis_t</b>	B-splines basis along the t-direction of class basisfd.
<b>beta_ders</b>	Initial estimate of the partial derivative of the coefficient function along the s-direction. Either a matrix or a class basisfd object. If NULL no adaptive penalty is used along the s-direction.
<b>beta_dert</b>	Initial estimate of the partial derivative of the coefficient function along the t-direction. Either a matrix or a class basisfd object. If NULL no adaptive penalty is used along the t-direction.
<b>grid_eval_ders</b>	Grid of evaluation of the partial derivatives along the s-direction.
<b>grid_eval_dert</b>	Grid of evaluation of the partial derivatives along the t-direction.
<b>rand_search_par</b>	List containing the initial population ranges for the tuning parameters.
<b>popul_size</b>	Initial population size.
<b>iter_num</b>	Algorithm iterations.
<b>r</b>	Truncation parameter in the exploitation phase.
<b>pert_vec</b>	Perturbation parameters in the exploration phase.
<b>X_fd_test</b>	Test set covariate functions. Default is NULL. If X_fd_test and Y_fd_test are both provided the prediction error on the test set is used as performance metric in place of the cross-validation prediction error.
<b>Y_fd_test</b>	Test set response functions. Default is NULL. If X_fd_test and Y_fd_test are both provided the prediction error on the test set is used as performance metric in place of the cross-validation prediction error.
<b>progress</b>	If TRUE a progress bar is printed. Default is TRUE.
<b>ncores</b>	If ncores>1, then parallel computing is used, with ncores cores. Default is 1.
<b>K</b>	Number of folds. Default is 10.

## Value

A list containing the following arguments:

- **tun\_par\_opt**: Vector of optimal tuning parameters.
- **CV**: Estimated prediction errors.
- **CV\_sd**: Standard errors of the estimated prediction errors.
- **comb\_list**: The combinations of tuning parameters explored.
- **Y\_fd**: The response functions.
- **X\_fd**: The covariate functions.

## References

Centofanti, F., Lepore, A., Menafoglio, A., Palumbo, B., Vantini, S. (2020). Adaptive Smoothing Spline Estimator for the Function-on-Function Linear Regression Model. *arXiv preprint arXiv:2011.12036*.

**See Also**[adass.fr\\_eaass](#)**Examples**

```
library(adass)
data<-simulate_data("Scenario HAT",n_obs=100)
X_fd=data$X_fd
Y_fd=data$Y_fd
basis_s <- fda::create.bspline.basis(c(0,1),nbasis = 5,norder = 4)
basis_t <- fda::create.bspline.basis(c(0,1),nbasis = 5,norder = 4)
mod_smooth <-adass.fr(Y_fd,X_fd,basis_s = basis_s,basis_t = basis_t,tun_par=c(10^-6,10^-6,0,0,0,0))
grid_s<-seq(0,1,length.out = 5)
grid_t<-seq(0,1,length.out = 5)
beta_der_eval_s<-fda::eval.bifd(grid_s,grid_t,mod_smooth$Beta_hat_fd,sLfdoj = 2)
beta_der_eval_t<-fda::eval.bifd(grid_s,grid_t,mod_smooth$Beta_hat_fd,tLfdoj = 2)
mod_adsm<-adass.fr_eaass(Y_fd,X_fd,basis_s,basis_t,
                           beta_ders=beta_der_eval_s, beta_dert=beta_der_eval_t,
                           rand_search_par=list(c(-8,4),c(-8,4),c(0,0.1),c(0,4),c(0,0.1),c(0,4)),
                           grid_eval_ders=grid_s, grid_eval_dert=grid_t,
                           popul_size = 1,ncores=1,iter_num=1)
```

**plot.adass***Plot the results of the AdaSS method***Description**

This function provides plots of the AdaSS coefficient function estimate when applied to the output of `adass.fr`.

**Usage**

```
## S3 method for class 'adass'
plot(x, ...)
```

**Arguments**

- `x` The output of `adass.fr`.
- `...` No additional parameters, called for side effects.

**Value**

No return value, called for side effects.

## Examples

```
library(adass)
data<-simulate_data("Scenario HAT",n_obs=100)
X_fd=data$X_fd
Y_fd=data$Y_fd
basis_s <- fda::create.bspline.basis(c(0,1),nbasis = 10,norder = 4)
basis_t <- fda::create.bspline.basis(c(0,1),nbasis = 10,norder = 4)
mod_adass <- adass.fr(Y_fd,X_fd,basis_s = basis_s, basis_t = basis_t,
  tun_par=c(10^-6,10^-6,0,0,0,0))
plot(mod_adass)
```

**simulate\_data**

*Simulate data through the function-on-function linear regression model*

## Description

Generate synthetic data as in the simulation study of Centofanti et al. (2020).

## Usage

```
simulate_data(scenario, n_obs = 3000)
```

## Arguments

- |          |   |
|----------|---|
| scenario | A character strings indicating the scenario considered. It could be "Scenario HAT", "Scenario DAMP", or "Scenario RCHANGE". |
| n_obs    | Number of observations.   |

## Value

A list containing the following arguments:

- X: Covariate matrix, where the rows correspond to argument values and columns to replications.
- Y: Response matrix, where the rows correspond to argument values and columns to replications.
- X\_fd: Coavariate functions.
- Y\_fd: Response functions.
- Beta\_vero\_fd: The true coefficient function.

## References

Centofanti, F., Lepore, A., Menafoglio, A., Palumbo, B., Vantini, S. (2020). Adaptive Smoothing Spline Estimator for the Function-on-Function Linear Regression Model. *arXiv preprint arXiv:2011.12036*.

## Examples

```
library(adass)
data<-simulate_data("Scenario HAT",n_obs=100)
```

# Index

adass (adass-package), 2

adass-package, 2

adass.fr, 2, 3

adass.fr\_eaass, 2, 4, 5, 7

plot.adass, 7

simulate\_data, 8