

Package ‘bSims’

December 20, 2019

Type Package

Title Bird Point Count Simulator

Version 0.2-1

Date 2019-12-16

Author Peter Solymos [aut, cre] (<<https://orcid.org/0000-0001-7337-1740>>)

Maintainer Peter Solymos <solymos@ualberta.ca>

Description A highly scientific and utterly addictive bird point count simulator to test statistical assumptions, aid survey design, and have fun while doing it. The simulations follow time-removal and distance sampling models based on Matsuoka et al. (2012) <[doi:10.1525/auk.2012.11190](https://doi.org/10.1525/auk.2012.11190)>, Solymos et al. (2013) <[doi:10.1111/2041-210X.12106](https://doi.org/10.1111/2041-210X.12106)>, and Solymos et al. (2018) <[doi:10.1650/CONDOR-18-32.1](https://doi.org/10.1650/CONDOR-18-32.1)>, and sound attenuation experiments by Yip et al. (2017) <[doi:10.1650/CONDOR-16-93.1](https://doi.org/10.1650/CONDOR-16-93.1)>.

License GPL-2

LazyLoad yes

LazyData true

Depends intrval, mefa4, MASS, deldir

Imports parallel, pbapply

URL <https://github.com/psolymos/bSims>

BugReports <https://github.com/psolymos/bSims/issues>

Suggests knitr, rmarkdown, detect, shiny

VignetteBuilder knitr

NeedsCompilation no

Repository CRAN

Date/Publication 2019-12-20 13:40:05 UTC

R topics documented:

acceptreject	2
bsims_init	3
dist_fun2	7
estimate	9
events	11
expand_list	12
get_nests	13
plot.bsims_landscape	15
rlnorm2	18
rmvn	19
run_app	20
Index	21

acceptreject	<i>Spatial point process simulator</i>
--------------	--

Description

Spatial point process simulator based on accept/reject algorithm.

Usage

```
acceptreject(n, f = NULL, x0 = 0, x1 = 1, y0 = 0, y1 = 1,
            m = 0, maxit = 100, fail = FALSE)
```

Arguments

n	number of points to generate.
f	a function returning probability (value between 0 and 1) given distance as the first and only argument. The function generates spatially uniform Poisson point process (complete spatial randomness) when NULL.
x0, x1, y0, y1	x and y ranges (bounding box).
m	margin width for avoiding edge effects.
maxit	maximum number of iterations per point to try if no acceptance happens.
fail	logical, what to do when there is a problem. TRUE gives error, the default FALSE gives only a warning.

Value

A matrix with n rows and 2 columns for x and y coordinates.

Author(s)

Peter Solymos

Examples

```

## complete spatial randomness
plot(acceptreject(100), asp=1)

## more systematic
distance <- seq(0,1,0.01)
f <- function(d)
  (1-exp(-d^2/0.1^2) + dlnorm(d, 0.2)/dlnorm(exp(0.2-1),0.2)) / 2
op <- par(mfrow = c(1, 2))
plot(distance, f(distance), type="l")
plot(acceptreject(100, f, m=1), asp=1)
par(op)

## more clustered
f <- function(d)
  exp(-d^2/0.1^2) + 0.5*(1-exp(-d^2/0.4^2))
op <- par(mfrow = c(1, 2))
plot(distance, f(distance), type="l")
plot(acceptreject(100, f, m=1), asp=1)
par(op)

```

bsims_init

bSims simulation functions

Description

Functions to initialize, populate, animate, detect, and transcribe simulated birds in a point count.

Usage

```
bsims_init(extent = 10, road = 0, edge = 0, offset = 0)
```

```
bsims_populate(x, density = 1, abund_fun = NULL, xy_fun = NULL,
  margin = 0, maxit = 100, fail = FALSE, ...)
```

```
bsims_animate(x, vocal_rate = 1, move_rate = 0, duration = 10,
  movement = 0, mixture = 1, avoid = c("none", "R", "ER"),
  initial_location=FALSE, allow_overlap=TRUE, ...)
```

```
bsims_detect(x, xy = c(0, 0), tau = 1, dist_fun = NULL,
  event_type = c("vocal", "move", "both"), ...)
```

```
bsims_transcribe(x, tint = NULL, rint = Inf, error = 0,
  condition=c("event1", "det1", "alldet"),
  event_type=NULL, perception=NULL, ...)
```

```
bsims_all(...)
```

```

## S3 method for class 'bsims_landscape'
print(x, ...)
## S3 method for class 'bsims_population'
print(x, ...)
## S3 method for class 'bsims_events'
print(x, ...)
## S3 method for class 'bsims_detections'
print(x, ...)
## S3 method for class 'bsims_transcript'
print(x, ...)
## S3 method for class 'bsims_all'
print(x, ...)

```

Arguments

extent	extent of simulation area, an extent x extent square with (0,0) at the center.
road	half width of the road stratum (perpendicular to the y axis).
edge	width of edge, same width on both sides of the road stratum.
offset	offset to apply to road and edge strata relative to the center in the x direction.
x	a simulation object.
density	population density, D, recycled 3x for the 3 strata (H: habitat, E: edge, R: road).
abund_fun	function to simulate abundance, $N \sim \text{Poisson}(\lambda)$, $\lambda = DA$ by default.
xy_fun	function used to simulate nest locations, see acceptreject . The function should return probability (value between 0 and 1), NULL means complete spatial randomness.
margin, maxit, fail	arguments passed to acceptreject when using xy_fun to simulate nest locations.
vocal_rate, move_rate	Vocal and movement rates (see events). Both of these rates can be: a single number; a vector of length <code>length(mixture)</code> (behavior based finite mixture groups); a vector of length 3 with <code>mixture=1</code> (corresponding to HER strata); or a matrix of dimension 3 x <code>length(mixture)</code> (HER strata x number of behavior based groups).
duration	total time duration to consider (in minutes), passed to events .
movement	standard deviation for a bivariate Normal kernel to simulate locations centered at the nest location, passed to events . Can refer to the same stratum and behavior based groups as <code>move_rate</code> .
mixture	behavior based finite mixture group proportions.
avoid	range along the x axis to avoid with respect to movement locations, passed to events .
initial_location	logical, <code>move_rate</code> and <code>vocal_rate</code> are silently ignored if TRUE and nest locations are provided as part of the events table. This renders all individuals equally available for detection.

allow_overlap	logical, allowing overlap between neighboring nests when movement is involved. If FALSE, Voronoi tessellation is used to prevent overlap. If TRUE, the unconstrained bivariate Normal kernel is used.
xy	a vector of x and y coordinates describing the position of the observer.
tau	parameter of the distance function. Can be a single numeric value or a vector of length 3 to provide parameter in the 3 strata (H: habitat, E: edge, R: road). Segmented sound attenuation is used when the values are different in the 3 strata (see dist_fun2).
dist_fun	distance function (1st argument is distance, second is tau).
event_type	type of events to access (vocal, movement, or both). Inherits value from input object when NULL.
tint	time interval break points in minutes.
rint	distance interval break points in units of 100 meter.
condition	conditioning type to define availability for each individual: "event1": the 1st event (detected or not); "det1": the 1st detection; "alldet": all detections (counting the same individual multiple times).
error	log scale standard deviation for distance estimation error, see rlnorm2 .
perception	perceived number of individuals relative to the actual number of individuals. A non-negative number (<1 values lead to under counting, >1 values lead to over counting), or NULL (observer correctly identifies all individuals).
...	other arguments passed to underlying functions. For the <code>bsims_all</code> wrapper, it means all the arguments (except for <code>x</code>) that the underlying <code>bsims_*</code> functions have. <code>bsims_all</code> can also take a single list as its argument.

Details

The functions capturing the simulation layers are supposed to be called in sequence, allowing to simulate multiple realities by keeping preceding layers intact. Construction allows easy piping. The `bsims_all` function is a wrapper for the `bsims_*` layer functions.

The simulations follow time-removal and distance sampling models based on Matsuoka et al. (2012) <doi:10.1525/auk.2012.11190>, Solymos et al. (2013) <doi:10.1111/2041-210X.12106>, and Solymos et al. (2018) <doi:10.1650/CONDOR-18-32.1>, and sound attenuation experiments by Yip et al. (2017) <doi:10.1650/CONDOR-16-93.1>.

Value

`bsims_init` returns a landscape object.

`bsims_populate` returns a population object.

`bsims_animate` returns an events object.

`bsims_detect` returns a detections object.

`bsims_transcribe` returns a transcript object.

`get_table` returns the removal table.

`bsims_all` returns a closure with `$settings()`, `$new(recover = FALSE)`, and `$replicate(B, recover = FALSE, c1 = NULL)` functions. The `settings` function returns the input arguments as a list; the `new`

function returns a single transcript object; the replicate function takes an argument for the number of replicates (B) and returns a list of transcript objects with B elements. The c1 argument is used to parallelize the work, can be a numeric value on Unix/Linux/OSX, or a cluster object on any OS, see examples. The 'recover = TRUE' argument allows to run simulations with error catching based on `try`.

Note that simulated objects returned by `bsims_all` will contain different realizations and all the conditionally independent layers. Use a layered approach if former layers are meant to be kept identical across runs.

Author(s)

Peter Solymos

References

- Matsuoka, S. M., Bayne, E. M., Solymos, P., Fontaine, P., Cumming, S. G., Schmiegelow, F. K. A., & Song, S. A., 2012. Using binomial distance-sampling models to estimate the effective detection radius of point-counts surveys across boreal Canada. *Auk*, **129**: 268–282. <doi:10.1525/auk.2012.11190>
- Solymos, P., Matsuoka, S. M., Bayne, E. M., Lele, S. R., Fontaine, P., Cumming, S. G., Stralberg, D., Schmiegelow, F. K. A. & Song, S. J., 2013. Calibrating indices of avian density from non-standardized survey data: making the most of a messy situation. *Methods in Ecology and Evolution*, **4**: 1047–1058. <doi:10.1111/2041-210X.12106>
- Solymos, P., Matsuoka, S. M., Cumming, S. G., Stralberg, D., Fontaine, P., Schmiegelow, F. K. A., Song, S. J., and Bayne, E. M., 2018. Evaluating time-removal models for estimating availability of boreal birds during point-count surveys: sample size requirements and model complexity. *Condor*, **120**: 765–786. <doi:10.1650/CONDOR-18-32.1>
- Yip, D. A., Bayne, E. M., Solymos, P., Campbell, J., and Proppe, J. D., 2017. Sound attenuation in forested and roadside environments: implications for avian point count surveys. *Condor*, **119**: 73–84. <doi:10.1650/CONDOR-16-93.1>

See Also

Plotting functions: [plot.bsims_landscape](#)

Getter functions: [get_nests](#), [get_events](#), [get_detections](#), [get_abundance](#), [get_density](#) [get_table](#)

Shiny apps: [run_app](#)

[acceptreject](#), [events](#), [estimate](#)

Examples

```
phi <- 0.5
tau <- 1:3
dur <- 10
rbr <- c(0.5, 1, 1.5, Inf)
tbr <- c(3, 5, 10)
(l <- bsims_init(10, 0.5, 1))
(p <- bsims_populate(l, 1))
(a <- bsims_animate(p, vocal_rate=phi, duration=dur))
(o <- bsims_detect(a, tau=tau))
```

```

(x <- bsims_transcribe(o, tint=tbr, rint=rbr))

plot(x)
get_table(x, "removal")
get_table(x, "visits")

head(get_events(a))
plot(get_events(a))

head(get_detections(o))
plot(get_detections(o), "time")
plot(get_detections(o), "distance")

## wrapper function for all the bsims_* layers
b <- bsims_all(road=1, density=0.5, tint=tbr, rint=rbr)
## alternatively: supply a list
#settings <- list(road=1, density=0.5, tint=tbr, rint=rbr)
#b <- bsims_all(settings)
b$settings()
b$new()
bb <- b$replicate(3)
lapply(bb, get_table)

## parallel simulations
library(parallel)
b <- bsims_all(density=0.5)
B <- 4 # number of runs
nc <- 2 # number of cores
## sequential
system.time(bb <- b$replicate(B, cl=NULL))
## parallel clusters
cl <- makeCluster(nc)
## note: loading the package is optional
system.time(clusterEvalQ(cl, library(bSims)))
system.time(bb <- b$replicate(B, cl=cl))
stopCluster(cl)
## parallel forking
if (.Platform$OS.type != "windows") {
  system.time(bb <- b$replicate(B, cl=nc))
}

```

Description

Distance function with segmented attenuation crossing a number of boundaries of strata with different attenuation characteristics following results in Yip et al. (2017).

Usage

```
dist_fun2(d, tau, dist_fun, breaks = numeric(0), ...)
```

Arguments

d	distance from observer.
tau	a parameter passed to the the distance function. Length of tau must equal length(b) + 1 referring to distance function parameters in the different strata (a stratum is defined by an interval surrounded by 1 or 2 boundaries).
dist_fun	distance function taking two arguments: distance, and tau, see examples.
breaks	distance breakpoints, must be length(tau) -1 in length. These breakpoints represent the boundaries between the intervals characterized by homogeneous attenuation characteristics.
...	other arguments passed to dist_fun

Value

Probability of detection given the distance, stratum specific parameters and the arrangement of breakpoints.

Author(s)

Peter Solymos

References

Yip, D. A., Bayne, E. M., Solymos, P., Campbell, J., and Proppe, J. D., 2017. Sound attenuation in forested and roadside environments: implications for avian point count surveys. *Condor*, **119**: 73–84. <doi:10.1650/CONDOR-16-93.1>

Examples

```
tau <- c(1, 2, 3, 2, 1)
d <- seq(0, 4, 0.01)
dist_fun <- function(d, tau) exp(-(d/tau)^2) # half normal
#dist_fun <- function(d, tau) exp(-d/tau) # exponential
#dist_fun <- function(d, tau) 1-exp(-(d/tau)^-2) # hazard rate

b <- c(0.5, 1, 1.5, 2) # boundaries

op <- par(mfrow=c(2, 1))
plot(d, dist_fun2(d, tau[1], dist_fun), type="n",
      ylab="P(detection)", xlab="Distance", axes=FALSE,
      main="Sound travels from left to right")
axis(1)
axis(2)
for (i in seq_len(length(b)+1)) {
  x1 <- c(0, b, 4)[i]
  x2 <- c(0, b, 4)[i+1]
```

```

    polygon(c(0, b, 4)[c(i, i, i+1, i+1)], c(0, 1, 1, 0),
            border=NA,
            col=c("darkolivegreen1", "burlywood1", "lightgrey",
                  "burlywood1", "darkolivegreen1")[i])
  }
  lines(d, dist_fun2(d, tau[1], dist_fun))
  lines(d, dist_fun2(d, tau[2], dist_fun))
  lines(d, dist_fun2(d, tau[3], dist_fun))
  lines(d, dist_fun2(d, tau, dist_fun, b), col=2, lwd=3)

  plot(rev(d), dist_fun2(d, tau[1], dist_fun), type="n",
        ylab="P(detection)", xlab="Distance", axes=FALSE,
        main="Sound travels from right to left")
  axis(1)
  axis(2)
  for (i in seq_len(length(b)+1)) {
    x1 <- c(0, b, 4)[i]
    x2 <- c(0, b, 4)[i+1]
    polygon(c(0, b, 4)[c(i, i, i+1, i+1)], c(0, 1, 1, 0),
            border=NA,
            col=c("darkolivegreen1", "burlywood1", "lightgrey",
                  "burlywood1", "darkolivegreen1")[i])
  }
  lines(rev(d), dist_fun2(d, tau[1], dist_fun))
  lines(rev(d), dist_fun2(d, tau[2], dist_fun))
  lines(rev(d), dist_fun2(d, tau[3], dist_fun))
  lines(rev(d), dist_fun2(d, tau, dist_fun, rev(4-b)), col=2, lwd=3)
  par(op)

```

 estimate

Estimate basic parameters

Description

Estimate singing rates, effective distances, and density based on simulation objects using the QPAD approach (Solymos et al. 2013).

Usage

```

estimate(object, ...)
## S3 method for class 'bsims_transcript'
estimate(object, ...)

```

Arguments

object	simulation object.
...	other arguments passed to internal functions.

Details

The method evaluates removal design to estimate model parameters and density using the QPAD methodology using the 'detect' package.

The function only works with multiple time and distance intervals. It returns NA otherwise.

Value

A vector with values for singing rate (ϕ), effective detection distance (τ), and density.

Author(s)

Peter Solymos

References

Solymos, P., Matsuoka, S. M., Bayne, E. M., Lele, S. R., Fontaine, P., Cumming, S. G., Stralberg, D., Schmiegelow, F. K. A. & Song, S. J., 2013. Calibrating indices of avian density from non-standardized survey data: making the most of a messy situation. *Methods in Ecology and Evolution*, 4: 1047–1058. <doi:10.1111/2041-210X.12106>

See Also

[bsims_init](#)

Examples

```
set.seed(2)
phi <- 0.5                # singing rate
tau <- 1                  # EDR by strata
dur <- 10                 # simulation duration
tbr <- c(2, 4, 6, 8, 10) # time intervals
rbr <- c(0.5, 1, 1.5, Inf) # counting radii

l <- bsims_init(10, 0.5, 1) # landscape
p <- bsims_populate(l, 10) # population
e <- bsims_animate(p,      # events
  vocal_rate=phi, duration=dur)
d <- bsims_detect(e,      # detections
  tau=tau)
x <- bsims_transcribe(d,  # transcription
  tint=tbr, rint=rbr)

estimate(x)
```

events

Event time simulator

Description

`timetoevent` turns exponential wait times to time-to-event data within a desired duration, it handles 0 and infinite rates in a robust manner. `events` simulates event times based on an exponential time-to-event distribution.

Usage

```
timetoevent(rate, duration)
```

```
events(vocal_rate = 1, move_rate = 1, duration = 10,  
       movement = 0, avoid = c(0, 0))
```

Arguments

<code>rate</code>	rate for the exponential distribution (rexp).
<code>duration</code>	total time duration to consider (in minutes).
<code>vocal_rate</code>	vocal rate for exponential distribution (rexp), how often a vocal event happens per minute.
<code>move_rate</code>	movement rate for exponential distribution (rexp), how often a movement event happens per minute.
<code>movement</code>	standard deviation for a bivariate Normal kernel to simulate locations centered at the nest location.
<code>avoid</code>	range along the x axis to avoid with respect to movement locations, i.e. location for a movement event within this interval will be rejected and a new location drawn.

Value

An events object data frame with coordinates (x, y; centered at 0 that is nest location), event times (t) and indicator for vocal events (v).

Author(s)

Peter Solymos

See Also

[rexp](#)

Examples

```

timetoevent(0, 10)
timetoevent(Inf, 10)

rr <- 1
tt <- timetoevent(rr, 10)
op <- par(mfrow=c(1,2))
plot(ecdf(tt))
curve(1-exp(-rr*x), add=TRUE, col=2) # cdf

plot(stepfun(sort(tt), 0:length(tt)/length(tt)), ylab="F(x)")
curve(1-exp(-rr*x), add=TRUE, col=2) # cdf
par(op)

e <- events(movement=1, duration=60)
mx <- max(abs(e[,1:2]))
plot(e[,1:2], col="grey", type="l", asp=1,
     xlim=2*c(-mx, mx), ylim=2*c(-mx, mx))
points(e[,1:2], col=e$v+1)
abline(h=0, v=0, lty=2)
legend("topright", pch=21, col=1:2, horiz=TRUE,
      legend=c("movement", "vocalization"))

```

expand_list

Create a list from all combinations of arguments

Description

Create a list from all combinations of the supplied vectors or lists.

Usage

```
expand_list(...)
```

Arguments

... vectors or lists. All arguments must be named.

Value

A list containing one element for each combination of the supplied vectors and lists. The first factors vary fastest. The nested elements are labeled by the factors.

The function allows list elements to be vectors, functions, or NULL. If a vector element is supposed to be kept as a vector, use `list()`.

Author(s)

Peter Solymos

See Also[expand.grid](#)**Examples**

```
b <- expand_list(
  movement = c(0, 1, 2),
  rint = list(c(0.5, 1, 1.5, Inf)), # in a list to keep as one
  xy_fun = list(NULL, function(z) z))
b[[1]]
str(b)
```

`get_nests`*Access nests, events, detections, and totals*

Description

Access nests, events, detections, abundance, and density from simulation objects.

Usage

```
get_nests(x, ...)
## S3 method for class 'bsims_population'
get_nests(x, ...)

get_events(x, ...)
## S3 method for class 'bsims_events'
get_events(x, ...)

get_detections(x, ...)
## S3 method for class 'bsims_detections'
get_detections(x, ...)

get_abundance(x, ...)
## S3 method for class 'bsims_population'
get_abundance(x, ...)

get_density(x, ...)
## S3 method for class 'bsims_population'
get_density(x, ...)

get_table(x, ...)
## S3 method for class 'bsims_transcript'
get_table(x,
  type = c("removal", "visits"), ...)
```

Arguments

x	simulation object.
type	character, the type of table to return: "removal" includes only new individuals as time progresses, "visits" counts individuals in each time interval independent of each other.
...	other arguments passed to internal functions.

Details

get_nests extracts the next locations.

get_events extracts the events.

get_detections extracts the detections.

get_abundance gets the realized total abundance (N), get_density gets the realized average density (abundance/area: N/A).

get_table returns the removal or visits table.

Value

get_abundance and get_density returns a non-negative numeric value.

get_nests returns a data frame with the following columns: i individual identifier, s spatial stratum (H: habitat, E: edge, R: road) x and y are coordinates of the nest locations, g is behavioral (mixture) group or NA.

get_events returns a data frame with the following columns: x and y are locations of the individual at the time of the event, t time of the event within the duration interval, v indicator variable for vocal (1) vs. movement (0) event, i individual identifier.

get_detections returns a data frame with the following columns: x and y are locations of the individual at the time of the event, t time of the event within the duration interval, v indicator variable for vocal (1) vs. movement (0) event, d distance from observer when detected (otherwise NA). i individual identifier, j perceived individual identifier.

get_table returns a matrix with distance bands as rows and time intervals as columns. The cell values are counts if the individuals detected in a removal fashion (only new individuals counter over the time periods) or in a multiple-visits fashion (counting of individuals restarts in every time interval).

Author(s)

Peter Solymos

See Also

[bsims_init](#)

Examples

```
phi <- 0.5           # singing rate
tau <- 1:3          # EDR by strata
dur <- 10           # simulation duration
tbr <- c(3, 5, 10)  # time intervals
rbr <- c(0.5, 1, 1.5, Inf) # counting radii

l <- bsims_init(10, 0.5, 1) # landscape
p <- bsims_populate(l, 1) # population
e <- bsims_animate(p,      # events
  vocal_rate=phi, duration=dur)
d <- bsims_detect(e,      # detections
  tau=tau)
x <- bsims_transcribe(d,  # transcription
  tint=tbr, rint=rbr)

## next locations
head(get_nests(p))
head(get_nests(e))
head(get_nests(d))
head(get_nests(x))

## abundance
get_abundance(p)
get_abundance(e)
get_abundance(d)
get_abundance(x)

## density
get_density(p)
get_density(e)
get_density(d)
get_density(x)

## events
head(get_events(e))
head(get_events(d))
head(get_events(x))

## detections
head(get_detections(d))
head(get_detections(x))

get_table(x, "removal")
get_table(x, "visits")
```

Description

Plot methods for different bSims objects.

Usage

```
## S3 method for class 'bsims_landscape'
plot(x,
     col_H, col_E, col_R,
     xlim = NULL, ylim = NULL, ...)

## S3 method for class 'bsims_population'
plot(x,
     pch_nest, col_nest, cex_nest, ...)

## S3 method for class 'bsims_events'
plot(x,
     event_type=c("vocal", "move", "both"), tlim = NULL,
     pch_nest, col_nest, cex_nest,
     pch_vocal, col_vocal, cex_vocal,
     lty_move, col_move, lwd_move, ...)

## S3 method for class 'bsims_detections'
plot(x,
     event_type=NULL, tlim = NULL,
     pch_nest, col_nest, cex_nest,
     pch_vocal, col_vocal, cex_vocal,
     lty_move, col_move, lwd_move,
     lty_det, col_det, lwd_det,
     condition = "event1", ...)

## S3 method for class 'bsims_transcript'
plot(x,
     pch_nest, col_nest, cex_nest,
     pch_vocal, col_vocal, cex_vocal,
     lty_move, col_move, lwd_move,
     lty_det, col_det, lwd_det,
     show_tint=TRUE, show_rint=TRUE,
     col_tint, col_rint, ...)

## S3 method for class 'bsims_events'
lines(x, tlim = NULL, ...)
## S3 method for class 'bsims_detections'
lines(x,
     event_type=NULL, tlim=NULL, condition="event1", ...)
## S3 method for class 'bsims_transcript'
lines(x,
     event_type=NULL, tlim=NULL, ...)
```

```

## S3 method for class 'bsims_population'
points(x, ...)
## S3 method for class 'bsims_events'
points(x,
  event_type=c("vocal", "move", "both"), tlim = NULL, ...)
## S3 method for class 'bsims_detections'
points(x,
  event_type=NULL, tlim=NULL, condition="event1", ...)

col2hex(col, alpha = FALSE)

## S3 method for class 'bsims_events_table'
plot(x,
  xlab, ylab, xlim, ylim, ...)
## S3 method for class 'bsims_detections_table'
plot(x,
  type=c("time", "distance"), xlab, ylab, xlim, ylim, ...)

```

Arguments

x simulation object.
col color values.
col_H, col_E, col_R color values for the Habitat, Edge, and Road strata.
event_type type of events to access. The value is inferred from the input object when NULL.
xlim, ylim, tlim x, y, time intervals.
xlab, ylab x and y axis labels.
pch_nest, col_nest, cex_nest visual characteristics of nest locations.
pch_vocal, col_vocal, cex_vocal visual characteristics of vocalization events.
lty_move, col_move, lwd_move visual characteristics of movement events.
lty_det, col_det, lwd_det visual characteristics of detection events.
alpha alpha channel for colors.
show_tint, show_rint whether time and distance intervals should be displayed.
col_tint, col_rint colors for time and distance intervals.
condition conditioning type to define availability for each individual, see [bsims_detect](#).
type what the x axis should be: time or distance.
... other graphical arguments.

Details

The main plotting functions use a theme defined in the option `getOption("bsims_theme")`. Overriding these default settings allows customization.

Value

These plotting functions are called for their side effects and silently return the input object.

`col2hex` is modeled after `col2rgb` and returns a character vector giving hexadecimal color codes with or without alpha channel values.

Author(s)

Peter Solymos

See Also

[bsims_init](#), [col2rgb](#)

Examples

```
b <- bsims_all(road=1, edge=2, move_rate=1, movement=0.2)$new()
o <- getOption("bsims_theme")
str(o)
n <- o
n$col_H <- "gold"
n$col_E <- "magenta"
n$col_R <- "black"
op <- par(mfrow=c(1, 2))
plot(b)
options("bsims_theme" = n) # apply new theme
plot(b)
par(op)
options("bsims_theme" = o) # reset old theme

col2hex(c(blu = "royalblue", reddish = "tomato"), alpha = FALSE)
col2hex(c(blu = "royalblue", reddish = "tomato"), alpha = TRUE)
```

rlnorm2

Reparametrized lognormal distribution

Description

A lognormal distribution parametrized as mean ($ybar$) and $SDlog$.

Usage

```
rlnorm2(n, mean = exp(0.5), sdlog = 1)
```

Arguments

n number of random numbers desired.
 mean mean.
 sdlog log scale standard deviation.

Details

Log scale mean is $\log(\text{mean}) - \text{sdlog}^2/2$.

Value

Vector of random numbers.

Author(s)

Peter Solymos

See Also

`link{rlnorm}`

Examples

```
summary(rlnorm2(10^6, 1.3, 0.5)) # mean ~ 1.3
exp(log(1.3) - 0.5^2/2) # ~ median
```

 rmvn

Multivariate normal distribution

Description

A shim of `mvrnorm` to return matrix when $n < 2$.

Usage

```
rmvn(n = 1L, mu, Sigma, ...)
```

Arguments

n number of random vectors desired (nonnegative integer, can be 0).
 mu mean vector.
 Sigma variance-covariance matrix.
 ... other arguments passed to `mvrnorm`.

Value

A matrix with n rows and $\text{length}(\text{mu})$ columns.

Author(s)

Peter Solymos

See Also

[mvrnorm](#)

Examples

```
rmvn(0, c(a=0, b=0), diag(1, 2, 2))
rmvn(1, c(a=0, b=0), diag(1, 2, 2))
rmvn(2, c(a=0, b=0), diag(1, 2, 2))

sapply(0:10, function(n) dim(rmvn(n, c(a=0, b=0), diag(1, 2, 2))))
```

run_app

Run Shiny apps

Description

Run the Shiny apps that are included in the bSims package.

Usage

```
run_app(app = c("bsimsH", "bsimsHER", "distfunH", "distfunHER"))
```

Arguments

app character, which app to run.

Details

"bsimsH": explore simulation settings in a single stratum.

"bsimsHER": explore simulation settings in multiple strata.

"distfunH": explore distance functions through a single stratum.

"distfunHER": explore distance functions through multiple strata with segmented sound attenuation (see [dist_fun2](#)).

See Also

[bsims_init](#)

Index

- *Topic **aplot**
 - plot.bsims_landscape, 15
 - *Topic **datagen**
 - acceptreject, 2
 - bsims_init, 3
 - events, 11
 - rlnorm2, 18
 - rmvn, 19
 - *Topic **distribution**
 - acceptreject, 2
 - events, 11
 - rlnorm2, 18
 - rmvn, 19
 - *Topic **hplot**
 - plot.bsims_landscape, 15
 - *Topic **manip**
 - expand_list, 12
 - get_nests, 13
 - *Topic **math**
 - dist_fun2, 7
 - *Topic **misc**
 - run_app, 20
 - *Topic **models**
 - estimate, 9
 - *Topic **spatial**
 - acceptreject, 2
- acceptreject, 2, 4, 6
- bSims (bsims_init), 3
- bSims-package (bsims_init), 3
- bsims_all (bsims_init), 3
- bsims_animate (bsims_init), 3
- bsims_detect, 17
- bsims_detect (bsims_init), 3
- bsims_init, 3, 10, 14, 18, 20
- bsims_populate (bsims_init), 3
- bsims_transcribe (bsims_init), 3
- col2hex (plot.bsims_landscape), 15
- col2rgb, 18
- dist_fun2, 5, 7, 20
- estimate, 6, 9
- events, 4, 6, 11
- expand.grid, 13
- expand_list, 12
- get_abundance, 6
- get_abundance (get_nests), 13
- get_density, 6
- get_density (get_nests), 13
- get_detections, 6
- get_detections (get_nests), 13
- get_events, 6
- get_events (get_nests), 13
- get_nests, 6, 13
- get_table, 6
- get_table (get_nests), 13
- lines.bsims_detections
(plot.bsims_landscape), 15
- lines.bsims_events
(plot.bsims_landscape), 15
- lines.bsims_transcript
(plot.bsims_landscape), 15
- mvrnorm, 19, 20
- plot.bsims_detections
(plot.bsims_landscape), 15
- plot.bsims_detections_table
(plot.bsims_landscape), 15
- plot.bsims_events
(plot.bsims_landscape), 15
- plot.bsims_events_table
(plot.bsims_landscape), 15
- plot.bsims_landscape, 6, 15
- plot.bsims_population
(plot.bsims_landscape), 15

plot.bsims_transcript
 (plot.bsims_landscape), 15
points.bsims_detections
 (plot.bsims_landscape), 15
points.bsims_events
 (plot.bsims_landscape), 15
points.bsims_population
 (plot.bsims_landscape), 15
print.bsims_all (bsims_init), 3
print.bsims_detections (bsims_init), 3
print.bsims_events (bsims_init), 3
print.bsims_landscape (bsims_init), 3
print.bsims_population (bsims_init), 3
print.bsims_transcript (bsims_init), 3

rexp, 11
rlnorm2, 5, 18
rmvn, 19
run_app, 6, 20

timetoevent (events), 11
try, 6