

Package ‘ctsem’

September 16, 2020

Type Package

Title Continuous Time Structural Equation Modelling

Version 3.3.11

Date 2020-09-16

Description Hierarchical continuous time state space modelling, for linear and nonlinear systems measured by continuous variables, with limited support for binary data. The subject specific dynamic system is modelled as a stochastic differential equation (SDE), measurement models are typically multivariate normal factor models. Linear mixed effects SDE's estimated via maximum likelihood and optimization are the default. Nonlinearities, (state dependent parameters) and random effects on all parameters are possible, using either max likelihood / max a posteriori optimization (with optional importance sampling) or Stan's Hamiltonian Monte Carlo sampling. See <<https://github.com/cdriveraus/ctsem/raw/master/vignettes/hierarchicalmanual.pdf>> for details. Priors may be used. For the conceptual overview of the hierarchical Bayesian linear SDE approach, see <https://www.researchgate.net/publication/324093594_Hierarchical_Bayesian_Continuous_Time_Dynamic_Modeling>. Exogenous inputs may also be included, for an overview of such possibilities see <https://www.researchgate.net/publication/328221807_Understanding_the_Time_Course_of_Interventions_with_Continuous_Time_State_Space_Modeling>. Stan based functions are not available on 32 bit Windows systems at present. <<https://cdriver.netlify.app/>> contains some tutorial blog posts.

License GPL-3

Depends R (>= 3.5.0), Rcpp (>= 0.12.16)

URL <https://github.com/cdriveraus/ctsem>

Imports cOde, expm, data.table (>= 1.12.8), datasets, Deriv, ggplot2, graphics, grDevices, MASS, Matrix, methods, mize, mvtnorm, parallel, pkgbuild, plyr, rstan (>= 2.19.0), stats, tools, utils, RcppParallel, tibble

Encoding UTF-8

LazyData true

ByteCompile true

LinkingTo BH ($\geq 1.66.0-1$), Rcpp ($\geq 0.12.16$), RcppEigen ($\geq 0.3.3.4.0$), RcppParallel ($\geq 5.0.1$), rstan (≥ 2.21), StanHeaders ($\geq 2.21.0$), RcppParallel ($\geq 5.0.1$)

SystemRequirements GNU make

NeedsCompilation yes

Suggests knitr, testthat, devtools, DEoptim, tinytex, lme4, GGally, shiny, gridExtra

VignetteBuilder knitr

RoxygenNote 7.1.1

Biarch true

Author Charles Driver [aut, cre, cph],
Manuel Voelkle [aut, cph],
Han Oud [aut, cph],
Trustees of Columbia University [cph]

Maintainer Charles Driver <driver@mpib-berlin.mpg.de>

Repository CRAN

Date/Publication 2020-09-16 11:10:04 UTC

R topics documented:

AnomAuth	4
ctCheckFit	4
ctCollapse	5
ctDeintervalise	5
ctDensity	6
ctDiscretePars	7
ctDiscretiseData	7
ctDocs	8
ctExample1	9
ctExample1TIpred	9
ctExample2	9
ctExample2level	10
ctExample3	10
ctExample4	10
ctExtract	11
ctFit	11
ctGenerate	12
ctIndplot	13
ctIntervalise	14
ctKalman	16
ctLongToWide	18
ctLOO	19
ctModel	20
ctModelHigherOrder	24
ctModelLatex	25

ctPlotArray	26
ctPoly	28
ctsem	28
ctStanContinuousPars	29
ctStanDiscretePars	30
ctStanDiscreteParsPlot	31
ctStanFit	33
ctStanFitUpdate	40
ctStanGenerate	41
ctStanGenerateFromFit	42
ctStanKalman	43
ctStanModel	44
ctStanParMatrices	45
ctStanParnames	46
ctStanPlotPost	47
ctStanPostPredict	48
ctstantestdat	49
ctstantestfit	49
ctStanTIpredeffects	50
ctStanTIpredMarginal	51
ctStanUpdModel	52
ctWideNames	53
ctWideToLong	53
datastructure	55
inv_logit	55
isdiag	56
Kalman	57
log1p_exp	58
longexample	59
Oscillating	59
plot.ctKalmanDF	60
plot.ctsemFitMeasure	61
plot.ctStanFit	62
plot.ctStanModel	63
sdpcor2cov	65
standatact_specificsubjects	65
stanoptimis	66
stanWplot	68
stan_checkdivergences	69
stan_postcalc	70
stan_reinitsf	70
stan_unconstrainsamples	71
summary.ctStanFit	72
w32chk	73

AnomAuth

AnomAuth

Description

A dataset containing panel data assessments of individuals Anomia and Authoritarianism.

Format

data frame with 2722 rows, 14 columns. Column Y1 represents anomia, Y2 Authoritarianism, dTx the time interval for measurement occasion x.

Source

See <http://psycnet.apa.org/journals/met/17/2/176/> for details.

ctCheckFit

Check absolute fit of ctFit or ctStanFit object.

Description

Check absolute fit of ctFit or ctStanFit object.

Usage

```
ctCheckFit(fit, niter = 500, probs = c(0.025, 0.5, 0.975))
```

Arguments

fit	ctsem fit object.
niter	number of data generation iterations to use to calculate quantiles.
probs	3 digit vector of quantiles to return and to test significance.

Details

for plotting help see [plot.ctsemFitMeasure](#)

Value

List containing a means and cov object, computed by sorting data into discrete time points. cov is a numeric matrix containing measures of the covariance matrices for observed and simulated data. The MisspecRatio column shows Z score difference for each lower triangular index of the covariance matrix of data – observed covariance minus mean of generated, weighted by sd of generated covariance. means contains the empirical and generated data means.

Examples

```
scheck <- ctCheckFit(ctstantestfit,niter=50)
```

ctCollapse	<i>ctCollapse Easily collapse an array margin using a specified function.</i>
------------	---

Description

ctCollapse Easily collapse an array margin using a specified function.

Usage

```
ctCollapse(inarray, collapsemargin, collapsefunc, plyr = TRUE, ...)
```

Arguments

inarray	Input array of more than one dimension.
collapsemargin	Integers denoting which margins to collapse.
collapsefunc	function to use over the collapsing margin.
plyr	Whether to use plyr.
...	additional parameters to pass to collapsefunc.

Examples

```
testarray <- array(rnorm(900,2,1),dim=c(100,3,3))
ctCollapse(testarray,1,mean)
```

ctDeintervalise	<i>ctDeintervalise</i>
-----------------	------------------------

Description

Converts intervals in ctsem long format data to absolute time

Usage

```
ctDeintervalise(datalong, id = "id", dT = "dT", startoffset = 0)
```

Arguments

datalong	data to use, in ctsem long format (attained via function ctWideToLong)
id	character string denoting column of data containing numeric identifier for each subject.
dT	character string denoting column of data containing time interval preceding observations in that row.
startoffset	Number of units of time to offset by when converting.

ctDensity	<i>ctDensity</i>
-----------	------------------

Description

Wrapper for base R density function that removes outliers and computes 'reasonable' bandwidth and x and y limits. Used for ctsem density plots.

Usage

```
ctDensity(x, bw = "auto", plot = FALSE, ...)
```

Arguments

x	numeric vector on which to compute density.
bw	either 'auto' or a numeric indicating bandwidth.
plot	logical to indicate whether or not to plot the output.
...	Further args to density.

Examples

```
y <- ctDensity(exp(rnorm(80)))
plot(y$density, xlim=y$xlim, ylim=y$ylim)

#### Compare to base defaults:
par(mfrow=c(1,2))
y=exp(rnorm(10000))
ctdens<-ctDensity(y)
plot(ctdens$density, ylim=ctdens$ylim, xlim=ctdens$xlim)
plot(density(y))
```

ctDiscretePars	<i>ctDiscretePars</i>
----------------	-----------------------

Description

Generate discrete time parameters for a sequence of times based on a list containing continuous time parameter matrices as used in ctsem.

Usage

```
ctDiscretePars(ctpars, times = seq(0, 10, 0.1), type = "all")
```

Arguments

ctpars	List of continuous time parameter matrices.
times	Numeric vector of positive values, discrete time parameters will be calculated for each.
type	String. 'all' returns all possible outputs in a list. 'discreteDRIFT' returns only discrete time auto and cross regression effects. 'latentMeans' returns only the expected latent means, given initial (T0MEANS) level, latent intercept (CINT) and temporal effects (DRIFT).

Examples

```
pars <- ctStanContinuousPars(ctstantestfit)
ctDiscretePars(pars, times=c(.5,1))
```

ctDiscretiseData	<i>Discretise long format continuous time (ctsem) data to specific timestep.</i>
------------------	--

Description

Extends and rounds timing information so equal intervals, according to specified timestep, are achieved. NA's are inserted in other columns as necessary, any columns specified by TDpredNames or TIpredNames have zeroes rather than NA's inserted (because some estimation routines do not tolerate NA's in covariates).

Usage

```
ctDiscretiseData(
  dlong,
  timestep,
  timecol = "time",
  idcol = "id",
  TDpredNames = NULL,
  TIpredNames = NULL
)
```

Arguments

dlong	Long format data
timestep	Positive real value to discretise
timecol	Name of column containing absolute (not intervals) time information.
idcol	Name of column containing subject id variable.
TDpredNames	Vector of column names of any time dependent predictors
TIpredNames	Vector of column names of any time independent predictors

Value

long format ctsem data.

Examples

```
long <- ctDiscretiseData(dlong=ctstantestdat, timestep = .1,
  TDpredNames=c('TD1'),TIpredNames=c('TI1', 'TI2', 'TI3'))
```

ctDocs

Get documentation pdf for ctsem

Description

Get documentation pdf for ctsem

Usage

```
ctDocs()
```

Value

Nothing. Opens a pdf.

Examples

```
ctDocs()
```

ctExample1

ctExample1

Description

Simulated example dataset for the ctsem package

Format

100 by 17 matrix containing containing ctsem wide format data. 6 measurement occasions of leisure time and happiness and 5 measurement intervals for each of 100 individuals.

ctExample1TIpred

ctExample1TIpred

Description

Simulated example dataset for the ctsem package

Format

100 by 18 matrix containing containing ctsem wide format data. 6 measurement occasions of leisure time and happiness, 1 measurement of number of friends, and 5 measurement intervals for each of 100 individuals.

ctExample2

ctExample2

Description

Simulated example dataset for the ctsem package

Format

100 by 18 matrix containing containing ctsem wide format data. 8 measurement occasions of leisure time and happiness, 7 measurement occasions of a money intervention dummy, and 7 measurement intervals for each of 50 individuals.

ctExample2level1

ctExample2level

Description

Simulated example dataset for the ctsem package

Format

100 by 18 matrix containing ctsem wide format data. 8 measurement occasions of leisure time and happiness, 7 measurement occasions of a money intervention dummy, and 7 measurement intervals for each of 50 individuals.

ctExample3

ctExample3

Description

Simulated example dataset for the ctsem package

Format

1 by 399 matrix containing containing ctsem wide format data. 100 observations of variables Y1 and Y2 and 199 measurement intervals, for 1 subject.

ctExample4

ctExample4

Description

Simulated example dataset for the ctsem package

Format

20 by 79 matrix containing 20 observations of variables Y1, Y2, Y3, and 19 measurement intervals dTx, for each of 20 individuals.

ctExtract	<i>Extract samples from a ctStanFit object</i>
-----------	--

Description

Extract samples from a ctStanFit object

Usage

```
ctExtract(object, subjectMatrices = FALSE, cores = 2)
```

Arguments

object	ctStanFit object, samples may be from Stan's HMC, or the importance sampling approach of ctsem.
subjectMatrices	Calculate subject specific system matrices?
cores	Only used if subjectMatrices = TRUE . For faster computation use more cores.

Value

Array of posterior samples.

Examples

```
e = ctExtract(ctstantestfit)
```

ctFit	<i>ctFit function placeholder</i>
-------	-----------------------------------

Description

For the original ctsem OpenMx functionality, the package ctsemOMX should be loaded.

Usage

```
ctFit(...)
```

Arguments

...	arguments to pass to ctFit, if ctsemOMX is loaded.
-----	--

Value

message or fit object.

Examples

```
data(AnomAuth)
AnomAuthmodel <- ctModel(LAMBDA = matrix(c(1, 0, 0, 1), nrow = 2, ncol = 2),
Tpoints = 5, n.latent = 2, n.manifest = 2, MANIFESTVAR=diag(0, 2), TRAITVAR = NULL)
AnomAuthfit <- ctFit(AnomAuth, AnomAuthmodel)
```

ctGenerate

ctGenerate

Description

This function generates data according to the specified ctsem model object.

Usage

```
ctGenerate(
  ctmodelobj,
  n.subjects = 100,
  burnin = 0,
  dtmean = 1,
  logdtsd = 0,
  dtmat = NA,
  wide = FALSE
)
```

Arguments

ctmodelobj	ctsem model object from ctModel .
n.subjects	Number of subjects to output.
burnin	Number of initial time points to discard (to simulate stationary data)
dtmean	Positive numeric. Average time interval (delta T) to use.
logdtsd	Numeric. Standard deviation for variability of the time interval.
dtmat	Either NA, or numeric matrix of n.subjects rows and burnin+Tpoints-1 columns, containing positive numeric values for all time intervals between measurements. If not NA, dtmean and logdtsd are ignored.
wide	Logical. Output in wide format?

Details

TRAITVAR and MANIFESTTRAITVAR are treated as Cholesky factor covariances of CINT and MANIFESTMEANS, respectively. TRAITTDPREDCOV and TIPREDCOV matrices are not accounted for, at present. The first 1:n.TDpred rows and columns of TDPREDCOV are used for generating tdpreds at each time point.

Examples

```
#generate data for 2 process model, each process measured by noisy indicator,
#stable individual differences in process levels.

generatingModel<-ctModel(Tpoints=8,n.latent=2,n.TDpred=0,n.TIpred=0,n.manifest=2,
  MANIFESTVAR=diag(.1,2),
  LAMBDA=diag(1,2),
  DRIFT=matrix(c(-.2,-.05,-.1,-.1),nrow=2),
  TRAITVAR=matrix(c(.5,.2,0,.8),nrow=2),
  DIFFUSION=matrix(c(1,.2,0,4),2),
  CINT=matrix(c(1,0),nrow=2),
  T0MEANS=matrix(0,ncol=1,nrow=2),
  T0VAR=diag(1,2))

data<-ctGenerate(generatingModel,n.subjects=15,burnin=10)
```

ctIndplot

ctIndplot

Description

Convenience function to simply plot individuals trajectories from ctsem wide format data

Usage

```
ctIndplot(
  datawide,
  n.manifest,
  Tpoints,
  n.subjects = "all",
  colourby = "variable",
  vars = "all",
  opacity = 1,
  varnames = NULL,
  xlab = "Time",
  ylab = "Value",
  type = "b",
  start = 0,
  legend = TRUE,
  legendposition = "topright",
  new = TRUE,
  jittersd = 0.05,
  ...
)
```

Arguments

datawide	ctsem wide format data
n.manifest	Number of manifest variables in data structure
Tpoints	Number of discrete time points per case in data structure
n.subjects	Number of subjects to randomly select for plotting, or character vector 'all'.
colourby	set plot colours by "subject" or "variable"
vars	either 'all' or a numeric vector specifying which manifest variables to plot.
opacity	Opacity of plot lines
varnames	vector of variable names for legend (defaults to NULL)
xlab	X axis label.
ylab	Y axis label.
type	character specifying plot type, as per usual base R plot commands. Defaults to 'b', both points and lines.
start	Measurement occasion to start plotting from - defaults to T0.
legend	Logical. Plot a legend?
legendposition	Where to position the legend.
new	logical. If TRUE, creates a new plot, otherwise overlays on current plot.
jittersd	positive numeric indicating standard deviation of noise to add to observed data for plotting purposes.
...	additional plotting parameters.

Examples

```
data(ctExample1)
ctIndplot(ctExample1, n.subjects=1, n.manifest=2, Tpoints=6, colourby='variable')
```

ctIntervalise

Converts absolute times to intervals for wide format ctsem panel data

Description

Converts absolute times to intervals for wide format ctsem panel data

Usage

```
ctIntervalise(
  datawide,
  Tpoints,
  n.manifest,
  n.TDpred = 0,
  n.TIpred = 0,
  imputedefs = F,
  manifestNames = "auto",
  TDpredNames = "auto",
  TIpredNames = "auto",
  digits = 5,
  mininterval = 0.001,
  individualRelativeTime = TRUE,
  startoffset = 0
)
```

Arguments

datawide	Wide format data, containing absolute time measurements, to convert to interval time scale. See ctLongToWide to easily convert long format data.
Tpoints	Maximum number of discrete time points (waves of data, or measurement occasions) for an individual in the input data structure.
n.manifest	number of manifest variables per time point in the data.
n.TDpred	number of time dependent predictors in the data structure.
n.TIpred	number of time independent predictors in the data structure.
imputedefs	if TRUE, impute time intervals based on the measurement occasion (i.e. column) they are in, if FALSE (default), set related observations to NA. FALSE is recommended unless you are certain that the imputed value (mean of the relevant time column) is appropriate. Noise and bias in estimates will result if wrongly set to TRUE.
manifestNames	vector of character strings giving variable names of manifest indicator variables (without <code>_Tx</code> suffix for measurement occasion).
TDpredNames	vector of character strings giving variable names of time dependent predictor variables (without <code>_Tx</code> suffix for measurement occasion).
TIpredNames	vector of character strings giving variable names of time independent predictor variables.
digits	How many digits to round to for interval calculations.
mininterval	set to lower than any possible observed measurement interval, but above 0 - this is used for filling NA values where necessary and has no impact on estimates when set in the correct range. (If all observed intervals are greater than 1, <code>mininterval=1</code> may be a good choice)
individualRelativeTime	if TRUE (default), the first measurement for each individual is assumed to be taken at time 0, and all other times are adjusted accordingly. If FALSE, new

columns for an initial wave are created, consisting only of observations which occurred at the earliest observation time of the entire sample.

`startoffset` if 0 (default) uses earliest observation as start time. If greater than 0, all first observations are NA, with distance of `startoffset` to first recorded observation.

Details

Time column must be numeric!

Examples

```
wideexample <- ctLongToWide(datalong = ctstantedat, id = "id",
  time = "time", manifestNames = c("Y1", "Y2"),
  TDpredNames = "TD1", TIpredNames = c("TI1", "TI2", "TI3"))

#Then convert the absolute times to intervals, using the Tpoints reported from the prior step.
wide <- ctIntervalise(datawide = wideexample, Tpoints = 10, n.manifest = 2,
  n.TDpred = 1, n.TIpred = 3, manifestNames = c("Y1", "Y2"),
  TDpredNames = "TD1", TIpredNames = c("TI1", "TI2", "TI3") )

print(wide)
```

ctKalman

ctKalman

Description

Outputs predicted, updated, and smoothed estimates of manifest indicators and latent states, with covariances, for specific subjects from data fit with `ctStanFit`, based on medians of parameter distribution.

Usage

```
ctKalman(
  fit,
  timerange = "asdata",
  timestep = "auto",
  subjects = 1,
  removeObs = FALSE,
  plot = FALSE,
  realid = FALSE,
  ...
)
```


Arguments

fit	fit object as generated by <code>ctStanFit</code> .
timerange	Either 'asdata' to just use the observed data range, or a numeric vector of length 2 denoting start and end of time range, allowing for estimates outside the range of observed data. Ranges smaller than the observed data are ignored.
timestep	Either 'asdata' to just use the observed data (which also requires 'asdata' for timerange) or a positive numeric value indicating the time step to use for interpolating values. Lower values give a more accurate / smooth representation, but take a little more time to calculate. Currently unavailable for ctStan fits.
subjects	vector of integers denoting which subjects (from 1 to N) to plot predictions for.
removeObs	Logical. If TRUE, observations (but not covariates) are set to NA, so only expectations based on parameters and covariates are returned.
plot	Logical. If TRUE, plots output instead of returning it. See <code>plot.ctKalmanDF</code> (Stan based fit) for the possible arguments.
realid	Output using original (not necessarily integer sequence) subject id's?
...	additional arguments to pass to <code>plot.ctKalmanDF</code> .

Value

Returns a list containing matrix objects `etaprior`, `etaupd`, `etasmooth`, `y`, `yprior`, `yupd`, `ysmooth`, `prederror`, `time`, `loglik`, with values for each time point in each row. `eta` refers to latent states and `y` to manifest indicators - `y` itself is thus just the input data. Covariance matrices `etapriorcov`, `etaupdcov`, `etasmoothcov`, `ypriorcov`, `yupdcov`, `ysmoothcov`, are returned in a row * column * time array. Some outputs are unavailable for ctStan fits at present. If `plot=TRUE`, nothing is returned but a plot is generated.

Examples

```
#Basic
ctKalman(ctstantestfit, timerange=c(0,60), plot=TRUE)

#Multiple subjects, y and yprior, showing plot arguments
plot1<-ctKalman(ctstantestfit, timerange=c(0,60), timestep=.1, plot=TRUE,
  subjects=2:3,
  kalmanvec=c('y','yprior'),
  errorvec=c(NA,'ypriorcov')) #'auto' would also have achieved this

#modify plot as per normal with ggplot
print(plot1+ggplot2::coord_cartesian(xlim=c(0,10)))

#or generate custom plot from scratch:#'
k=ctKalman(ctstantestfit, timerange=c(0,60), timestep=.1, subjects=2:3)
library(ggplot2)
ggplot(k[k$Element %in% 'yprior',],
  aes(x=Time, y=value, colour=Subject, linetype=Row)) +
  geom_line() +
```

```
theme_bw()
```

ctLongToWide	<i>ctLongToWide Restructures time series / panel data from long format to wide format for ctsem analysis</i>
--------------	--

Description

ctLongToWide Restructures time series / panel data from long format to wide format for ctsem analysis

Usage

```
ctLongToWide(
  datalong,
  id,
  time,
  manifestNames,
  TDpredNames = NULL,
  TIpredNames = NULL
)
```

Arguments

datalong	dataset in long format, including subject/id column, observation time (or change in observation time, with 0 for first observation) column, indicator (manifest / observed) variables, any time dependent predictors, and any time independent predictors.
id	character string giving column name of the subject/id column
time	character string giving column name of the time columnn
manifestNames	vector of character strings giving column names of manifest indicator variables
TDpredNames	vector of character strings giving column names of time dependent predictor variables
TIpredNames	vector of character strings giving column names of time independent predictor variables

Details

Time column must be numeric

See Also

[ctIntervalise](#)

Examples

```
wideexample <- ctLongToWide(datalong = ctstantedat, id = "id",
  time = "time", manifestNames = c("Y1", "Y2"),
  TDpredNames = "TD1", TIpredNames = c("TI1", "TI2", "TI3"))

#Then convert the absolute times to intervals, using the Tpoints reported from the prior step.
wide <- ctIntervalise(datawide = wideexample, Tpoints = 10, n.manifest = 2,
  n.TDpred = 1, n.TIpred = 3, manifestNames = c("Y1", "Y2"),
  TDpredNames = "TD1", TIpredNames = c("TI1", "TI2", "TI3") )

print(wide)
```

ctLOO

K fold cross validation for ctStanFit objects

Description

K fold cross validation for ctStanFit objects

Usage

```
ctLOO(
  fit,
  folds = 10,
  cores = 2,
  parallelFolds = TRUE,
  subjectwise = FALSE,
  keepfirstobs = TRUE
)
```

Arguments

fit	ctStanfit object
folds	Number of cross validation splits to use – 10 folds implies that the model is re-fit 10 times, each time to a data set with 1/10 of the observations randomly removed.
cores	Number of processor cores to use.
parallelFolds	compute folds in parallel or use cores to finish single folds faster.
subjectwise	drop random subjects instead of data rows?
keepfirstobs	do not drop first observation (more stable estimates)

Value

list

Examples

```
ctL00(ctstantestfit)
```

```
ctModel
```

```
Define a ctsem model
```

Description

This function is used to specify a continuous time structural equation model, which can then be fit to data with function [ctStanFit](#).

Usage

```
ctModel(
  LAMBDA,
  type = "omx",
  n.manifest = "auto",
  n.latent = "auto",
  Tpoints = NULL,
  manifestNames = "auto",
  latentNames = "auto",
  id = "id",
  time = "time",
  T0VAR = "auto",
  T0MEANS = "auto",
  MANIFESTMEANS = "auto",
  MANIFESTVAR = "auto",
  DRIFT = "auto",
  CINT = "auto",
  DIFFUSION = "auto",
  n.TDpred = "auto",
  TDpredNames = "auto",
  n.TIpred = "auto",
  TIpredNames = "auto",
  tipredDefault = TRUE,
  TRAITVAR = NULL,
  T0TRAITEFFECT = NULL,
  MANIFESTTRAITVAR = NULL,
  TDPREDMEANS = "auto",
  TDPREDEFFECT = "auto",
  T0TDPREDCOV = "auto",
  TDPREDVAR = "auto",
  TRAITTDPREDCOV = "auto",
  TDTIPREDCOV = "auto",
  TIPREDMEANS = "auto",
```

```

    TIPREDEFFECT = "auto",
    T0TIPREDEFFECT = "auto",
    TIPREDVAR = "auto",
    PARS = NULL,
    startValues = NULL
)

```

Arguments

LAMBDA	n.manifest*n.latent loading matrix relating latent to manifest variables, with latent processes 1:n.latent along the columns, and manifest variables 1:n.manifest in the rows.
type	character string. If 'omx' (default) configures model for maximum likelihood fitting with ctFit, using OpenMx. If 'stancf' or 'standt' configures either continuous ('stancf') or discrete ('standt') time model for Bayesian fitting with ctStanFit, using Stan.
n.manifest	Number of manifest indicators per individual at each measurement occasion / time point. Manifest variables are included as the first element of the wide data matrix, with all the 1:n.manifest manifest variables at time 1 followed by those of time 2, and so on.
n.latent	Number of latent processes.
Tpoints	For type='omx' only. Number of time points, or measurement occasions, in the data. This will generally be the maximum number of time points for a single individual, but may be one extra if sample relative time intervals are used, see ctIntervalise.
manifestNames	n.manifest length vector of manifest variable names as they appear in the data structure, without any _Tx time point suffix that may be present in wide data. Defaults to Y1, Y2, etc.
latentNames	n.latent length vector of latent variable names (used for naming parameters, defaults to eta1, eta2, etc).
id	character string denoting column name containing subject identification variables. id data may be of any form, though will be coerced internally to an integer sequence rising from 1.
time	character string denoting column name containing timing data. Timing data must be numeric.
T0VAR	lower triangular n.latent*n.latent cholesky matrix of latent process initial variance / covariance. "auto" freely estimates all parameters.
T0MEANS	n.latent*1 matrix of latent process means at first time point, T0. "auto" freely estimates all parameters.
MANIFESTMEANS	n.manifest*1 matrix of manifest intercept parameters. "auto" frees all parameters.
MANIFESTVAR	lower triangular n.manifest*n.manifest cholesky matrix of variance / covariance between manifests at each measurement occasion (i.e. measurement error / residual). "auto" freely estimates variance parameters, and fixes covariances between manifests to 0. "free" frees all values, including covariances.

DRIFT	n.latent*n.latent DRIFT matrix of continuous auto and cross effects, relating the processes over time. "auto" freely estimates all parameters.
CINT	n.latent * 1 matrix of latent process intercepts, allowing for non 0 asymptotic levels of the latent processes. Generally only necessary for additional trends and more complex dynamics. "auto" fixes all parameters to 0.
DIFFUSION	lower triangular n.latent*n.latent cholesky matrix of diffusion process variance and covariance (latent error / dynamic innovation). "auto" freely estimates all parameters.
n.TDpred	Number of time dependent predictor variables in the dataset.
TDpredNames	n.TDpred length vector of time dependent predictor variable names, as they appear in the data structure, without any _Tx time point suffix that may appear in wide data. Default names are TD1, TD2, etc.
n.TIpred	Number of time independent predictors. Each TIpredictor is inserted at the right of the data matrix, after the time intervals.
TIpredNames	n.TIpred length vector of time independent predictor variable names, as they appear in the data structure. Default names are TI1, TI2, etc.
tipredDefault	Logical. TRUE sets any parameters with unspecified time independent predictor effects to have effects estimated, FALSE fixes the effect to zero unless individually specified.
TRAITVAR	For type='omx' only. Either NULL, if no trait / unobserved heterogeneity effect, or lower triangular n.latent*n.latent cholesky matrix of trait variance / covariance across subjects. "auto" freely estimates all parameters.
T0TRAITEFFECT	For type='omx' only. Either NULL, if no trait / individual heterogeneity effect, or lower triangular n.latent*n.latent cholesky matrix of initial trait variance / covariance. "auto" freely estimates all parameters, if the TRAITVAR matrix is specified.
MANIFESTTRAITVAR	For type='omx' only. Either NULL (default) if no trait variance / individual heterogeneity in the level of the manifest indicators, otherwise a lower triangular n.manifest * n.manifest variance / covariance matrix. Set to "auto" to include and free all parameters - but identification problems will arise if TRAITVAR is also set.
TDPREDMEANS	For type='omx' only. (n.TDpred * (Tpoints - 1)) rows * 1 column matrix of time dependent predictor means. If 'auto', the means are freely estimated. Otherwise, the means for the Tpoints observations of your first time dependent predictor are followed by those of TDpred 2, and so on.
TDPREDEFFECT	n.latent*n.TDpred matrix of effects from time dependent predictors to latent processes. Effects from 1:n.TDpred columns TDpredictors go to 1:n.latent rows of latent processes. "auto" freely estimates all parameters.
T0TDPREDCOV	For type='omx' only. n.latent rows * (Tpoints * n.TDpred) columns covariance matrix between latents at T0 and time dependent predictors. Default of "auto" restricts covariance to 0, which is consistent with covariance to other time points. To freely estimate parameters, specify either 'free', or the desired matrix.
TDPREDVAR	For type='omx' only. lower triangular (n.TDpred * Tpoints) rows * (n.TDpred * Tpoints) columns variance / covariance cholesky matrix for time dependent predictors. "auto" (default) freely estimates all parameters.

TRAITTPREDCOV	For type='omx' only. n.latent rows * (n.TDpred*Tpoints) columns covariance matrix of latent traits and time dependent predictors. Defaults to zeroes, assuming predictors are independent of subjects baseline levels. When predictors depend on the subjects, this should instead be set to 'free' or manually specified. The Tpoints columns of the first predictor are followed by those of the second and so on. Covariances with the trait variance of latent process 1 are specified in row 1, process 2 in row 2, etc. "auto" (default) sets this matrix to zeroes, (if both traits and time dependent predictors exist, otherwise this matrix is set to NULL, and ignored in any case).
TDTIPREDCOV	For type='omx' only. (n.TDpred * Tpoints) rows * n.TIpred columns covariance matrix between time dependent and time independent predictors. "auto" (default) freely estimates all parameters.
TIPREDMEANS	For type='omx' only. n.TIpred * 1 matrix of time independent predictor means. If 'auto', the means are freely estimated.
TIPREDEFFECT	For type='omx' only. n.latent*n.TIpred effect matrix of time independent predictors on latent processes. "auto" freely estimates all parameters and generates starting values. TIPREDEFFECT parameters for type='stan' are estimated by default on all subject level parameters, to restrict this, manually edit the model object after creation.
T0TIPREDEFFECT	For type='omx' only.n.latent*n.TIpred effect matrix of time independent predictors on latents at T0. "auto" freely estimates all parameters, though note that under the default setting of stationary for ctFit, this matrix is ignored as the effects are determined based on the overall process parameters.
TIPREDVAR	For type='omx' only.lower triangular n.TIpred * n.TIpred Cholesky decomposed covariance matrix for all time independent predictors. "auto" (default) freely estimates all parameters.
PARS	for types 'stanct' and 'standt' only. May be of any structure, only needed to contain extra parameters for certain non-linear models.
startValues	For type='omx' only. A named vector, where the names of each value must match a parameter in the specified model, and the value sets the starting value for that parameter during optimization. If not set, random starting values representing relatively stable processes with small effects and covariances are generated by ctFit. Better starting values may improve model fit speed and the chance of an appropriate model fit.

Examples

```
### Frequentist example:
### impulse and level change time dependent predictor
### example from Driver, Oud, Voelkle (2015)
data('ctExample2')
tdpredmodel <- ctModel(n.manifest = 2, n.latent = 3, n.TDpred = 1,
  Tpoints = 8, manifestNames = c('LeisureTime', 'Happiness'),
  TDpredNames = 'MoneyInt',
  latentNames = c('LeisureTime', 'Happiness', 'MoneyIntLatent'),
  LAMBDA = matrix(c(1,0, 0,1, 0,0), ncol = 3), TRAITVAR = "auto")

tdpredmodel$TRAITVAR[3, ] <- 0
```

```

tdpredmodel$TRAITVAR[, 3] <- 0
tdpredmodel$DIFFUSION[, 3] <- 0
tdpredmodel$DIFFUSION[3, ] <- 0
tdpredmodel$T0VAR[3, ] <- 0
tdpredmodel$T0VAR[, 3] <- 0
tdpredmodel$CINT[3] <- 0
tdpredmodel$T0MEANS[3] <- 0
tdpredmodel$TDPREDEFFECT[3, ] <- 1
tdpredmodel$DRIFT[3, ] <- 0

###Bayesian example:
model<-ctModel(type='stanct',
n.latent=2, latentNames=c('eta1','eta2'),
n.manifest=2, manifestNames=c('Y1','Y2'),
n.TDpred=1, TDpredNames='TD1',
n.TIpred=3, TIpredNames=c('TI1','TI2','TI3'),
LAMBDA=diag(2))

```

ctModelHigherOrder *Raise the order of a ctsem model object of type 'omx'.*

Description

Raise the order of a ctsem model object of type 'omx'.

Usage

```

ctModelHigherOrder(
  ctm,
  indices,
  diffusion = TRUE,
  crosseffects = FALSE,
  cint = FALSE,
  explosive = FALSE
)

```

Arguments

ctm	ctModel
indices	Vector of integers, which latents to raise the order of.
diffusion	Shift the diffusion parameters / values to the higher order?
crosseffects	Shift cross coupling parameters of the DRIFT matrix to the higher order?
cint	shift continuous intercepts to higher order?
explosive	Allow explosive (non equilibrium returning) processes?

Value

extended ctModel

Examples

```
om <- ctModel(LAMBDA=diag(1,2),DRIFT=0,
  MANIFESTMEANS=0,type='omx',Tpoints=4)
```

```
om <- ctModelHigherOrder(om,1:2)
print(om$DRIFT)
```

```
m <- ctStanModel(om)
print(m$pars)
```

ctModelLatex	<i>Generate and optionally compile latex equation of subject level ctsem model.</i>
--------------	---

Description

Generate and optionally compile latex equation of subject level ctsem model.

Usage

```
ctModelLatex(
  x,
  matrixnames = TRUE,
  digits = 3,
  linearise = class(x) %in% "ctStanFit",
  textsize = "normalsize",
  folder = tempdir(),
  filename = paste0("ctsemTex", as.numeric(Sys.time())),
  tex = TRUE,
  equationonly = FALSE,
  compile = TRUE,
  open = TRUE,
  minimal = FALSE
)
```

Arguments

x	ctsem model object or ctStanFit object.
matrixnames	Logical. If TRUE, includes ctsem matrix names such as DRIFT and DIFFUSION under the matrices.
digits	Precision of decimals for numeric values.
linearise	Logical. Show the linearised normal approximation for subject parameters and covariate effects, or the raw parameters?

textsize	Standard latex text sizes – tiny scriptsize footnotesize small normalsize large Large LARGE huge Huge. Useful if output overflows page.
folder	Character string specifying folder to save to, defaults to temporary directory, use "/" for working directory.
filename	filename, without suffix, to output .tex and .pdf files too.
tex	Save .tex file? Otherwise latex is simply returned within R as a string.
equationonly	Logical. If TRUE, output is only the latex relevant to the equation, not a compileable document.
compile	Compile to .pdf? (Depends on tex = TRUE)
open	Open after compiling? (Depends on compile = TRUE)
minimal	if TRUE, outputs reduced form version displaying matrix dimensions and equation structure only.

Value

character string of latex code. Side effects include saving a .tex, .pdf, and displaying the pdf.

Examples

```
ctmodel <- ctModel(type='stanct',
  n.latent=2, n.manifest=1,
  manifestNames='sunspots',
  latentNames=c('ss_level', 'ss_velocity'),
  LAMBDA=matrix(c( 1, 'ma1' ), nrow=1, ncol=2),
  DRIFT=matrix(c(0, 1, 'a21', 'a22'), nrow=2, ncol=2, byrow=TRUE),
  MANIFESTMEANS=matrix(c('m1'), nrow=1, ncol=1),
  CINT=matrix(c(0, 0), nrow=2, ncol=1),
  DIFFUSION=matrix(c(
    0, 0,
    0, "diffusion"), ncol=2, nrow=2, byrow=TRUE))

l=ctModelLatex(ctmodel,compile=FALSE, open=FALSE)
cat(l)
```

ctPlotArray

Plots three dimensional y values for quantile plots

Description

1st margin of \$Y sets line values, 2nd sets variables, 3rd quantiles.

Usage

```
ctPlotArray(
  input,
  grid = FALSE,
  add = FALSE,
  colvec = "auto",
  lwdvec = "auto",
  ltyvec = "auto",
  typevec = "auto",
  plotcontrol = list(ylab = "Array values", xaxs = "i"),
  legend = TRUE,
  legendcontrol = list(),
  polygon = TRUE,
  polygonalpha = 0.1,
  polygoncontrol = list(steps = 25)
)
```

Arguments

input	list containing 3 dimensional array to use for Y values, \$y and vector of corresponding x values \$x.
grid	Logical. Plot with a grid?
add	Logical. If TRUE, plotting is overlayed on current plot, without creating new plot.
colvec	color vector of same length as 2nd margin.
lwdvec	lwd vector of same length as 2nd margin.
ltyvec	lty vector of same length as 2nd margin.
typevec	type vector of same length as 2nd margin.
plotcontrol	list of arguments to pass to plot.
legend	Logical. Draw a legend?
legendcontrol	list of arguments to pass to legend .
polygon	Logical. Draw the uncertainty polygon?
polygonalpha	Numeric, multiplier for alpha (transparency) of the uncertainty polygon.
polygoncontrol	list of arguments to pass to ctPoly

Value

Nothing. Generates plots.

Examples

```
#'
input<-ctStanTIpredeffects(ctstantestfit, plot=FALSE, whichpars='CINT',
  nsamples=10, nsubjects=10)

ctPlotArray(input=input)
```

ctPoly	<i>Plots uncertainty bands with shading</i>
--------	---

Description

Plots uncertainty bands with shading

Usage

```
ctPoly(x, y, ylow, yhigh, steps = 20, ...)
```

Arguments

x	x values
y	y values
ylow	lower limits of y
yhigh	upper limits of y
steps	number of polygons to overlay - higher integers lead to smoother changes in transparency between y and yhigh / ylow.
...	arguments to pass to polygon()

Value

Nothing. Adds a polygon to existing plot.

Examples

```
plot(0:100, sqrt(0:100), type='l')
ctPoly(x=0:100, y=sqrt(0:100),
       yhigh=sqrt(0:100) - runif(101),
       ylow=sqrt(0:100) + runif(101),
       col=adjustcolor('red', alpha.f=.1))
```

ctsem	<i>ctsem</i>
-------	--------------

Description

ctsem is an R package for continuous time structural equation modelling of panel ($N > 1$) and time series ($N = 1$) data, using either a frequentist or Bayesian approach, or middle ground forms like maximum a posteriori.

The general workflow begins by specifying a model using the `ctModel` function, in which the type of model is also specified. Then the model is fit to data using `ctStanFit`. The `ctFit` function which allows for fitting using the OpenMx / SEM form, as described in the original JSS ctsem paper, can now be found in the ctsemOMX package. The omx forms are no longer in development and for most purposes, the newer stan based forms are more robust and flexible. For examples, see `ctStanFit`. For citation info, please run `citation('ctsem')`.

References

<https://www.jstatsoft.org/article/view/v077i05>

Driver, C. C., & Voelkle, M. C. (2018). Hierarchical Bayesian continuous time dynamic modeling. *Psychological Methods*. Advance online publication. <http://dx.doi.org/10.1037/met0000168>

Stan Development Team (2018). RStan: the R interface to Stan. R package version 2.17.3. <http://mc-stan.org>

ctStanContinuousPars *ctStanContinuousPars*

Description

Returns the continuous time parameter matrices of a ctStanFit fit object

Usage

```
ctStanContinuousPars(
  ctstanfitobj,
  calcfunc = quantile,
  calcfuncargs = list(probs = 0.5)
)
```

Arguments

ctstanfitobj	fit object from ctStanFit
calcfunc	Function to apply over samples, must return a single value. By default the median over all samples is returned using the quantile function, but one might also be interested in the mean or sd , for instance.
calcfuncargs	A list of additional parameters to pass to calcfunc. For instance, with the default of calcfunc = quantile, the probs argument is needed to ensure only a single value is returned.

Examples

```
#posterior median over all subjects (also reflects mean of unconstrained pars)
ctStanContinuousPars(ctstantestfit)
```

 ctStanDiscretePars *ctStanDiscretePars*

Description

Calculate model implied regressions for a sequence of time intervals based on a continuous time model fit from ctStanFit, for specified subjects.

Usage

```
ctStanDiscretePars(
  ctstanfitobj,
  subjects = "all",
  times = seq(from = 0, to = 10, by = 0.1),
  quantiles = c(0.025, 0.5, 0.975),
  nsamples = 500,
  observational = FALSE,
  standardise = FALSE,
  cov = FALSE,
  plot = FALSE,
  ...
)
```

Arguments

ctstanfitobj	Continuous time model fit from ctStanFit
subjects	Either 'all', to take the average over all subjects, or a vector of integers denoting which subjects.
times	Numeric vector of positive values, discrete time parameters will be calculated for each.
quantiles	Which quantiles to return. If plotting, specify 3 quantiles, the 2nd will be plotted as a line with 1 and 3 as uncertainty bounds.
nsamples	Number of samples from the stanfit to use for plotting. Higher values will increase smoothness / accuracy, at cost of plotting speed. Values greater than the total number of samples will be set to total samples.
observational	Logical. If TRUE, outputs expected change in processes *conditional on observing* a 1 unit change in each – this change is correlated according to the DIFFUSION matrix. If FALSE, outputs expected regression values – also interpretable as an independent 1 unit change on each process, giving the expected response under a 1 unit experimental impulse.
standardise	Logical. If TRUE, output is standardised according to expected total within subject variance, given by the asymDIFFUSION matrix.
cov	Logical. If TRUE, covariances are returned instead of regression coefficients.
plot	Logical. If TRUE, plots output using ctStanDiscreteParsPlot instead of returning output.
...	additional plotting arguments to control ctStanDiscreteParsPlot

Examples

```

if(w32chk()){

ctStanDiscretePars(ctstantestfit,times=seq(.5,4,.1),
  plot=TRUE,indices='all')

#modify plot
require(ggplot2)
g=ctStanDiscretePars(ctstantestfit,times=seq(.5,4,.1),
  plot=TRUE,indices='CR')
g= g+ labs(title='Cross effects')
print(g)
}

```

```

ctStanDiscreteParsPlot
      ctStanDiscreteParsPlot

```

Description

Plots model implied regression strengths at specified times for continuous time models fit with ctStanFit.

Usage

```

ctStanDiscreteParsPlot(
  x,
  indices = "all",
  add = FALSE,
  legend = TRUE,
  polygon = TRUE,
  gg = TRUE,
  plot = TRUE,
  quantiles = c(0.025, 0.5, 0.975),
  times = seq(0, 10, 0.1),
  latentNames = "auto",
  lwdvec = "auto",
  colvec = "auto",
  ltyvec = "auto",
  plotcontrol = list(ylab = "Value", xlab = "Time interval", main =
    "Regression coefficients", type = "l", xaxs = "i"),
  grid = FALSE,
  legendcontrol = list(x = "topright", bg = "white"),
  polygonalpha = 0.1,
  polygoncontrol = list(steps = 20),
  ...
)

```

Arguments

x	list object returned from <code>ctStanDiscretePars</code> .
indices	Either a string specifying type of plot to create, or an n by 2 matrix specifying which indices of the output matrix to plot. 'AR' specifies all diagonals, for discrete time autoregression parameters. 'CR' specifies all off-diagonals, for discrete time cross regression parameters. 'all' plots all AR and CR effects at once.
add	Logical. If FALSE, a new plot is generated, if TRUE, specified plot/s are overlaid on existing plot.
legend	Logical. If TRUE, generates a legend.
polygon	Logical. If TRUE, fills a polygon between the first and last specified quantiles.
gg	Logical – use GGplot2 or not? if TRUE, other graphical parameters are ignored, and the ggplot object is returned and may be modified further.
plot	Logical. Only relevant with gg=TRUE.
quantiles	numeric vector of length 3, with values between 0 and 1, specifying which quantiles to plot. The default of <code>c(.05,.5,.95)</code> plots 95% credible intervals and the posterior median at 50%.
times	Numeric vector of positive values, discrete time parameters will be calculated for each.
latentNames	Vector of character strings denoting names for the latent variables. 'auto' just uses <code>eta1 eta2</code> etc.
lwdvec	Either 'auto', or a vector of positive integers denoting line widths for each quantile. 'auto' specifies <code>c(1,3,1)</code> if there are 3 quantiles to be plotted (default), otherwise simply 3.
colvec	Either 'auto', or a vector of color values denoting colors for each index to be plotted. 'auto' generates colors using the <code>grDevices::rainbow</code> function.
ltyvec	Either 'auto', or a vector of line type integers (as for the <code>lty</code> parameter normally) denoting line types for each quantile. 'auto' specifies <code>c(3, 1, 3)</code> if there are 3 quantiles to be plotted (default), otherwise simply 1.
plotcontrol	list of arguments to pass to plot function. The following arguments are ignored: <code>ylim,lwd,lty,col,x,y</code> .
grid	Logical. Plot with a grid?
legendcontrol	list of arguments to pass to legend function. 'legend=' and 'text.col=' arguments will be ignored.
polygonalpha	Numeric between 0 and 1 to multiply the alpha (transparency) of colvec by for the fill polygon.
polygoncontrol	list of arguments to pass to <code>ctPoly</code> function (if polygon=TRUE). <code>x,y</code> , and <code>col</code> arguments will be ignored. <code>Steps</code> specifies the number of polygons to overlay to create a graduated transparency. Set to 1 for a flat looking plot.
...	for plot adjustments a <code>ggeval</code> argument can be added, which should be based on the default code found in the <code>ctsem:::ctPlotArrayGG</code> function.

Examples

```

if(w32chk()){
x <- ctStanDiscretePars(ctstantestfit)
ctStanDiscreteParsPlot(x, indices='CR')

#to modify plot:
g <- ctStanDiscreteParsPlot(x, indices='CR',plot=FALSE) +
  ggplot2::labs(title='My ggplot modification')
print(g)
}

```

ctStanFit

ctStanFit

Description

Fits a ctsem model specified via [ctModel](#) with type either 'stanct' or 'standt'.

Usage

```

ctStanFit(
  datalong,
  ctstanmodel,
  stanmodeltext = NA,
  iter = 1000,
  intoverstates = TRUE,
  binomial = FALSE,
  fit = TRUE,
  intoverpop = "auto",
  stationary = FALSE,
  plot = FALSE,
  derrind = "all",
  optimize = TRUE,
  optimcontrol = list(),
  nlcontrol = list(),
  nopriors = TRUE,
  chains = 2,
  cores = ifelse(optimize, getOption("mc.cores", 2L), "maxneeded"),
  inits = NULL,
  forcerecompile = FALSE,
  savescores = FALSE,
  savesubjectmatrices = FALSE,
  gendata = FALSE,
  control = list(),
  verbose = 0,
  ...
)

```

Arguments

<code>datalong</code>	long format data containing columns for subject id (numeric values, 1 to max subjects), manifest variables, any time dependent (i.e. varying within subject) predictors, and any time independent (not varying within subject) predictors.
<code>ctstanmodel</code>	model object as generated by <code>ctModel</code> with <code>type='stanct'</code> or <code>'standt'</code> , for continuous or discrete time models respectively.
<code>stanmodeltext</code>	already specified Stan model character string, generally leave NA unless modifying Stan model directly. (Possible after modification of output from <code>fit=FALSE</code>)
<code>iter</code>	number of iterations, half of which will be devoted to warmup by default when sampling. When optimizing, this is the maximum number of iterations to allow – convergence hopefully occurs before this!
<code>intoverstates</code>	logical indicating whether or not to integrate over latent states using a Kalman filter. Generally recommended to set TRUE unless using non-gaussian measurement model.
<code>binomial</code>	Deprecated. Logical indicating the use of binary rather than Gaussian data, as with IRT analyses. This now sets <code>intoverstates = FALSE</code> and the <code>manifesttype</code> of every indicator to 1, for binary.
<code>fit</code>	If TRUE, fit specified model using Stan, if FALSE, return stan model object without fitting.
<code>intoverpop</code>	if 'auto', set to TRUE if optimizing and FALSE if using hmc. if TRUE, integrates over population distribution of parameters rather than full sampling. Allows for optimization of non-linearities and random effects.
<code>stationary</code>	Logical. If TRUE, TOVAR and TOMEANS input matrices are ignored, the parameters are instead fixed to long run expectations. More control over this can be achieved by instead setting parameter names of TOMEANS and TOVAR matrices in the input model to 'stationary', for elements that should be fixed to stationarity.
<code>plot</code>	if TRUE, for sampling, a Shiny program is launched upon fitting to interactively plot samples. May struggle with many (e.g., > 5000) parameters. For optimizing, various optimization details are plotted – in development.
<code>derrind</code>	vector of integers denoting which latent variables are involved in dynamic error calculations. latents involved only in deterministic trends or input effects can be removed from matrices (ie, that obtain no additional stochastic inputs after first observation), speeding up calculations. If unsure, leave default of 'all' ! Ignored if <code>intoverstates=FALSE</code> .
<code>optimize</code>	if TRUE, use <code>stanoptimis</code> function for maximum a posteriori / importance sampling estimates, otherwise use the HMC sampler from Stan, which is (much) slower, but generally more robust, accurate, and informative.
<code>optimcontrol</code>	list of parameters sent to <code>stanoptimis</code> governing optimization / importance sampling.
<code>nlcontrol</code>	List of non-linear control parameters. <code>nldynamics</code> defaults to "auto", but may also be a logical. Set to FALSE to use estimator that assumes linear dynamics, TRUE to use non-linear estimator. "auto" selects linear when the model is obviously linear, otherwise nonlinear – nonlinear is slower. <code>maxtimestep</code> must be

a positive numeric, specifying the largest time span covered by the numerical integration. The large default ensures that for each observation time interval, only a single step of exponential integration is used. When `maxtimestep` is smaller than the observation time interval, the integration is nested within an Euler like loop. Smaller values may offer greater accuracy, but are slower and not always necessary. Given the exponential integration, linear model elements are fit exactly with only a single step.

<code>nopriors</code>	logical. If TRUE, any priors are disabled – sometimes desirable for optimization.
<code>chains</code>	number of chains to sample, during HMC or post-optimization importance sampling. Unless the <code>cores</code> argument is also set, the number of chains determines the number of cpu cores used, up to the maximum available minus one. Irrelevant when <code>optimize=TRUE</code> .
<code>cores</code>	number of cpu cores to use. Either 'maxneeded' to use as many as available minus one, up to the number of chains, or a positive integer. If <code>optimize=TRUE</code> , more cores are generally faster.
<code>inits</code>	vector of parameter start values, as returned by the <code>rstan</code> function <code>rstan::unconstrain_pars</code> for instance.
<code>forcerecompile</code>	logical. For development purposes. If TRUE, stan model is recompiled, regardless of apparent need for compilation.
<code>savescores</code>	Logical. If TRUE, output from the Kalman filter is saved in output. For datasets with many variables or time points, will increase file size substantially.
<code>savesubjectmatrices</code>	Logical. If TRUE, subject specific matrices are saved – only relevant when either time dependent predictors are used, or individual differences are obtained via sampling (not via optimization, where they are integrated over).
<code>gendata</code>	Logical – If TRUE, uses provided data for only covariates and a time and missingness structure, and generates random data according to the specified model / priors. Generated data is in the <code>\$Ygen</code> subobject after running <code>extract</code> on the fit object. For datasets with many manifest variables or time points, file size may be large. To generate data based on the posterior of a fitted model, see ctStanGenerateFromFit .
<code>control</code>	List of arguments sent to <code>stan</code> control argument, regarding warmup / sampling behaviour. Unless specified, values used are: <code>list(adapt_delta = .8, adapt_window=2, max_treedepth=10, adapt_init_buffer=2, stepsize = .001)</code>
<code>verbose</code>	Integer from 0 to 2. Higher values print more information during model fit – for debugging.
<code>...</code>	additional arguments to pass to <code>stan</code> function.

Examples

```
#generate a ctStanModel relying heavily on defaults
model<-ctModel(type='stanct',
  latentNames=c('eta1', 'eta2'),
```

```

manifestNames=c('Y1','Y2'),
MANIFESTVAR=diag(.1,2),
TDpredNames='TD1',
TIpredNames=c('TI1','TI2','TI3'),
LAMBDA=diag(2))

fit<-ctStanFit(ctstantestdat, model,nopriors=FALSE)

summary(fit)

plot(fit,wait=FALSE)

#### extended examples

library(ctsem)
set.seed(3)

# Data generation (run this, but no need to understand!) -----

Tpoints <- 20
nmanifest <- 4
nlatent <- 2
nsubjects<-20

#random effects
age <- rnorm(nsubjects) #standardised
cint1<-rnorm(nsubjects,2,.3)+age*.5
cint2 <- cint1*.5+rnorm(nsubjects,1,.2)+age*.5
tdpredeffect <- rnorm(nsubjects,5,.3)+age*.5

for(i in 1:nsubjects){
  #generating model
  gm<-ctModel(Tpoints=Tpoints,n.manifest = nmanifest,n.latent = nlatent,n.TDpred = 1,
  LAMBDA = matrix(c(1,0,0,0, 0,1,.8,1.3),nrow=nmanifest,ncol=nlatent),
  DRIFT=matrix(c(-.3, .2, 0, -.5),nlatent,nlatent),
  TDPREMEANS=matrix(c(rep(0,Tpoints-10),1,rep(0,9)),ncol=1),
  TDPREDEFFECT=matrix(c(tdpredeffect[i],0),nrow=nlatent),
  DIFFUSION = matrix(c(1, 0, 0, .5),2,2),
  CINT = matrix(c(cint1[i],cint2[i]),ncol=1),
  T0VAR=diag(2,nlatent,nlatent),
  MANIFESTVAR = diag(.5, nmanifest))

  #generate data
  newdat <- ctGenerate(ctmodelobj = gm,n.subjects = 1,burnin = 2,
  dtmat<-rbind(c(rep(.5,8),3,rep(.5,Tpoints-9))))
  newdat[, 'id'] <- i #set id for each subject
  newdat <- cbind(newdat,age[i]) #include time independent predictor
  if(i ==1) {
    dat <- newdat[1:(Tpoints-10),] #pre intervention data
    dat2 <- newdat #including post intervention data
  }
  if(i > 1) {
    dat <- rbind(dat, newdat[1:(Tpoints-10),])
  }
}

```

```

    dat2 <- rbind(dat2,newdat)
  }
}
colnames(dat)[ncol(dat)] <- 'age'
colnames(dat2)[ncol(dat)] <- 'age'

#plot generated data for sanity
plot(age)
matplot(dat[,gm$manifestNames],type='l',pch=1)
plotvar <- 'Y1'
plot(dat[dat[, 'id']==1, 'time'],dat[dat[, 'id']==1,plotvar],type='l',
      ylim=range(dat[,plotvar],na.rm=TRUE))
for(i in 2:nsubjects){
  points(dat[dat[, 'id']==i, 'time'],dat[dat[, 'id']==i,plotvar],type='l',col=i)
}

dat2[,gm$manifestNames][sample(1:length(dat2[,gm$manifestNames]),size = 100)] <- NA

#data structure
head(dat2)

# Model fitting -----

##simple univariate default model

m <- ctModel(type = 'stanct', manifestNames = c('Y1'), LAMBDA = diag(1))
ctModelLatex(m)

#Specify univariate linear growth curve

m1 <- ctModel(type = 'stanct',
  manifestNames = c('Y1'), latentNames=c('eta1'),
  DRIFT=matrix(-.0001,nrow=1,ncol=1),
  DIFFUSION=matrix(0,nrow=1,ncol=1),
  T0VAR=matrix(0,nrow=1,ncol=1),
  CINT=matrix(c('cint1'),ncol=1),
  T0MEANS=matrix(c('t0m1'),ncol=1),
  LAMBDA = diag(1),
  MANIFESTMEANS=matrix(0,ncol=1),
  MANIFESTVAR=matrix(c('merror'),nrow=1,ncol=1))

ctModelLatex(m1)

#fit
f1 <- ctStanFit(datalong = dat2, ctstanmodel = m1, optimize=TRUE, nopriors=TRUE)

summary(f1)

#plots of individual subject models v data

```

```

ctKalman(f1,plot=TRUE,subjects=1,kalmanvec=c('y','yprior'),timestep=.01)
ctKalman(f1,plot=TRUE,subjects=1:3,kalmanvec=c('y','ysmooth'),timestep=.01,errorvec=NA)

ctStanPostPredict(f1, wait=FALSE) #compare randomly generated data from posterior to observed data

cf<-ctCheckFit(f1) #compare mean and covariance of randomly generated data to observed cov
plot(cf,wait=FALSE)

### Further example models

#Include intervention
m2 <- ctModel(type = 'stanct',
  manifestNames = c('Y1'), latentNames=c('eta1'),
  n.TDpred=1,TDpredNames = 'TD1', #this line includes the intervention
  TDPREDEFFECT=matrix(c('tdpredeffect'),nrow=1,ncol=1), #intervention effect
  DRIFT=matrix(-1e-5,nrow=1,ncol=1),
  DIFFUSION=matrix(0,nrow=1,ncol=1),
  CINT=matrix(c('cint1'),ncol=1),
  T0MEANS=matrix(c('t0m1'),ncol=1),
  T0VAR=matrix(0,nrow=1,ncol=1),
  LAMBDA = diag(1),
  MANIFESTMEANS=matrix(0,ncol=1),
  MANIFESTVAR=matrix(c('merror'),nrow=1,ncol=1))

#Individual differences in intervention, Bayesian estimation, covariates
m2i <- ctModel(type = 'stanct',
  manifestNames = c('Y1'), latentNames=c('eta1'),
  TIpredNames = 'age',
  TDpredNames = 'TD1', #this line includes the intervention
  TDPREDEFFECT=matrix(c('tdpredeffect||TRUE'),nrow=1,ncol=1), #intervention effect
  DRIFT=matrix(-1e-5,nrow=1,ncol=1),
  DIFFUSION=matrix(0,nrow=1,ncol=1),
  CINT=matrix(c('cint1'),ncol=1),
  T0MEANS=matrix(c('t0m1'),ncol=1),
  T0VAR=matrix(0,nrow=1,ncol=1),
  LAMBDA = diag(1),
  MANIFESTMEANS=matrix(0,ncol=1),
  MANIFESTVAR=matrix(c('merror'),nrow=1,ncol=1))

#Including covariate effects
m2ic <- ctModel(type = 'stanct',
  manifestNames = c('Y1'), latentNames=c('eta1'),
  n.TIpred = 1, TIpredNames = 'age',
  n.TDpred=1,TDpredNames = 'TD1', #this line includes the intervention
  TDPREDEFFECT=matrix(c('tdpredeffect'),nrow=1,ncol=1), #intervention effect
  DRIFT=matrix(-1e-5,nrow=1,ncol=1),
  DIFFUSION=matrix(0,nrow=1,ncol=1),
  CINT=matrix(c('cint1'),ncol=1),
  T0MEANS=matrix(c('t0m1'),ncol=1),
  T0VAR=matrix(0,nrow=1,ncol=1),

```

```

LAMBDA = diag(1),
MANIFESTMEANS=matrix(0,ncol=1),
MANIFESTVAR=matrix(c('merror'),nrow=1,ncol=1))

m2ic$pars$indvarying[m2ic$pars$matrix %in% 'TDPREDEFFECT'] <- TRUE

#Include deterministic dynamics
m3 <- ctModel(type = 'stanct',
  manifestNames = c('Y1'), latentNames=c('eta1'),
  n.TDpred=1,TDpredNames = 'TD1', #this line includes the intervention
  TDPREDEFFECT=matrix(c('tdpredeffect'),nrow=1,ncol=1), #intervention effect
  DRIFT=matrix('drift11',nrow=1,ncol=1),
  DIFFUSION=matrix(0,nrow=1,ncol=1),
  CINT=matrix(c('cint1'),ncol=1),
  T0MEANS=matrix(c('t0m1'),ncol=1),
  T0VAR=matrix('t0var11',nrow=1,ncol=1),
  LAMBDA = diag(1),
  MANIFESTMEANS=matrix(0,ncol=1),
  MANIFESTVAR=matrix(c('merror1'),nrow=1,ncol=1))

#Add system noise to allow for fluctuations that persist in time
m3n <- ctModel(type = 'stanct',
  manifestNames = c('Y1'), latentNames=c('eta1'),
  n.TDpred=1,TDpredNames = 'TD1', #this line includes the intervention
  TDPREDEFFECT=matrix(c('tdpredeffect'),nrow=1,ncol=1), #intervention effect
  DRIFT=matrix('drift11',nrow=1,ncol=1),
  DIFFUSION=matrix('diffusion',nrow=1,ncol=1),
  CINT=matrix(c('cint1'),ncol=1),
  T0MEANS=matrix(c('t0m1'),ncol=1),
  T0VAR=matrix('t0var11',nrow=1,ncol=1),
  LAMBDA = diag(1),
  MANIFESTMEANS=matrix(0,ncol=1),
  MANIFESTVAR=matrix(c(0),nrow=1,ncol=1))

#include 2nd latent process
m4 <- ctModel(n.manifest = 2,n.latent = 2, type = 'stanct',
  manifestNames = c('Y1','Y2'), latentNames=c('L1','L2'),
  n.TDpred=1,TDpredNames = 'TD1',
  TDPREDEFFECT=matrix(c('tdpredeffect1','tdpredeffect2'),nrow=2,ncol=1),
  DRIFT=matrix(c('drift11','drift21','drift12','drift22'),nrow=2,ncol=2),
  DIFFUSION=matrix(c('diffusion11','diffusion21',0,'diffusion22'),nrow=2,ncol=2),
  CINT=matrix(c('cint1','cint2'),nrow=2,ncol=1),
  T0MEANS=matrix(c('t0m1','t0m2'),nrow=2,ncol=1),
  T0VAR=matrix(c('t0var11','t0var21',0,'t0var22'),nrow=2,ncol=2),
  LAMBDA = matrix(c(1,0,0,1),nrow=2,ncol=2),

```

```

MANIFESTMEANS=matrix(c(0,0),nrow=2,ncol=1),
MANIFESTVAR=matrix(c('merror1',0,0,'merror2'),nrow=2,ncol=2))

#dynamic factor model -- fixing CINT to 0 and freeing indicator level intercepts

m3df <- ctModel(type = 'stanct',
  manifestNames = c('Y2','Y3'), latentNames=c('eta1'),
  n.TDpred=1,TDpredNames = 'TD1', #this line includes the intervention
  TDPREDEFFECT=matrix(c('tdpredeffect'),nrow=1,ncol=1), #intervention effect
  DRIFT=matrix('drift11',nrow=1,ncol=1),
  DIFFUSION=matrix('diffusion',nrow=1,ncol=1),
  CINT=matrix(c(0),ncol=1),
  T0MEANS=matrix(c('t0m1'),ncol=1),
  T0VAR=matrix('t0var11',nrow=1,ncol=1),
  LAMBDA = matrix(c(1,'Y3loading'),nrow=2,ncol=1),
  MANIFESTMEANS=matrix(c('Y2_int','Y3_int'),nrow=2,ncol=1),
  MANIFESTVAR=matrix(c('Y2residual',0,0,'Y3residual'),nrow=2,ncol=2))

```

ctStanFitUpdate

Update a ctStanFit object

Description

Either to include different data, or because you have upgraded ctsem and the internal data structure has changed.

Usage

```
ctStanFitUpdate(oldfit, data = NA, recompile = FALSE, ...)
```

Arguments

oldfit	fit object to be upgraded
data	replacement long format data object
recompile	whether to force a recompile – safer but slower and usually unnecessary.
...	extra arguments to pass to ctStanFit

Value

updated ctStanFit object.

Examples

```

if(w32chk()){
newfit <- ctStanFitUpdate(ctstantestfit)
}

```

ctStanGenerate	<i>Generate data from a ctstanmodel object</i>
----------------	--

Description

Generate data from a ctstanmodel object

Usage

```
ctStanGenerate(
  ctm,
  datastruct,
  optimize = TRUE,
  is = FALSE,
  fullposterior = TRUE,
  nsamples = 200,
  parsonly = FALSE,
  includePreds = FALSE,
  ...
)
```

Arguments

ctm	ctStanModel object.
datastruct	long format data structure as used by ctsem.
optimize	Whether to optimize or use Stan's HMC sampler
is	If optimizing, follow up with importance sampling?
fullposterior	Generate from the full posterior or just the mean?
nsamples	How many samples to generate?
parsonly	If TRUE, only return samples of raw parameters, don't generate data.
includePreds	if TRUE, the prior for covariate effects (TD and TI predictors) is included, as well as the TD and TI pred data. Else the effects are set to zero.
...	arguments to pass to stanoptimis

Value

Array of nsamples x time points x manifest variables.

Examples

```
#generate and plot samples from prior predictive
priorpred <- ctStanGenerate(ctm = ctstantestfit$ctstanmodelbase,
  datastruct = ctstantestdat,cores=2,nsamples = 50)
```

`ctStanGenerateFromFit` *Add a \$generated object to ctstanfit object, with random data generated from posterior of ctstanfit object*

Description

Add a \$generated object to ctstanfit object, with random data generated from posterior of ctstanfit object

Usage

```
ctStanGenerateFromFit(
  fit,
  nsamples = 200,
  fullposterior = FALSE,
  verboseErrors = FALSE
)
```

Arguments

<code>fit</code>	ctstanfit object
<code>nsamples</code>	Positive integer specifying number of datasets to generate.
<code>fullposterior</code>	Logical indicating whether to sample from the full posterior (original nsamples) or the posterior mean.
<code>verboseErrors</code>	if TRUE, print verbose output when errors in generation encountered.

Value

Matrix of generated data – one dataset per iteration, according to original time and missingness structure.

Examples

```
if(w32chk()){
  gen <- ctStanGenerateFromFit(ctstantestfit, nsamples=3,fullposterior=TRUE)
  plot(gen$generated$Y[,3,2],type='l') #Third random data sample, 2nd manifest var, all time points.
}
```

ctStanKalman

Get Kalman filter estimates from a ctStanFit object

Description

Get Kalman filter estimates from a ctStanFit object

Usage

```
ctStanKalman(
  fit,
  nsamples = NA,
  collapsefunc = NA,
  cores = 2,
  standardisederrors = FALSE,
  subjectpars = FALSE,
  tformsubjectpars = TRUE,
  indvarstates = FALSE,
  ...
)
```

Arguments

fit	fit object from ctStanFit .
nsamples	either NA (to extract all) or a positive integer from 1 to maximum samples in the fit.
collapsefunc	function to apply over samples, such as mean
cores	Integer number of cpu cores to use. Only needed if savescores was set to FALSE when fitting.
standardisederrors	If TRUE, computes standardised errors for prior, upd, smooth conditions.
subjectpars	if TRUE, state estimates are not returned, instead, predictions of each subjects parameters are returned, for parameters that had random effects specified.
tformsubjectpars	if FALSE, subject level parameters are returned in raw, pre transformation form.
indvarstates	if TRUE, do not remove indvarying states from output
...	additional arguments to collapsefunc.

Value

list containing Kalman filter elements, each element in array of iterations, data row, variables. llrow is the log likelihood for each row of data.

Examples

```
if(w32chk()){
k=ctStanKalman(ctstantestfit,subjectpars=TRUE,collapsefunc=mean)
}
```

ctStanModel	<i>Convert a frequentist (omx) ctsem model specification to Bayesian (Stan).</i>
-------------	--

Description

Convert a frequentist (omx) ctsem model specification to Bayesian (Stan).

Usage

```
ctStanModel(ctmodelobj, type = "stanct", tipredDefault = TRUE)
```

Arguments

ctmodelobj	ctsem model object of type 'omx' (default)
type	either 'stanct' for continuous time, or 'standt' for discrete time.
tipredDefault	Logical. TRUE sets any parameters with unspecified time independent predictor effects to have effects estimated, FALSE fixes the effect to zero unless individually specified.

Value

List object of class ctStanModel, with random effects specified for any intercept type parameters (TOMEANS, MANIFESTMEANS, and or CINT), and time independent predictor effects for all parameters. Adjust these after initial specification by directly editing the pars subobject, so model\$pars.

Examples

```
model <- ctModel(type='omx', Tpoints=50,
n.latent=2, n.manifest=1,
manifestNames='sunspots',
latentNames=c('ss_level', 'ss_velocity'),
LAMBDA=matrix(c( 1, 'ma1' ), nrow=1, ncol=2),
DRIFT=matrix(c(0, 1, 'a21', 'a22'), nrow=2, ncol=2, byrow=TRUE),
MANIFESTMEANS=matrix(c('m1'), nrow=1, ncol=1),
# MANIFESTVAR=matrix(0, nrow=1, ncol=1),
CINT=matrix(c(0, 0), nrow=2, ncol=1),
DIFFUSION=matrix(c(
0, 0,
0, "diffusion"), ncol=2, nrow=2, byrow=TRUE))

stanmodel=ctStanModel(model)
```

ctStanParMatrices	Returns population system matrices from a ctStanFit object, and vector of values for free parameters.
-------------------	---

Description

Returns population system matrices from a ctStanFit object, and vector of values for free parameters.

Usage

```
ctStanParMatrices(fit, parvalues, timeinterval = 1, sf = NA)
```

Arguments

fit	ctStanFit object.
parvalues	vector of parameter values to assign to free parameters in the model
timeinterval	time interval to use for discrete time (dt) matrix calculations.
sf	stanfit object. Generally not necessary, but for repeated calls to this function, can speed things up.

Value

A list containing various matrices related to a continuous time dynamic model. Matrices with "dt" in front refers to discrete time, "asym" refers to asymptotic (time interval = infinity), and "cor" refers to correlations.

Examples

```
if(w32chk()){  
  
  ctStanParMatrices(ctstantestfit,  
    rnorm(length(ctstantestfit$stanfit$rawest),0,.1))  
}
```

ctStanParnames	<i>ctStanParnames</i>
----------------	-----------------------

Description

Gets internal stan parameter names of a ctStanFit object sampled via stan based on specified substrings.

Usage

```
ctStanParnames(x, substrings = c("pop_", "popsd"))
```

Arguments

x	ctStanFit object
substrings	vector of character strings, parameter names of the stan model containing any of these strings will be returned. Useful strings may be 'pop_' for population means, 'popsd' for population standard deviations, or specific combinations such as 'pop_DRIFT' for the population means of temporal dynamics parameters

Value

vector of character strings.

Examples

```
sunspots<-sunspot.year
sunspots<-sunspots[50: (length(sunspots) - (1988-1924))]
id <- 1
time <- 1749:1924
datalong <- cbind(id, time, sunspots)

#setup model
ssmodel <- ctModel(type='stanct', n.latent=2, n.manifest=1,
  manifestNames='sunspots',
  latentNames=c('ss_level', 'ss_velocity'),
  LAMBDA=matrix(c( 1, 'ma1| log(1+(exp(param)))' ), nrow=1, ncol=2),
  DRIFT=matrix(c(0, 'a21 | -log(1+exp(param))', 1, 'a22'), nrow=2, ncol=2),
  MANIFESTMEANS=matrix(c('m1|param * 10 + 44'), nrow=1, ncol=1),
  MANIFESTVAR=diag(0,1), #As per original spec
  CINT=matrix(c(0, 0), nrow=2, ncol=1),
  DIFFUSION=matrix(c(0, 0, 0, "diffusion"), ncol=2, nrow=2))

#fit
ssfit <- ctStanFit(datalong, ssmodel, iter=2,
  optimize=FALSE, chains=1)
ctStanParnames(ssfit,substrings=c('pop_', 'popsd'))
```

ctStanPlotPost	<i>ctStanPlotPost</i>
----------------	-----------------------

Description

Plots prior and posterior distributions of model parameters in a ctStanModel or ctStanFit object.

Usage

```
ctStanPlotPost(
  obj,
  rows = "all",
  npp = 6,
  priorwidth = TRUE,
  smoothness = 1,
  priorsamples = 10000,
  plot = TRUE,
  wait = FALSE,
  ...
)
```

Arguments

obj	fit or model object as generated by <code>ctStanFit</code> , <code>ctModel</code> , or <code>ctStanModel</code> .
rows	vector of integers denoting which rows of <code>obj\$setup\$popsetup</code> to plot priors for. Character string 'all' plots all rows with parameters to be estimated.
npp	Integer number of parameters to show per page.
priorwidth	if TRUE, plots will be scaled to show bulk of both the prior and posterior distributions. If FALSE, scale is based only on the posterior.
smoothness	Positive numeric – multiplier to modify smoothness of density plots, higher is smoother but can cause plots to exceed natural boundaries, such as standard deviations below zero.
priorsamples	number of samples from prior to use. More is slower.
plot	Logical, if FALSE, ggplot objects are returned in a list instead of plotting.
wait	If true, user is prompted to continue before plotting next graph. If false, graphs are plotted one after another without waiting.
...	Parameters to pass to <code>ctStanFit</code> . <code>cores = x</code> will speed things up, where x is the number of cpu cores to use.

Examples

```
ctStanPlotPost(ctstantestfit, rows=3:4)
```

ctStanPostPredict	<i>Compares model implied density and values to observed, for a ctStanFit object.</i>
-------------------	---

Description

Compares model implied density and values to observed, for a ctStanFit object.

Usage

```
ctStanPostPredict(
  fit,
  diffsize = 1,
  jitter = 0.02,
  wait = TRUE,
  probs = c(0.025, 0.5, 0.975),
  datarows = "all",
  nsamples = 500,
  resolution = 100,
  plot = TRUE
)
```

Arguments

fit	ctStanFit object.
diffsize	Integer > 0. Number of discrete time lags to use for data viz.
jitter	Positive numeric between 0 and 1, if TRUE, jitters empirical data by specified proportion of std dev.
wait	Logical, if TRUE and plot=TRUE, waits for input before plotting next plot.
probs	Vector of length 3 containing quantiles to plot – should be rising numeric values between 0 and 1.
datarows	integer vector specifying rows of data to plot. Otherwise 'all' uses all data.
nsamples	Number of datasets to generate for comparisons, if fit object does not contain generated data already.
resolution	Positive integer, the number of rows and columns to split plots into for shading.
plot	logical. If FALSE, a list of ggplot objects is returned.

Details

This function relies on the data generated during each iteration of fitting to approximate the model implied distributions – thus, when limited iterations are available, the approximation will be worse.

Value

If `plot=FALSE`, an array containing quantiles of generated data. If `plot=TRUE`, nothing, only plots.
 if `plot=TRUE`, nothing is returned and plots are created. Otherwise, a list containing ggplot objects is returned and may be customized as desired.

Examples

```
if(w32chk()){
  ctStanPostPredict(ctstantestfit,wait=FALSE, diffsize=2,resolution=100)
}
```

ctstantestdat	<i>ctstantestdat</i>
---------------	----------------------

Description

Generated dataset for testing [ctStanFit](#) from ctsem package.

Format

matrix

ctstantestfit	<i>ctstantestfit</i>
---------------	----------------------

Description

Dummy fit for testing functions from ctsem package.

Format

ctStanFit object

ctStanTIpredEffects *Get time independent predictor effect estimates*

Description

Computes and plots combined effects and quantiles for effects of time independent predictors on subject level parameters of a ctStanFit object.

Usage

```
ctStanTIpredEffects(
  fit,
  returndifference = FALSE,
  probs = c(0.025, 0.5, 0.975),
  includeMeanUncertainty = FALSE,
  whichTIpreds = 1,
  parmatrices = TRUE,
  whichpars = "all",
  nsamples = 100,
  timeinterval = 1,
  nsubjects = 20,
  filter = NA,
  plot = FALSE
)
```

Arguments

fit	fit object from ctStanFit
returndifference	logical. If FALSE, absolute parameter values are returned. If TRUE, only the effect of the covariate (i.e. without the average value of the parameter) are returned. The former can be easier to interpret, but the latter are more likely to fit multiple plots together. Not used if parmatrices=TRUE.
probs	numeric vector of quantile probabilities from 0 to 1. Specify 3 values if plotting, the 2nd will be drawn as a line with uncertainty polygon based on 1st and 3rd.
includeMeanUncertainty	if TRUE, output includes sampling variation in the mean parameters. If FALSE, mean parameters are fixed at their median, only uncertainty in time independent predictor effects is included.
whichTIpreds	integer vector specifying which of the tipreds in the fit object you want to use to calculate effects. Unless quadratic / higher order versions of predictors have been included, selecting more than one probably doesn't make sense. If for instance a squared predictor has been included, then you can specify both the linear and squared version. The x axis of the plot (if generated) will be based off the first indexed predictor. To check what predictors are in the model, run <code>fit\$ctstanmodel\$TIpredNames</code> .

parmatrices	Logical. If TRUE (default), the <code>ctStanParMatrices</code> function is used to return an expanded range of possible matrices of interest.
whichpars	if <code>parmatrices==TRUE</code> , character vector specifying which matrices, and potentially which indices of the matrices, to plot. <code>c('dtDRIFT[2,1]', 'DRIFT')</code> would output for row 2 and column 1 of the discrete time drift matrix, as well as all indices of the continuous time drift matrix. If <code>parmatrices==FALSE</code> , integer vector specifying which of the subject level parameters to compute effects on. The integers corresponding to certain parameters can be found in the <code>param</code> column of the <code>fit\$setup\$matsetup</code> object. In either case 'all' uses all available parameters.
nsamples	Positive integer specifying the maximum number of saved iterations to use. Character string 'all' can also be used.
timeinterval	positive numeric indicating time interval to use for discrete time parameter matrices, if <code>parmatrices=TRUE</code> .
nsubjects	Positive integer specifying the number of subjects to compute values for. When only one TIpred is used, this specifies the number of points along the curve. Character string 'all' can also be used. Time taken for plotting is a function of <code>nsubjects*niterations</code> .
filter	either NA, or a length 2 vector, where the first element contains the time independent predictor index to filter by, and the second contains the comparison operator in string form (e.g. "< 3", to only calculate effects for subjects where the tipreds of the denoted index are less than 3).
plot	Logical. If TRUE, nothing is returned but instead <code>ctPlotArray</code> is used to plot the output instead.

Value

Either a three dimensional array of predictor effects, or nothing with a plot generated.

Examples

```
if(w32chk()){
  ctStanTIpredEffects(ctstantestfit,
    whichpars=c('CINT', 'dtDIFFUSION[2,2]'), plot=TRUE)
}
```

`ctStanTIpredMarginal` *Plot marginal relationships between covariates and parameters for a ctStanFit object.*

Description

Plot marginal relationships between covariates and parameters for a ctStanFit object.

Usage

```
ctStanTIpredMarginal(fit, tipred, pars, matrices = TRUE, plot = TRUE)
```

Arguments

fit	ctStanFit object.
tipred	character vector representing which tipreds to use.
pars	Character vector of either parameter names, or if matrices=TRUE, system matrices with optional indices – e.g, 'DRIFT' or 'DIFFUSION[2,1]'.
matrices	Logical, see pars argument.
plot	Logical, whether to plot.

Value

If plot=TRUE, nothing, otherwise an array that can be used with ctPlotArray.

Examples

```
if(w32chk()){#'
ctStanTIpredMarginal(ctstantestfit,pars=c('CINT'),
  matrices=TRUE, tipred=c('TI1'))
}
```

 ctStanUpdModel

Update an already compiled and fit ctStanFit object

Description

Allows one to change data and or model elements that don't require recompiling, then re fit.

Usage

```
ctStanUpdModel(fit, datalong, ctstanmodel, ...)
```

Arguments

fit	ctStanFit object
dalong	data as normally passed to ctStanFit
ctstanmodel	model as normally passed to ctStanFit
...	extra args for ctStanFit

ctWideNames	<i>ctWideNames sets default column names for wide ctsem datasets. Primarily intended for internal ctsem usage.</i>
-------------	--

Description

ctWideNames sets default column names for wide ctsem datasets. Primarily intended for internal ctsem usage.

Usage

```
ctWideNames(
  n.manifest,
  Tpoints,
  n.TDpred = 0,
  n.TIpred = 0,
  manifestNames = "auto",
  TDpredNames = "auto",
  TIpredNames = "auto"
)
```

Arguments

n.manifest	number of manifest variables per time point in the data.
Tpoints	Maximum number of discrete time points (waves of data, or measurement occasions) for an individual in the input data structure.
n.TDpred	number of time dependent predictors in the data structure.
n.TIpred	number of time independent predictors in the data structure.
manifestNames	vector of character strings giving column names of manifest indicator variables
TDpredNames	vector of character strings giving column names of time dependent predictor variables
TIpredNames	vector of character strings giving column names of time independent predictor variables

ctWideToLong	<i>ctWideToLong Convert ctsem wide to long format</i>
--------------	---

Description

ctWideToLong Convert ctsem wide to long format

Usage

```
ctWideToLong(
  datawide,
  Tpoints,
  n.manifest,
  n.TDpred = 0,
  n.TIpred = 0,
  manifestNames = "auto",
  TDpredNames = "auto",
  TIpredNames = "auto"
)
```

Arguments

datawide	ctsem wide format data
Tpoints	number of measurement occasions in data
n.manifest	number of manifest variables
n.TDpred	number of time dependent predictors
n.TIpred	number of time independent predictors
manifestNames	Character vector of manifest variable names.
TDpredNames	Character vector of time dependent predictor names.
TIpredNames	Character vector of time independent predictor names.

Details

Names must account for **all** the columns in the data - i.e. do not leave certain variables out just because you do not need them.

Examples

```
#create wide data
wideexample <- ctLongToWide(datalong = ctstantestdat, id = "id",
  time = "time", manifestNames = c("Y1", "Y2"),
  TDpredNames = "TD1", TIpredNames = c("TI1", "TI2", "TI3"))

wide <- ctIntervalise(datawide = wideexample, Tpoints = 10, n.manifest = 2,
  n.TDpred = 1, n.TIpred = 3, manifestNames = c("Y1", "Y2"),
  TDpredNames = "TD1", TIpredNames = c("TI1", "TI2", "TI3") )

#Then convert to long format
longexample <- ctWideToLong(datawide = wideexample, Tpoints=10,
  n.manifest=2, manifestNames = c("Y1", "Y2"),
  n.TDpred=1, TDpredNames = "TD1",
  n.TIpred=3, TIpredNames = c("TI1", "TI2", "TI3"))

#Then convert the time intervals to absolute time
long <- ctDeintervalise(datalong = longexample, id='id', dT='dT')
head(long,22)
```

datastructure	<i>datastructure</i>
---------------	----------------------

Description

Simulated example dataset for the ctsem package

Format

2 by 15 matrix containing containing ctsem wide format data. 3 measurement occasions of manifest variables Y1 and Y2, 2 measurement occasions of time dependent predictor TD1, 2 measurement intervals dTx, and 2 time independent predictors TI1 and TI2, for 2 individuals.

inv_logit	<i>Inverse logit</i>
-----------	----------------------

Description

Maps the stan function so the same code works in R.

Usage

```
inv_logit(x)
```

Arguments

x value to calculate the inverse logit for.

Examples

```
inv_logit(-3)
```

 isdiag

Diagnostics for ctsem importance sampling

Description

Diagnostics for ctsem importance sampling

Usage

```
isdiag(fit)
```

Arguments

`fit` Output from `ctStanFit` when `optimize=TRUE` and `isloops > 0`

Value

Nothing. Plots convergence of parameter mean estimates from initial Hessian based distribution to final sampling distribution.

Examples

```
#get data
sunspots<-sunspot.year
sunspots<-sunspots[50: (length(sunspots) - (1988-1924))]
id <- 1
time <- 1749:1924
datalong <- cbind(id, time, sunspots)

#setup model
model <- ctModel(type='stanct',
  manifestNames='sunspots',
  latentNames=c('ss_level', 'ss_velocity'),
  LAMBDA=matrix(c( -1, 'ma1 | log(exp(-param)+1)' ), nrow=1, ncol=2),
  DRIFT=matrix(c(0, 'a21', 1, 'a22'), nrow=2, ncol=2),
  MANIFESTMEANS=matrix(c('m1 | (param)*5+44'), nrow=1, ncol=1),
  CINT=matrix(c(0, 0), nrow=2, ncol=1),
  T0VAR=matrix(c(1,0,0,1), nrow=2, ncol=2), #Because single subject
  DIFFUSION=matrix(c(0.0001, 0, 0, "diffusion"), ncol=2, nrow=2))

#fit and plot importance sampling diagnostic
fit <- ctStanFit(datalong, model,
  optimcontrol=list(finishsamples=500),nopriors=FALSE)
isdiag(fit)
```

Kalman	<i>Kalman</i>
--------	---------------

Description

Takes list containing ctsem subject matrices, as well as long form data object, and calculates predicted and updated latent states, likelihoods, and predicted observations using the Kalman filter.

Usage

```
Kalman(
  kpars,
  datalong,
  manifestNames,
  latentNames,
  imputeMissings = FALSE,
  TDpredNames = NULL,
  continuoustime = TRUE,
  idcol = "id",
  timecol = "time",
  derrind = "all",
  optimize = FALSE,
  ukf = FALSE,
  plotoptim = FALSE
)
```

Arguments

<code>kpars</code>	list object containing DRIFT, T0VAR, DIFFUSION, CINT, T0MEANS, TDPREDEFFECT, MANIFESTMEANS, LAMBDA, and MANIFESTVAR matrices, with list elements named accordingly. Such a list is returned by ctStanContinuousPars .
<code>dalong</code>	long format data object as used by ctStanFit , but must contain only a single subjects' data and does not need an id column.
<code>manifestNames</code>	String vector of names of manifest variables to use from <code>dalong</code> .
<code>latentNames</code>	String vector of names of latent variables.
<code>imputeMissings</code>	Logical. If TRUE, randomly generate any missing observations of manifest variables according to model.
<code>TDpredNames</code>	If model contains time dependent predictors, string vector of their names in the data.
<code>continuoustime</code>	Logical, whether to use a continuous time Kalman filter or discrete time. Refers only to latent states, observations are always at discrete time points.
<code>idcol</code>	Character string giving name of subject identification column in data.
<code>timecol</code>	name of time column in <code>dalong</code> . Note that time column must be an ascending sequence of numeric values from row 1 to row n. Ignored if <code>continuoustime=FALSE</code> .

derrind	vector of integers denoting which latent variables are involved in covariance calcs.
optimize	Set to TRUE when using for optimization.
ukf	set to TRUE to use the unscented Kalman filter, only necessary for fitting non-linear models, currently only for optimizing.
plotoptim	set to TRUE to plot / print optimization steps.

Value

When optimize=TRUE, returns log likelihood. Else, returns a list containing matrix objects etaprior, etaupd, etasmooth, y, yprior, yupd, ysmooth, prederror, time, loglik, with values for each time point in each row. eta refers to latent states and y to manifest indicators - y itself is thus just the input data. Covariance matrices etapriorcov, etaupdcov, etasmoothcov, ypriorcov, yupdcov, ysmoothcov, are returned in a row * column * time array.

Examples

```
### get parameter matrices

kpars <- ctStanContinuousPars(ctstantestfit)

#construct dummy data
datalong <- cbind(0:9, 1, matrix(rnorm(20,2,1),ncol=2))
datalong[c(1:3,9:10),3:4]<-NA #missing data to pre/fore cast
colnames(datalong) <- c('time', 'id', paste0('Y',1:2))
print(datalong)

#obtain Kalman filtered estimates
kout <- Kalman(kpars=kpars, datalong=datalong,
  manifestNames=paste0('Y',1:nrow(kpars$MANIFESTMEANS)),
  latentNames=paste0('eta',1:nrow(kpars$DRIFT)))

#print and plot smoothed estimates (conditional on all states) of indicators.
print(kout$ysmooth)
matplot(kout$time,kout$ysmooth,type='l')
matplot(kout$time,datalong[,3:4],type='p',add=TRUE,pch=1)
```

log1p_exp

log1p_exp

Description

Maps the stan function so the same code works in R.

Usage

```
log1p_exp(x)
```

Arguments

x value to use.

Examples

```
log1p_exp(-3)
```

longexample	<i>longexample</i>
-------------	--------------------

Description

Simulated example dataset for the ctsem package

Format

7 by 8 matrix containing ctsem long format data, for two subjects, with three manifest variables Y1, Y2, Y3, one time dependent predictor TD1, two time independent predictors TI1 and TI2, and absolute timing information Time.

Oscillating	<i>Oscillating</i>
-------------	--------------------

Description

Simulated example dataset for the ctsem package.

Format

200 by 21 matrix containing containing ctsem wide format data. 11 measurement occasions and 10 measurement intervals for each of 200 individuals

Source

See <https://onlinelibrary.wiley.com/doi/10.1111/j.2044-8317.2012.02043.x>

plot.ctKalmanDF *Plots Kalman filter output from ctKalman.*

Description

Plots Kalman filter output from ctKalman.

Usage

```
## S3 method for class 'ctKalmanDF'
plot(
  x,
  subjects = 1,
  kalmanvec = c("y", "yprior"),
  errorvec = "auto",
  errormultiply = 1.96,
  plot = TRUE,
  elementNames = NA,
  polygonsteps = 10,
  polygonalpha = 0.1,
  facets = vars(Variable),
  ...
)
```

Arguments

x	Output from <code>ctKalman</code> . In general it is easier to call <code>ctKalman</code> directly with the <code>plot=TRUE</code> argument, which calls this function.
subjects	vector of integers denoting which subjects (from 1 to N) to plot predictions for.
kalmanvec	string vector of names of any elements of the output you wish to plot, the defaults of 'y' and 'ysmooth' plot the original data, 'y', and the estimates of the 'true' value of y given all data. Replacing 'y' by 'eta' will plot latent states instead (though 'eta' alone does not exist) and replacing 'smooth' with 'upd' or 'prior' respectively plots updated (conditional on all data up to current time point) or prior (conditional on all previous data) estimates.
errorvec	vector of names indicating which kalmanvec elements to plot uncertainty bands for. 'auto' plots all possible.
errormultiply	Numeric denoting the multiplication factor of the std deviation of errorvec objects. Defaults to 1.96, for 95% intervals.
plot	if FALSE, plots are not generated and the ggplot object is simply returned invisibly.
elementNames	if NA, all relevant object elements are included – e.g. if yprior is in the kalmanvec argument, all manifest variables are plotted, and likewise for latent states if etasmooth was specified. Alternatively, a character vector specifying the manifest and latent names to plot explicitly can be specified.

polygonsteps	Number of steps to use for uncertainty band shading.
polygonalpha	Numeric for the opacity of the uncertainty region.
facets	when multiple subjects are included in multivariate plots, the default is to facet plots by variable type. This can be set to NA for no facets, or variable(Subject) for facetting by subject.
...	not used.

Value

A ggplot2 object. Side effect – Generates plots.

Examples

```
if(w32chk()){

### Get output from ctKalman
x<-ctKalman(ctstantestfit,subjects=2,timestep=.01)

### Plot with plot.ctKalmanDF
plot(x, subjects=2)

###Single step procedure:
ctKalman(ctstantestfit,subjects=2,
  kalmanvec=c('y','yprior'),
  elementNames=c('Y1','Y2'),
  plot=TRUE,timestep=.01)
}
```

plot.ctsemFitMeasure *Misspecification plot using ctCheckFit output*

Description

Misspecification plot using ctCheckFit output

Usage

```
## S3 method for class 'ctsemFitMeasure'
plot(
  x,
  indices = "all",
  means = TRUE,
  separatemeans = TRUE,
  cov = TRUE,
  covtype = "MisspecRatio",
  cov2cor = FALSE,
  wait = TRUE,
```

```

ggcorrArgs = list(data = NULL, cor_matrix = get(covtype), limits = limits, geom =
  "circle", max_size = 10, name = covtype),
  ...
)

```

Arguments

x	Object output from ctCheckFit function.
indices	Either 'all' or a vector of integers denoting which observations to include (from 1 to n.manifest * maximum number of obs for a subject, blocked by manifest).
means	Logical – plot simulated means vs observed?
separatemeans	Logical – means from different variables on same or different plots?
cov	Logical – plot simulated cov vs observed?
covtype	Column name of \$cov sub object
cov2cor	Logical – convert covariances to correlations?
wait	Logical – wait for input before new plot?
ggcorrArgs	List of arguments to GGally::ggcorr .
...	not used.

Value

Nothing, just plots.

Examples

```

if(w32chk()){

scheck <- ctCheckFit(ctstantestfit,niter=50)
plot(scheck,wait=FALSE)

}

```

plot.ctStanFit

plot.ctStanFit

Description

Plots for ctStanFit objects

Usage

```

## S3 method for class 'ctStanFit'
plot(x, types = "all", wait = TRUE, ...)

```

Arguments

x	Fit object from ctStanFit .
types	Vector of character strings defining which plots to create. 'all' plots all possible types, including: 'regression', 'kalman', 'priorcheck', 'trace', 'density', 'intervals'.
wait	Logical. Pause between plots?
...	Arguments to pass through to the specific plot functions. Bewar of clashes may occur if types='all'. For details see the specific functions generating each type of plot.

Details

This function is just a wrapper calling the necessary functions for plotting - it may be simpler in many cases to access those directly. They are: [ctStanDiscretePars](#), [ctKalman](#), [ctStanPlotPost](#), [stan_trace](#), [stan_dens](#), [stan_plot](#) rstan offers many plotting possibilities not available here, to use that functionality one must simply call the relevant rstan plotting function. Use `x$stanfit` as the stan fit object (where x is the name of your ctStanFit object). Because a ctStanFit object has many parameters, the additional argument `pars=ctStanParnames(x, 'pop_')` is recommended. This denotes population means, but see [ctStanParnames](#) for other options.

Value

Nothing. Generates plots.

Examples

```
plot(ctstantestfit, types=c('regression', 'kalman', 'priorcheck'), wait=FALSE)
```

plot.ctStanModel *Prior plotting*

Description

Plots priors for free model parameters in a ctStanModel.

Usage

```
## S3 method for class 'ctStanModel'
plot(
  x,
  rows = "all",
  wait = FALSE,
  nsamples = 1e+06,
  rawpopsd = "marginalise",
  indifdevs = c(-1, 1),
```

```

    plot = TRUE,
    ...
  )

```

Arguments

x	ctStanModel object as generated by <code>ctModel</code> with type='stanct' or 'standt'.
rows	vector of integers denoting which rows of <code>ctstanmodel\$pars</code> to plot priors for. Character string 'all' plots all rows with parameters to be estimated.
wait	If true, user is prompted to continue before plotting next graph.
nsamples	Numeric. Higher values increase fidelity (smoothness / accuracy) of density plots, at cost of speed.
rawpopstd	Either 'marginalise' to sample from the specified (in the <code>ctstanmodel</code>) prior distribution for the raw population standard deviation, or a numeric value to use for the raw population standard deviation for all subject level prior plots - the plots in dotted blue or red.
inddifdevs	numeric vector of length 2, setting the means for the individual differences distributions.
plot	If FALSE, outputs list of GGplot objects that can be further modified.
...	not used.

Details

Plotted in black is the prior for the population mean. In red and blue are the subject level priors that result given that the population mean is estimated as 1 std deviation above the mean of the prior, or 1 std deviation below. The distributions around these two points are then obtained by marginalising over the prior for the raw population std deviation - so the red and blue distributions do not represent any specific subject level prior, but rather characterise the general amount and shape of possible subject level priors at the specific points of the population mean prior.

Examples

```

model <- ctModel(type='stanct',
  manifestNames='sunspots',
  latentNames=c('ss_level', 'ss_velocity'),
  LAMBDA=matrix(c( 1, 'ma1' ), nrow=1, ncol=2),
  DRIFT=matrix(c(0, 1, 'a21', 'a22'), nrow=2, ncol=2, byrow=TRUE),
  MANIFESTMEANS=matrix(c('m1'), nrow=1, ncol=1),
  # MANIFESTVAR=matrix(0, nrow=1, ncol=1),
  CINT=matrix(c(0, 0), nrow=2, ncol=1),
  DIFFUSION=matrix(c(
    0, 0,
    0, "diffusion"), ncol=2, nrow=2, byrow=TRUE))

plot(model, rows=8)

```

sdpcor2cov

sdcor2cov

Description

Converts a lower triangular matrix with standard deviations on the diagonal and partial correlations on lower triangle, to a covariance (or cholesky decomposed covariance)

Usage

```
sdpcor2cov(mat, cholesky = FALSE)
```

Arguments

mat	input square matrix with std dev on diagonal and lower tri of partial correlations.
cholesky	Logical. To return the cholesky decomposition instead of full covariance, set to TRUE.

Examples

```
testmat <- diag(exp(rnorm(5,-3,2)),5) #generate arbitrary std deviations
testmat[row(testmat) > col(testmat)] <- runif((5^2-5)/2, -1, 1)
print(testmat)
covmat <- sdpcor2cov(testmat) #convert to covariance
cov2cor(covmat) #convert covariance to correlation
```

standatact_specificsubjects

Adjust standata from ctsem to only use specific subjects

Description

Adjust standata from ctsem to only use specific subjects

Usage

```
standatact_specificsubjects(standata, subjects, timestep = NA)
```

Arguments

standata	standata
subjects	vector of subjects
timestep	ignored at present

Value

list of updated structure

Examples

```
if(w32chk()){  
  
d <- standatact_specificsubjects(ctstantestfit$standata, 1:2)  
}
```

stanoptimis

Optimize / importance sample a stan or ctStan model.

Description

Optimize / importance sample a stan or ctStan model.

Usage

```
stanoptimis(  
  standata,  
  sm,  
  init = "random",  
  initsd = 0.01,  
  sampleinit = NA,  
  deoptim = FALSE,  
  estonly = FALSE,  
  tol = 1e-12,  
  decontrol = list(),  
  stochastic = TRUE,  
  nopriors = FALSE,  
  carefulfit = TRUE,  
  subsamplesize = 0.5,  
  finitediff = FALSE,  
  parsteps = c(),  
  plot = FALSE,  
  is = FALSE,  
  isloopsize = 1000,  
  finishsamples = 1000,  
  tdf = 10,  
  chancethreshold = 100,  
  finishmultiply = 5,  
  verbose = 0,  
  cores = 2  
)
```

Arguments

standata	list object conforming to rstan data standards.
sm	compiled stan model object.
init	vector of unconstrained parameter values, or character string 'random' to initialise with random values very close to zero.
initsd	positive numeric specifying sd of normal distribution governing random sample of init parameters, if init='random' .
sampleinit	either NA, or an niterations * nparams matrix of samples to initialise importance sampling.
deoptim	Do first pass optimization using differential evolution? Slower, but better for cases with multiple minima / difficult optimization.
estonly	if TRUE, just return point estimates under \$rawest subobject.
tol	objective tolerance.
decontrol	List of control parameters for differential evolution step, to pass to DEoptim.control.
stochastic	Logical. Use stochastic gradient descent instead of mize (bfgs) optimizer. Still experimental, worth trying for either robustness checks or problematic, high dimensional, nonlinear, problems.
nopriors	logical. If TRUE, a nopriors integer is set to 1 (TRUE) in the standata object – only has an effect if the stan model uses this value.
carefulfit	Logical. If TRUE, priors are always used for a rough first pass to obtain starting values when nopriors=TRUE.
subsamplesize	value between 0 and 1 representing proportion of subjects to include in first pass fit.
finitediff	Either 'ask', TRUE, or FALSE. Whether to use the slow finite difference calculations for the Hessian (used for confidence intervals) if other approaches do not give a positive definite result.
parsteps	ordered list of vectors of integers denoting which parameters should begin fixed at zero, and freed sequentially (by list order). Useful for complex models, e.g. keep all cross couplings fixed to zero as a first step, free them in second step.
plot	Logical. If TRUE, plot iteration details. Probably slower.
is	Logical. Use importance sampling, or just return map estimates?
isloopsiz	Number of samples of approximating distribution per iteration of importance sampling.
finishsamples	Number of samples to draw (either from hessian based covariance or posterior distribution) for final results computation.
tdf	degrees of freedom of multivariate t distribution. Higher (more normal) generally gives more efficient importance sampling, at risk of truncating tails.
chancethreshold	drop iterations of importance sampling where any samples are chancethreshold times more likely to be drawn than expected.
finishmultiply	Importance sampling stops once available samples reach finishsamples * finishmultiply , then the final samples are drawn without replacement from this set.

verbose	Integer from 0 to 2. Higher values print more information during model fit – for debugging.
cores	Number of cpu cores to use, should be at least 2.

Value

list containing fit elementsF

stanWplot	<i>Runs stan, and plots sampling information while sampling.</i>
-----------	--

Description

Runs stan, and plots sampling information while sampling.

Usage

```
stanWplot(object, iter = 2000, chains = 4, ...)
```

Arguments

object	stan model object
iter	Number of iterations
chains	Number of chains
...	All the other regular arguments to stan()

Details

On windows, requires Rtools installed and able to be found by `pkgbuild::rtools_path()`

Examples

```
if(w32chk()){
  library(rstan)
  ##### example 1
  scode <- "
  parameters {
    real y[2];
  }
  model {
    y[1] ~ normal(0, .5);
    y[2] ~ double_exponential(0, 2);
  }
  "

  #Uncomment the following lines -- launches rscript not compatible with cran check.
  #sm <- stan_model(model_code = scode)
  #fit1 <- stanWplot(object = sm, iter = 100000, chains=2, cores=1)
}
```

stan_checkdivergences *Analyse divergences in a stanfit object*

Description

Analyse divergences in a stanfit object

Usage

```
stan_checkdivergences(sf, nupars = "all")
```

Arguments

sf	stanfit object.
nupars	either the string 'all', or an integer reflecting how many pars (from first to nupars) to use.

Value

A list of four matrices. \$locationssort and \$sdssort contain the bivariate interactions of unconstrained parameters, sorted by either the relative location of any divergences, or the relative standard deviation. \$locationmeans and \$sdmeans collapse across the bivariate interactions to return the means for each parameter.

Examples

```
sunspots<-sunspot.year
sunspots<-sunspots[50:(length(sunspots) - (1988-1924))]
id <- 1
time <- 1749:1924
datalong <- cbind(id, time, sunspots)

#setup model
ssmodel <- ctModel(type='stanct', n.latent=2, n.manifest=1,
  manifestNames='sunspots',
  latentNames=c('ss_level', 'ss_velocity'),
  LAMBDA=matrix(c( 1, 'ma1 | log(1+(exp(param)))' ), nrow=1, ncol=2),
  DRIFT=matrix(c(0, 'a21 | -log(1+exp(param))', 1, 'a22'), nrow=2, ncol=2),
  MANIFESTMEANS=matrix(c('m1|param * 10 + 44'), nrow=1, ncol=1),
  MANIFESTVAR=diag(0,1), #As per original spec
  CINT=matrix(c(0, 0), nrow=2, ncol=1),
  DIFFUSION=matrix(c(0, 0, 0, "diffusion"), ncol=2, nrow=2))

#fit
ssfit <- ctStanFit(datalong, ssmodel, iter=2,
  optimize=FALSE, chains=1)

stan_checkdivergences(ssfit$stanfit) #stan object
```

stan_postcalc	<i>Compute functions of matrices from samples of a stanfit object</i>
---------------	---

Description

Compute functions of matrices from samples of a stanfit object

Usage

```
stan_postcalc(
  stanfit,
  object,
  calc = "object",
  objectindices = "all",
  summary = TRUE
)
```

Arguments

stanfit	object of class stanfit.
object	name of stan sub object from stanfit to use for calculations.
calc	string containing R calculation to evaluate, with the string 'object' in place of the actual object name.
objectindices	matrix of indices, with the number of columns matching the number of dimensions of the object. 'all' computes <code>which(array(1, objdims)==1, arr.ind=TRUE)</code> , where objdims is what would be returned by <code>dim(object)</code> if the object existed in the R environment.
summary	if FALSE, a iterations * parameters matrix is returned, if TRUE, <code>rstan::monitor</code> is first run on the output.

Value

matrix of values of the specified interactions at each iteration.

stan_reinitsf	<i>Quickly initialise stanfit object from model and data</i>
---------------	--

Description

Quickly initialise stanfit object from model and data

Usage

```
stan_reinitsf(model, data, fast = FALSE)
```

Arguments

model	stanmodel
data	standata
fast	Use cut down form for speed

Value

stanfit object

Examples

```
if(w32chk()){
  sf <- stan_reinitsf(ctstantestfit$stanmodel,ctstantestfit$standata)
}
```

stan_unconstrainsamples

Convert samples from a stanfit object to the unconstrained scale

Description

Convert samples from a stanfit object to the unconstrained scale

Usage

```
stan_unconstrainsamples(fit, standata = NA)
```

Arguments

fit	stanfit object.
standata	only necessary if R session has been restarted since fitting model – used to reinitialize stanfit object.

Value

Matrix containing columns of unconstrained parameters for each post-warmup iteration.

Examples

```
#get data
sunspots<-sunspot.year
sunspots<-sunspots[50: (length(sunspots) - (1988-1924))]
id <- 1
time <- 1749:1924
datalong <- cbind(id, time, sunspots)
```

```

#setup model
ssmodel <- ctModel(type='stanct', n.latent=2, n.manifest=1,
  manifestNames='sunspots',
  latentNames=c('ss_level', 'ss_velocity'),
  LAMBDA=matrix(c( 1, 'ma1| log(1+(exp(param)))' ), nrow=1, ncol=2),
  DRIFT=matrix(c(0, 'a21 | -log(1+exp(param))', 1, 'a22'), nrow=2, ncol=2),
  MANIFESTMEANS=matrix(c('m1|param * 10 + 44'), nrow=1, ncol=1),
  MANIFESTVAR=diag(0,1), #As per original spec
  CINT=matrix(c(0, 0), nrow=2, ncol=1),
  DIFFUSION=matrix(c(0, 0, 0, "diffusion"), ncol=2, nrow=2))

#fit
ssfit <- ctStanFit(datalong, ssmodel,
  iter=200, chains=2,optimize=FALSE, nopriors=FALSE,control=list(max_treedepth=4))
umat <- stan_unconstrainsamples(ssfit$stanfit)

```

summary.ctStanFit

summary.ctStanFit

Description

Summarise a ctStanFit object that was fit using [ctStanFit](#).

Usage

```

## S3 method for class 'ctStanFit'
summary(
  object,
  timeinterval = 1,
  digits = 4,
  parmatrices = TRUE,
  priorcheck = TRUE,
  residualcov = TRUE,
  ...
)

```

Arguments

object	fit object from ctStanFit , of class ctStanFit.
timeinterval	positive numeric indicating time interval to use for discrete time parameter calculations reported in summary.
digits	integer denoting number of digits to report.
parmatrices	if TRUE, also return additional parameter matrices – can be slow to compute for large models with many samples.
priorcheck	Whether or not to use <code>ctsem:::priorchecking</code> to compare posterior mean and sd to prior mean and sd.

residualcov Whether or not to show standardised residual covariance. Takes a little longer to compute.

... Additional arguments to pass to `ctsem::priorcheckreport`, such as `meanlim`, or `sdlim`.

Value

List containing summary items.

Examples

```
if(w32chk()){
  summary(ctstantestfit)
}
```

w32chk	<i>Check for non win32</i>
--------	----------------------------

Description

If win32, returns FALSE, else TRUE

Usage

```
w32chk()
```

Value

Logical

Examples

```
w32chk()
```

Index

AnomAuth, 4

ctCheckFit, 4
ctCollapse, 5
ctDeintervalise, 5
ctDensity, 6
ctDiscretePars, 7
ctDiscretiseData, 7
ctDocs, 8
ctExample1, 9
ctExample1TIpred, 9
ctExample2, 9
ctExample2level, 10
ctExample3, 10
ctExample4, 10
ctExtract, 11
ctFit, 11
ctGenerate, 12
ctIndplot, 13
ctIntervalise, 14, 18, 21
ctKalman, 16, 60, 63
ctLongToWide, 15, 18
ctL00, 19
ctModel, 12, 20, 28, 33, 34, 47, 64
ctModelHigherOrder, 24
ctModelLatex, 25
ctPlotArray, 26, 51
ctPoly, 27, 28
ctsem, 28
ctStanContinuousPars, 29, 57
ctStanDiscretePars, 30, 32, 63
ctStanDiscreteParsPlot, 30, 31
ctStanFit, 16, 17, 20, 21, 28–30, 33, 43, 47, 49, 50, 52, 57, 63, 72
ctStanFitUpdate, 40
ctStanGenerate, 41
ctStanGenerateFromFit, 35, 42
ctStanKalman, 43
ctStanModel, 41, 44, 47
ctStanParMatrices, 45, 51
ctStanParnames, 46, 63
ctStanPlot (plot.ctStanFit), 62
ctStanPlotPost, 47, 63
ctStanPostPredict, 48
ctstantestdat, 49
ctstantestfit, 49
ctStanTIpredeffects, 50
ctStanTIpredMarginal, 51
ctStanUpdModel, 52
ctWideNames, 53
ctWideToLong, 53

datastructure, 55

extract (ctExtract), 11

inv_logit, 55
isdiag, 56

Kalman, 57

legend, 27
log1p_exp, 58
longexample, 59

mean, 29

Oscillating, 59

plot.ctKalmanDF, 17, 60
plot.ctsemFitMeasure, 4, 61
plot.ctStanFit, 62
plot.ctStanModel, 63

quantile, 29

sd, 29
sdpcor2cov, 65
stan, 35
stan_checkdivergences, 69
stan_postcalc, 70

stan_reinitsf, [70](#)
stan_unconstrainsamples, [71](#)
standatact_specificsubjects, [65](#)
stanoptimis, [34](#), [66](#)
stanWplot, [68](#)
summary.ctStanFit, [72](#)

w32chk, [73](#)