

# Package ‘gfonts’

May 9, 2020

**Title** Offline 'Google' Fonts for 'Markdown' and 'Shiny'

**Version** 0.1.1

**Description** Download 'Google' fonts and generate CSS to use in 'rmarkdown' documents and 'shiny' applications. Some popular fonts are included and ready to use.

**URL** <https://github.com/dreamRs/gfonts>

**BugReports** <https://github.com/dreamRs/gfonts/issues>

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**Depends** R (>= 2.10)

**Imports** utils, htmltools, shiny, crul, jsonlite, glue, usethis

**RoxygenNote** 7.1.0

**Suggests** knitr, rmarkdown, testthat (>= 2.1.0), vcr, covr

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Victor Perrier [aut, cre],  
Fanny Meyer [aut],  
Mario Ranftl [ctb, cph] (google-webfonts-helper)

**Maintainer** Victor Perrier <[victor.perrier@dreamrs.fr](mailto:victor.perrier@dreamrs.fr)>

**Repository** CRAN

**Date/Publication** 2020-05-09 16:30:03 UTC

## R topics documented:

download_font	2
generate_css	3
get_all_fonts	4
get_font_info	4
gfonts	5

included_fonts . . . . .	5
setup_font . . . . .	6
tag_example . . . . .	7
use_font . . . . .	8
use_pkg_gfont . . . . .	9

<b>Index</b>	<b>12</b>
--------------	-----------

---

download_font	<i>Download font files</i>
---------------	----------------------------

---

## Description

Download font files

## Usage

```
download_font(id, output_dir, variants = NULL, ...)
```

## Arguments

id	Id of the font, correspond to column id from <a href="#">get_all_fonts</a> .
output_dir	Output directory where to save font files.
variants	Variant(s) to download, default is to includes all available ones.
...	Additional parameters to API query.

## Value

a character vector of the filepaths extracted to, invisibly.

## Examples

```
if (interactive()) {

# For example, we use a temporary directory
path_to_dir <- tempfile()
dir.create(path_to_dir)

# Download Roboto font
download_font(
  id = "roboto",
  output_dir = path_to_dir
)

# Get only regular, italic and bold
download_font(
  id = "roboto",
  output_dir = path_to_dir,
  variants = c("regular", "300italic", "700")
)
```

```
)  
  
# Clean up  
unlink(path_to_dir, recursive = TRUE)  
  
}
```

---

generate\_css

*Generate CSS to import fonts*

---

## Description

Generate CSS to import fonts

## Usage

```
generate_css(  
  id,  
  variants = NULL,  
  output = NULL,  
  font_dir = "../fonts/",  
  prefer_local_source = TRUE  
)
```

## Arguments

id	Id of the font, correspond to column id from <a href="#">get_all_fonts</a> .
variants	Variant of font to use.
output	Specifies path to output file for CSS generated.
font_dir	Fonts directory relative to ouput.
prefer_local_source	Generate CSS font-face rules in which user installed fonts are preferred. Use FALSE if you want to force the use of the downloaded font.

## Value

a character string with CSS code (invisibly).

## Examples

```
if (interactive()) {  
  
  # Generate CSS code to use Roboto font  
  cat(generate_css("roboto", "regular"))  
  
}
```

---

get_all_fonts	<i>Get infos about all fonts available</i>
---------------	--

---

**Description**

Get infos about all fonts available

**Usage**

```
get_all_fonts()
```

**Value**

a `data.frame`.

**Examples**

```
if (interactive()) {  
  
  # Retrieve all fonts currently available  
  all_fonts <- get_all_fonts()  
  
}
```

---

get_font_info	<i>Get detailed information about a font</i>
---------------	--

---

**Description**

Get detailed information about a font

**Usage**

```
get_font_info(id, subsets = NULL)
```

**Arguments**

id	Id of the font, correspond to column <code>id</code> from <a href="#">get_all_fonts</a> .
subsets	Select charsets, for example "latin".

**Value**

a `data.frame`.

## Examples

```
if (interactive()) {  
  
  # Info about Roboto  
  roboto <- get_font_info("roboto")  
  
}
```

---

gfonts

*Use Google fonts offline*

---

## Description

Download Google fonts and generate CSS to use in rmarkdown documents and shiny applications. Some popular fonts are included and ready to use.

## Download a font

Use [setup\\_font](#) to get a font inside your current project, then in a {shiny} application or {rmarkdown} document, you can use [use\\_font](#) to import the font.

## Ready-to-use fonts

Some fonts are included in this package and can be used directly with [use\\_pkg\\_gfont](#).

## Author(s)

Victor Perrier (@dreamRs\_fr)

---

included\_fonts

*Detail about included fonts.*

---

## Description

Id and version of fonts included and available through [use\\_pkg\\_gfont](#).

## Usage

included\_fonts

**Format**

A data frame with 8 rows and 5 variables:

**id** Id for the font.

**family** Name of the font.

**category** Category.

**version** Version number.

**lastModified** Last modified date.

**Source**

<https://google-webfonts-helper.herokuapp.com/fonts>

---

setup\_font

*Setup a font to be used in Shiny or Markdown*

---

**Description**

This function will download the specified font into a directory of your project and generate CSS code to use it in a Shiny application or RMarkdown document.

**Usage**

```
setup_font(id, output_dir, variants = NULL, prefer_local_source = TRUE)
```

**Arguments**

**id** Id of the font, correspond to column `id` from [get\\_all\\_fonts](#).

**output\_dir** Output directory where to save font and CSS files. Must be a directory.

**variants** Variant(s) to download, default is to includes all available ones.

**prefer\_local\_source**

Generate CSS font-face rules in which user installed fonts are preferred. Use FALSE if you want to force the use of the downloaded font.

**Value**

None.

**Note**

Two directories will be created (if they do not exist) in the `output_dir` specified: **fonts/** and **css/**.

**Examples**

```
if (interactive()) {  
  
  # For example, we use a temporary directory  
  path_to_www <- tempfile()  
  dir.create(path_to_www)  
  
  # In a Shiny app, you can use the www/ directory  
  # in Markdown, use a subfolder of your Rmd directory  
  setup_font(  
    id = "open-sans-condensed",  
    output_dir = path_to_www  
  )  
  
  # Clean up  
  unlink(path_to_www, recursive = TRUE)  
  
}
```

---

tag\_example

*Generate HTML tags used in examples*

---

**Description**

Generate HTML tags used in examples

**Usage**

```
tag_example(class = NULL)
```

**Arguments**

class            Class of the main div.

**Value**

HTML tags.

**Examples**

```
tag_example()
```

---

`use_font`*Use a downloaded font in Shiny or Markdown*

---

### Description

Use a downloaded font in Shiny or Markdown

### Usage

```
use_font(id, css_path, selector = "body", css = NULL)
```

### Arguments

<code>id</code>	Id of the font downloaded.
<code>css_path</code>	Path to CSS generated by <a href="#">setup_font</a> .
<code>selector</code>	CSS selector for which to use the font, usually an HTML tag, default to "body" (all document).
<code>css</code>	CSS variables needed to use font, normally this should be automatic.

### Value

an HTML tag with an HTML dependency ([htmlDependency](#)).

### Examples

```
if (interactive()) {
  library(gfonts)

  # Here we use a temp directory
  # but in Shiny, it can be www/ folder
  directory <- tempfile()
  dir.create(directory)

  # Setup a font (only needed once)
  setup_font(
    id = "dancing-script",
    output_dir = directory
  )

  library(shiny)

  ui <- fluidPage(

    # Use font
    use_font(
      id = "dancing-script",
      css_path = file.path(directory, "css/dancing-script.css")
    )
  )
}
```



```
),
tags$p(
  paste(letters, collapse = "")
),
tags$p(
  paste(LETTERS, collapse = "")
),
tags$p(
  style = "font-weight: bold;",
  paste(letters, collapse = "")
),
tags$p(
  style = "font-weight: bold;",
  paste(LETTERS, collapse = "")
),
tags$p(
  style = "font-style: italic;",
  paste(letters, collapse = "")
),
tags$p(
  style = "font-style: italic;",
  paste(LETTERS, collapse = "")
),
tags$h1("First level title"),
tags$h2("Second level title"),
tags$h3("Third level title"),
tags$h4("Fourth level title"),
tags$h5("Fifth level title"),
tags$h6("Sixth level title")
)

server <- function(input, output, session) {
}
shinyApp(ui, server)
}
```

**Description**

For convenience, some fonts are included in the package, you can use them without having to download them, but only few variants are available.

**Usage**

```
use_pkg_gfont(
  font = c("roboto", "open-sans", "lato", "montserrat", "alegreya", "nunito-sans",
    "baloo", "happy-monkey", "henny-penny"),
  selector = "body"
)
```

**Arguments**

font	Name of the font to use, possible choices are: "roboto", "open-sans", "lato", "montserrat", "alegreya", "nunito-sans", "baloo", "happy-monkey", "henny-penny".
selector	CSS selector for which to use the font, usually an HTML tag, default to "body" (all document).

**Value**

An HTML tag with an [htmlDependency](#).

**Examples**

```
if (interactive()) {

  library(gfonts)
  library(htmltools)

  browsable(tags$div(
    use_pkg_gfont("open-sans"),
    tag_example(),
    tags$h1("First level title"),
    tags$h2("Second level title"),
    tags$h3("Third level title"),
    tags$h4("Fourth level title"),
    tags$h5("Fifth level title"),
    tags$h6("Sixth level title")
  ))

  browsable(tags$div(
    use_pkg_gfont("henny-penny"),
    tag_example(),
    tags$h1("First level title"),
    tags$h2("Second level title"),
    tags$h3("Third level title"),
    tags$h4("Fourth level title"),
    tags$h5("Fifth level title"),
    tags$h6("Sixth level title")
  ))
}
```

*use\_pkg\_gfont*

11

```
    ))  
  }
```

# Index

## \*Topic **datasets**

included\_fonts, [5](#)

download\_font, [2](#)

generate\_css, [3](#)

get\_all\_fonts, [2-4](#), [4](#), [6](#)

get\_font\_info, [4](#)

gfonts, [5](#)

htmlDependency, [8](#), [10](#)

included\_fonts, [5](#)

setup\_font, [5](#), [6](#), [8](#)

tag\_example, [7](#)

use\_font, [5](#), [8](#)

use\_pkg\_gfont, [5](#), [9](#)