

Package ‘tabr’

February 20, 2021

Version 0.4.5

Title Music Notation Syntax, Manipulation, Analysis and Transcription
in R

Description Provides a music notation syntax and a collection of music programming functions for generating, manipulating, organizing and analyzing musical information in R. The music notation framework facilitates creating and analyzing music data in notation form. Music data can be viewed, manipulated and analyzed while in different forms of representation based around different data structures: strings and data frames. Each representation offers advantages over the other for different use cases. Music syntax can be entered directly and represented in character strings to minimize the formatting overhead of data entry by using simple data structures, for example when wanting to quickly enter and transcribe short pieces of music to sheet music or tablature. The package contains functions for directly performing various mathematical, logical and organizational operations and musical transformations on special object classes that facilitate working with music data and notation. The same music data can also be organized in tidy data frames, allowing for a more familiar and powerful approach to the analysis of large amounts of structured music data. Functions are available for mapping seamlessly between these data structures and their representations of musical information. The package also provides API wrapper functions for transcribing musical representations in R into guitar tablature (“`tabs”) and basic sheet music using the ‘LilyPond’ backend (<<http://lilypond.org>>). ‘LilyPond’ is open source music engraving software for generating high quality sheet music based on markup syntax. The package generates ‘LilyPond’ files from R code and can pass them to ‘LilyPond’ to be rendered into sheet music pdf files. The package offers nominal MIDI file output support in conjunction with rendering sheet music. The package can read MIDI files and attempts to structure the MIDI data to integrate as best as possible with the data structures and functionality found throughout the package.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

ByteCompile true

URL <https://github.com/leonawicz/tabr>

BugReports <https://github.com/leonawicz/tabr/issues>

Depends R (>= 2.10)

SystemRequirements LilyPond v2.23.0+ (only needed for rendering sheet music or writing MIDI files)

Imports magrittr, tibble, dplyr, purrr, tidyr, crayon, ggplot2

Suggests testthat, knitr, rmarkdown, covr, kableExtra, gridExtra, htmltools, fansi, tuneR, png

VignetteBuilder knitr

RoxygenNote 7.1.1

NeedsCompilation no

Author Matthew Leonawicz [aut, cre] (<<https://orcid.org/0000-0001-9452-2771>>)

Maintainer Matthew Leonawicz <mflleonawicz@gmail.com>

Repository CRAN

Date/Publication 2021-02-20 22:20:06 UTC

R topics documented:

append_phrases	4
articulations	5
as_music_df	5
chord-compare	7
chord-filter	8
chord-mapping	9
chords	11
chord_arpeggiate	14
chord_break	15
chord_def	16
chord_invert	17
chord_is_major	18
chord_set	19
double-bracket	20
dyad	21
freq_ratio	22
guitarChords	23
hp	24
intervals	24
interval_semitones	26
is_diatonic	27
keys	28
lilypond	29
lilypond_root	32
lp_chord_id	33
lyrics	34
mainIntervals	35

midily	35
miditab	37
mode-helpers	38
music	40
music-helpers	42
notate	43
note-checks	44
note-coerce	45
note-equivalence	47
note-logic	49
note-metadata	50
note-summaries	53
noteinfo	54
note_ngram	55
note_slice	56
n_measures	58
phrase	59
phrase-checks	61
pitch_freq	63
pitch_seq	64
plot_fretboard	65
plot_music	68
ratio_to_cents	71
read_midi	72
render_chordchart	73
render_music	75
repeats	80
rest	81
scale-deg	82
scale-helpers	84
scale_chords	86
score	87
sf_phrase	88
simplify_phrase	91
single-bracket	92
string_unfold	93
tab	94
tabr	97
tabr-c	98
tabr-head	99
tabr-length	100
tabr-methods	101
tabr-rep	104
tabr-rev	105
tabrSyntax	106
tabr_options	106
tie	107
to_tabr	107

track	109
trackbind	111
transpose	112
tunings	113
tuplet	114
valid-noteinfo	115
valid-notes	116

Index	118
--------------	------------

append_phrases	<i>Concatenate and repeat</i>
----------------	-------------------------------

Description

Helper functions for concatenating musical phrases and other strings together as well as repetition. The functions `pc` and `pn` are based on base functions `paste` and `andrep`, respectively, but are tailored for efficiency in creating musical phrases.

Usage

`pc(...)`

`pn(x, n = 1)`

Arguments

<code>...</code>	character, phrase or non-phrase string.
<code>x</code>	character, phrase or non-phrase string.
<code>n</code>	integer, number of repetitions.

Details

These functions respect and retain the phrase class when applied to phrases. They are aggressive for phrases and secondarily for noteworthy strings. Combining a phrase with a non-phrase string will assume compatibility and result in a new phrase object. If no phrase objects are present, the presence of any noteworthy string will in turn attempt to force conversion of all strings to noteworthy strings. The aggressiveness provides convenience, but is counter to expected coercion rules. It is up to the user to ensure all inputs can be forced into the more specific child class.

This is especially useful for repeated instances. This function applies to general slur notation as well. Multiple input formats are allowed. Total number of note durations must be even because all slurs require start and stop points.

Value

phrase on non-phrase character string, noteworthy string if applicable.

Examples

```
pc(8, "16-", "8^")
pn(1, 2)
x <- phrase("c ec'g' ec'g'", "4 4 2", "5 432 432")
y <- phrase("a", 1, 5)
pc(x, y)
pc(x, pn(y, 2))
pc(x, "r1") # add a simple rest instance
class(pc(x, y))
class(pn(y, 2))
class(pc(x, "r1"))
class(pn("r1", 2))
class(pc("r1", "r4"))
```

articulations

Single note articulations and syntax

Description

A data frame containing categorized sets of articulations that can be used in phrase construction.

Usage

```
articulations
```

Format

A data frame with 3 column and 44 rows.

as_music_df

Noteworthy string to data frame

Description

Convert a noteworthy string to a tibble data frame and include additional derivative variables.

Usage

```
as_music_df(
  notes,
  info = NULL,
  key = NULL,
  scale = "diatonic",
  chords = c("root", "list", "character"),
  si_format = c("mmp_abb", "mmp", "ad_abb", "ad")
)
```

Arguments

notes	character, a noteworthy string. Alternatively, a music object or a phrase object, in which case info is ignored.
info	NULL or character, a note info string.
key	character, key signature, only required for inclusion of scale degrees.
scale	character, defaults to "diatonic". Only used in conjunction with key, this can be used to alter scale degrees. Not any arbitrary combination of valid key and valid scale is valid. See scale_degree .
chords	character, how to structure columns containing multiple values per chord/row of data frame. See details.
si_format	character, format for scale intervals. See scale_interval .

Details

If info is provided or notes is a phrase object, the resulting data frame also contains note durations and other info variables. The duration column is always included in the output even as a vector of NAs when info = NULL. This makes it more explicit that a given music data frame was generated without any time information for the timesteps. Other note info columns are not included in this case.

For some derived column variables the root note (lowest pitch) in chord is used. This is done for pitch intervals and scale intervals between adjacent timesteps. This also occurs for scale degrees.

chord = "root" additionally collapses columns like semitone, octave, and frequency to the value for the root note so that all rows contain one numeric value. chord = "list" retains full information as list columns. chord = "character" collapses into strings so that values are readily visible when printing the table, but information is not stripped and can be recovered without recomputing from the original pitches.

Value

a tibble data frame

Examples

```
x <- "a, b, c d e f g# a r ac'e' a c' e' c' r r r a"
as_music_df(x, key = "c", scale = "major")
as_music_df(x, key = "am", scale = "harmonic_minor", si_format = "ad_abb")

a <- notate("8", "Start here.")
time <- paste(a, "8^*2 16-_ 4.. 16( 16)( 2) 2 4. t8- t8 t8- 8[accent]*4 1")
d1 <- as_music_df(x, time)
d1

# Go directly from music object to data frame
m1 <- as_music(x, time)
d2 <- as_music_df(m1)
identical(d1, d2)

# Go directly from phrase object to data frame
```

```
p1 <- phrase("a b cgc'", "4++ 4[accent] 2", 5)
identical(as_music_df(as_music("a4-+;5 b[accent] cgc'2")), as_music_df(p1))
```

chord-compare *Rank, order and sort chords and notes*

Description

Rank, order and sort chords and notes by various definitions.

Usage

```
chord_rank(notes, pitch = c("min", "mean", "max"), ...)
chord_order(notes, pitch = c("min", "mean", "max"), ...)
chord_sort(notes, pitch = c("min", "mean", "max"), decreasing = FALSE, ...)
```

Arguments

notes	character, a noteworthy string.
pitch	character, how ranking of chords is determined; lowest pitch, mean pitch, or highest pitch.
...	additional arguments passed to rank or order.
decreasing	logical, sort in decreasing order.

Details

There are three options for comparing the relative pitch position of chords provided: comparison of the lowest or root note of each chord, the highest pitch note, or taking the mean of all notes in a chord.

Value

integer for rank and order, character for sort

Examples

```
x <- "a2 c a2 ceg ce_g cea"
chord_rank(x, "min")
chord_rank(x, "max")
chord_rank(x, "mean")

chord_order(x)
chord_order(x, "mean")
chord_sort(x, "mean")
```

chord-filter

Extract notes from chords

Description

Filter or slice chords to extract individual notes.

Usage

```
chord_root(notes)
```

```
chord_top(notes)
```

```
chord_slice(notes, index)
```

Arguments

notes character, a noteworthy string.

index integer, the order of a note in a chord by pitch (not scale degrees).

Details

These functions extract notes from chords such as the root note, the highest pitch, specific position among the notes by pitch, or trim chords to simplify them. They operate based only on ordered pitches.

For `chord_slice`, any entry that is empty after slicing is dropped. An error is thrown if `index` is completely out of bounds for all chords.

Value

a noteworthy string

Examples

```
x <- "a_2 c#eg# e_gc egc,cc'"
chord_root(x)
chord_top(x)
identical(chord_slice(x, 1), chord_root(x))
chord_slice(x, 2)
chord_slice(x, 4)
chord_slice(x, 3:5)
```

chord-mapping	<i>Chord mapping</i>
---------------	----------------------

Description

Helper functions for chord mapping.

Usage

```
gc_info(  
    name,  
    root_octave = NULL,  
    root_fret = NULL,  
    min_fret = NULL,  
    bass_string = NULL,  
    open = NULL,  
    key = "c",  
    ignore_octave = TRUE  
)
```

```
gc_fretboard(  
    name,  
    root_octave = NULL,  
    root_fret = NULL,  
    min_fret = NULL,  
    bass_string = NULL,  
    open = NULL,  
    key = "c",  
    ignore_octave = TRUE  
)
```

```
gc_notes_to_fb(  
    notes,  
    root_octave = NULL,  
    root_fret = NULL,  
    min_fret = NULL,  
    bass_string = NULL,  
    open = NULL  
)
```

```
gc_notes(  
    name,  
    root_octave = NULL,  
    root_fret = NULL,  
    min_fret = NULL,  
    bass_string = NULL,  
    open = NULL,
```

```

  key = "c",
  ignore_octave = TRUE
)

```

```
gc_is_known(notes)
```

```
gc_name_split(name)
```

```
gc_name_root(name)
```

```
gc_name_mod(name)
```

Arguments

name	character, chord name in tabr format, e.g., "bM b_m b_m7#5", etc.
root_octave	integer, optional filter for chords whose root note is in a set of octave numbers. May be a vector.
root_fret	integer, optional filter for chords whose root note matches a specific fret. May be a vector.
min_fret	integer, optional filter for chords whose notes are all at or above a specific fret. May be a vector.
bass_string	integer, optional filter for chords whose lowest pitch string matches a specific string, 6, 5, or 4. May be a vector.
open	logical, optional filter for open and movable chords. NULL retains both types.
key	character, key signature, used to enforce type of accidentals.
ignore_octave	logical, if TRUE, functions like <code>gc_info</code> and <code>gc_fretboard</code> return more results.
notes	character, a noteworthy string.

Details

These functions assist with mapping between different information that define chords.

For `gc_is_known`, a check is done against chords in the `guitarChords` dataset. A simple noteworthy string is permitted, but any single-note entry will automatically yield a FALSE result.

`gc_info` returns a tibble data frame containing complete information for the subset of predefined guitar chords specified by name and key. Any accidentals present in the chord root of name (but not in the chord modifier, e.g., `m7_5` or `m7#5`) are converted according to key if necessary. `gc_notes` and `gc_fretboard` are wrappers around `gc_info`, which return noteworthy strings of chord notes and a named vector of LilyPond fretboard diagram data, respectively. Note that although the input to these functions can contain multiple chord names, whether as a vector or as a single space-delimited string, the result is not intended to be of equal length. These functions filter `guitarChords`. The result is the set of all chords matched by the supplied input filters.

`gc_name_split` splits a vector or space-delimited set of chord names into a tibble data frame containing separate chord root and chord modifier columns. `gc_name_root` and `gc_name_mod` are wrappers around this.

Value

various, see details regarding each function.

Examples

```
gc_is_known("a b_,fb_d'f'")

gc_name_root("a aM b_,m7#5")
gc_name_mod("a aM b_,m7#5")

gc_info("a") # a major chord, not a single note
gc_info("ceg a#m7_5") # only second entry is a guitar chord
gc_info("ceg a#m7_5", key = "f")

gc_info("a,m c d f,")
gc_fretboard("a,m c d f,", root_fret = 0:3)
gc_notes_to_fb("a,eac'e' cgc'e'g'")

x <- gc_notes("a, b,", root_fret = 0:2)
summary(x)
```

chords

Chord constructors

Description

These functions construct basic chord string notation from root notes.

Usage

```
chord_min(notes, key = "c", octaves = "tick")
chord_maj(notes, key = "c", octaves = "tick")
chord_min7(notes, key = "c", octaves = "tick")
chord_dom7(notes, key = "c", octaves = "tick")
chord_7s5(notes, key = "c", octaves = "tick")
chord_maj7(notes, key = "c", octaves = "tick")
chord_min6(notes, key = "c", octaves = "tick")
chord_maj6(notes, key = "c", octaves = "tick")
chord_dim(notes, key = "c", octaves = "tick")
```

```
chord_dim7(notes, key = "c", octaves = "tick")
chord_m7b5(notes, key = "c", octaves = "tick")
chord_aug(notes, key = "c", octaves = "tick")
chord_5(notes, key = "c", octaves = "tick")
chord_sus2(notes, key = "c", octaves = "tick")
chord_sus4(notes, key = "c", octaves = "tick")
chord_dom9(notes, key = "c", octaves = "tick")
chord_7s9(notes, key = "c", octaves = "tick")
chord_maj9(notes, key = "c", octaves = "tick")
chord_add9(notes, key = "c", octaves = "tick")
chord_min9(notes, key = "c", octaves = "tick")
chord_madd9(notes, key = "c", octaves = "tick")
chord_min11(notes, key = "c", octaves = "tick")
chord_7s11(notes, key = "c", octaves = "tick")
chord_maj7s11(notes, key = "c", octaves = "tick")
chord_11(notes, key = "c", octaves = "tick")
chord_maj11(notes, key = "c", octaves = "tick")
chord_13(notes, key = "c", octaves = "tick")
chord_min13(notes, key = "c", octaves = "tick")
chord_maj13(notes, key = "c", octaves = "tick")
xm(notes, key = "c", octaves = "tick")
xM(notes, key = "c", octaves = "tick")
xm7(notes, key = "c", octaves = "tick")
x7(notes, key = "c", octaves = "tick")
```

```
x7s5(notes, key = "c", octaves = "tick")
xM7(notes, key = "c", octaves = "tick")
xm6(notes, key = "c", octaves = "tick")
xM6(notes, key = "c", octaves = "tick")
xdim(notes, key = "c", octaves = "tick")
xdim7(notes, key = "c", octaves = "tick")
xm7b5(notes, key = "c", octaves = "tick")
xaug(notes, key = "c", octaves = "tick")
x5(notes, key = "c", octaves = "tick")
xs2(notes, key = "c", octaves = "tick")
xs4(notes, key = "c", octaves = "tick")
x9(notes, key = "c", octaves = "tick")
x7s9(notes, key = "c", octaves = "tick")
xM9(notes, key = "c", octaves = "tick")
xadd9(notes, key = "c", octaves = "tick")
xm9(notes, key = "c", octaves = "tick")
xma9(notes, key = "c", octaves = "tick")
xm11(notes, key = "c", octaves = "tick")
x7s11(notes, key = "c", octaves = "tick")
xM7s11(notes, key = "c", octaves = "tick")
x_11(notes, key = "c", octaves = "tick")
xM11(notes, key = "c", octaves = "tick")
x_13(notes, key = "c", octaves = "tick")
xm13(notes, key = "c", octaves = "tick")
```

```
xM13(notes, key = "c", octaves = "tick")
```

Arguments

notes	character, a noteworthy string of chord root notes.
key	key signature. See details.
octaves	character, passed to transpose.

Details

Providing a key signature is used only to ensure flats or sharps for accidentals. An additional set of aliases with efficient names, of the form `x*` where `*` is a chord modifier abbreviation, is provided to complement the set of `chord_*` functions.

These functions create standard chords, not the multi-octave spanning types of chords commonly played on guitar.

Value

character

See Also

[transpose](#)

Examples

```
chord_min("d")
chord_maj("d")
xM("d")
xm("c f g")
xm("c, f, g,", key = "e_")
```

chord_arpeggiate	<i>Arpeggiate a chord</i>
------------------	---------------------------

Description

Create an arpeggio from a chord.

Usage

```
chord_arpeggiate(
  chord,
  n = 0,
  by = c("note", "chord"),
  broken = FALSE,
  collapse = FALSE
)
```

Arguments

chord	character, a single chord.
n	integer, number of steps, negative indicates reverse direction (decreasing pitch).
by	whether each of the n steps refers to individual notes in the chord (an inversion) or raising the entire chord in its given position by one octave.
broken	logical, return result as an arpeggio of broken chords.
collapse	logical, collapse result into a single string ready for phrase construction.

Details

This function is based on `chord_invert`. If `n = 0` then `chord` is returned immediately; other arguments are ignored.

Value

character

Examples

```
chord_arpeggiate("ce_gb_", 2)
chord_arpeggiate("ce_gb_", -2)
chord_arpeggiate("ce_gb_", 2, by = "chord")
chord_arpeggiate("ce_gb_", 1, broken = TRUE, collapse = TRUE)
```

chord_break	<i>Broken chords</i>
-------------	----------------------

Description

Convert chords in a noteworthy string or vector to broken chords.

Usage

```
chord_break(notes)
```

Arguments

notes	character, noteworthy string that may contain chords.
-------	---

Value

character

Examples

```
chord_break("c e g ceg ceg")
```

chord_def	<i>Define chords</i>
-----------	----------------------

Description

Function for creating new chord definition tables.

Usage

```
chord_def(fret, id, optional = NA, tuning = "standard", ...)
```

Arguments

fret	integer vector defining fretted chord. See details.
id	character, the chord type. See details.
optional	NA when all notes required. Otherwise an integer vector giving the indices offret that are considered optional notes for the chord.
tuning	character, string tuning. See tunings for predefined tunings. Custom tunings are specified with a similar value string.
...	additional arguments passed to transpose.

Details

This function creates a tibble data frame containing information defining various attributes of chords. It is used to create the `guitarChords` dataset, but can be used to create other pre-defined chord collections. The tibble has only one row, providing all information for the defined chord. The user can decide which arguments to vectorize over when creating a chord collection. See examples.

This function uses a vector of fret integers (NA for muted string) to define a chord, in conjunction with a string tuning (defaults to standard tuning, six-string guitar). fret is from lowest to highest pitch strings, e.g., strings six through one.

The `id` is passed directly to the output. It represents the type of chord and should conform to accepted `tabr` notation. See `id` column in `guitar Chords` for examples.

Note that the `semitones` column gives semitone intervals between chord notes. These count from zero as the lowest pitch based on the tuning of the instrument, e.g., zero is E2 with standard guitar tuning. To convert these semitone intervals to standard semitone values assigned to pitches, use e.g., `pitch_semitones("e2")` (40) if that is the lowest pitch and add that value to the instrument semitone interval values. This is the explanation, but doing this is not necessary. You can use [chord_semitones](#) to compute semitones directly on pitches in a chord.

Value

a data frame

Examples

```
frets <- c(NA, 0, 2, 2, 1, 0)
chord_def(frets, "m")
chord_def(frets, "m", 6)

purrr::map_dfr(c(0, 2, 3), ~chord_def(frets + .x, "m"))
```

chord_invert	<i>Chord inversion</i>
--------------	------------------------

Description

This function inverts a single chord given as a character string. If $n = 0$, chord is returned immediately. Otherwise, the notes of the chord are inverted. If $\text{abs}(n)$ is greater than the number of inversions (excluding root position), an error is thrown.

Usage

```
chord_invert(chord, n = 0, limit = FALSE)
```

Arguments

chord	character, a single chord.
n	inversion.
limit	logical, limit inversions in either direction to one less than the number of notes in the chord.

Details

Note that `chord_invert` has no knowledge of whether a chord might be considered as in root position or some inversion already, as informed by a key signature, chord name or user's intent. This function simply inverts what it receives, treating any defined chord string as in root position.

Octave number applies to this function. Chords should always be defined by notes of increasing pitch. Remember that an unspecified octave number on a note is octave 3. When the chord is inverted, it moves up the scale. The lowest note is moved to the top of the chord, increasing its octave if necessary, to ensure that the note takes the lowest octave number while having the highest pitch. The second lowest note becomes the lowest. It's octave does not change. This pattern is repeated for higher order inversions. The opposite happens if n is negative.

The procedure ensures that the resulting inverted chord is still defined by notes of increasing pitch. However, if you construct an unusual chord that spans multiple octaves, the extra space will be condensed by inversion.

Value

character

Examples

```
chord_invert("ce_gb_", 3)
```

chord_is_major	<i>Check if chords are major or minor</i>
----------------	---

Description

Check if chords are major or minor where possible.

Usage

```
chord_is_major(notes)
```

```
chord_is_minor(notes)
```

Arguments

notes character, a noteworthy string.

Details

These functions operate based only on ordered pitches. They do not recognize what a human might interpret and name an inverted chord with a root other than the lowest pitch. This imposes limitations on the utility of these functions, which scan the intervals for a minor or major third in a chord whose notes are sorted by pitch.

In several cases including single notes or no major or minor third interval present, NA is returned. TRUE or FALSE is only returned if such an interval is present. If more than one is present, it is based on the lowest in pitch. It prioritizes major/minor and minor/major adjacent intervals (recognizing a common triad). If these do not occur adjacent, the lowest third is selected. This is still imperfect, but a useful method. Second and higher unknown chord inversions are problematic.

Value

logical vector

Examples

```
x <- "c cg, ce ce_ ceg ce_gb g,ce g,ce_ e_,g,c e_,g,ce_ e_,g,c"
chord_is_major(x)
identical(chord_is_major(x), !chord_is_minor(x))
```

chord_set	<i>Generate a chord set</i>
-----------	-----------------------------

Description

Generate a chord set for a music score.

Usage

```
chord_set(x, id = NULL, n = 6)
```

Arguments

x	character, n-string chord description from lowest to highest pitch, strings n through 1. E.g., "xo221o". You can use spaces or semicolons when 2-digit fret numbers are present, e.g., "8 10 10 9 o". Do not mix formats. Leading x are inferred if the number of entries is less than n.
id	character, the name of the chord in LilyPond readable format, e.g., "a:m". Ignored if x is already a named vector.
n	number of instrument strings.

Details

The chord set list returned by chord_set is only used for top center placement of a full set of chord fretboard diagrams for a music score. chord_set returns a named list. The names are the chords and the list elements are strings defining string and fret fingering readable by LilyPond. Multiple chord positions can be defined for the same chord name. Instruments with a number of strings other than six are not currently supported.

When defining chords, you may also wish to define rests or silent rests for chords that are to be added to a score for placement above the staff in time, where no chord is to be played or explicitly written. Therefore, there are occasions where you may pass chord names and positions that happen to include entries r and/or s as NA as shown in the example. These two special cases are passed through by chord_set but are ignored when the chord chart is generated.

Value

a named list.

Examples

```
chord_names <- c("e:m", "c", "d", "e:m", "d", "r", "s")
chord_position <- c("997x", "5553x", "7775x", "ooo22o", "232oxx", NA, NA)
chord_set(chord_position, chord_names)
```

double-bracket

Double bracket methods for tabr classes

Description

Double bracket indexing and assignment. See [tabr-methods](#) for more details on methods for tabr classes.

Usage

```
## S3 method for class 'noteworthy'
x[[i]]

## S3 method for class 'noteinfo'
x[[i]]

## S3 method for class 'music'
x[[i]]

## S3 method for class 'lyrics'
x[[i]]

## S3 replacement method for class 'noteworthy'
x[[i]] <- value

## S3 replacement method for class 'noteinfo'
x[[i]] <- value

## S3 replacement method for class 'music'
x[[i]] <- value

## S3 replacement method for class 'lyrics'
x[[i]] <- value
```

Arguments

x	object.
i	index.
value	values to assign at index.

See Also

[tabr-methods](#), [note-metadata](#)

Examples

```

# noteworthy class examples
x <- as_noteworthy("a, b, c ce_g")
x[[3]]
x[[2]] <- paste0(transpose(x[2], 1), "~")
x

# noteinfo class examples
x <- as_noteinfo(c("4-", "t8(", "t8)", "t8x"))
x[[3]]
x[[3]] <- c("t8)")
x

# music class examples
x <- as_music("c,~4 c,1 c'e_'g'4-.*2")
x[[3]]
x[[3]] <- "c'e_'g'8"
x

```

dyad

Construct a dyad

Description

Construct a dyad given one note, an interval, and a direction.

Usage

```

dyad(
  notes,
  interval,
  reverse = FALSE,
  octaves = c("tick", "integer"),
  accidentals = c("flat", "sharp"),
  key = NULL
)

```

Arguments

notes	character, a noteworthy string, single notes only, no chords. Number of timesteps must equal the length of interval.
interval	integer or character vector; semitones or interval ID, respectively. See details.
reverse	logical, reverse the transposition direction. Useful when interval is character.
octaves, accidentals, key	See transpose .

Details

The interval may be specified by semitones or by common interval name or abbreviation. See examples. For a complete list of valid interval names and abbreviations see [mainIntervals](#). `key` enforces the use of sharps or flats. This function is based on `transpose.notes` and `interval` may be vectors, but must be equal length. Recycling occurs only if one argument is scalar.

Value

character

See Also

[mainIntervals](#)

Examples

```
dyad("a", 4)
x <- c("minor third", "m3", "augmented second", "A2")
dyad("a", x)
dyad("c'", x, reverse = TRUE)

x <- c("M3", "m3", "m3", "M3", "M3", "m3", "m3")
dyad(letters[c(3:7, 1, 2)], x)

x <- c("P1", "m3", "M3", "P4", "P5", "P8", "M9")
dyad("c", x)
dyad("c", x, reverse = TRUE)
dyad("d e", "m3")
```

freq_ratio

Frequency ratios

Description

Obtain frequency ratios data frame.

Usage

```
freq_ratio(x, ...)
```

Arguments

`x` noteworthy or music object, or a numeric vector or list of numeric vectors for frequencies.

`...` additional arguments: `ratios`, which is one of "all" (default), "root", or "range" for filtering results. For frequency input, you may also specify octaves and accidentals. See details and examples.

Details

This generic function returns a data frame of frequency ratios from a vector or list of frequencies, a noteworthy object, or a music object. For frequency inputs, a list can be used to represent multiple timesteps. Octave numbering and accidentals are inferred from noteworthy and music objects, but can be specified for frequency. See examples.

By default ratios are returned for all combinations of intervals in each chord (`ratios = "all"`). `ratios = "root"` filters the result to only include chord ratios with respect to the root note of each chord. `ratios = "range"` filters to only the chord ratio between the root and highest note.

Value

a tibble data frame

Examples

```
x <- as_music("c4 e_ g ce_g")
(fr <- freq_ratio(x))

x <- music_notes(x)
identical(fr, freq_ratio(x))

x <- chord_freq(x)
identical(fr, freq_ratio(x))

freq_ratio(x, accidentals = "sharp")

freq_ratio(x, ratios = "root")

freq_ratio(x, ratios = "range")
```

guitarChords

Predefined guitar chords

Description

A data frame containing information for many predefined guitar chords.

Usage

```
guitarChords
```

Format

A data frame with 12 columns and 3,967 rows

hp	<i>Hammer ons and pull offs</i>
----	---------------------------------

Description

Helper function for generating hammer on and pull off syntax.

Usage

```
hp(...)
```

Arguments

... character, note durations. Numeric is allowed for lists of single inputs. See examples.

Details

This is especially useful for repeated instances. This function applies to general slur notation as well. Multiple input formats are allowed. Total number of note durations must be even because all slurs require start and stop points.

Value

character.

Examples

```
hp(16, 16)  
hp("16 16")  
hp("16 8 16", "8 16 8")
```

intervals	<i>Interval helpers</i>
-----------	-------------------------

Description

Helper functions for musical intervals defined by two notes.

Usage

```
pitch_interval(notes1, notes2, use_root = TRUE)

pitch_diff(notes, use_root = TRUE, n = 1, trim = FALSE)

scale_interval(
  notes1,
  notes2,
  use_root = TRUE,
  format = c("mmp_abb", "mmp", "ad_abb", "ad")
)

scale_diff(
  notes,
  use_root = TRUE,
  n = 1,
  trim = FALSE,
  format = c("mmp_abb", "mmp", "ad_abb", "ad")
)

tuning_intervals(tuning = "standard")
```

Arguments

<code>use_root</code>	logical, use lowest pitch in chord for pitch intervals or scale intervals between adjacent timesteps. Otherwise intervals involving chords are NA.
<code>notes, notes1, notes2</code>	character, a noteworthy string. <code>notes1</code> and <code>notes2</code> must have equal number of timesteps.
<code>n</code>	integer, size of lag.
<code>trim</code>	logical, trim the <code>n</code> leading NA values from lagged intervals.
<code>format</code>	character, format of the scale notation: major/minor/perfect, augmented/diminished, and respective abbreviations. See argument options in defaults.
<code>tuning</code>	character, string tuning.

Details

Numeric intervals are directional. `pitch_interval` returns the signed number of semitones defining the distance between two notes. Named scale intervals are names only. Use `pitch` for direction.

`scale_interval` returns a character string that provides the named main interval, simple or compound, defined by the two notes. This function will return NA for any uncommon out of range large interval not listed as a named interval in [mainIntervals](#).

`pitch_interval` and `scale_interval` compute intervals element-wise between two noteworthy strings. `pitch_diff` and `scale_diff` work similarly but compute lagged intervals on the elements in notes.

Value

a musical interval, integer or character depending on the function.

See Also

[mainIntervals](#)

Examples

```
pitch_interval("b", "c4")
pitch_interval("c, e_, g_, a,", "e_, g_, a, c")
pitch_interval("c r", "dfa d")
pitch_interval("c r", "dfa d", use_root = FALSE)
scale_interval("c", "e_")
scale_interval("ceg", "egd'")

x <- "a, b, c d e f g# ac'e' a c' e'"
pitch_diff(x)
pitch_diff(x, use_root = FALSE)
scale_diff(x)
scale_diff(x, n = 2, trim = TRUE, use_root = FALSE)

# Lagged intervals respect rest timesteps.
# All timestep position including rests are retained.
# But the lag-n difference skips rest entries.
x <- "a, c r r r r g"
pitch_diff(x)
scale_diff(x)
pitch_diff(x, n = 2)
scale_diff(x, n = 2)
pitch_diff(x, n = 2, trim = TRUE)
scale_diff(x, n = 2, trim = TRUE)
```

interval_semitones *Interval semitones*

Description

Convert named intervals to numbers of semitones. For a complete list of valid interval names and abbreviations see [mainIntervals](#). interval may be a vector.

Usage

```
interval_semitones(interval)
```

Arguments

interval character, interval ID. See details.

Value

integer

See Also[mainIntervals](#)**Examples**

```
x <- c("minor third", "m3", "augmented second", "A2")
y <- c("P1", "m2", "M2", "m3", "M3", "P4", "TT", "P5")
interval_semitones(x)
interval_semitones(y)
```

`is_diatonic`*Check if notes and chords are diatonic*

Description

Check if notes and chords are diatonic in a given key.

Usage

```
is_diatonic(notes, key = "c")
```

Arguments

`notes` character, a noteworthy string.
`key` character, key signature.

Details

This function is a wrapper around [is_in_scale](#). To check if individual notes are in a scale, see [note_in_scale](#).

Value

logical

See Also[is_in_scale](#)**Examples**

```
is_diatonic("ceg ace ce_g", "c")
is_diatonic(c("r", "d", "dfa", "df#a"), "d")
```

keys

Key signatures

Description

Helper functions for key signature information.

Usage

```
keys(type = c("all", "sharp", "flat"))  
  
key_is_natural(key)  
  
key_is_sharp(key)  
  
key_is_flat(key)  
  
key_n_sharps(key)  
  
key_n_flats(key)  
  
key_is_major(key)  
  
key_is_minor(key)
```

Arguments

type	character, defaults to "all".
key	character, key signature.

Details

The `keys` function returns a vector of valid key signature IDs. These IDs are how key signatures are specified throughout `tabr`, including in the other helper functions here via `key`. Like the other functions here, `key_is_sharp` and `key_is_flat` are for *key signatures*, not single pitches whose sharp or flat status is always self-evident from their notation. Major and minor keys are also self-evident from their notation, but `key_is_major` and `key_is_minor` can still be useful when programming.

Value

character vector.

Examples

```
keys()  
key_is_natural(c("c", "am", "c#"))  
x <- c("a", "e_")  
key_is_sharp(x)
```

```
key_is_flat(x)
key_n_sharps(x)
key_n_flats(x)
```

lilypond

Save score to LilyPond file

Description

Write a score to a LilyPond format (.ly) text file for later use by LilyPond or subsequent editing outside of R.

Usage

```
lilypond(
  score,
  file,
  key = "c",
  time = "4/4",
  tempo = "2 = 60",
  header = NULL,
  paper = NULL,
  string_names = NULL,
  endbar = "|.",
  midi = TRUE,
  colors = NULL,
  crop_png = TRUE,
  simplify = TRUE
)
```

Arguments

score	a score object.
file	character, LilyPond output file ending in .ly. May include an absolute or relative path.
key	character, key signature, e.g., c, b_, f#m, etc.
time	character, defaults to "4/4".
tempo	character, defaults to "2 = 60".
header	a named list of arguments passed to the header of the LilyPond file. See details.
paper	a named list of arguments for the LilyPond file page layout. See details.
string_names	label strings at beginning of tab staff. NULL (default) for non-standard tunings only, TRUE or FALSE for force on or off completely.
endbar	character, the global end bar.
midi	logical, add midi inclusion specification to LilyPond file.

colors	a named list of LilyPond element color overrides. See details.
crop_png	logical, alter template for cropped height. See details.
simplify	logical, uses <code>simplify_phrase</code> to convert to simpler, more efficient LilyPond syntax.

Details

This function only writes a LilyPond file to disk. It does not require a LilyPond installation. It checks for the version number of an installation, but LilyPond is not required to be found.

This function can be used directly but is commonly used by `render_*` functions, which call this function internally to create the LilyPond file and then call LilyPond to render that file to sheet music.

Value

nothing returned; a file is written.

Header options

All header list elements are character strings. The options for header include:

- title
- subtitle
- composer
- album
- arranger
- instrument
- meter
- opus
- piece
- poet
- copyright
- tagline

Paper options

All paper list elements are numeric except `page_numbers` and `print_first_page_number`, which are logical. `page_numbers = FALSE` suppresses all page numbering. When `page_numbers = TRUE`, you can set `print_first_page_number = FALSE` to suppress printing of only the first page number. `first_page_number` is the number of the first page, defaulting to 1, and determines all subsequent page numbers. These arguments correspond to LilyPond paper block variables.

The options for paper include the following and have the following default values if not provided:

- `textheight = 220`
- `linewidth = 150`

- indent = 0
- fontsize = 10
- page_numbers = TRUE
- print_first_page_number = TRUE
- first_page_number = 1

PNG-related options

By default `crop_png = TRUE`. This alters the template so that when the LilyPond output file is created, it contains specifications for cropping the image to the content when that file is rendered by LilyPond to png. The image will have its width and height automatically cropped rather than retain the standard page dimensions. This only applies to png outputs made from the LilyPond file, not pdf. The argument is also ignored if explicitly providing `textheight` to `paper`. You may still provide `linewidth` to `paper` if you find you need to increase it beyond the default 150mm, generally as a result of using a large fontsize. Various `render_*` functions that wrap `lilypond` make use of this argument as well.

Color options

You can provide a named list of global color overrides for various sheet music elements with the `colors` argument of `lilypond` or one of the associated rendering functions.

By default, everything is black. Overrides are only inserted into the generated LilyPond file if given. Values are character; either the hex color or a named R color. The named list options include:

- color
- background
- staff
- time
- clef
- bar
- beam
- head
- stem
- accidental
- slur
- tabhead
- lyrics

`color` is a global font color for the entire score. It affects staff elements and header elements. It does not affect everything, e.g., page numbers. `background` controls the background color of the entire page. Do not use this if making a transparent background png with the `transparent` argument available in the various `render_*` functions. The other options are also global but override color. You can change the color of elements broadly with `color` and then change the color of specific elements using the other options.

There are currently some limitations. Specifically, if you provide any background color override, most header elements will not display.

See Also

[tab](#), [render_chordchart](#), [midily](#)

Examples

```
x <- phrase("c ec'g' ec'g'", "4 4 2", "5 432 432")
x <- track(x)
x <- score(x)
outfile <- file.path(tempdir(), "out.ly")
lilypond(x, outfile)
```

lilypond_root

LilyPond installation information

Description

Details about local LilyPond installation and package API.

Usage

```
lilypond_root()
lilypond_version()
tabr_lilypond_api()
```

Details

Version information and installation directory are returned if the installation can be found. The LilyPond API references the currently loaded version of tabr.

Value

a message or system standard output.

Examples

```
lilypond_root()
lilypond_version()
tabr_lilypond_api()
```

lp_chord_id	<i>LilyPond chord notation</i>
-------------	--------------------------------

Description

Obtain LilyPond quasi-chord notation.

Usage

```
lp_chord_id(root, chord, exact = FALSE, ...)
```

```
lp_chord_mod(root, chord, exact = FALSE, ...)
```

Arguments

root	character, root note.
chord	character, tabl format chord name.
exact	logical, return a more exact LilyPond chord representation.
...	additional arguments passed to transpose.

Details

These functions take a tabl syntax representation of a chord name and convert it to quasi-LilyPond syntax; "quasi" because the result still uses _ for flats and # for sharps, whereas LilyPond itself uses es and is (mostly). This is the format used by tabl functions involved in communicating with LilyPond for music transcription, and they make these final conversions on the fly. This can be overridden with exact = TRUE.

Value

character

Examples

```
lp_chord_id("a a a", "m M m7_5")
lp_chord_mod("a a a", "m M m7_5")
lp_chord_id("a a a", "m M m7_5", exact = TRUE)
lp_chord_mod("a a a", "m M m7_5", exact = TRUE)
```

 lyrics

Create lyrics and check lyrics string validity

Description

Functions for creating and checking lyrics objects.

Usage

```

lyrical(x)

as_lyrics(x, format = NULL)

is_lyrics(x)

lyrics_template(x, format = NULL)

```

Arguments

x	character or lyrics object. For <code>lyrics_template</code> , an integer or one of the classes <code>noteworthy</code> , <code>noteinfo</code> or <code>music</code> to derive the number of timesteps from.
format	NULL or character, the timestep delimiter format, "space" or "vector".

Details

The lyrics class is a simple class for arranging lyrics text by timestep. Its structure and behavior aligns with that of the classes `noteworthy`, `noteinfo` and `music`.

`lyrical` is a trivial function that returns a scalar logical result essentially for any object that inherits from `character`, though this check may become more specific in the future.

`as_lyrics` can be used to coerce to the lyrics class. Coercion will fail if the string is not lyrical. The lyrics class has its own `print` and `summary` methods.

When `format = NULL`, the timestep delimiter format is inferred from the lyrical string input.

Value

depends on the function

Examples

```

# space-delimited lyrics; use periods for timesteps with no lyric
x <- "These are the ly- rics . . . to this song"
is_lyrics(x)
lyrical(x)
as_lyrics(x)

# character vector; empty, period or NA for no lyric
x <- c("These", "are", "the", "ly-", "rics",

```

```

      "", ".", NA, "to", "this", "song") #
as_lyrics(x)

# generate empty lyrics object from noteworthy, noteinfo or music object
notes <- as_noteworthy("c d e d c r*3 e g c'")
x <- lyrics_template(notes)
x

x[1:5] <- strsplit("These are the lyrics", " ")[[1]]
x[9:11] <- c("to", "this", "song")
x

summary(x)

attributes(x)

```

mainIntervals	<i>Main musical intervals</i>
---------------	-------------------------------

Description

A data frame containing descriptions of the main intervals, simple and compound.

Usage

```
mainIntervals
```

Format

A data frame with 5 columns and 26 rows

midily	<i>Convert MIDI to LilyPond file</i>
--------	--------------------------------------

Description

Convert a MIDI file (.mid) to a LilyPond format (.ly) text file.

Usage

```

midily(
  midi_file,
  file,
  key = "c",
  absolute = FALSE,
  quantize = NULL,
  explicit = FALSE,

```

```

    start_quant = NULL,
    allow_tuplet = c("4*2/3", "8*2/3", "16*2/3"),
    lyric = FALSE
  )

```

Arguments

<code>midi_file</code>	character, MIDI file (.mid). May include an absolute or relative path.
<code>file</code>	LilyPond output file ending in .ly.
<code>key</code>	key signature, defaults to "c".
<code>absolute</code>	logical, print absolute pitches.
<code>quantize</code>	integer, duration, quantize notes on duration.
<code>explicit</code>	logical, print explicit durations.
<code>start_quant</code>	integer, duration, quantize note starts on the duration.
<code>allow_tuplet</code>	character vector, allow tuplet durations. See details.
<code>lyric</code>	logical, treat all text as lyrics.

Details

Under development/testing. See warning and details below.

This function is a wrapper around the `midily` command line utility provided by LilyPond. It inherits all the limitations thereof. LilyPond is not intended to be used to produce meaningful sheet music from arbitrary MIDI files. While `lilypond` converts R code score objects to LilyPond markup directly, MIDI conversion to LilyPond markup by `midily` requires LilyPond.

WARNING: Even though the purpose of the command line utility is to convert an existing MIDI file to a LilyPond file, it nevertheless generates a LilyPond file that *specifies inclusion of MIDI output*. This means when you subsequently process the LilyPond file with LilyPond or if you use `miditab` to go straight from your MIDI file to pdf output, the command line tool will also produce a MIDI file output. It will overwrite your original MIDI file if it has the same file name and location! The next version of this function will add a default argument `midi_out = FALSE` to remove this from the generated LilyPond file. If `TRUE` and the basename of `midi_file` matches the basename of `file`, then `file` will be renamed, the basename appended with a `-1`.

`allow_tuplets = NULL` to disallow all triplets. Fourth, eighth and sixteenth note triplets are allowed. The format is a character vector where each element is `duration*numerator/denominator`, no spaces. See default argument.

On Windows systems, it may be necessary to specify a path in `tabr_options` to both `midily` and `python` if they are not already successfully set as follows. On package load, `tabr` will attempt to check for `midily.exe` at `C:/Program Files (x86)/LilyPond/usr/bin/midily.py` and similarly for the `python.exe` that ships with LilyPond at `C:/Program Files (x86)/LilyPond/usr/bin/python.exe`. If this is not where LilyPond is installed, then LilyPond and Python need to be provided to `tabr_options` or added to the system `PATH` variable.

Value

nothing returned; a file is written.

See Also

[miditab](#), [tab](#), [lilypond](#)

Examples

```
## Not run:
if(tabr_options()$midi2ly != ""){
  midi <- system.file("example.mid", package = "tabr")
  outfile <- file.path(tempdir(), "out.ly")
  midily(midi, outfile) # requires LilyPond installation
}

## End(Not run)
```

miditab

Convert MIDI to tablature

Description

Convert a MIDI file to sheet music/guitar tablature.

Usage

```
miditab(midi_file, file, keep_ly = FALSE, details = FALSE, ...)
```

Arguments

mid_i_file	character, MIDI file (.mid). May include an absolute or relative path.
file	character, output file ending in .pdf or .png.
keep_ly	logical, keep LilyPond file.
details	logical, set to TRUE to print LilyPond log output to console. Windows only.
...	additional arguments passed to midily .

Details

Under development/testing. See warning and details below.

Convert a MIDI file to a pdf or png music score using the LilyPond music engraving program. Output format is inferred from file extension. This function is a wrapper around [midily](#), the function that converts the MIDI file to a LilyPond (.ly) file using a LilyPond command line utility.

WARNING: Even though the purpose of the command line utility is to convert an existing MIDI file to a LilyPond file, it nevertheless generates a LilyPond file that *specifies inclusion of MIDI output*. This means when you subsequently process the LilyPond file with LilyPond or if you use `miditab` to go straight from your MIDI file to pdf output, the command line tool will also produce a MIDI file output. It will overwrite your original MIDI file if it has the same file name and location! The next version of this function will add a default argument `mid_i_out = FALSE` to remove this from

the generated LilyPond file. If TRUE and the basename of `midi_file` matches the basename of `file`, then `file` will be renamed, the basename appended with a `-1`.

On Windows systems, it may be necessary to specify a path in `tabr_options` to both `midi2ly` and `python` if they are not already successfully set as follows. On package load, `tabr` will attempt to check for `midi2ly.exe` at `C:/Program Files (x86)/LilyPond/usr/bin/midi2ly.py` and similarly for the `python.exe` that ships with LilyPond at `C:/Program Files (x86)/LilyPond/usr/bin/python.exe`. If this is not where LilyPond is installed, then LilyPond and Python need to be provided to `tabr_options` or added to the system PATH variable.

Value

nothing returned; a file is written.

See Also

[midily](#), [tab](#), [lilypond](#)

Examples

```
## Not run:
if(tabr_options()$midi2ly != ""){
  midi <- system.file("example.mid", package = "tabr")
  outfile <- file.path(tempdir(), "out.pdf")
  miditab(midi, outfile, details = FALSE) # requires LilyPond installation
}

## End(Not run)
```

mode-helpers

Mode helpers

Description

Helper functions for working with musical modes.

Usage

```
modes(mode = c("all", "major", "minor"))

is_mode(notes, ignore_octave = FALSE)

mode_rotate(notes, n = 0, ignore_octave = FALSE)

mode_modern(
  mode = "ionian",
  key = "c",
  collapse = FALSE,
  ignore_octave = FALSE
```

```

)
mode_ionian(key = "c", collapse = FALSE, ignore_octave = FALSE)
mode_dorian(key = "c", collapse = FALSE, ignore_octave = FALSE)
mode_phrygian(key = "c", collapse = FALSE, ignore_octave = FALSE)
mode_lydian(key = "c", collapse = FALSE, ignore_octave = FALSE)
mode_mixolydian(key = "c", collapse = FALSE, ignore_octave = FALSE)
mode_aeolian(key = "c", collapse = FALSE, ignore_octave = FALSE)
mode_locrian(key = "c", collapse = FALSE, ignore_octave = FALSE)

```

Arguments

mode	character, which mode.
notes	character, for mode, may be a noteworthy string of seven notes, space- or vector-delimited.
ignore_octave	logical, strip octave numbering from modes not rooted on C.
n	integer, degree of rotation.
key	character, key signature.
collapse	logical, collapse result into a single string ready for phrase construction.

Details

For valid key signatures, see [keys](#).

Modern modes based on major scales are available by key signature using the `mode_*` functions. The seven modes can be listed with `modes`. Noteworthy strings of proper length can be checked to match against a mode with `is_mode`. Modes can be rotated with `mode_rotate`, a wrapper around `note_rotate`.

Value

character

See Also

[keys](#), [scale-helpers](#)

Examples

```

modes()
mode_dorian("c")
mode_modern("dorian", "c")
mode_modern("dorian", "c", ignore_octave = TRUE)

```

```

identical(mode_rotate(mode_ionian("c"), 1), mode_dorian("d"))
identical(
  mode_rotate(mode_ionian("c", ignore_octave = TRUE), 1),
  mode_dorian("d", ignore_octave = TRUE)
)

x <- sapply(modes(), mode_modern, ignore_octave = TRUE)
setNames(data.frame(t(x)), as.roman(1:7))

```

music

Create music objects and check music string validity

Description

Check whether a string is comprised exclusively of valid syntax for music strings. A music object can be built from such a string. It combines a noteworthy string and a note info string.

Usage

```

musical(x)

as_music(
  notes,
  info = NULL,
  lyrics = NA,
  key = "c",
  time = "4/4",
  tempo = "2 = 60",
  accidentals = NULL,
  format = NULL,
  labels = NULL,
  at = seq_along(labels)
)

is_music(x)

music_split(x)

```

Arguments

x	character or music, a string to be coerced or an existing music object.
notes, info	noteworthy and note info strings. For <code>as_music</code> , a complete music string is assumed for notes when <code>info = NULL</code> .
lyrics	optional lyrics object or NA, attached to output as an attribute.
key	character, store the key signature as a music attribute. Defaults to "c". See details.

time	character, store the time signature as a music attribute. Defaults to "4/4". See details.
tempo	character, defaults to "2 = 60". See details.
accidentals	NULL or character, represent accidentals, "flat" or "sharp".
format	NULL or character, the timestep delimiter format, "space" or "vector".
labels	character, text annotations to attach to timesteps using notate.
at	integer, timesteps for labels, defaults to starting from time one.

Details

With note info strings, you are required to enter something at every timestep, even if it is only the duration. This makes sense because if you do not enter something, there is simply no indication of a timestep. A nice feature of music strings is that explicit timesteps are achieved just by having notes present, allowing you to leave out durations entirely when they repeat, inheriting them from the previous timestep where duration was given explicitly. There is no need to enter the same number across consecutive timesteps; the first will suffice and the rest are automatically filled in for you when the object is constructed.

musical returns a scalar logical result indicating whether all timesteps contain exclusively valid entries.

as_music can be used to coerce to the music class. Coercion will fail if the string is not musical. The music class has its own print and summary methods. music objects are primarily intended to represent an aggregation of a noteworthy object and a noteinfo. You can optionally fold in a lyrics object as well. However, for music data analysis, any operations will involve first splitting the object into its component parts. The value of this class is for the more efficient data entry it provides.

When accidentals or format are NULL, these settings are inferred from the musical string input. When mixed formats are present, flats are the default for accidentals.

Other attributes are attached to a music object. key uses the tabr syntax, e.g., "c", "b_", "f#m", etc. time and tempo use the LilyPond string format. For music programming and analysis, key, time and tempo can most likely be ignored. They are primarily relevant when rendering a music snippet directly from a music object with LilyPond. These additional attributes provide more complete context for the rendered sheet music.

If you plan to render music snippets from a music object that you are defining from a new character string, and the context you have in mind is a stringed and fretted instrument like guitar, you can specify string numbers at the end of each timestep with numbers following a semicolon delimiter. This would still precede any * timestep multiplier number. See examples.

Note that if you convert a music object to a phrase object, you are changing contexts. The phrase object is the simplest LilyPond-format music structure. Coercion with phrase strips all attributes of a music object and retains only notes, note info and string numbers.

Value

depends on the function

See Also

[music-helpers](#), [note-checks](#), [note-metadata](#), [note-summaries](#), [note-coerce](#)

Examples

```

# note durations inherit from previous timestep if missing
x <- "a#4+ b_[staccato] c,x d''t8( e)( g_)- a4 c,e_,g, ce_g4. a~8 a1"
is_music(x)
musical(x)
x <- as_music(x)
is_music(x)
x

y <- lyrics_template(x)
y[3:8] <- strsplit("These are some song lyrics", " ")[[1]]
y

x <- as_music(x, lyrics = y, accidentals = "sharp")
summary(x)

# Starting string = 5: use ';'5'. Carries over until an explicit change.
x <- "a,4;5*5 b,4+ c4[staccato] cgc'e'~4 cgc'e'1 e'4;2 c';3 g;4 c;5 ce'1;51"
x <- as_music_df(as_music(x))
x$string

```

music-helpers

Accessing music object values and attributes

Description

Helper functions for accessing music object values and attributes.

Usage

```

music_notes(x)

music_info(x)

music_strings(x)

music_key(x)

music_time(x)

music_tempo(x)

music_lyrics(x)

```

Arguments

x music object.

Details

Note that while lyrics always shows as an attribute even when NA, strings is completely absent as a value if it was not part of the object construction from a new character string.

Value

depends on the function

See Also

[music](#), [note-checks](#), [note-metadata](#), [note-summaries](#), [note-coerce](#)

Examples

```
# Starting string = 5: use ';'5'. Carries over until an explicit change.
x <- "a,4;5*5 b,4- c4 cgc'e'~4 cgc'e'1 e'4;2 c';3 g;4 c;5 ce'1;51"
x <- as_music(x)

y <- lyrics_template(x)
y[3:8] <- strsplit("These are some song lyrics", " ")[[1]]
y

x <- as_music(x, lyrics = y)

attributes(x)

music_split(x)

music_notes(x)
music_info(x)
music_key(x)
music_time(x)
music_tempo(x)
music_lyrics(x)
music_strings(x)
```

notate

Add text to music staff

Description

Annotate a music staff, vertically aligned above or below the music staff at a specific note/time.

Usage

```
notate(x, text, position = "top")
```

Arguments

<code>x</code>	character.
<code>text</code>	character.
<code>position</code>	character, top or bottom.

Details

This function binds text annotation in LilyPond syntax to a note's associated info entry. Technically, the syntax is a hybrid form, but is later updated safely and unambiguously to LilyPond syntax with respect to the rest of the note info substring when it is fed to phrase for musical phrase assembly.

Value

a character string.

Examples

```
notate("8", "Solo")
phrase("c'~ c' d' e'", pc(notate(8, "First solo"), "8 8 4."), "5 5 5 5")
```

note-checks

Basic noteworthy string checks

Description

The simplest functions for inspecting noteworthy strings to see if their notes have certain properties.

Usage

```
note_is_accidental(notes)
note_is_natural(notes)
note_is_flat(notes)
note_is_sharp(notes)
note_has_accidental(notes)
note_has_natural(notes)
note_has_flat(notes)
note_has_sharp(notes)
```

Arguments

notes character, a noteworthy string.

Details

Note that these functions are the weakest in terms of checking noteworthiness. They are simple regular expression-based wrappers. They are often used internally by more complex functions without wasting computational overhead on performing input validity checks, but they are exported from the package for user convenience. Their results will only make sense on strings that you define in accordance with noteworthy string rules.

The `note_is_*` functions return a logical vector with length equal to the number of timesteps in `notes`. The `note_has_*` functions summarize these to a single logical value.

Value

logical

See Also

[note-metadata](#), [note-summaries](#), [note-coerce](#), [valid-notes](#)

Examples

```
x <- "r a_2 a a#' s"
note_has_accidental(x)
note_has_natural(x)
note_has_flat(x)
note_has_sharp(x)
note_is_accidental(x)
note_is_natural(x)
note_is_flat(x)
note_is_sharp(x)
note_has_tick(x)
note_has_integer(x)
note_is_tick(x)
note_is_integer(x)
note_has_rest(x)
note_is_rest(x)
```

Description

Helper functions for setting formatting attributes of noteworthy strings including representation of timesteps, octaves and accidentals.

Usage

```
naturalize(notes, type = c("both", "flat", "sharp"))

sharpen_flat(notes)

flatten_sharp(notes)

note_set_key(notes, key = "c")

as_tick_octaves(notes)

as_integer_octaves(notes)

as_space_time(x)

as_vector_time(x)

pretty_notes(notes, ignore_octave = TRUE)
```

Arguments

notes	character, a noteworthy string, space-delimited or vector of individual entries.
type	character, type of note to naturalize.
key	character, key signature to coerce any accidentals to the appropriate form for the key. May also specify "sharp" or "flat".
x	for generic functions: notes, info or music string.
ignore_octave	logical, strip any octave notation that may be present, returning only the basic notes without explicit pitch.

Details

For `sharpen_flat` and `flatten_sharp`, sharpening flats and flattening sharps refer to inverting their respective notation, not to raising or lowering a flatted or sharped note by one semitone. For the latter, use `naturalize`, which removes flat and/or sharp notation from a string. `note_set_key` is used for coercing a noteworthy string to a specific and consistent notation for accidentals based on a key signature. This is a wrapper around `sharpen_flat` and `flatten_sharp`. `as_tick_octaves`, `as_integer_octaves`, `as_space_time` and `as_vector_time` similarly affect octave and timestep format. For simultaneous control over the representation of timesteps, octave numbering and accidentals, all three are available as arguments to [as_noteworthy](#).

Value

character

A note on generic functions

`as_space_time` and `as_vector_time` are generic since they apply clearly to and are useful for not only noteworthy strings, but also note info and music objects. If `x` is still a simple character string,

these functions attempt to guess which of the three it is. It is recommended to set the class before using these functions.

There are many package functions that operate on noteworthy strings that could in concept work on music objects, but the expectation is that sound and time/info are disentangled. The music class is convenient for data entry, e.g., for transcription purposes, but it is not sensible to perform data analysis with quantities like pitch and time tightly bound together. This would only lead to repetitive deconstructions and reconstructions of music class objects. Most functions that operate on noteworthy strings or note info strings strictly apply to one or the other. Generic functions are reserved for only the most fundamental and generally applicable metadata retrieval and format coercion.

See Also

[note-checks](#), [note-metadata](#), [note-summaries](#), [valid-notes](#)

Examples

```
x <- "e_2 a_, b_, c##f#a# c#'f#'a#'"
note_set_key(x, "f")
note_set_key(x, "g")
as_tick_octaves(x)
as_integer_octaves(x)
y <- as_vector_time(x)
is_vector_time(y)
is_space_time(as_space_time(y))

naturalize(x)
naturalize(x, "sharp")
sharpen_flat(x)
flatten_sharp(x)
pretty_notes(x)
```

note-equivalence

Note, pitch and chord equivalence

Description

Helper functions to check the equivalence of two noteworthy strings, and other related functions.

Usage

```
note_is_equal(notes1, notes2, ignore_octave = TRUE)
```

```
note_is_identical(notes1, notes2, ignore_octave = TRUE)
```

```
pitch_is_equal(notes1, notes2)
```

```
pitch_is_identical(notes1, notes2)
```

```
octave_is_equal(notes1, notes2)
```

```
octave_is_identical(notes1, notes2, single_octave = FALSE)
```

Arguments

notes1 character, noteworthy string, space-delimited or vector of individual entries.

notes2 character, noteworthy string, space-delimited or vector of individual entries.

ignore_octave logical, ignore octave position when considering equivalence.

single_octave logical, for octave equality, require all notes share the same octave. See details.

Details

Noteworthy strings may contain notes, pitches and chords. Noteworthy strings are equal if they sound the same. This means that if one string contains Eb (e_) and the other contains D# (d#) then the two strings may be equal, but they are not identical.

pitch_is_equal and pitch_is_identical perform these respective tests of equivalence on both notes and chords. These are the strictest functions in terms of equivalent sound because pitch includes the octave number.

note_is_equal and note_is_identical are similar but include a default argument ignore_octave = TRUE, focusing only on the notes and chords. This allows an even more relaxed definition of equivalence. Setting this argument to FALSE is the same as calling the pitch_is_* variant.

Chords can be checked the same as notes. Every timestep in the sequence is checked pairwise between note1 and note2.

These functions will return TRUE or FALSE for every timestep in a sequence. If the two noteworthy strings do not contain the same number of notes at a specific step, such as a single note compared to a chord, this yields a FALSE value, even in a case of an octave dyad with octave number ignored. If the two sequences have unequal length NA is returned. These are bare minimum requirements for equivalence. See examples.

octave_is_equal and octave_is_identical allow much weaker forms of equivalence in that they ignore notes completely. These functions are only concerned with comparing the octave numbers spanned by any pitches present at each timestep. When checking for equality, octave_is_equal only looks at the octave number associated with the first note at each step, e.g., only the root note of a chord. octave_is_identical compares all octaves spanned at a given timestep.

It does not matter when comparing two chords that they may be comprised of a different numbers of notes. If the set of unique octaves spanned by one chord is identical to the set spanned by the other, they are considered to have identical octave coverage. For example, a1b2c3 is identical to d1e1f2g3. To be equal, it only matters that the two chords begin with x1, where x is any note. Alternatively, for octave_is_identical only, setting single_octave = TRUE additionally requires that all notes from both chords being compared at a given timestep share a single octave.

Value

logical

Examples

```

x <- "b_2 ce_g"
y <- "b_ cd#g"
note_is_equal(x, y)
note_is_identical(x, y)

x <- "b_2 ce_g"
y <- "b_2 cd#g"
pitch_is_equal(x, y)
pitch_is_identical(x, y)

# same number of same notes, same order: unequal sequence length
x <- "b_2 ce_g b_"
y <- "b_2 ce_gb_"
note_is_equal(x, y)

# same number of same notes, order, equal length: unequal number per timestep
x <- "b_2 ce_g b_"
y <- "b_2 ce_gb_"
note_is_equal(x, y)

x <- "a1 b_2 a1b2c3 a1b4 g1a1b1"
y <- "a_2 g#2 d1e1f2g3 a1b2b4 d1e1"
octave_is_equal(x, y)
octave_is_identical(x, y)
octave_is_identical(x, y, single_octave = TRUE)

```

note-logic

Relational operators for noteworthy class

Description

Relational operators for comparing two noteworthy class objects.

Usage

```

## S3 method for class 'noteworthy'
e1 == e2

## S3 method for class 'noteworthy'
e1 != e2

## S3 method for class 'noteworthy'
e1 < e2

## S3 method for class 'noteworthy'
e1 <= e2

```

```
## S3 method for class 'noteworthy'  
e1 > e2
```

```
## S3 method for class 'noteworthy'  
e1 >= e2
```

Arguments

e1 noteworthy string.
e2 noteworthy string.

Details

Equality is assessed in the same manner as used for `note_sort` when sorting pitches. What matters is the underlying semitone value associated with each pitch, not the string notation such as flat vs. sharp (see `pitch_is_identical`). When comparing chords, or a chord vs. a single note, comparison favors the root. Comparison is made of the respective lowest pitches, then proceeds to the next pitch if equal.

For these operators, the objects on the left and right side of the operator must both be noteworthy or an error is returned.

The examples include a chord with its pitches entered out of pitch order. This does not affect the results because pitches within chords are sorted before note to note comparisons at each timestep are done between e1 and e2.

Value

logical vector

Examples

```
x <- as_noteworthy("f# a d'f#'a' d'f#'a'")  
y <- as_noteworthy("g_ b f#'a'd' d'd'")  
x == y  
x != y  
x < y  
x > y  
x <= y  
x >= y
```

note-metadata

Noteworthy string metadata

Description

Inspect basic metadata for noteworthy strings.

Usage

n_steps(x)
n_notes(notes)
n_chords(notes)
n_octaves(notes)
chord_size(notes)
octave_type(notes)
accidental_type(x)
time_format(x)
is_space_time(x)
is_vector_time(x)
note_is_tick(notes)
note_is_integer(notes)
note_has_tick(notes)
note_has_integer(notes)
note_is_rest(notes)
note_has_rest(notes)

Arguments

x for generic functions: notes, info or music string.
notes character, a noteworthy string, space-delimited or vector of individual entries.

Details

These functions inspect the basic metadata of noteworthy strings. For functions that perform basic checks on strings, see [note-checks](#).

The n_* functions give summary totals of the number of timesteps, number of individual note (non-chord) timesteps, number of chord time steps, and the number of distinct octaves present across timesteps.

Functions pertaining to type or format of a noteworthy string provide information on how a particular string is defined, e.g. `time_format`. Note that the result pertains to true noteworthy-

class objects. If inspecting a standard character string, the result pertains to post-conversion to the noteworthy class and does not necessarily reflect what is found in notes verbatim. See examples.

Value

varies by function

A note on generic functions

`n_steps` and the three time format functions are generic since they apply clearly to and are useful for not only noteworthy strings, but also note info, music, and lyrics objects. If `x` is still a simple character string, these functions attempt to guess if it is noteworthy, note info, or music. Lyrics content is arbitrary so is never considered for a simple character string. Best practice is to set the class before using these functions anyway.

There are many package functions that operate on noteworthy strings that could in concept also work on music objects, but the expectation is that sound and time/info are disentangled for analysis. The music class is convenient and relatively efficient data entry, e.g., for transcription purposes, but it is not sensible to perform data analysis with quantities like pitch and time tightly bound together in a single string. This would only lead to repetitive deconstructions and reconstructions of music class objects.

The music class is intended to be a transient class such as during data import, data entry, or data export. Most functions that operate on noteworthy strings or note info strings strictly apply to one or the other. Generic functions are reserved for only the most fundamental and generally applicable metadata retrieval and format coercion.

See Also

[tabr-methods](#), [note-checks](#), [note-summaries](#), [note-coerce](#), [valid-notes](#)

Examples

```
x <- "e_2 a_, c#f#a#"
n_steps(x)
n_notes(x)
n_chords(x)
n_octaves(x)
chord_size(x)

# Type is mixed in \code{x} but is inferred under default conversion rules.
# These check \code{x} once validated and coerced to 'noteworthy' class.
octave_type(x)
accidental_type(x)
# The default is tick octaves and flats
as_noteworthy(x)

time_format(x)
is_space_time(x)
is_vector_time(x)
```

note-summaries	<i>Noteworthy string summaries</i>
----------------	------------------------------------

Description

Basic summary functions for noteworthy strings.

Usage

```
tally_notes(notes, rests = FALSE)
tally_pitches(notes, rests = FALSE)
octaves(notes)
tally_octaves(notes)
distinct_notes(notes, rests = FALSE)
distinct_pitches(notes, rests = FALSE)
distinct_octaves(notes)
pitch_range(notes)
semitone_range(notes)
semitone_span(notes)
octave_range(notes)
octave_span(notes)
```

Arguments

notes	character, a noteworthy string, space-delimited or vector of individual entries.
rests	logical, include rests <i>r</i> and silent rests <i>s</i> in tally.

Details

These functions provide basic summaries of noteworthy strings.

Returned object depends on the nature of the function. It can be integers, logical, character. Results can be a vector of equal length of a single value summary.

Use the `tally_*` and `distinct_*` functions specifically for summaries of unique elements.

`distinct_notes` and `distinct_pitches` filter a noteworthy string to its unique elements, respectively. These functions return another noteworthy string.

`*_span` functions are just the size of a range, e.g., `semitone_range` and `semitone_span`.

Value

varies by function

See Also

[note-checks](#), [note-metadata](#), [note-coerce](#), [valid-notes](#)

Examples

```
x <- "r s e_2 a_, c#f#a#"
tally_notes(x)
tally_pitches(x)
octaves(x)
tally_octaves(x)
distinct_notes(x)
distinct_pitches(x)
distinct_octaves(x)

pitch_range(x)
semitone_range(x)
semitone_span(x)
octave_range(x)
octave_span(x)
```

noteinfo

Note info helpers

Description

Functions for working with note info strings.

Usage

```
info_duration(x)

info_slur_on(x)

info_slur_off(x)

info_slide(x)

info_bend(x)

info_dotted(x)

info_single_dotted(x)

info_double_dotted(x)
```

```
info_annotation(x)
```

```
info_articulation(x)
```

Arguments

`x` character, note info string normally accompanying a noteworthy string for building phrase objects. `x` may also be a phrase object.

Details

If `x` is a phrase object, there are some parsing limitations such as tuplets and repeats.

Value

character

See Also

[valid-noteinfo](#)

Examples

```
a <- notate("t8x", "Start here")
notes <- "a, b, c d e f g# a r ac'e' a c' e' c' r*3 ac'e'~ ac'e'"
info <- paste(a, "t8x t8-. 16 4.. 16- 16 2^ 2 4. 8( 4)( 4) 8*4 1 1")
x <- as_music(notes, info)
```

```
data.frame(
  duration = info_duration(x),
  slur_on = info_slur_on(x),
  slur_off = info_slur_off(x),
  slide = info_slide(x),
  bend = info_bend(x),
  dotted = info_dotted(x),
  dotted1 = info_single_dotted(x),
  dotted2 = info_double_dotted(x),
  annotation = info_annotation(x),
  articulation = info_articulation(x)
)
```

note_ngram

Note/chord n-gram

Description

Convert a noteworthy string to a list of noteworthy n-grams.

Usage

```
note_ngram(notes, n = 2, tally = FALSE, rests = FALSE)
```

Arguments

notes	a noteworthy string.
n	Number of grams. Must be ≥ 1 and \leq number of timesteps in notes.
tally	logical, tally n-grams in a data frame. Otherwise a list.
rests	logical, exclude rests. Affects the number of timesteps.

Value

list of noteworthy objects or a tibble

Examples

```
x <- as_noteworthy("c r ceg dfa ceg dfa")
note_ngram(x)
(x <- note_ngram(x, tally = TRUE))
x$ngram <- as.character(x$ngram)
x
```

note_slice

Slice, sort, rotate, shift and arpeggiate notes

Description

Helper functions for indexing and moving notes within noteworthy strings.

Usage

```
note_slice(notes, ...)

note_sort(notes, decreasing = FALSE)

note_rotate(notes, n = 0)

note_shift(notes, n = 0)

note_arpeggiate(notes, n = 0, step = 12)
```


Arguments

notes	character, a noteworthy string, space-delimited or vector of individual entries.
...	For note_slice, an integer or logical vector.
decreasing	logical, short in decreasing order.
n	integer, number of rotations or extensions of note sequence. See details.
step	integer, number of semitone steps from the first (or last) note in notes at which to begin repeating the shifted notes sequence as an arpeggio. See examples. arpeggio.

Details

note_slice subsets the timesteps of a noteworthy string by integer index or logical vector of length equal to the number of timesteps.

note_sort sorts the timesteps of a noteworthy string by pitch. When a tie exists by root note, the next note in chords are compared, if they exist. For example, a, sorts lower than a, ce.

note_rotate simply rotates anything space-delimited or vectorized in place. It allows chords. Octave numbering is ignored if present.

For note_shift the entire sequence is shifted up or down in pitch, as if inverting a broken chord. If notes contains chords, they are broken into successive notes. Then all notes are ordered by pitch. Finally shifting occurs.

Instead of a moving window, note_arpeggiate grows its sequence from the original set of timesteps by repeating the entire sequence n times (n must be positive). Each repeated sequence contributing to the arpeggio is offset by step semitones from the original. step can be negative. It defaults to 12, increasing all notes by one octave.

Value

character

Examples

```
x <- "bd'f#' a c'e'g' b ba c'g' gd'g'd'"
note_sort(x)
note_sort(x, decreasing = TRUE)

x <- "e_2 a_, c#f#a#"
note_slice(x, 2:3)
note_slice(x, c(FALSE, TRUE, TRUE))

note_rotate(x, 1)

note_shift("c e g", 1)
note_shift("c e g", -4)

note_arpeggiate("c e g ceg", 3)
note_arpeggiate("c e g", 3, step = -12)
note_arpeggiate("g e c", 3, step = -12)
```

```
note_arpeggiate("c e_ g_ a", 3, step = 3)
note_arpeggiate("c a g_ e_", 3, step = -3)
```

n_measures	<i>Summarize rhythm and time of music objects</i>
------------	---

Description

These functions assist with summarizing temporal data for music objects.

Usage

```
n_measures(x)

n_beats(x, unit = 4)

steps_per_measure(x)

bpm(x, unit = 4, tempo = NULL)

seconds(x, tempo = NULL)

seconds_per_measure(x, tempo = NULL)

seconds_per_step(x, tempo = NULL)

steps_start_time(x, tempo = NULL)
```

Arguments

x	note info or music object.
unit	character, or an equivalent integer. A beat unit. See details.
tempo	character, LilyPond format tempo, e.g., "4 = 120" is 120 quarter note beats per minute.

Details

These functions also work with the simpler `noteinfo` class, though some functions require you to provide additional arguments.

Functions that deal with real time require a known tempo, which music objects have. The simpler `noteinfo` object does not contain this information. You can provide a value to the `tempo` argument of such functions. This overrides the tempo of `x` if a music object. But the reason to use `tempo` is to provide one when `x` is a note info object. By default `tempo = NULL`, in which case it will derive the value from the music object or return an error for note info objects.

`n_measures` gives the total number of measures covered by all timesteps. Functions providing the number of beats and beats per minute both take a `unit`, defaulting to 4 for quarter note beats. The unit can be any even beat, triplet beat, dotted, or double dotted beat, from "t32" up to 1.

The number of timesteps starting in each measure is obtained with `steps_per_measure`.

Value

depends on function

Examples

```
a <- notate("t8x", "Start here")
notes <- "a, b, c d e f g# a r ac'e' a c' e' c' r*3 ac'e'~ ac'e'"
info <- paste(a, "t8x t8-. 16 4.. 16- 16 2^ 2 4. 8( 4)( 4) 8*4 1 1")
info <- as_noteinfo(info)
x <- as_music(notes, info)

n_measures(info) # fraction indicates incomplete final measure
n_measures(x)

n_beats(x)
n_beats(x, 1)
n_beats(x, "t16")

bpm(x)
bpm(x, "t8")

seconds(x)
seconds(info, "4 = 120")
seconds(info, "2 = 60")
seconds(x, "4 = 100")

steps_per_measure(x)
seconds_per_measure(x)
seconds_per_step(x)
steps_start_time(x)
```

phrase

Create a musical phrase

Description

Create a musical phrase from character strings that define notes, note metadata, and optionally explicit strings fretted. The latter can be used to ensure proper tablature layout.

Usage

```
phrase(notes, info = NULL, string = NULL, bar = NULL)
```

```
p(notes, info = NULL, string = NULL, bar = NULL)
```

Arguments

notes, info	noteworthy and note info strings. When info = NULL, it is assumed that notes refers to a music object or string formatted as such.
string	space-delimited character string or vector (or integer vector if simple string numbers). This is an optional argument that specifies which instrument strings to play for each specific timestep. Otherwise NULL.
bar	character or NULL (default). Terminates the phrase with a bar or bar check. See details. Also see the LilyPond help documentation on bar notation for all the valid options.

Details

A phrase object combines a valid string of notes with a corresponding valid string of note info. The only required note info is time, but other information can be included as well. You do not need to input an existing noteworthy class object and noteinfo class object, but both inputs must be valid and thus coercible to these classes. This is similar to how the music class works. The difference with phrase objects is that they are used to create LilyPond syntax analogous to what a music object contains.

Note that if you convert a music object to a phrase object, you are changing contexts. The phrase object is the simplest LilyPond-format music structure. Coercion with phrase strips all attributes of a music object and retains only notes, note info and string numbers.

See the help documentation on noteworthy, noteinfo, and music classes for an understanding of the input data structures. The function p is a convenient shorthand wrapper for phrase.

If a string is provided to bar, it is interpreted as LilyPond bar notation. E.g., bar = "|" adds the LilyPond syntax \bar "|" to the end of a phrase. If only a bar check is desired, use bar = TRUE. FALSE is treated as NULL for completeness.

Value

a phrase.

See Also

[valid-notes](#), [valid-noteinfo](#), [music](#)

Examples

```
phrase("c ec'g' ec'g'", "4- 4 2") # no string arg (not recommended for tabs)
phrase("c ec4g4 ec4g4", "4 4 2") # same as above
phrase("c b, c", "4. 8( 8)", "5 5 5") # direction implies hammer on
phrase("b2 c d", "4( 4)- 2", "5 5 5") # hammer and slide
```

```
phrase("c ec'g' ec'g'", "1 1 1", "5 432 432")
p("c ec'g' ec'g'", 1, "5 4 4") # same as above
```

```
n <- "a, b, c d e f g e f g a~ a"
i <- "8- 8 8 8-. t8( t8)( t8) t16( t16)( t16) 8 1"
```

```

m <- as_music(n, i)

x <- p(n, i)
x
identical(x, p(m))

x <- "a,4;5*5 b,4- c4 cgc'e'~4 cgc'e'1 e'4;2 c';3 g;4 c;5 ce'1;51"
p(x)
identical(p(x), p(as_music(x)))

x <- p("a b", 2, bar = "|.")
x2 <- pc(p("a b", 2), '\\bar "|.")
identical(x, x2)

```

phrase-checks

Phrase validation and coercion

Description

These helper functions add some validation checks for phrase and candidate phrase objects.

Usage

```

as_phrase(phrase)

phrasey(phrase)

notify(phrase)

phrase_notes(phrase, collapse = TRUE)

phrase_info(phrase, collapse = TRUE, annotations = TRUE)

phrase_strings(phrase, collapse = FALSE)

notable(phrase)

```

Arguments

phrase	phrase object or character string (candidate phrase).
collapse	logical, collapse result into a single string ready for phrase construction.
annotations	logical, strip any text annotations from the note info converted from phrase.

Details

Use these functions with some caution. They are not intended for strictness and perfection. `phrasey` checks whether an object is weakly phrase-like and returns `TRUE` or `FALSE`. It can be used to safeguard against the most obvious cases of phrase not containing valid phrase syntax when programming. However, it may also be limiting. Use wear sensible.

`as_phrase` coerces an object to a phrase object if possible. This function performs an internal phrasey check.

`notify` attempts to decompose a phrase object back to its original input vectors consisting of notes, note info, and optionally, instrument string numbering. If successful, it returns a tibble data frame with columns: notes, info, string.

Unless decomposing very simple phrases, this function is likely to reveal limitations. Complex phrase objects constructed originally with `phrase` can be challenging to deconstruct in a one to one manner. Information may be lost, garbled, or the function may fail. For example, this function is not advanced enough to unravel repeat notation or tuples.

`notable` returns TRUE or FALSE regarding whether a phrase can be converted back to character string inputs, not necessarily with complete correctness, but without simple failure. It checks for phrasiness. Then it tries to call `notify` and returns FALSE gracefully if that call throws an exception.

Value

see details for each function's purpose and return value.

Examples

```
# Create a list of phrase objects
p1 <- phrase("c ec'g' ec'g'", "4 4 2") # no string numbers (not recommended)
p2 <- phrase("c ec4g4 ec4g4", "4 4 2") # same as above
p3 <- phrase("c b, c", "4. 8( 8)", "5 5 5") # direction implies hammer on
p4 <- phrase("b2 c d", "4( 4)- 2", "5 5 5") # hammer and slide
p5 <- phrase("c ec'g'~ ec'g'", 1, "5 432 432") # tied chord
x <- list(p1, p2, p3, p4, p5)

# Check if phrases and strings are phrasey
sapply(x, phrasey)
sapply(as.character(x), phrasey, USE.NAMES = FALSE)

# Coerce character string representation to phrase and compare with original
y <- lapply(as.character(x), as_phrase)
identical(x, y)

# Check if notable
sapply(x, notable)
notable(p("a b c", 1))
notable("a b x") # note: not constructible as a phrase in the first place

# Notify phrases
d <- do.call(rbind, lapply(x, notify))
d

# Wrappers around notify extract components, default to collapsed strings
phrase_notes(p5)
phrase_info(p5)
phrase_strings(p5)

# If phrase decomposition works well, coercion is one to one
x2 <- lapply(x,
```

```

    function(x) p(phrase_notes(x), phrase_info(x), phrase_strings(x))
  )
  identical(x, x2)

```

pitch_freq

Pitch conversions

Description

Convert between pitches, chords, semitones and frequencies.

Usage

```
pitch_freq(notes, a4 = 440)
```

```
pitch_semitones(notes)
```

```
chord_freq(notes, a4 = 440)
```

```
chord_semitones(notes)
```

```

freq_pitch(
  freq,
  octaves = c("tick", "integer"),
  accidentals = c("flat", "sharp"),
  collapse = FALSE,
  a4 = 440
)

```

```
freq_semitones(freq, a4 = 440)
```

```

semitone_pitch(
  semitones,
  octaves = c("tick", "integer"),
  accidentals = c("flat", "sharp"),
  collapse = FALSE
)

```

```
semitone_freq(semitones, a4 = 440)
```

Arguments

notes	character, noteworthy string, space-delimited or vector of individual entries. See details.
a4	the fixed frequency of the A above middle C, typically 440 Hz.
freq	numeric vector, frequencies in Hz.
octaves	NULL or character, "tick" or "integer" octave numbering in result.

accidentals NULL or character, represent accidentals, "flat" or "sharp".
 collapse logical, collapse result into a single string. key and style.
 semitones integer values of pitches.

Details

Frequencies are in Hertz. Values are based on the 12-tone equal-tempered scale. When converting an arbitrary frequency to pitch, it is rounded to the nearest pitch. `pitch_freq` and `pitch_semitones` strictly accept single notes in noteworthy strings and return numeric vectors. `chord_freq` and `chord_semitones` accept any noteworthy string and always return a list. These are provided so that all functions are type-safe. See examples.

Value

integer, numeric or noteworthy vector

Examples

```

x <- "a e4 a4 e5 a5"
y <- pitch_freq(x)
y

freq_semitones(y)
freq_pitch(y)

identical(as_noteworthy(x), freq_pitch(y, "integer", collapse = TRUE))

s <- pitch_semitones(x)
s
semitone_pitch(s)

x <- "a, a,c#e"
chord_semitones(x)
chord_freq(x)

```

pitch_seq

Create a sequence from pitch notation

Description

Create a noteworthy string of a sequence of consecutive pitches.

Usage

```
pitch_seq(x, y, key = NULL, scale = NULL, format = c("space", "vector"))
```


Arguments

x	character, valid pitch notation, e.g., "a2" or "a,".
y	character, same as x for the sequence x:y. If a number, the length of the sequence from x and the sign of y determines the direction.
key	character, key signature for a diatonic sequence. key = NULL (default) results in a chromatic sequence.
scale	character, if you want to use a different scale in conjunction with the key/root note, you can provide it, e.g., scale = "harmonic minor". Ignored if key = NULL.
format	character, the timestep delimiter format, "space" or "vector".

Details

Note that all pitches resulting from the defined sequence must be in the semitone range 0-131 or an error is thrown.

If not using a chromatic sequence and x (or y if also a pitch) is not part of the key signature or scale, the sequence is internally bound. See examples.

Format of accidentals in the result is prioritized by the scale and key, the key when no scale is given, then x (and y if also a pitch), and finally defaults to flats if ambiguous.

Value

noteworthy

Examples

```
# chromatic sequence (default)
pitch_seq("a,", 13)
pitch_seq("c5", -2)
pitch_seq("c", "b")

# diatonic sequence
pitch_seq("c", 8, key = "c")
pitch_seq("c", 8, "am")
pitch_seq("c#", "a#", "am")

# combine with alternative scale
pitch_seq("a", 8, "am", "harmonic minor")
```

plot_fretboard

Chord and fretboard diagram plots

Description

Create a fretboard diagram for a single chord or a general progression.

Usage

```
plot_fretboard(  
  string,  
  fret,  
  labels = NULL,  
  mute = FALSE,  
  label_size = 10,  
  label_color = "white",  
  point_size = 10,  
  point_color = "black",  
  point_fill = "black",  
  group = NULL,  
  horizontal = FALSE,  
  left_handed = FALSE,  
  fret_range = NULL,  
  accidentals = c("flat", "sharp"),  
  tuning = "standard",  
  show_tuning = FALSE,  
  asp = NULL,  
  base_size = 20  
)
```

```
plot_chord(  
  chord,  
  labels = NULL,  
  label_size = 10,  
  label_color = "white",  
  point_size = 10,  
  point_color = "black",  
  point_fill = "black",  
  group = NULL,  
  horizontal = FALSE,  
  left_handed = FALSE,  
  fret_range = NULL,  
  accidentals = c("flat", "sharp"),  
  tuning = "standard",  
  show_tuning = FALSE,  
  asp = NULL,  
  base_size = 20  
)
```

Arguments

string	integer or as a space-delimited character string; instrument string numbers.
fret	integer or as a space-delimited character string; fret numbers.
labels	character, optional text labels, must be one for every point.
mute	logical vector or specific integer indices, which notes to mute.

label_size	numeric, size of fretted note labels.
label_color	character, label color.
point_size	numeric, size of fretted note points.
point_color	character, point color.
point_fill	character, point fill color.
group	optional vector to facet by.
horizontal	logical, directional orientation.
left_handed	logical, handedness orientation.
fret_range	fret limits, if not NULL, overrides limits derived from fret.
accidentals	character, when labels = "notes" represent accidentals: "flat" or "sharp".
tuning	explicit tuning, e.g., "e, a, d g b e'", or a pre-defined tuning. See details.
show_tuning	logical, show tuning of each string.
asp	numeric, aspect ratio, overrides default aspect ratio derived from number of strings and frets.
base_size	base size for ggplot2::theme_void.
chord	character, a single chord given in fret notation. See details.

Details

These functions are under development and subject to change. They each return a ggplot object.

Use `plot_chord` to create a fretboard diagram of a specific chord. `plot_chord` accepts a character string in simple fretboard format, e.g., `chord = "xo221o"`. Zero is allowed in place of "o". This only works when no spaces or semicolons are detected. The function checks for spaces first, then semicolons, to split fret numbers. Do not mix formats. For example, you can use `chord = "xo221o"`, `chord = "x 8 10 10 9 8"` or `chord = "x;8;10;10;9;8"`. Trailing delimiters are ignored (LilyPond format: `"x;8;10;10;9;8;"`). If there are fewer fret values than there are strings on the instrument, as inferred from tuning, then muted strings, x, are inferred for the remaining lower-pitch strings.

`plot_fretboard` produces a more general fretboard diagram plot. It is intended for scales, arpeggios and other patterns along the fretboard. For this function, provide vectors of string and fret numbers. `mute` is available but not as applicable for this function. For single chord diagrams, use `plot_chord`.

Number of strings is derived from tuning. See [tunings](#) for pre-defined tunings and examples of explicit tunings. `tuning` affects point labels when `labels = "notes"`.

Value

a ggplot object

Examples

```

# General patterns: scale shifting exercise
string <- c(6, 6, 6, 5, 5, 5, 4, 4, 4, 4, 4, 3, 3, 3, 2, 2, 2, 1, 1, 1)
fret <- "2 4 5 2 4 5 2 4 6 7 9 6 7 9 7 9 10 7 9 10" # string input accepted
plot_fretboard(string, fret, labels = "notes")

# Single chord diagrams
# open chord
idx <- c(1, 1, 2, 2, 2, 1)
fill <- c("white", "black")[idx]
lab_col <- c("black", "white")[idx]
plot_chord("xo221o", "notes", label_color = lab_col, point_fill = fill)

# moveable chord
plot_chord("355433", horizontal = TRUE, show_tuning = TRUE)

plot_chord("0231") # leading x inferred; same as plot_chord("xx0321")

plot_chord("10 12 13 11", fret_range = c(10, 14))

```

plot_music

Plot sheet music snippet with LilyPond

Description

These functions are wrappers around the `render_music_*` functions. They abstract the process of rendering a sheet music snippet to png and loading the rendered image back into R to be displayed as a plot in an open graphics device or inserted into an R Markdown code chunk.

Usage

```

plot_music(
  music,
  clef = "treble",
  tab = FALSE,
  tuning = "standard",
  string_names = NULL,
  header = NULL,
  paper = NULL,
  colors = NULL,
  transparent = FALSE,
  res = 300
)

plot_music_tc(
  music,
  header = NULL,
  paper = NULL,

```

```
    colors = NULL,  
    transparent = FALSE,  
    res = 300  
  )  
  
plot_music_bc(  
  music,  
  header = NULL,  
  paper = NULL,  
  colors = NULL,  
  transparent = FALSE,  
  res = 300  
)  
  
plot_music_tab(  
  music,  
  clef = NA,  
  tuning = "standard",  
  string_names = NULL,  
  header = NULL,  
  paper = NULL,  
  colors = NULL,  
  transparent = FALSE,  
  res = 300  
)  
  
plot_music_guitar(  
  music,  
  tuning = "standard",  
  string_names = NULL,  
  header = NULL,  
  paper = NULL,  
  colors = NULL,  
  transparent = FALSE,  
  res = 300  
)  
  
plot_music_bass(  
  music,  
  tuning = "bass",  
  string_names = FALSE,  
  header = NULL,  
  paper = NULL,  
  colors = NULL,  
  transparent = FALSE,  
  res = 300  
)
```

Arguments

music	a music object.
clef	character, include a music staff with the given clef. NA to suppress. See track for details.
tab	logical, include tablature staff. NA to suppress. See track.
tuning	character, string tuning, only applies to tablature. See track.
string_names	label strings at beginning of tab staff. NULL (default) for non-standard tunings only, TRUE or FALSE for force on or off completely.
header	a named list of arguments passed to the header of the LilyPond file. See lilypond details.
paper	a named list of arguments for the LilyPond file page layout. See lilypond details.
colors	a named list of LilyPond element color global overrides. See lilypond for details.
transparent	logical, transparent background for intermediate png file.
res	numeric, resolution, png only. Defaults to 300.

Details

While these functions abstract away the details of the process, this is not the same as making the plot completely in R. R is only displaying the intermediary png file. LilyPond is required to engrave the sheet music.

For R Markdown you can alternatively render the png using the corresponding `render_music_*` function and then place it in the document explicitly using `knitr::include_graphics`. See [render_music](#) for more details.

Value

a plot

See Also

`render_music`, [phrase](#), [track](#), [score](#), [lilypond](#), [tab](#)

Examples

```
x <- "a,4;5*5 b,4- c4 cgc'e'~4 cgc'e'1 e'4;2 c';3 g;4 c;5 ce'1;51"
x <- as_music(x)

y <- "a,,4;3*5 b,,4- c,4 c,g,c~4 c,g,c1 c4;1 g,,2 c,,3 g,,2 c,c1;31"
y <- as_music(y)

## Not run:
if(tabr_options()$lilypond != ""){ # requires LilyPond installation
  plot_music(x)
  plot_music(x, "treble_8", tab = TRUE)
```

```
plot_music_tc(x)
plot_music_bc(x)

plot_music_tab(x)
plot_music_guitar(x)
plot_music_bass(y)
}

## End(Not run)
```

ratio_to_cents	<i>Convert between chord frequency ratios and cents</i>
----------------	---

Description

Convert between frequency ratios and logarithmic cents

Usage

```
ratio_to_cents(x, y = NULL)
cents_to_ratio(x)
```

Arguments

x a vector of ratios if y = NULL, otherwise frequencies. Cents for cents_to_ratio.
y if not NULL, frequencies and the ratios are given by y / x.

Value

numeric

Examples

```
ratio_to_cents(c(0.5, 1, 1.5, 2))
cents_to_ratio(c(-1200, 0, 701.955, 1200))
```

`read_midi`*Read, inspect and convert MIDI file contents*

Description

Read MIDI file into a data frame and inspect the music data with supporting functions.

Usage

```
read_midi(file, ticks_per_qtr = 480)
```

```
midi_metadata(x)
```

```
midi_notes(x, channel = NULL, track = NULL, noteworthy = TRUE)
```

```
midi_time(x)
```

```
midi_key(x)
```

```
ticks_to_duration(x, ticks_per_qtr = 480)
```

```
duration_to_ticks(x, ticks_per_qtr = 480)
```

Arguments

<code>file</code>	character, path to MIDI file.
<code>ticks_per_qtr</code>	ticks per quarter note. Used to compute durations from MIDI file ticks.
<code>x</code>	a data frame returned by <code>read_midi</code> . An integer vector for <code>ticks_to_duration</code> ; a character vector (may be a space-delimited string) for <code>duration_to_ticks</code> .
<code>channel, track</code>	integer, filter rows on channel or track.
<code>noteworthy</code>	logical, convert to noteworthy and noteinfo data.

Details

The `read_midi` function wraps around `tuneR::readMidi` by Uwe Ligges and Johanna Mielke. `midi_notes` is a work in progress, but converts MIDI data to noteworthy strings and note info formats. This makes it easy to analyze, transform and edit the music data as well as render it to sheet music and a new MIDI file.

`read_midi` does not parse the ticks per quarter note from the MIDI file input at this time. It must be specified with `ticks_per_qtr`

Value

a tibble data frame

Examples

```

ticks_to_duration(c(120, 160))
ticks_to_duration(c(128, 192, 512), ticks_per_qtr = 384)
duration_to_ticks(c("t8", "8", "8.", "8.."))
duration_to_ticks(c("t8 8 8. 8.."), ticks_per_qtr = 384)

file <- system.file("example2.mid", package = "tabr")
if(require("tunerR")){
  x <- read_midi(file, ticks_per_qtr = 384)
  midi_metadata(x)
  midi_time(x)
  midi_key(x)
  midi_notes(x, channel = 0, noteworthy = FALSE)

  (x <- midi_notes(x, channel = 0))
  (x <- as_music(x$pitch, x$duration))

  # requires LilyPond installation
  if(tabr_options()$lilypond != ""){
    out <- file.path(tempdir(), "out.pdf")
    phrase(x) %>% track_bc() %>% score() %>% tab(out, details = FALSE)
  }
}

```

render_chordchart

Render a chord chart with LilyPond

Description

Render a standalone chord chart of chord fretboard diagrams with LilyPond for a set of chords.

Usage

```

render_chordchart(
  chords,
  file,
  size = 1.2,
  header = NULL,
  paper = NULL,
  colors = NULL,
  crop_png = TRUE,
  transparent = FALSE,
  res = 150,
  keep_ly = FALSE,
  details = FALSE
)

```

Arguments

chords	named character vector of valid formatting for LilyPond chord names and values. See examples.
file	output file.
size	numeric, size of fretboard diagrams (relative to paper font size). Use this to scale diagrams up or down.
header	a named list of arguments passed to the header of the LilyPond file. See details.
paper	a named list of arguments for the LilyPond file page layout. See details.
colors	reserved; not yet implemented for this function.
crop_png	logical, see <code>lilypond</code> for details.
transparent	logical, transparent background, png only.
res	numeric, resolution, png only. <code>transparent = TRUE</code> may fail when <code>res</code> exceeds ~150.
keep_ly	logical, keep intermediate LilyPond file.
details	logical, set to <code>TRUE</code> to print LilyPond log output to console. Windows only.

Details

This function uses a generates a LilyPond template for displaying only a fretboard diagram chart. It then passes the file to LilyPond for rendering. To plot specific fretboard diagrams in R using `ggplot` and with greater control, use `plot_fretboard`.

The options for `paper` include the following and have the following default values if not provided.

- `textheight = 220`
- `linewidth = 150`
- `indent = 0`
- `fontsize = 10`
- `page_numbers = FALSE`
- `print_first_page_number = TRUE`
- `first_page_number = 1`

`fontsize` only controls the global font size. If you want to scale the size of the fretboard diagrams up or down use the `size` argument rather than this `paper` value.

Note that chord chart output must fit on a single page. If the full set of chord diagrams does not fit on one page then diagrams will be clipped in the rendered output. Use `size` to keep the output to one page or make multiple sheets separately.

Value

writes files to disk

See Also

[plot_fretboard](#), [lilypond](#), [tab](#)

Examples

```

suppressPackageStartupMessages(library(dplyr))

chords <- filter(
  guitarChords, root %in% c("c", "f") & id %in% c("7", "M7", "m7") &
  !grepl("#", notes) & root_fret <= 12) %>%
  arrange(root, id)
chords <- setNames(chords$fretboard, chords$lp_name)
head(chords)

# requires LilyPond installation
if(tabr_options()$lilypond != ""){
  outfile <- file.path(tempdir(), "out.pdf")
  hdr <- list(
    title = "Dominant 7th, major 7th and minor 7th chords",
    subtitle = "C and F root"
  )
  render_chordchart(chords, outfile, 2, hdr, list(textheight = 175))
}

```

render_music

Render sheet music snippet with LilyPond

Description

Render a sheet music/tablature snippet from a music object with LilyPond.

Usage

```

render_music(
  music,
  file,
  clef = "treble",
  tab = FALSE,
  tuning = "standard",
  string_names = NULL,
  header = NULL,
  paper = NULL,
  midi = FALSE,
  colors = NULL,
  transparent = FALSE,
  res = 150,
  keep_ly = FALSE,
  simplify = TRUE
)

render_music_tc(
  music,

```

```
file,  
header = NULL,  
paper = NULL,  
midi = FALSE,  
colors = NULL,  
transparent = FALSE,  
res = 150,  
keep_ly = FALSE,  
simplify = TRUE  
)
```

```
render_music_bc(  
  music,  
  file,  
  header = NULL,  
  paper = NULL,  
  midi = FALSE,  
  colors = NULL,  
  transparent = FALSE,  
  res = 150,  
  keep_ly = FALSE,  
  simplify = TRUE  
)
```

```
render_music_tab(  
  music,  
  file,  
  clef = NA,  
  tuning = "standard",  
  string_names = NULL,  
  header = NULL,  
  paper = NULL,  
  midi = FALSE,  
  colors = NULL,  
  transparent = FALSE,  
  res = 150,  
  keep_ly = FALSE,  
  simplify = TRUE  
)
```

```
render_music_guitar(  
  music,  
  file,  
  tuning = "standard",  
  string_names = NULL,  
  header = NULL,  
  paper = NULL,  
  midi = FALSE,
```

```

    colors = NULL,
    transparent = FALSE,
    res = 150,
    keep_ly = FALSE,
    simplify = TRUE
)

render_music_bass(
  music,
  file,
  tuning = "bass",
  string_names = NULL,
  header = NULL,
  paper = NULL,
  midi = FALSE,
  colors = NULL,
  transparent = FALSE,
  res = 150,
  keep_ly = FALSE,
  simplify = TRUE
)

```

Arguments

music	a music object.
file	character, output file ending in .pdf or .png.
clef	character, include a music staff with the given clef. NA to suppress. See track for details.
tab	logical, include tablature staff. NA to suppress. See track.
tuning	character, string tuning, only applies to tablature. See track.
string_names	label strings at beginning of tab staff. NULL (default) for non-standard tunings only, TRUE or FALSE for force on or off completely.
header	a named list of arguments passed to the header of the LilyPond file. See lilypond details.
paper	a named list of arguments for the LilyPond file page layout. See lilypond details.
midi	logical, also output an corresponding MIDI file.
colors	a named list of LilyPond element color global overrides. See lilypond for details.
transparent	logical, transparent background, png only.
res	numeric, resolution, png only. transparent = TRUE may fail when res exceeds ~150.
keep_ly	logical, keep the intermediary LilyPond file.
simplify	logical, uses simplify_phrase to convert to simpler, more efficient LilyPond syntax.

Details

These functions allow you to render short, simple snippets of sheet music directly from a music object. This is useful when you do not need to build up from phrases to tracks to a full score. They treat music as a single voice for a single track. This simplifies the possible output but is very convenient when this is all you need.

These functions abstract the following pipeline,

```
music %>% phrase() %>% track() %>% score() %>% render_*()
```

for this simple edge case and directly expose the most relevant arguments.

All header list elements are character strings. The options for header include:

- title
- subtitle
- composer
- album
- arranger
- instrument
- meter
- opus
- piece
- poet
- copyright
- tagline

All paper list elements are numeric except `page_numbers` and `print_first_page_number`, which are logical. `page_numbers = FALSE` suppresses all page numbering. When `page_numbers = TRUE`, you can set `print_first_page_number = FALSE` to suppress printing of only the first page number. `first_page_number` is the number of the first page, defaulting to 1, and determines all subsequent page numbers. These arguments correspond to LilyPond paper block variables.

The options for paper include the following and have the following default values if not provided:

- `textheight = 220`
- `linewidth = 150`
- `indent = 0`
- `fontsize = 20`
- `page_numbers = FALSE`
- `print_first_page_number = TRUE`
- `first_page_number = 1`

`textheight = 150` is the default, but for music snippet rendering, a value must be provided explicitly via `paper` when rendering to png. Otherwise for png outputs the height is cropped automatically rather than remaining a full page. See `lilypond` for details.

Passing arguments to `header` can completely or partially prevent cropping in both direction, which must then be done manually with `linewidth` and `textheight`. This is all based on underlying LilyPond behavior.

If music contains lyrics and there are rests in the note sequence, note-lyric alignment is maintained automatically when these functions remove the lyric timesteps corresponding to the rests prior to sending to LilyPond. LilyPond skips rests when engraving lyrics and expects a shortened lyrics sequence in comparison to how `tabr` matches by timestep including rests. This is in contrast to `track`, for which you have to shorten the lyrics object yourself prior to combining with a phrase object that has rests.

Value

nothing returned; a file is written.

See Also

[plot_music](#), [phrase](#), [track](#), [score](#), [lilypond](#), [tab](#)

Examples

```
x <- "a,4;5*5 b,- c cgc'e'~ cgc'e'1 e'4;2 c';3 g;4 c;5 ce'1;51"
x <- as_music(x)

y <- "a,,4;3*5 b,,- c, c,g,c~ c,g,c1 c4;1 g,,2 c,,3 g,,2 c,c1;31"
y <- as_music(y)

z <- as_music("a,4 b, r c~ c2 d", lyrics = as_lyrics("A2 B2 . C3 . D3"))

## Not run:
if(tabr_options()$lilypond != ""){ # requires LilyPond installation
  outfile <- file.path(tempdir(), "out.pdf")
  render_music(x, outfile)

  outfile <- file.path(tempdir(), "out.png")
  render_music(x, outfile, "treble_8", tab = TRUE)

  render_music_tc(x, outfile)
  render_music_bc(x, outfile)

  render_music_tab(x, outfile)
  render_music_guitar(x, outfile)
  render_music_bass(y, outfile)

  # lyrics example
  render_music_guitar(z, outfile)
}

## End(Not run)
```

repeats *Repeat phrases*

Description

Create a repeat section in LilyPond readable format.

Usage

```
rp(phrase, n = 1)
```

```
pct(phrase, n = 1, counter = FALSE, step = 1, reset = TRUE)
```

```
volta(phrase, n = 1, endings = NULL, silent = FALSE)
```

Arguments

phrase	a phrase object or equivalent string to be repeated.
n	integer, number of repeats of phrase (one less than the total number of plays).
counter	logical, if TRUE, print the percent repeat counter above the staff, applies only to <i>measure</i> repeats of more than two repeats ($n > 2$).
step	integer, print the <i>measure</i> percent repeat counter above the staff only at every step measures when counter = TRUE.
reset	logical, percent repeat counter and step settings are only applied to the single pct call and are reset afterward. If reset = FALSE, the settings are left open to apply to any subsequent percent repeat sections in a track.
endings	a single phrase or a list of phrases, alternate endings.
silent	if TRUE, no text will be printed above the staff at the beginning of a volta section. See details.

Details

These functions wraps a phrase object or a character string in LilyPond repeat syntax. The most basic is `rp` for basic wrapping a LilyPond `unfold` repeat tag around a phrase. This repeats the phrase n times, but it is displayed in the engraved sheet music fully written out as a literal propagation of the phrase with no repeat notation used to reduce redundant presentation. The next is `pct`, which wraps a percent repeat tag around a phrase. This is displayed in sheet music as percent repeat notation whose specific notation changes based on the length of the repeated section of music, used for beats or whole measures. `volta` wraps a phrase in a `volta` repeat tag, used for long repeats of one or more full measures or bars of music, optionally with alternate endings.

Note that basic strings should still be interpretable as a valid musical phrase by LilyPond and such strings will be coerced to the phrase class by these functions. For example, a one-measure rest, "`r1`", does not need to be a phrase object to work with these functions, nor does any other character string explicitly written out in valid LilyPond syntax. As always, see the LilyPond documentation if you are not familiar with LilyPond syntax.

VOLTA REPEAT: When `silent = TRUE` there is no indication of the number of plays above the staff at the start of the volta section. This otherwise happens automatically when the number of repeats is greater than one and no alternate endings are included (which are already numbered). This override creates ambiguity on its own, but is important to use multiple staves are present and another staff already displays the text regarding the number or plays. This prevents printing the same text above every staff.

PERCENT REPEAT: As indicated in the parameter descriptions, the arguments `counter` and `step` only apply to full measures or bars of music. It does not apply to shorter beats that are repeated using `pct`.

Value

a phrase.

See Also

[phrase](#)

Examples

```
x <- phrase("c ec'g' ec'g'", "4 4 2", "5 432 432")
e1 <- phrase("a", 1, 5) # ending 1
e2 <- phrase("b", 1, 5) # ending 2

rp(x) # simple unfolded repeat, one repeat or two plays
rp(x, 3) # three repeats or four plays

pct(x) # one repeat or two plays
pct(x, 9, TRUE, 5) # 10 plays, add counter every 5 steps
pct(x, 9, TRUE, 5, FALSE) # as above, but do not reset counter settings

volta(x) # one repeat or two plays
volta(x, 1, list(e1, e2)) # one repeat with alternate ending
volta(x, 4, list(e1, e2)) # multiple repeats with only one alternate ending
volta(x, 4) # no alternates, more than one repeat
```

rest

Create rests

Description

Create multiple rests efficiently with a simple wrapper around `rep` using the `times` argument.

Usage

```
rest(x, n = 1)
```

Arguments

x integer, duration.
n integer, number of repetitions.

Value

a character string.

Examples

```
rest(c(1, 8), c(1, 4))
```

scale-deg	<i>Scale degrees and mappings</i>
-----------	-----------------------------------

Description

These functions assist with mapping between scale degrees, notes and chords.

Usage

```
scale_degree(
  notes,
  key = "c",
  scale = "diatonic",
  use_root = TRUE,
  strict_accidentals = TRUE,
  naturalize = FALSE,
  roman = FALSE
)

scale_note(deg, key = "c", scale = "diatonic", collapse = FALSE, ...)

note_in_scale(
  notes,
  key = "c",
  scale = "diatonic",
  use_root = TRUE,
  strict_accidentals = TRUE
)

chord_degree(
  notes,
  key = "c",
  scale = "diatonic",
  strict_accidentals = TRUE,
  naturalize = FALSE,
```

```

    roman = FALSE
  )

  is_in_scale(notes, key = "c", scale = "diatonic", strict_accidentals = TRUE)

```

Arguments

notes	character, a string of notes.
key	character, key signature (or root note) for scale, depending on the type of scale.
scale	character, the suffix of a supported scale_* function.
use_root	logical, use lowest pitch in chord. Otherwise yield an NA in output.
strict_accidentals	logical, whether representation must match key and scale. See details.
naturalize	logical, whether to naturalize any sharps or flats before obtaining the scale degree.
roman	logical, return integer scale degrees as Roman numerals.
deg	integer, roman class, or character roman, the scale degree.
collapse	logical, collapse result into a single string ready for phrase construction.
...	additional arguments passed to the scale function, e.g., sharp = FALSE for scale_chromatic.

Details

Obtain the scale degree of a note in a supported scale with `scale_degree`. This function works on any noteworthy string. It ignores octave numbering. Rests and any note not explicitly in the scale return NA. If `deg` is greater than the number of degrees in the scale, it is recycled, e.g., in C major 8 starts over as C.

By default, flats and sharps checked strictly against the scale. Setting `strict_accidentals = FALSE` will convert any flats or sharps present, if necessary based on the combination of key signature and scale. The chromatic scale is a special case where strict accidental is always ignored.

Not any arbitrary combination of valid key and valid scale is valid. For example, `key = "am"` and `scale = "harmonic"` is valid, but not with `key = "a"`.

`note_in_scale` is a wrapper around `scale_degree`. To check if full chords are diatonic to the scale, see [is_diatonic](#).

The inverse of `scale_degree` is `scale_note`, for obtaining the note associated with a scale degree. This could be done simply by calling a `scale_*` function and indexing its output directly, but this wrapper is provided to complement `scale_degree`. Additionally, it accepts the common Roman numeral input for the degree. This can be with the roman class or as a character string. Degrees return NA if outside the scale degree range.

Value

integer, or roman class if `roman = TRUE` for `scale_degree`. character for `scale_note`.

See Also

[scale-helpers](#), [is_diatonic](#)

Examples

```

scale_degree("r c, e3 g~ g s g# ceg")
note_in_scale("r c, e3 g~ g s g# ceg")

scale_degree("c e g", roman = TRUE)

scale_degree("c c# d_ e", key = "d")
scale_degree("c c# d_ e", key = "d", strict_accidentals = FALSE)

scale_degree("c, e_3 g' f#ac#", use_root = FALSE)
scale_degree("c, e_3 g' f#ac#", naturalize = TRUE) # lowest chord pitch: c#

scale_degree("c# d_ e' e4 f f# g", key = "c#", scale = "chromatic")

scale_note(1:3, key = "am")
scale_note(c(1, 3, 8), "d", collapse = TRUE)
all(sapply(list(4, "IV", as.roman(4)), scale_note) == "f")

x <- "d dfa df#a f#ac#"
chord_degree(x, "d")
is_in_scale(x, "d")

```

scale-helpers

Scale helpers

Description

Helper functions for working with musical scales.

Usage

```

scale_diatonic(key = "c", collapse = FALSE, ignore_octave = FALSE)

scale_major(key = "c", collapse = FALSE, ignore_octave = FALSE)

scale_minor(key = "am", collapse = FALSE, ignore_octave = FALSE)

scale_harmonic_minor(key = "am", collapse = FALSE, ignore_octave = FALSE)

scale_hungarian_minor(key = "am", collapse = FALSE, ignore_octave = FALSE)

scale_melodic_minor(
  key = "am",
  descending = FALSE,
  collapse = FALSE,
  ignore_octave = FALSE
)

```

```

scale_jazz_minor(key = "am", collapse = FALSE, ignore_octave = FALSE)

scale_chromatic(
  root = "c",
  collapse = FALSE,
  sharp = TRUE,
  ignore_octave = FALSE
)

```

Arguments

key	character, key signature.
collapse	logical, collapse result into a single string ready for phrase construction.
ignore_octave	logical, strip octave numbering from scales not rooted on C.
descending	logical, return the descending scale, available as a built-in argument for the melodic minor scale, which is different in each direction.
root	character, root note.
sharp	logical, accidentals in arbitrary scale output should be sharp rather than flat.

Details

For valid key signatures, see [keys](#).

Value

character

See Also

[keys](#), [mode-helpers](#)

Examples

```

scale_diatonic(key = "dm")
scale_minor(key = "dm")
scale_major(key = "d")

scale_chromatic(root = "a")

scale_harmonic_minor("am")
scale_hungarian_minor("am")

identical(scale_melodic_minor("am"), scale_jazz_minor("am"))
rev(scale_melodic_minor("am", descending = TRUE))
scale_jazz_minor("am")

```

scale_chords	<i>Diatonic chords</i>
--------------	------------------------

Description

Obtain an ordered sequence of the diatonic chords for a given scale, as triads or sevenths.

Usage

```
scale_chords(  
  root = "c",  
  scale = "major",  
  type = c("triad", "seventh"),  
  collapse = FALSE  
)
```

Arguments

root	character, root note or starting position of scale.
scale	character, a valid named scale, referring to one of the existing scale_* functions.
type	character, type of chord, triad or seventh.
collapse	logical, collapse result into a single string ready for phrase construction.

Value

character

Examples

```
scale_chords("c", "major")  
scale_chords("a", "minor")  
scale_chords("a", "harmonic minor")  
scale_chords("a", "melodic minor")  
scale_chords("a", "jazz minor")  
scale_chords("a", "hungarian minor")  
  
scale_chords("c", "major", "seventh", collapse = TRUE)  
scale_chords("a", "minor", "seventh", collapse = TRUE)
```

score	<i>Create a music score</i>
-------	-----------------------------

Description

Create a music score from a collection of tracks.

Usage

```
score(track, chords = NULL, chord_seq = NULL)
```

Arguments

track	a track table consisting of one or more tracks.
chords	an optional named list of chords and respective fingerings generated by <code>chord_set</code> , for inclusion of a top center chord diagram chart.
chord_seq	an optional named vector of chords and their durations, for placing chord diagrams above staves in time.

Details

Score takes track tables generated by `track` and fortifies them as a music score. It optionally binds tracks with a set of chord diagrams. There may be only one track in `track` as well as no chord information passed, but for consistency `score` is still required to fortify the single track as a score object that can be rendered by `tab`.

Value

a tibble data frame

See Also

[phrase](#), [track](#), [trackbind](#)

Examples

```
x <- phrase("c ec'g' ec'g'", "4 4 2", "5 432 432")
x <- track(x)
score(x)
```

sf_phrase

*Create a musical phrase from string/fret combinations***Description**

Create a musical phrase from character strings that define string numbers, fret numbers and note metadata. This function is a wrapper around `phrase`. It allows for specifying string/fret combinations instead of unambiguous pitch as is used by `phrase`. In order to remove ambiguity, it is critical to specify the instrument string tuning and key signature. It essentially uses `string` and `fret` in combination with a known tuning and key signature to generate notes for `phrase`. `info` is passed straight through to `phrase`, as is `string` once it is done being used to help derive notes.

Usage

```
sf_phrase(
  string,
  fret = NULL,
  info = NULL,
  key = "c",
  tuning = "standard",
  to_notes = FALSE,
  bar = NULL
)
```

```
sfp(
  string,
  fret = NULL,
  info = NULL,
  key = "c",
  tuning = "standard",
  to_notes = FALSE,
  bar = NULL
)
```

```
sf_note(...)
```

```
sfn(...)
```

Arguments

<code>string</code>	character, space-delimited or vector. String numbers associated with notes. Alternatively, provide all information here in a single space-delimited string and ignore <code>fret</code> and <code>info</code> . See details.
<code>fret</code>	character, space-delimited or vector (or integer vector) of fret numbers associated with notes. Same number of timesteps as <code>string</code> .
<code>info</code>	character, space-delimited or vector (or integer vector if simple durations) giving metadata associated with notes. Same number of timesteps as <code>string</code> .

key	character, key signature or just specify "sharp" or "flat".
tuning	character, instrument tuning.
to_notes	logical, return only the mapped notes character string rather than the entire phrase object.
bar	character or NULL (default). Terminates the phrase with a bar or bar check. See details for phrase . Also see the LilyPond help documentation on bar notation for all the valid options.
...	arguments passed to sf_phrase.

Details

See the main function `phrase` for general details on phrase construction.

Value

a phrase.

Comparison with `phrase`

This function is a wrapper function for users not working with musical notes (what to play), but rather just position on the guitar neck (where to play). This approach has conveniences, but is more limiting. In order to remove ambiguity, it is necessary to specify the instrument tuning and the key signature.

In the standard approach with `phrase` you specify what to play; specifying exactly where to play is optional, but highly recommended (by providing `string`). With `sf_phrase`, the `string` argument is of course required along with `fret`. But any time the tuning changes, this "where to play" method breaks down and must be redone. It is more robust to provide the string and pitch rather than the string and fret. The key is additionally important because it is the only way to indicate if accidentals should be notated as sharps or flats.

This wrapper also increases redundancy and typing. In order to specify rests `r`, silent rests `s`, and tied notes `~`, these must now be providing in parallel in both the `string` and `fret` arguments, whereas in the standard method using `phrase`, they need only be provided once to notes. A mismatch will throw an error. Despite the redundancy, this is helpful for ensuring proper match up between `string` and `fret`, which is essentially a dual entry method that aims to reduce itself inside `sf_phrase` to a single notes string that is passed internally to `phrase`.

The important thing to keep in mind is that by its nature, this method of writing out music does not lend itself well to high detail. Tabs that are informed by nothing but string and fret number remove a lot of important information, and those that attempt to compensate with additional symbols in say, an ascii tab, are difficult to read. This wrapper function providing this alternative input method to `phrase` does its job of allowing users to create phrase objects that are equivalent to standard `phrase`-generated objects, including rests and ties. But practice and comfort working with `phrase` is highly recommended for greater control of development support.

The function `sfp` is a convenient shorthand wrapper for `sf_phrase`. `sf_note` and the alias `sfn` are wrappers around `sf_phrase` that force `to_notes = TRUE`.

Single-string input

Another way to use `sf_phrase` is to provide all musical input to `string` and ignore `fret` and `info` as explicit arguments. Providing all three explicit arguments more closely mimics the inputs of `phrase` and is useful when you have this information as three independent sources. However, in some cases the single-argument input method can reduce typing, though this depends on the phrase. More importantly, it allow you to reason about your musical inputs by time step rather than by argument. If you provide all three components as a single character string to the `string` argument, leaving both `fret` and `info` as `NULL`, then `sf_phrase` will decompose `string` into its three component parts internally.

There are some rules for single-argument input. The three components are separated by semicolons as "`string;fret;info`". For example, "`3;7x7;4`" means begin on the third string (infer higher number strings muted). The frets are 7th and 7th, meaning two notes are played. When an `x` is present in the second entry it means a string is not played. This is how it is inferred that the string numbers starting from the third string are strings 3 and 1 rather than 3 and 2 in this example. The 4 indicates a quarter note since it is part of the third entry where the additional `info` is specified. This is contextual. For example, an `x` here would still indicate a dead note, rather than an unplayed string in the second entry, so this is contextual.

A bonus when using this input method is that explicit `string` and `info` values persist from one timestep to the next. Neither needs to be provided again until there is a change in value. For example, "`3;7x7;4 7x7 ;7x7;1`" repeats the `string` and `info` values from timestep one for timestep two. In timestep three, `string` numbers repeat again, but the duration changes from quarter note to whole note.

Note that except when both `string` and `info` are repeating and only `fret` numbers are provided (see timestep two above), two semicolons must be present so that it is unambiguous whether the sole missing component is a `string` or `info` (see timestep three).

Ambiguity would arise from a case like "`4;4`" without the second semicolon. This type of indexing was chosen over using two different delimiters.

If a rest, `r` or `s`, is provided for the `fret` entry, then the `string` entry is ignored. When using this input method, ties `~` are given in the `info` entry.

See the examples for a comparison of two identical phrases specified using both input methods for `sf_phrase`.

See Also

[phrase](#)

Examples

```
sf_phrase("5 4 3 2 1", "1 3 3 3 1", "8*4 1", key = "b_")
sf_phrase("6 6 12 1 21", "133211 355333 11 (13) (13)(13)", "4 4 8 8 4",
  key = "f")
sfp("6*2 1*4", "000232*2 2*4", "4 4 8*4", tuning = "dropD", key = "d")

# compare with single-argument input
s <- "3*5 53~*3 543*2 643"
f <- "987*2 775 553 335 77~*3 545 325 210"
i <- "2*3 4. 16 4.*3 4*3"
```

```
p1 <- sfp(s, f, i)

# Nominally shorter syntax, but potentially much easier to reason about
p2 <- sfp("3;987;2*2 775 ;553;4. ;335;16 5;7x7;4.~*3 ;545;4 325 6;2x10;")

identical(p1, p2)
```

simplify_phrase	<i>Simplify the LilyPond syntax of a phrase</i>
-----------------	---

Description

This function can be used to simplify the LilyPond syntax of a phrase. Not intended for direct use. See details.

Usage

```
simplify_phrase(phrase)
```

Arguments

phrase a phrase object.

Details

This function not intended to be used directly, but is available so that you can see how LilyPond syntax for phrases will be transformed by default in the process of creating a LilyPond file. This function is used by the `lilypond` function and associated `render_*` functions. When using `lilypond` directly, this can be controlled by the `simplify` argument.

The result of this function is a character string containing simpler, more efficient LilyPond syntax. It can be coerced back to a phrase with `as_phrase`, but its print method colors will no longer display properly. More importantly, this simplification removes any possibility of transforming the phrase back to its original inputs. The more complex but nicely structured original representation does a better job at maintaining reasonable possibility of one to one transformation between a phrase object and the inputs that it was built from.

Value

character

Examples

```
notes <- "a~ a b c' c'e'g'~ c'e'g'"
info <- "8.. 8..-. 8- 8-^ 4.^ 4."
(x <- p(notes, info))
as_phrase(simplify_phrase(x))

(x <- p(notes, info, 5))
as_phrase(simplify_phrase(x))
```

single-bracket

Single bracket methods for tabr classes

Description

Single bracket indexing and assignment. See [tabr-methods](#) for more details on methods for tabr classes.

Usage

```
## S3 method for class 'noteworthy'  
x[i]  
  
## S3 method for class 'noteinfo'  
x[i]  
  
## S3 method for class 'music'  
x[i]  
  
## S3 method for class 'lyrics'  
x[i]  
  
## S3 replacement method for class 'noteworthy'  
x[i] <- value  
  
## S3 replacement method for class 'noteinfo'  
x[i] <- value  
  
## S3 replacement method for class 'music'  
x[i] <- value  
  
## S3 replacement method for class 'lyrics'  
x[i] <- value
```

Arguments

x	object.
i	index.
value	values to assign at index.

See Also

[tabr-methods](#), [note-metadata](#)

Examples

```

# noteworthy class examples
x <- as_noteworthy("a, b, c ce_g d4f#4a4")
x[3:4]
x[-2]
x[2] <- paste0(transpose(x[2], 1), "~")
x

# noteinfo class examples
x <- as_noteinfo(c("4-", "t8(", "t8)", "t8x", "8^", "16"))
x[2:4]
x[-1]
x[5:6] <- c("16^", "8")
x
x[x == "4-"]

# music class examples
x <- as_music("c,~4 c,1 c'e_'g'4-.*4")
x[1:3]
x[-c(1:2)]
x[3:6] <- "c'e'g'8"
x

```

string_unfold

Fold and unfold strings

Description

Fold or unfold a string on the expansion operator.

Usage

```
string_unfold(x)
```

```
string_fold(x, n = 3)
```

Arguments

x	character string, should be valid notes or note info such as beats.
n	integer, minimum number of consecutive repeated values to warrant folding, defaults to 3.

Details

These function work on arbitrary stings. They do not perform a noteworthy check. This allows them to work for info strings as well. Make sure your strings are properly formatted. `string_fold` always collapses the output string as space-delimited.

Value

character

Examples

```
time <- "8*3 16 4.. 16 16 2 2 4. 8 4 4 8*4 1"
x <- string_unfold(time)
x
string_fold(x) == time

notes <- "a, b, c d e f g# a r ac'e' a c' e' c' r r r a"
x <- string_fold(notes)
x
string_unfold(x) == notes
```

 tab

Render sheet music with LilyPond

Description

Render sheet music/tablatore from a music score with LilyPond.

Usage

```
tab(
  score,
  file,
  key = "c",
  time = "4/4",
  tempo = "2 = 60",
  header = NULL,
  paper = NULL,
  string_names = NULL,
  endbar = "|.",
  midi = TRUE,
  colors = NULL,
  crop_png = TRUE,
  transparent = FALSE,
  res = 150,
  keep_ly = FALSE,
  simplify = TRUE,
  details = FALSE
)

render_tab(
  score,
  file,
```

```

    key = "c",
    time = "4/4",
    tempo = "2 = 60",
    header = NULL,
    paper = NULL,
    string_names = NULL,
    endbar = "|.",
    midi = TRUE,
    colors = NULL,
    crop_png = TRUE,
    transparent = FALSE,
    res = 150,
    keep_ly = FALSE,
    simplify = TRUE,
    details = FALSE
)

render_score(
  score,
  file,
  key = "c",
  time = "4/4",
  tempo = "2 = 60",
  header = NULL,
  paper = NULL,
  endbar = "|.",
  colors = NULL,
  crop_png = TRUE,
  transparent = FALSE,
  res = 150,
  keep_ly = FALSE,
  simplify = TRUE,
  details = FALSE
)

render_midi(score, file, key = "c", time = "4/4", tempo = "2 = 60")

```

Arguments

score	a score object.
file	character, output file ending in .pdf or .png for sheet music or tablature for score. May include an absolute or relative path. For render_midi, a file ending in .mid.
key	character, key signature, e.g., c, b_, f#m, etc.
time	character, defaults to "4/4".
tempo	character, defaults to "2 = 60". Set to NULL to suppress display of the time signature in the output.

header	a named list of arguments passed to the header of the LilyPond file. See <code>lilypond</code> for details.
paper	a named list of arguments for the LilyPond file page layout. See <code>lilypond</code> for details.
string_names	label strings at beginning of tab staff. NULL (default) for non-standard tunings only, TRUE or FALSE for force on or off completely.
endbar	character, the global end bar.
midi	logical, output midi file in addition to sheet music.
colors	a named list of LilyPond element color overrides. See <code>lilypond</code> for details.
crop_png	logical, see <code>lilypond</code> for details.
transparent	logical, transparent background, png only.
res	numeric, resolution, png only. <code>transparent = TRUE</code> may fail when <code>res</code> exceeds ~150.
keep_ly	logical, keep the intermediary LilyPond file.
simplify	logical, uses <code>simplify_phrase</code> to convert to simpler, more efficient LilyPond syntax for the LilyPond file before rendering it.
details	logical, set to TRUE to print LilyPond log output to console. Windows only.

Details

Generate a pdf or png of a music score using the LilyPond music engraving program. Output format is inferred from file extension. This function is a wrapper around `lilypond`, the function that creates the LilyPond (.ly) file.

`render_score` renders score to pdf or png. `render_midi` renders a MIDI file based on score. This is still done via LilyPond. The sheet music is created automatically in the process behind the scenes but is deleted and only the MIDI output is retained.

The original `tab` or `render_tab` (equivalent) produces both the sheet music and the MIDI file output by default and includes other arguments such as the tablature-relevant argument `string_names`. This is the all-purpose function. Also use this when you intend to create both a sheet music document and a MIDI file.

Remember that whether a track contains a tablature staff, standard music staff, or both, is defined in each individual track object contained in `score`. It is the contents you have assembled in `score` that dictate what render function you should use. `render_tab` is general and always works, but `render_score` would not be the best choice when a tablature staff is present unless you accept the default string naming convention.

`render_midi` is different from `midily` and `miditab`, whose purpose is to create sheet music from an existing MIDI file using a LilyPond command line utility.

For Windows users, add the path to the LilyPond executable to the system path variable. For example, if the file is at `C:/Program Files (x86)/LilyPond/usr/bin/lilypond.exe`, then add `C:/Program Files (x86)/LilyPond/usr/bin` to the system path.

Value

nothing returned; a file is written.

See Also

[lilypond](#), [render_chordchart](#), [miditab](#)

Examples

```
if(tabr_options()$lilypond != ""){
  x <- phrase("c ec'g' ec'g'", "4 4 2", "5 432 432")
  x <- track(x)
  x <- score(x)
  outfile <- file.path(tempdir(), "out.pdf")
  tab(x, outfile) # requires LilyPond installation
}
```

 tabr

tabr: Music notation syntax, manipulation, analysis and transcription in R.

Description

The `tabr` package provides a music notation syntax and a collection of music programming functions for generating, manipulating, organizing and analyzing musical information in R.

Details

The music notation framework facilitates creating and analyzing music data in notation form. Music data can be viewed, manipulated and analyzed while in different forms of representation based around different data structures: strings and data frames. Each representation offers advantages over the other for different use cases. Music syntax can be entered directly and represented in character strings to minimize the formatting overhead of data entry by using simple data structures, for example when wanting to quickly enter and transcribe short pieces of music to sheet music or tablature. The package contains functions for directly performing various mathematical, logical and organizational operations and musical transformations on special object classes that facilitate working with music data and notation. The same music data can also be organized in tidy data frames, allowing for a more familiar and powerful approach to the analysis of large amounts of structured music data. Functions are available for mapping seamlessly between these data structures and their representations of musical information. The package also provides API wrapper functions for transcribing musical representations in R into guitar tablature ("tabs") and basic sheet music using the LilyPond backend <<http://lilypond.org>>.

LilyPond is an open source music engraving program for generating high quality sheet music based on markup syntax. The package generates LilyPond files from R code and can pass them to LilyPond to be rendered into sheet music pdf files.

While LilyPond caters to sheet music in general and `tabr` can be used to create basic sheet music, the transcription functions focus on leveraging LilyPond specifically for creating quality guitar tablature.

The package offers nominal MIDI file output support in conjunction with rendering sheet music. The package can read MIDI files and attempts to structure the MIDI data to integrate as best as possible with the data structures and functionality found throughout the package.

tabr offers a useful but limited LilyPond API and is not intended to access all LilyPond functionality from R, nor is transcription via the API the entire scope of tabr. If you are only creating sheet music on a case by case basis, write your own LilyPond files manually. There is no need to use tabr or limit yourself to its existing LilyPond API. If you are generating music notation programmatically, tabr provides the ability to do so in R and has the added benefit of converting what you write in R code to the LilyPond file format to be rendered as printable guitar tablature.

While LilyPond is listed as a system requirement for tabr, you can use the package for music analysis without installing LilyPond if you do not intend to render tabs.

tabr-c

Concatenate for tabr classes

Description

Several methods are implemented for the classes `noteworthy`, `noteinfo`, and `music`. See [tabr-methods](#) for more details on methods for tabr classes.

Usage

```
## S3 method for class 'noteworthy'
c(...)

## S3 method for class 'noteinfo'
c(...)

## S3 method for class 'music'
c(...)

## S3 method for class 'lyrics'
c(...)

## S3 method for class 'phrase'
c(...)
```

Arguments

... objects.

See Also

[tabr-methods](#), [note-metadata](#)

Examples

```

# noteworthy class examples
x <- "a b c"
c(x, x)
c(as_noteworthy(x), x)

# noteinfo class examples
x <- "4- t8( t8)( t8) 4*2"
c(as_noteinfo(x), x)

# music class examples
x <- "c,~4 c,1 c'e_'g'4-.*2"
c(as_music(x), x)

# phrase class examples
c(phrase(x), x)

```

tabr-head

Head and tail for tabr classes

Description

Several methods are implemented for the classes noteworthy, noteinfo, and music. See [tabr-methods](#) for more details on methods for tabr classes.

Usage

```

## S3 method for class 'noteworthy'
head(x, ...)

## S3 method for class 'noteinfo'
head(x, ...)

## S3 method for class 'music'
head(x, ...)

## S3 method for class 'lyrics'
head(x, ...)

## S3 method for class 'noteworthy'
tail(x, ...)

## S3 method for class 'noteinfo'
tail(x, ...)

## S3 method for class 'music'
tail(x, ...)

```

```
## S3 method for class 'lyrics'
tail(x, ...)
```

Arguments

`x` object.
`...` number of elements to return.

See Also

[tabr-methods](#), [note-metadata](#)

Examples

```
# noteworthy class examples
x <- "a b c d e f g"
head(x, 2)
head(as_noteworthy(x), 2)
tail(as_noteworthy(x), 2)

# noteinfo class examples
x <- "4x 4-.*8 2 4"
head(as_noteinfo(x))
tail(as_noteinfo(x))

# music class examples
x <- "c,~4 c,1 c'e_'g'4-."
head(as_music(x), 2)
tail(as_music(x), 2)
```

tabr-length

Length for tabr classes

Description

Several methods are implemented for the classes `noteworthy`, `noteinfo`, and `music`. See [tabr-methods](#) for more details on methods for `tabr` classes.

Usage

```
## S3 method for class 'noteworthy'
length(x)

## S3 method for class 'noteinfo'
length(x)

## S3 method for class 'music'
length(x)
```

```
## S3 method for class 'lyrics'
length(x)
```

Arguments

x object.

See Also

[tabr-methods](#), [note-metadata](#)

Examples

```
# noteworthy class examples
x <- "a b c"
length(x)
length(as_noteworthy(x))
length(as_noteworthy("a b*2 c*2"))

# noteinfo class examples
x <- "4- t8( t8)( t8) 4*2"
length(x)
length(as_noteinfo(x))

# music class examples
x <- "c,~4 c,1 c'e_'g'4-. *4"
length(x)
length(as_music(x))
```

tabr-methods

Summary of implemented S3 generic methods

Description

Several methods are implemented for the classes noteworthy, noteinfo, music and lyrics. See further below for details on limited implementations for the phrase class.

Arguments

x object.
i index.
value values to assign at index.
... additional arguments.

Details

In addition to custom print and summary methods, the following methods have been implemented for all four classes: [, [<-, [[, [[<-, length, c, rep, rev, head and tail. Logical operators are also implemented for noteworthy strings.

Methods length and c

The implementation of `length` is equivalent to `n_steps`. They access the same attribute, returning the number of timesteps in the object. This gives the same result even when the underlying string is in space-delimited format. To obtain the character string length, coerce with `as.character` or any other function that would have the same effect.

The implementation of `c` for these classes is strict and favors the object class in question. This is different from how `c` might normally behave, coercing objects of different types such as numeric and character to character.

For these four classes, `c` is strict in that it will return an error if attempting to concatenate one of these classes with any other class besides character. This includes each other. While it would be possible to coerce a music object down to a noteworthy object or a noteinfo object, this is the opposite of the aggressive coercion these classes are intended to have with `c` so this is not done.

While other classes such as numeric immediately return an error, any concatenation with character strings attempts to coerce each character string present to the given class. If coercion fails for any character class object, the usual error is returned concerning invalid notes or note info present. If coercion succeeds for all character strings, the result of `c` is to concatenate the timesteps of all objects passed to it. The output is a new noteworthy, noteinfo or music object.

Methods rep rev head and tail

The `rep` function is similar to `c` except that it never has to consider other classes. You could pass a vector of objects to `rep`, but doing so with `c` will already have resolved all objects to the single class. Again, what matters is not the underlying length or elements in the character vector the class is built upon, but the timesteps. `rep` will extend `x` in terms of timesteps. You can also provide the `each` or `times` arguments.

`rev`, `head` and `tail` work similarly, based on the sequence of timesteps, not the character vector length.

Remember that this accounts not only for vectors of length one that contain multiple timesteps in space-delimited time format, but also that multiple timesteps can be condensed even in space-delimited time format with the `*` expansion operator. For example, `"a"*4 b"*2"` has six timesteps in this form as well as in vector form. The object length is neither one nor two. All of these generic method implementations work in this manner.

Square brackets

Single and double bracket subsetting by index work similarly to what occurs with lists. Single bracket subsetting returns the same object, but only containing the indexed timesteps. Double bracket subsetting only operates on a single timestep and extracts the character string value.

For assignment, single and double brackets change the value at timesteps and return the same object, but again double brackets only allow indexing a single timestep. Double bracket indexing is mostly useful for combining the steps of extracting a single value and discarding the special class in one command.

Limited phrase implementations

Methods implemented for the phrase are limited to `c` and `rep`. Due to the complex LilyPond syntax, applying most of the functions above directly to phrases is problematic. `c` is implemented like it

is for the other classes. `rep` is restricted in that it can only repeat the entire phrase sequence, not the timesteps within. However, you can convert a phrase class back to `noteworthy` and `noteinfo` objects (under reasonable conditions). See [notify](#).

One exception made for phrase with respect to concatenation is that an attempt to concatenate any combination of phrase and music objects, in any order, results in coercion to a new phrase. This happens even in a case where the first object in the sequence is a music object (thus calling `c.music` rather than `c.phrase`). It will subsequently fall back to `c.phrase` in that case.

See Also

[note-logic](#), [note-metadata](#)

Examples

```
# noteworthy class examples
x <- as_noteworthy("a, b, c ce_g d4f#4a4")
x
x[3:4]
x[-2]
x[2] <- paste0(transpose(x[2], 1), "~")
x
length(x) # equal to number of timesteps
c(x, x)
tail(rep(x, times = c(1, 2, 1, 3, 1)))

# noteinfo class examples
x <- as_noteinfo(c("4-", "t8(", "t8)", "t8x", "8^", "16"))
x
x[2:4]
x[-1]
x[5:6] <- c("16^", "8")
x
x[x == "4-"]
c(x[1], x[2]) == c(x[1:2])
head(rep(x, each = 2))

# music class examples
x <- as_music("c,~4 c,1 c'e_'g'4-.*4")
x
x[1:3]
x[-c(1:2)]
x[3:6] <- "c'e'g'8"
x
c(x[1], x[1]) == x[c(1, 1)]
rev(x)

x[[3]]
x[[3]] <- "b_t8"
x
```

 tabr-rep

Repeat for tabr classes

Description

Several methods are implemented for the classes `noteworthy`, `noteinfo`, and `music`. See [tabr-methods](#) for more details on methods for tabr classes.

Usage

```
## S3 method for class 'noteworthy'
rep(x, ...)

## S3 method for class 'noteinfo'
rep(x, ...)

## S3 method for class 'music'
rep(x, ...)

## S3 method for class 'lyrics'
rep(x, ...)

## S3 method for class 'phrase'
rep(x, ...)
```

Arguments

`x` object.
`...` additional arguments. Not accepted for phrase objects.

See Also

[tabr-methods](#), [note-metadata](#)

Examples

```
# noteworthy class examples
x <- "a b c"
rep(x, 2)
rep(as_noteworthy(x), 2)

# noteinfo class examples
x <- "4x 4-.*2 2"
rep(as_noteinfo(x), times = c(2, 1, 1, 2))

# music class examples
x <- "c,~4 c,1 c'e_'g'4-."
rep(as_music(x), each = 2)
```



```
# phrase class examples
rep(phrase(x), 2)
```

tabr-rev	<i>Reverse for tabr classes</i>
----------	---------------------------------

Description

Several methods are implemented for the classes `noteworthy`, `noteinfo`, and `music`. See [tabr-methods](#) for more details on methods for tabr classes.

Usage

```
## S3 method for class 'noteworthy'
rev(x)

## S3 method for class 'noteinfo'
rev(x)

## S3 method for class 'music'
rev(x)

## S3 method for class 'lyrics'
rev(x)
```

Arguments

x object.

See Also

[tabr-methods](#), [note-metadata](#)

Examples

```
# noteworthy class examples
x <- "a b c"
rev(x)
rev(as_noteworthy(x))

# noteinfo class examples
x <- "4x 4-. *2 2"
rev(as_noteinfo(x))

# music class examples
x <- "c,~4 c,1 c'e_'g'4-."
rev(as_music(x))
```

tabrSyntax	<i>tabr syntax</i>
------------	--------------------

Description

A data frame containing descriptions of syntax used in phrase construction in tabr.

Usage

```
tabrSyntax
```

Format

A data frame with 3 columns for syntax description, operators and examples.

tabr_options	<i>Options</i>
--------------	----------------

Description

Options for tabr package.

Usage

```
tabr_options(...)
```

Arguments

... a list of options.

Details

Currently only lilypond, midi2ly and python are used. On Windows systems, if the system path for lilypond.exe, midi2ly and python.exe are not stored in the system PATH environmental variable, they must be provided by the user after loading the package.

Value

The function prints all set options if called with no arguments. When setting options, nothing is returned.

Examples

```
tabr_options()
lilypond_path <- "C:/Program Files (x86)/LilyPond/usr/bin/lilypond.exe"
tabr_options(lilypond = lilypond_path)
```

tie	<i>Tied notes</i>
-----	-------------------

Description

Tie notes efficiently.

Usage

```
tie(x)
```

```
untie(x)
```

Arguments

x character, a single chord.

Details

This function is useful for bar chords.

Value

a character string.

Examples

```
tie("e,b,egbe'")
```

to_tabr	<i>Music notation syntax converters</i>
---------	---

Description

Convert alternative representations of music notation to tabr syntax.

Usage

```
to_tabr(id, ...)
```

```
from_chorrrds(x, key = "c", guitar = FALSE, gc_args = list())
```

```
from_music21(x, accidentals = c("flat", "sharp"), output = c("music", "list"))
```

Arguments

id	character, suffix of from_* function, e.g., "chorrds"
...	arguments passed to the function matched by id.
x	character, general syntax input. See details and examples for how inputs are structured for each converter.
key	key signature, used to enforce consistent use of flats or sharps.
guitar	logical, attempt to match input chords to known guitar chords in guitarChords . Otherwise by default standard piano chords of consecutive pitches covering minimum pitch range are returned.
gc_args	named list of additional arguments passed to gc_info , used when guitar = TRUE.
accidentals	character, represent accidentals, "flat" or "sharp".
output	character, type of output when multiple options are available.

Details

These functions convert music notation from other data sources into the style used by `tabr` for music analysis and sheet music transcription.

Value

noteworthy string for `chorrds`; music string or list for `music21`.

Syntax converter for `chorrds`

The input `x` is a character vector of chords output from the `chorrds` package, as shown in the examples. Output is a noteworthy string object.

Some sources do not offer as complete or explicit information in order to make sheet music. However, what is available in those formats is converted to the extent possible and available function arguments can allow the user to add some additional specification. Different input syntax makes use of a different syntax converter. Depending on the format, different arguments may be available and/or required. The general wrapper function for all of the available syntax converters is `to_tabr`. This function takes an `id` argument for the appropriate converter function. See examples.

For example, output from the `chorrds` package that scrapes chord information from the Cifraclub website only provides chords, not note for note transcription data for any particular instrument. This means the result of syntax conversion still yields only chords, which is fine for data analysis but doesn't add anything useful for sheet music transcription.

The input in this case also does not specify distinct pitches by assigning octaves numbers to a chord's notes, not even the root note. It remains up to the user if they want to apply the information. By default, every chord starts in octave three. It is also ambiguous how the chord is played since all that is provided is a generic chord symbol. By default a standard chord is constructed if it can be determined.

Setting `guitar = TRUE` switches to using the [guitarChords](#) dataset to find matching guitar chords using [gc_info](#), which can be provided additional arguments in a named list to `gc_args`. For guitar, this allows some additional control over the actual structure of the chord, its shape and position on

the guitar neck. The options will never work perfectly for all chords in chords, but at a minimum, typical default component pitches will be determined and returned in tabr notation style.

Syntax converter for music21

The input `x` is a character vector of in music21 tiny notation syntax, as shown in the examples. Default output is a music object. Setting `output = "list"` returns a list of three elements: a noteworthy string, a note info string, and the time signature.

The recommendation for music21 syntax is to keep it simple. Do not use the letter `n` for explicit natural notes. Do not add text annotations such as lyrics. Double flats and sharps are not supported. The examples demonstrate what is currently supported.

Examples

```
# chorrrds package output
chords <- c("Bb", "Bbm", "Bbm7", "Bbm7(b5)", "Bb7(#5)/G", "Bb7(#5)/Ab")
from_chorrrds(chords)
to_tabr(id = "chorrrds", x = chords)

from_chorrrds(chords, guitar = TRUE)
to_tabr(id = "chorrrds", x = chords, guitar = TRUE)

# music21 tiny notation
x <- "4/4 CC#FF4.. trip{c#8eg# d'- e-' f g a'} D4~# D E F r B16"
from_music21(x)

from_music21(x, accidentals = "sharp")

from_music21(x, output = "list")
```

track

Create a music track

Description

Create a music track from a collection of musical phrases.

Usage

```
track(
  phrase,
  clef = "treble_8",
  key = NA,
  tab = TRUE,
  tuning = "standard",
  voice = 1,
  lyrics = NA
)
```

```

track_guitar(
  phrase,
  clef = "treble_8",
  key = NA,
  tab = TRUE,
  tuning = "standard",
  voice = 1,
  lyrics = NA
)

track_tc(phrase, key = NA, voice = 1, lyrics = NA)

track_bc(phrase, key = NA, voice = 1, lyrics = NA)

track_bass(phrase, key = NA, voice = 1, lyrics = NA)

```

Arguments

phrase	a phrase object.
clef	character, include a music staff with the given clef. NA to suppress. See details.
key	character, key signature for music staff. See details.
tab	logical, include tablature staff. NA to suppress.
tuning	character, pitches describing the instrument string tuning or a predefined tuning ID (see tunings). Defaults to standard guitar tuning; not relevant if tablature staff is suppressed.
voice	integer, ID indicating the unique voice phrase belongs to within a single track (another track may share the same tab/music staff but have a different voice ID). Up to two voices are supported per track.
lyrics	a lyrics object or NA. See details.

Details

Musical phrases generated by [phrase](#) are fortified in a track table. All tracks are stored as track tables, one per row, even if that table consists of a single track. `track` creates a single-entry track table. See [trackbind](#) for merging single tracks into a multi-track table. This is row binding that also properly preserves phrase and track classes.

There are various `track_*` functions offering sensible defaults based on the function suffix. The original `track` function is equivalent to `track_guitar`. See examples. Setting `clef = NA` or `tab = NA` suppresses the music staff or tablature staff, respectively. By default `key = NA`, in which case it inherits the global key from the key argument of various sheet music rendering functions. If planning to bind two tracks as one where they are given `voice = 1` and `voice = 2`, respectively, they must also have a common key, even if `key = NA`.

`lyrics` should only be used for simple tracks that do not contain repeats. You also need to ensure the timesteps for lyrics align with those of `phrase` in advance. Additionally, LilyPond does not engrave lyrics at rests or tied notes (excluding first note in tied sequence) so if Therefore, if `phrase`

contains rests and tied notes then the lyrics object should be subset to exclude these timesteps as well. This is in contrast to using `render_music*` functions, which handle this automatically for music objects.

Value

a tibble data frame

See Also

[phrase](#), [score](#)

Examples

```
x <- phrase("c ec'g' ec'g'", "4 4 2", "5 4 4")
track(x) # same as track_guitar(x); 8va treble clef above tab staff
track_tc(x) # treble clef sheet music, no tab staff
track_bc(x) # bass clef sheet music, no tab staff

x <- phrase("c, g,c g,c", "4 4 2", "3 2 2")
track_bass(x) # includes tab staff and standard bass tuning
```

trackbind

Bind track tables

Description

Bind together track tables by row.

Usage

```
trackbind(..., id)
```

Arguments

<code>...</code>	single-entry track data frames.
<code>id</code>	integer, ID vector indicating distinct tracks corresponding to distinct sheet music staves. See details.

Details

This function appends multiple track tables into a single track table for preparation of generating a multi-track score. `id` is used to separate staves in the sheet music/tablature output. A track's voice is used to separate distinct voices within a common music staff.

If not provided, `id` automatically propagates `1:n` for `n` tracks passed to `...` when binding these tracks together. This expresses the default assumption of one staff or music/tab staff pair per track. This is the typical use case.

Some tracks represent different voices that share the same staff. These should be assigned the same `id`, in which case you must provide the `id` argument. Up to two voices per track are supported. An error will be thrown if any two tracks have both the same voice and the same `id`. The pair must be unique. E.g., provide `id = c(1, 1)` when you have two tracks with voice equal to 1 and 2. See examples.

Note that the actual ID values assigned to each track do not matter; only the order in which tracks are bound, first to last.

Value

a tibble data frame

See Also

[phrase](#), [track](#), [score](#)

Examples

```
x <- phrase("c ec'g' ec'g'", "4 4 2", "5 432 432")
x1 <- track(x)
x2 <- track(x, voice = 2)
trackbind(x1, x1)
trackbind(x1, x2, id = c(1, 1))
```

transpose

Transpose pitch

Description

Transpose pitch by a number of semitones.

Usage

```
transpose(notes, n = 0, octaves = NULL, accidentals = NULL, key = NULL)
```

```
tp(notes, n = 0, octaves = NULL, accidentals = NULL, key = NULL)
```

Arguments

<code>notes</code>	character, a noteworthy string.
<code>n</code>	integer, positive or negative number of semitones to transpose.
<code>octaves</code>	NULL or character, "tick" or "integer" octave numbering in result.
<code>accidentals</code>	NULL or character, represent accidentals, "flat" or "sharp".
<code>key</code>	NULL or character, use a key signature to specify and override accidentals. Ignored if <code>c</code> or <code>am</code> .

Details

This function transposes the pitch of notes in a noteworthy string.

Transposing is not currently supported on a phrase object. The notes in a phrase object have already been transformed to LilyPond syntax and mixed with other potentially complex information. Transposing is intended to be done on a string of notes prior to passing it to phrase. It will work on strings that use either integer or tick mark octave numbering formats and flats or sharps, in any combination. The transposed result conforms according to the function arguments. When integer octaves are returned, all 3s are dropped since the third octave is implicit in LilyPond.

When octaves, accidentals and key are NULL, formatting is inferred from notes. When mixed formats are present, tick format is the default for octave numbering and flats are the default for accidentals.

Value

character

Examples

```
transpose("a_3 b_4 c5", 0)
tp("a_3 b_4 c5", -1)
tp("a_3 b_4 c5", 1)
tp("a#3 b4 c#5", 11)
tp("a#3 b4 c#5", 12)
tp("r s a#3 b4 c#5", 13)
tp("a b' c#' ", 2, "integer", "flat")
tp("a, b ceg", 2, "tick", "sharp")
```

tunings

Predefined instrument tunings

Description

A data frame containing some predefined instrument tunings commonly used for guitar, bass, mandolin, banjo, ukulele and orchestral instruments.

Usage

tunings

Format

A data frame with 2 columns for the tuning ID and corresponding pitches and 32 rows for all predefined tunings.

tuplet	<i>Tuplets</i>
--------	----------------

Description

Helper function for generating tuplet syntax.

Usage

```
tuplet(x, n, string = NULL, a = 3, b = 2)
triplet(x, n, string = NULL)
```

Arguments

x	noteworthy string or phrase object.
n	integer, duration of each tuplet note, e.g., 8 for 8th note tuplet.
string,	character, optional string or vector with same number of timesteps as x that specifies which strings to play for each specific note. Only applies when x is a noteworthy string.
a	integer, notes per tuplet.
b	integer, beats per tuplet.

Details

This function gives control over tuplet construction. The default arguments $a = 3$ and $b = 2$ generates a triplet where three triplet notes, each lasting for two thirds of a beat, take up two beats. n is used to describe the beat duration with the same fraction-of-measure denominator notation used for notes in tabl phrases, e.g., 16th note triplet, 8th note triplet, etc.

If you provide a note sequence for multiple tuplets in a row of the same type, they will be connected automatically. It is not necessary to call `tuplet` each time when the pattern is constant. If you provide a complete phrase object, it will simply be wrapped in the tuplet tag, so take care to ensure the phrase contents make sense as part of a tuplet.

Value

phrase

Examples

```
tuplet("c c# d", 8)
triplet("c c# d", 8)
tuplet("c c# d c c# d", 4, a = 6, b = 4)

p1 <- phrase("c c# d", "8-. 8( 8)", "5*3")
tuplet(p1, 8)
```

valid-noteinfo	<i>Check note info validity</i>
----------------	---------------------------------

Description

Check whether a note info string is comprised exclusively of valid note info syntax. `noteinfo` returns a scalar logical result indicating whether the entire set contains exclusively valid entries.

Usage

```
informable(x, na.rm = FALSE)
```

```
as_noteinfo(x, format = NULL)
```

```
is_noteinfo(x)
```

Arguments

<code>x</code>	character, a note info string.
<code>na.rm</code>	remove NAs.
<code>format</code>	NULL or character, the timestep delimiter format, "space" or "vector".

Details

`as_noteinfo` can be used to coerce to the `noteinfo` class. Coercion will fail if the string is has any syntax that is not valid for note info. Using the `noteinfo` class is generally not needed by the user during an interactive session, but is available and offers its own `print` and `summary` methods for note info strings. The class is often used by other functions, and functions that output a note info string attach the `noteinfo` class.

When `format = NULL`, the timestep delimiter format is inferred from the note info string input. When unclear, such as with phrase objects, the default is space-delimited time.

Value

depends on the function

See Also

[noteinfo](#), [valid-notes](#)

Examples

```
a <- notate("8x", "Start here")
x <- paste(a, "8[stacatto] 8-. 16 4.. 16- 16 2^ 2 4. 8( 4)( 4) 8*4 1 1")

informable(x) # is it of 'noteinfo' class; a validity check for any string
x <- as_noteinfo(x) # coerce to 'noteinfo' class
```

```
is_noteinfo(x) # check for 'noteinfo' class
x
summary(x)
```

 valid-notes

Check note and chord validity

Description

Check whether a string is comprised exclusively of valid note and/or chord syntax. `is_note` and `is_chord` are vectorized and their positive results are mutually exclusive. `noteworthy` is also vectorized and performs both checks, but it returns a scalar logical result indicating whether the entire set contains exclusively valid entries.

Usage

```
is_note(x, na.rm = FALSE)
is_chord(x, na.rm = FALSE)
noteworthy(x, na.rm = FALSE)
as_noteworthy(x, octaves = NULL, accidentals = NULL, format = NULL)
is_noteworthy(x)
```

Arguments

<code>x</code>	character, a noteworthy string.
<code>na.rm</code>	remove NAs.
<code>octaves</code>	NULL or character, "tick" or "integer" octave numbering in result.
<code>accidentals</code>	NULL or character, represent accidentals, "flat" or "sharp".
<code>format</code>	NULL or character, the timestep delimiter format, "space" or "vector".

Details

`as_noteworthy` can be used to coerce to the noteworthy class. Coercion will fail if the string is not noteworthy. While many functions will work on simple character strings and, if their syntax is valid, coerce them to the 'noteworthy' class, it is recommended to use this class. Not all functions are so aggressive, and several generic methods are implemented for the class. It also offers its own print and summary methods for noteworthy strings. An added benefit to using `as_noteworthy` is to conform all notes in a noteworthy string to specific formatting for accidentals and octave numbering. Functions that output a noteworthy string attach the noteworthy class.

When `octaves`, `accidentals`, and `format` are NULL, formatting is inferred from the noteworthy string input. When mixed formats are present, tick format is the default for octave numbering and flats are the default for accidentals.

Value

depends on the function

See Also

[note-checks](#), [note-metadata](#), [note-summaries](#), [note-coerce](#)

Examples

```
x <- "a# b_ c, d'' e3 g_4 A m c2e_2g2 cegh" # includes invalid syntax
data.frame(
  x = strsplit(x, " ")[[1]],
  note = is_note(x),
  chord = is_chord(x),
  either = noteworthy(x))

is_diatonic("ace ac#e d e_", "c")

x <- "a# b_ c,~ c, d'' e3 g_4 c2e_2g2"
noteworthy(x) # is it noteworthy; a validity check for any string
x <- as_noteworthy(x) # coerce to 'noteworthy' class, conform formatting
is_noteworthy(x) # check for 'noteworthy' class
x

summary(x)

x <- as_noteworthy(x, format = "vector", octaves = "integer",
  accidentals = "flat")
x

summary(x)
```

Index

`!=.noteworthy (note-logic)`, 49

*** datasets**

- `articulations`, 5
- `guitarChords`, 23
- `mainIntervals`, 35
- `tabrSyntax`, 106
- `tunings`, 113

`<.noteworthy (note-logic)`, 49

`<=.noteworthy (note-logic)`, 49

`==.noteworthy (note-logic)`, 49

`>.noteworthy (note-logic)`, 49

`>=.noteworthy (note-logic)`, 49

`[.lyrics (single-bracket)`, 92

`[.music (single-bracket)`, 92

`[.noteinfo (single-bracket)`, 92

`[.noteworthy (single-bracket)`, 92

`[<-.lyrics (single-bracket)`, 92

`[<-.music (single-bracket)`, 92

`[<-.noteinfo (single-bracket)`, 92

`[<-.noteworthy (single-bracket)`, 92

`[[.lyrics (double-bracket)`, 20

`[[.music (double-bracket)`, 20

`[[.noteinfo (double-bracket)`, 20

`[[.noteworthy (double-bracket)`, 20

`[[<-.lyrics (double-bracket)`, 20

`[[<-.music (double-bracket)`, 20

`[[<-.noteinfo (double-bracket)`, 20

`[[<-.noteworthy (double-bracket)`, 20

`accidental_type (note-metadata)`, 50

`append_phrases`, 4

`articulations`, 5

`as_integer_octaves (note-coerce)`, 45

`as_lyrics (lyrics)`, 34

`as_music (music)`, 40

`as_music_df`, 5

`as_noteinfo (valid-noteinfo)`, 115

`as_noteworthy`, 46

`as_noteworthy (valid-notes)`, 116

`as_phrase (phrase-checks)`, 61

`as_space_time (note-coerce)`, 45

`as_tick_octaves (note-coerce)`, 45

`as_vector_time (note-coerce)`, 45

`bpm (n_measures)`, 58

`c.lyrics (tabr-c)`, 98

`c.music (tabr-c)`, 98

`c.noteinfo (tabr-c)`, 98

`c.noteworthy (tabr-c)`, 98

`c.phrase (tabr-c)`, 98

`cents_to_ratio (ratio_to_cents)`, 71

`chord-compare`, 7

`chord-filter`, 8

`chord-mapping`, 9

`chord_11 (chords)`, 11

`chord_13 (chords)`, 11

`chord_5 (chords)`, 11

`chord_7s11 (chords)`, 11

`chord_7s5 (chords)`, 11

`chord_7s9 (chords)`, 11

`chord_add9 (chords)`, 11

`chord_arpeggiate`, 14

`chord_aug (chords)`, 11

`chord_break`, 15

`chord_def`, 16

`chord_degree (scale-deg)`, 82

`chord_dim (chords)`, 11

`chord_dim7 (chords)`, 11

`chord_dom7 (chords)`, 11

`chord_dom9 (chords)`, 11

`chord_freq (pitch_freq)`, 63

`chord_invert`, 17

`chord_is_major`, 18

`chord_is_minor (chord_is_major)`, 18

`chord_m7b5 (chords)`, 11

`chord_madd9 (chords)`, 11

`chord_maj (chords)`, 11

`chord_maj11 (chords)`, 11

`chord_maj13 (chords)`, 11

- chord_maj6 (chords), 11
- chord_maj7 (chords), 11
- chord_maj7s11 (chords), 11
- chord_maj9 (chords), 11
- chord_min (chords), 11
- chord_min11 (chords), 11
- chord_min13 (chords), 11
- chord_min6 (chords), 11
- chord_min7 (chords), 11
- chord_min9 (chords), 11
- chord_order (chord-compare), 7
- chord_rank (chord-compare), 7
- chord_root (chord-filter), 8
- chord_semitones, 16
- chord_semitones (pitch_freq), 63
- chord_set, 19
- chord_size (note-metadata), 50
- chord_slice (chord-filter), 8
- chord_sort (chord-compare), 7
- chord_sus2 (chords), 11
- chord_sus4 (chords), 11
- chord_top (chord-filter), 8
- chords, 11

- distinct_notes (note-summaries), 53
- distinct_octaves (note-summaries), 53
- distinct_pitches (note-summaries), 53
- double-bracket, 20
- duration_to_ticks (read_midi), 72
- dyad, 21

- flatten_sharp (note-coerce), 45
- freq_pitch (pitch_freq), 63
- freq_ratio, 22
- freq_semitones (pitch_freq), 63
- from_chorrds (to_tabr), 107
- from_music21 (to_tabr), 107

- gc_fretboard (chord-mapping), 9
- gc_info, 108
- gc_info (chord-mapping), 9
- gc_is_known (chord-mapping), 9
- gc_name_mod (chord-mapping), 9
- gc_name_root (chord-mapping), 9
- gc_name_split (chord-mapping), 9
- gc_notes (chord-mapping), 9
- gc_notes_to_fb (chord-mapping), 9
- guitarChords, 23, 108

- head.lyrics (tabr-head), 99
- head.music (tabr-head), 99
- head.noteinfo (tabr-head), 99
- head.noteworthy (tabr-head), 99
- hp, 24

- info_annotation (noteinfo), 54
- info_articulation (noteinfo), 54
- info_bend (noteinfo), 54
- info_dotted (noteinfo), 54
- info_double_dotted (noteinfo), 54
- info_duration (noteinfo), 54
- info_single_dotted (noteinfo), 54
- info_slide (noteinfo), 54
- info_slur_off (noteinfo), 54
- info_slur_on (noteinfo), 54
- informable (valid-noteinfo), 115
- interval_semitones, 26
- intervals, 24
- is_chord (valid-notes), 116
- is_diatonic, 27, 83
- is_in_scale, 27
- is_in_scale (scale-deg), 82
- is_lyrics (lyrics), 34
- is_mode (mode-helpers), 38
- is_music (music), 40
- is_note (valid-notes), 116
- is_noteinfo (valid-noteinfo), 115
- is_noteworthy (valid-notes), 116
- is_space_time (note-metadata), 50
- is_vector_time (note-metadata), 50

- key_is_flat (keys), 28
- key_is_major (keys), 28
- key_is_minor (keys), 28
- key_is_natural (keys), 28
- key_is_sharp (keys), 28
- key_n_flats (keys), 28
- key_n_sharps (keys), 28
- keys, 28, 39, 85

- length.lyrics (tabr-length), 100
- length.music (tabr-length), 100
- length.noteinfo (tabr-length), 100
- length.noteworthy (tabr-length), 100
- lilypond, 29, 36–38, 70, 74, 79, 96, 97
- lilypond_root, 32
- lilypond_version (lilypond_root), 32
- lp_chord_id, 33
- lp_chord_mod (lp_chord_id), 33

- lyrical (lyrics), 34
- lyrics, 34
- lyrics_template (lyrics), 34
- mainIntervals, 22, 25–27, 35
- midi_key (read_midi), 72
- midi_metadata (read_midi), 72
- midi_notes (read_midi), 72
- midi_time (read_midi), 72
- midily, 32, 35, 37, 38
- miditab, 37, 37, 97
- mode-helpers, 38
- mode_aeolian (mode-helpers), 38
- mode_dorian (mode-helpers), 38
- mode_ionian (mode-helpers), 38
- mode_locrian (mode-helpers), 38
- mode_lydian (mode-helpers), 38
- mode_mixolydian (mode-helpers), 38
- mode_modern (mode-helpers), 38
- mode_phrygian (mode-helpers), 38
- mode_rotate (mode-helpers), 38
- modes (mode-helpers), 38
- music, 40, 43, 60
- music-helpers, 42
- music_info (music-helpers), 42
- music_key (music-helpers), 42
- music_lyrics (music-helpers), 42
- music_notes (music-helpers), 42
- music_split (music), 40
- music_strings (music-helpers), 42
- music_tempo (music-helpers), 42
- music_time (music-helpers), 42
- musical (music), 40
- n_beats (n_measures), 58
- n_chords (note-metadata), 50
- n_measures, 58
- n_notes (note-metadata), 50
- n_octaves (note-metadata), 50
- n_steps (note-metadata), 50
- naturalize (note-coerce), 45
- notable (phrase-checks), 61
- notate, 43
- note-checks, 44
- note-coerce, 45
- note-equivalence, 47
- note-logic, 49
- note-metadata, 50
- note-summaries, 53
- note_arpeggiate (note_slice), 56
- note_has_accidental (note-checks), 44
- note_has_flat (note-checks), 44
- note_has_integer (note-metadata), 50
- note_has_natural (note-checks), 44
- note_has_rest (note-metadata), 50
- note_has_sharp (note-checks), 44
- note_has_tick (note-metadata), 50
- note_in_scale, 27
- note_in_scale (scale-deg), 82
- note_is_accidental (note-checks), 44
- note_is_equal (note-equivalence), 47
- note_is_flat (note-checks), 44
- note_is_identical (note-equivalence), 47
- note_is_integer (note-metadata), 50
- note_is_natural (note-checks), 44
- note_is_rest (note-metadata), 50
- note_is_sharp (note-checks), 44
- note_is_tick (note-metadata), 50
- note_ngram, 55
- note_rotate (note_slice), 56
- note_set_key (note-coerce), 45
- note_shift (note_slice), 56
- note_slice, 56
- note_sort, 50
- note_sort (note_slice), 56
- noteinfo, 54, 115
- noteworthy (valid-notes), 116
- notify, 103
- notify (phrase-checks), 61
- octave_is_equal (note-equivalence), 47
- octave_is_identical (note-equivalence), 47
- octave_range (note-summaries), 53
- octave_span (note-summaries), 53
- octave_type (note-metadata), 50
- octaves (note-summaries), 53
- p (phrase), 59
- pc (append_phrases), 4
- pct (repeats), 80
- phrase, 59, 70, 79, 81, 87–90, 110–112
- phrase-checks, 61
- phrase_info (phrase-checks), 61
- phrase_notes (phrase-checks), 61
- phrase_strings (phrase-checks), 61
- phrasey (phrase-checks), 61
- pitch_diff (intervals), 24

- pitch_freq, 63
- pitch_interval (intervals), 24
- pitch_is_equal (note-equivalence), 47
- pitch_is_identical, 50
- pitch_is_identical (note-equivalence), 47
- pitch_range (note-summaries), 53
- pitch_semitones (pitch_freq), 63
- pitch_seq, 64
- plot_chord (plot_fretboard), 65
- plot_fretboard, 65, 74
- plot_music, 68, 79
- plot_music_bass (plot_music), 68
- plot_music_bc (plot_music), 68
- plot_music_guitar (plot_music), 68
- plot_music_tab (plot_music), 68
- plot_music_tc (plot_music), 68
- pn (append_phrases), 4
- pretty_notes (note-coerce), 45

- ratio_to_cents, 71
- read_midi, 72
- render_chordchart, 32, 73, 97
- render_midi (tab), 94
- render_music, 70, 75
- render_music_bass (render_music), 75
- render_music_bc (render_music), 75
- render_music_guitar (render_music), 75
- render_music_tab (render_music), 75
- render_music_tc (render_music), 75
- render_score (tab), 94
- render_tab (tab), 94
- rep.lyrics (tabr-rep), 104
- rep.music (tabr-rep), 104
- rep.noteinfo (tabr-rep), 104
- rep.noteworthy (tabr-rep), 104
- rep.phrase (tabr-rep), 104
- repeats, 80
- rest, 81
- rev.lyrics (tabr-rev), 105
- rev.music (tabr-rev), 105
- rev.noteinfo (tabr-rev), 105
- rev.noteworthy (tabr-rev), 105
- rp (repeats), 80

- scale-deg, 82
- scale-helpers, 84
- scale_chords, 86
- scale_chromatic (scale-helpers), 84
- scale_degree, 6
- scale_degree (scale-deg), 82
- scale_diatonic (scale-helpers), 84
- scale_diff (intervals), 24
- scale_harmonic_minor (scale-helpers), 84
- scale_hungarian_minor (scale-helpers), 84
- scale_interval, 6
- scale_interval (intervals), 24
- scale_jazz_minor (scale-helpers), 84
- scale_major (scale-helpers), 84
- scale_melodic_minor (scale-helpers), 84
- scale_minor (scale-helpers), 84
- scale_note (scale-deg), 82
- score, 70, 79, 87, 111, 112
- seconds (n_measures), 58
- seconds_per_measure (n_measures), 58
- seconds_per_step (n_measures), 58
- semitone_freq (pitch_freq), 63
- semitone_pitch (pitch_freq), 63
- semitone_range (note-summaries), 53
- semitone_span (note-summaries), 53
- sf_note (sf_phrase), 88
- sf_phrase, 88
- sfn (sf_phrase), 88
- sfp (sf_phrase), 88
- sharpen_flat (note-coerce), 45
- simplify_phrase, 91
- single-bracket, 92
- steps_per_measure (n_measures), 58
- steps_start_time (n_measures), 58
- string_fold (string_unfold), 93
- string_unfold, 93

- tab, 32, 37, 38, 70, 74, 79, 87, 94
- tabr, 97
- tabr-c, 98
- tabr-head, 99
- tabr-length, 100
- tabr-methods, 101
- tabr-rep, 104
- tabr-rev, 105
- tabr_lilypond_api (lilypond_root), 32
- tabr_options, 106
- tabrSyntax, 106
- tail.lyrics (tabr-head), 99
- tail.music (tabr-head), 99
- tail.noteinfo (tabr-head), 99
- tail.noteworthy (tabr-head), 99

tally_notes (note-summaries), 53
tally_octaves (note-summaries), 53
tally_pitches (note-summaries), 53
ticks_to_duration (read_midi), 72
tie, 107
time_format (note-metadata), 50
to_tabr, 107
tp (transpose), 112
track, 70, 79, 87, 109, 112
track_bass (track), 109
track_bc (track), 109
track_guitar (track), 109
track_tc (track), 109
trackbind, 87, 110, 111
transpose, 14, 21, 112
triplet (tuple), 114
tuning_intervals (intervals), 24
tunings, 67, 110, 113
tuple, 114

untie (tie), 107

valid-noteinfo, 115
valid-notes, 116
volta (repeats), 80

x5 (chords), 11
x7 (chords), 11
x7s11 (chords), 11
x7s5 (chords), 11
x7s9 (chords), 11
x9 (chords), 11
x_11 (chords), 11
x_13 (chords), 11
xadd9 (chords), 11
xaug (chords), 11
xdim (chords), 11
xdim7 (chords), 11
xM (chords), 11
xm (chords), 11
xM11 (chords), 11
xm11 (chords), 11
xM13 (chords), 11
xm13 (chords), 11
xM6 (chords), 11
xm6 (chords), 11
xM7 (chords), 11
xm7 (chords), 11
xm7b5 (chords), 11
xM7s11 (chords), 11
xM9 (chords), 11
xm9 (chords), 11
xma9 (chords), 11
xs2 (chords), 11
xs4 (chords), 11