

Package ‘EvaluateCore’

June 11, 2021

Title Quality Evaluation of Core Collections

Version 0.1.2

Description Implements various quality evaluation statistics to assess the value of plant germplasm core collections using qualitative and quantitative phenotypic trait data according to Odong et al. (2015) <[doi:10.1007/s00122-012-1971-y](https://doi.org/10.1007/s00122-012-1971-y)>.

Copyright 2018-2021, ICAR-NBPGR

License GPL-2 | GPL-3

Encoding UTF-8

RoxygenNote 7.1.1

URL <https://github.com/aravind-j/EvaluateCore>
<https://CRAN.R-project.org/package=EvaluateCore>
<https://aravind-j.github.io/EvaluateCore/>
<https://doi.org/10.5281/zenodo.3875930>

BugReports <https://github.com/aravind-j/EvaluateCore/issues>

RdMacros mathjaxr,
Rdpack

Depends R (>= 3.5.0)

Imports agricolae,
car,
cluster,
dplyr,
entropy,
ggcorrplot,
ggplot2,
grDevices,
gridExtra,
kSamples,
mathjaxr,
psych,
reshape2,
Rdpack,
stats,
vegan

Suggests ccChooser,
corehunter,
rJava (>= 0.9-8)

R topics documented:

bar.evaluate.core	2
box.evaluate.core	3
chisquare.evaluate.core	5
corr.evaluate.core	6
coverage.evaluate.core	8
cr.evaluate.core	9
dist.evaluate.core	11
freqdist.evaluate.core	13
iqr.evaluate.core	15
levene.evaluate.core	16
pca.evaluate.core	18
pdfdist.evaluate.core	19
percentdiff.evaluate.core	21
qq.evaluate.core	23
shannon.evaluate.core	24
signtest.evaluate.core	26
snk.evaluate.core	28
tttest.evaluate.core	29
vr.evaluate.core	31
wilcox.evaluate.core	32
Index	34

bar.evaluate.core	<i>Bar Plots</i>
-------------------	------------------

Description

Plot Bar plots to graphically compare the frequency distributions of qualitative traits between entire collection (EC) and core set (CS).

Usage

```
bar.evaluate.core(data, names, qualitative, selected)
```

Arguments

data	The data as a data frame object. The data frame should possess one row per individual and columns with the individual names and multiple trait/character data.
names	Name of column with the individual names as a character string
qualitative	Name of columns with the qualitative traits as a character vector.
selected	Character vector with the names of individuals selected in core collection and present in the names column.

Value

A list with the ggplot objects of relative frequency bar plots of CS and EC for each trait specified as qualitative.

See Also

[barplot](#), [geom_bar](#)

Examples

```
#####
# Use data from R package ccChooser
#####

library(ccChooser)
data("dactylis_CC")
data("dactylis_EC")

ec <- cbind(genotypes = rownames(dactylis_EC), dactylis_EC[, -1])
ec$genotypes <- as.character(ec$genotypes)
rownames(ec) <- NULL
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) cut(x, breaks = 4))
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) factor(as.numeric(x)))

head(ec)

core <- rownames(dactylis_CC)

quant <- c("X2", "X3", "X4", "X5", "X8")
qual <- c("X1", "X6", "X7")

#####
# EvaluateCore
#####

bar.evaluate.core(data = ec, names = "genotypes",
                  qualitative = qual, selected = core)
```

box.evaluate.core

Box Plots

Description

Plot Box-and-Whisker plots (Tukey 1970; McGill et al. 1978) to graphically compare the probability distributions of quantitative traits between entire collection (EC) and core set (CS).

Usage

```
box.evaluate.core(data, names, quantitative, selected)
```

Arguments

data	The data as a data frame object. The data frame should possess one row per individual and columns with the individual names and multiple trait/character data.
names	Name of column with the individual names as a character string
quantitative	Name of columns with the quantitative traits as a character vector.
selected	Character vector with the names of individuals selected in core collection and present in the names column.

Value

A list with the ggplot objects of box plots of CS and EC for each trait specified as quantitative.

References

McGill R, Tukey JW, Larsen WA (1978). "Variations of box plots." *The American Statistician*, 32(1), 12.

Tukey JW (1970). *Exploratory Data Analysis. Preliminary edition*. Addison-Wesley.

See Also

[boxplot](#), [geom_boxplot](#)

Examples

```
#####
# Use data from R package ccChooser
#####

library(ccChooser)
data("dactylis_CC")
data("dactylis_EC")

ec <- cbind(genotypes = rownames(dactylis_EC), dactylis_EC[, -1])
ec$genotypes <- as.character(ec$genotypes)
rownames(ec) <- NULL
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) cut(x, breaks = 4))
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) factor(as.numeric(x)))

head(ec)

core <- rownames(dactylis_CC)

quant <- c("X2", "X3", "X4", "X5", "X8")
qual <- c("X1", "X6", "X7")

#####
# EvaluateCore
#####

box.evaluate.core(data = ec, names = "genotypes",
                  quantitative = quant, selected = core)
```

 chisquare.evaluate.core

Chi-squared Test for Homogeneity

Description

Compare the distribution frequencies of qualitative traits between entire collection (EC) and core set (CS) by Chi-squared test for homogeneity (Pearson 1900; Snedecor and Irwin 1933).

Usage

```
chisquare.evaluate.core(data, names, qualitative, selected)
```

Arguments

data	The data as a data frame object. The data frame should possess one row per individual and columns with the individual names and multiple trait/character data.
names	Name of column with the individual names as a character string
qualitative	Name of columns with the qualitative traits as a character vector.
selected	Character vector with the names of individuals selected in core collection and present in the names column.

Value

A data frame with the following columns.

Trait	The qualitative trait.
EC_No.Classes	The number of classes in the trait for EC.
EC_Classes	The frequency of the classes in the trait for EC.
CS_No.Classes	The number of classes in the trait for CS.
CS_Classes	The frequency of the classes in the trait for CS.
chisq_statistic	The χ^2 test statistic.
chisq_pvalue	The p value for the test statistic.
chisq_significance	The significance of the test statistic (*: $p \leq 0.01$; **: $p \leq 0.05$; ns: $p > 0.05$).

References

Pearson K (1900). "X. On the criterion that a given system of deviations from the probable in the case of a correlated system of variables is such that it can be reasonably supposed to have arisen from random sampling." *The London, Edinburgh, and Dublin Philosophical Magazine and Journal of Science*, **50**(302), 157–175.

Snedecor G, Irwin MR (1933). "On the chi-square test for homogeneity." *Iowa State College Journal of Science*, **8**, 75–81.

See Also[chisq.test](#)**Examples**

```
#####
# Use data from R package ccChooser
#####

library(ccChooser)
data("dactylis_CC")
data("dactylis_EC")

ec <- cbind(genotypes = rownames(dactylis_EC), dactylis_EC[, -1])
ec$genotypes <- as.character(ec$genotypes)
rownames(ec) <- NULL
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) cut(x, breaks = 4))
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) factor(as.numeric(x)))

head(ec)

core <- rownames(dactylis_CC)

quant <- c("X2", "X3", "X4", "X5", "X8")
qual <- c("X1", "X6", "X7")

#####
# EvaluateCore
#####

chisquare.evaluate.core(data = ec, names = "genotypes",
                       qualitative = qual, selected = core)
```

corr.evaluate.core *Phenotypic Correlations*

Description

Compute phenotypic correlations (Pearson 1895) between traits, plot correlation matrices as correlograms (Friendly 2002) and calculate mantel correlation (Legendre and Legendre 2012) between them to compare entire collection (EC) and core set (CS).

Usage

```
corr.evaluate.core(data, names, quantitative, qualitative, selected)
```

Arguments

data The data as a data frame object. The data frame should possess one row per individual and columns with the individual names and multiple trait/character data.

names	Name of column with the individual names as a character string
quantitative	Name of columns with the quantitative traits as a character vector.
qualitative	Name of columns with the qualitative traits as a character vector.
selected	Character vector with the names of individuals selected in core collection and present in the names column.

Value

A list with the following components.

Correlation Matrix

The matrix with phenotypic correlations between traits in EC (below diagonal) and CS (above diagonal).

Correologram A correologram of phenotypic correlations between traits in EC (below diagonal) and CS (above diagonal) as a ggplot object.

Mantel Correlation

A data frame with Mantel correlation coefficient (r) between EC and CS phenotypic correlation matrices, its p value and significance (*: $p \leq 0.01$; **: $p \leq 0.05$; ns: $p > 0.05$).

References

Friendly M (2002). "Corrgrams." *The American Statistician*, **56**(4), 316–324.

Legendre P, Legendre L (2012). "Interpretation of ecological structures." In *Developments in Environmental Modelling*, volume 24, 521–624. Elsevier.

Pearson K (1895). "Note on regression and inheritance in the case of two parents." *Proceedings of the Royal Society of London*, **58**, 240–242.

See Also

[cor](#), [cor_pmat](#) [ggcorrplot](#), [mantel](#)

Examples

```
#####
# Use data from R package ccChooser
#####

library(ccChooser)
data("dactylis_CC")
data("dactylis_EC")

ec <- cbind(genotypes = rownames(dactylis_EC), dactylis_EC[, -1])
ec$genotypes <- as.character(ec$genotypes)
rownames(ec) <- NULL
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) cut(x, breaks = 4))
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) factor(as.numeric(x)))

head(ec)

core <- rownames(dactylis_CC)
```

```

quant <- c("X2", "X3", "X4", "X5", "X8")
qual <- c("X1", "X6", "X7")

#####
# EvaluateCore
#####

corr.evaluate.core(data = ec, names = "genotypes", quantitative = quant,
                  qualitative = qual, selected = core)

```

coverage.evaluate.core

Class Coverage

Description

Compute the Class Coverage (Kim et al. 2007) to compare the distribution frequencies of qualitative traits between entire collection (EC) and core set (CS).

Usage

```
coverage.evaluate.core(data, names, qualitative, selected)
```

Arguments

data	The data as a data frame object. The data frame should possess one row per individual and columns with the individual names and multiple trait/character data.
names	Name of column with the individual names as a character string
qualitative	Name of columns with the qualitative traits as a character vector.
selected	Character vector with the names of individuals selected in core collection and present in the names column.

Details

Class Coverage (Kim et al. 2007) is computed as follows.

$$Class\ Coverage = \left(\frac{1}{n} \sum_{i=1}^n \frac{A_{CS_i}}{A_{EC_i}} \right) \times 100$$

Where, A_{CS_i} is the sets of categories in the CS for the i th trait, A_{EC_i} is the sets of categories in the EC for the i th trait and n is the total number of traits.

Value

The Class Coverage value.

References

Kim K, Chung H, Cho G, Ma K, Chandrabalan D, Gwag J, Kim T, Cho E, Park Y (2007). "PowerCore: A program applying the advanced M strategy with a heuristic search for establishing core sets." *Bioinformatics*, **23**(16), 2155–2162.

Examples

```
#####
# Use data from R package ccChooser
#####

library(ccChooser)
data("dactylis_CC")
data("dactylis_EC")

ec <- cbind(genotypes = rownames(dactylis_EC), dactylis_EC[, -1])
ec$genotypes <- as.character(ec$genotypes)
rownames(ec) <- NULL
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) cut(x, breaks = 4))
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) factor(as.numeric(x)))

head(ec)

core <- rownames(dactylis_CC)

quant <- c("X2", "X3", "X4", "X5", "X8")
qual <- c("X1", "X6", "X7")

#####
# EvaluateCore
#####

coverage.evaluate.core(data = ec, names = "genotypes",
                      qualitative = qual, selected = core)
```

cr.evaluate.core

Coincidence Rate of Range

Description

Compute the Coincidence Rate of Range (*CR*) (Diwan et al. 1995; Hu et al. 2000) to compare quantitative traits of the entire collection (EC) and core set (CS).

Usage

```
cr.evaluate.core(data, names, quantitative, selected)
```



```

head(ec)

core <- rownames(dactylis_CC)

quant <- c("X2", "X3", "X4", "X5", "X8")
qual <- c("X1", "X6", "X7")

#####
# EvaluateCore
#####

cr.evaluate.core(data = ec, names = "genotypes",
                 quantitative = quant, selected = core)

```

dist.evaluate.core *Distance Measures*

Description

Compute average Entry-to-nearest-entry distance ($E-EN$), Accession-to-nearest-entry distance ($A-EN$) and Entry-to-entry distance ($E-E$) (Odong et al. 2013) to evaluate a core set (CS) selected from an entire collection (EC).

Usage

```
dist.evaluate.core(data, names, quantitative, qualitative, selected, d = NULL)
```

Arguments

data	The data as a data frame object. The data frame should possess one row per individual and columns with the individual names and multiple trait/character data.
names	Name of column with the individual names as a character string
quantitative	Name of columns with the quantitative traits as a character vector.
qualitative	Name of columns with the qualitative traits as a character vector.
selected	Character vector with the names of individuals selected in core collection and present in the names column.
d	A distance matrix of class "dist" with individual names in the names column in data as labels. If NULL (default), then a distance matrix is computed using Gower's metric. (Gower 1971).

Value

A data frame with the average values of $E-EN$, $A-EN$ and $E-E$.

References

Gower JC (1971). "A general coefficient of similarity and some of its properties." *Biometrics*, **27**(4), 857–871.

Odong TL, Jansen J, van Eeuwijk FA, van Hintum TJJ (2013). "Quality of core collections for effective utilisation of genetic resources review, discussion and interpretation." *Theoretical and Applied Genetics*, **126**(2), 289–305.

See Also

[evaluateCore](#)

Examples

```
#####
# Use data from R package ccChooser
#####

library(ccChooser)
data("dactylis_CC")
data("dactylis_EC")

ec <- cbind(genotypes = rownames(dactylis_EC), dactylis_EC[, -1])
ec$genotypes <- as.character(ec$genotypes)
rownames(ec) <- NULL
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) cut(x, breaks = 4))
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) factor(as.numeric(x)))

head(ec)

core <- rownames(dactylis_CC)

quant <- c("X2", "X3", "X4", "X5", "X8")
qual <- c("X1", "X6", "X7")

#####
# EvaluateCore
#####

dist.evaluate.core(data = ec, names = "genotypes", quantitative = quant,
                  qualitative = qual, selected = core)

#####
# Compare with corehunter
#####

library(corehunter)
# Prepare phenotype dataset
dtype <- c(rep("RD", length(quant)),
           rep("NS", length(qual)))
rownames(ec) <- ec[, "genotypes"]
ecdata <- corehunter::phenotypes(data = ec[, c(quant, qual)],
                               types = dtype)
```

```

# Compute average distances
EN <- evaluateCore(core = rownames(dactylis_CC), data = ecdata,
                   objective = objective("EN", "GD"))
AN <- evaluateCore(core = rownames(dactylis_CC), data = ecdata,
                   objective = objective("AN", "GD"))
EE <- evaluateCore(core = rownames(dactylis_CC), data = ecdata,
                   objective = objective("EE", "GD"))

EN
AN
EE

```

freqdist.evaluate.core

Frequency Distribution Histogram

Description

Plot stacked frequency distribution histogram to graphically compare the probability distributions of traits between entire collection (EC) and core set (CS).

Usage

```

freqdist.evaluate.core(
  data,
  names,
  quantitative,
  qualitative,
  selected,
  highlight = NULL,
  include.highlight = TRUE,
  highlight.se = NULL,
  highlight.col = "red"
)

```

Arguments

data	The data as a data frame object. The data frame should possess one row per individual and columns with the individual names and multiple trait/character data.
names	Name of column with the individual names as a character string
quantitative	Name of columns with the quantitative traits as a character vector.
qualitative	Name of columns with the qualitative traits as a character vector.
selected	Character vector with the names of individuals selected in core collection and present in the names column.
highlight	Individual names to be highlighted as a character vector.
include.highlight	If TRUE, the highlighted individuals are included in the frequency distribution histogram. Default is TRUE.

- `highlight.se` Optional data frame of standard errors for the individuals specified in `highlight`. It should have the same column names as in `data`.
- `highlight.col` The colour(s) to be used to highlighting individuals in the plot as a character vector of the same length as `highlight`. Must be valid colour values in R (named colours, hexadecimal representation, index of colours [1:8] in default R `palette()` etc.).

Value

A list with the `ggplot` objects of stacked frequency distribution histograms plots for each trait specified as quantitative and qualitative.

See Also

[hist](#), [geom_histogram](#)

Examples

```
#####
# Use data from R package ccChooser
#####

library(ccChooser)
data("dactylis_CC")
data("dactylis_EC")

ec <- cbind(genotypes = rownames(dactylis_EC), dactylis_EC[, -1])
ec$genotypes <- as.character(ec$genotypes)
rownames(ec) <- NULL
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) cut(x, breaks = 4))
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) factor(as.numeric(x)))

head(ec)

core <- rownames(dactylis_CC)

quant <- c("X2", "X3", "X4", "X5", "X8")
qual <- c("X1", "X6", "X7")

#####
# EvaluateCore
#####

freqdist.evaluate.core(data = ec, names = "genotypes",
                      quantitative = quant, qualitative = qual,
                      selected = core)

checks <- c("D120559", "D120773")

freqdist.evaluate.core(data = ec, names = "genotypes",
                      quantitative = quant, qualitative = qual,
                      selected = core,
                      highlight = checks, highlight.col = "red")
```

```

quant.se <- data.frame(genotypes = checks, X2 = c(0.275, 0.25),
                      X3 = c(0.1, 0.081), X4 = c(0.002, 0.002),
                      X5 = c(0.093, 0.087), X8 = c(0.125, 0.074))

freqdist.evaluate.core(data = ec, names = "genotypes",
                      quantitative = quant,
                      selected = core,
                      highlight = checks, highlight.col = "red",
                      highlight.se = quant.se)

```

iqr.evaluate.core	<i>Interquartile Range</i>
-------------------	----------------------------

Description

Compute the Interquartile Range (IQR) (Upton and Cook 1996) to compare quantitative traits of the entire collection (EC) and core set (CS).

Usage

```
iqr.evaluate.core(data, names, quantitative, selected)
```

Arguments

data	The data as a data frame object. The data frame should possess one row per individual and columns with the individual names and multiple trait/character data.
names	Name of column with the individual names as a character string
quantitative	Name of columns with the quantitative traits as a character vector.
selected	Character vector with the names of individuals selected in core collection and present in the names column.

Value

A data frame with the IQR values of the EC and CS for the traits specified as quantitative.

References

Upton G, Cook I (1996). "General summary statistics." In *Understanding statistics*. Oxford University Press.

See Also

[IQR](#)

Examples

```
#####
# Use data from R package ccChooser
#####

library(ccChooser)
data("dactylis_CC")
data("dactylis_EC")

ec <- cbind(genotypes = rownames(dactylis_EC), dactylis_EC[, -1])
ec$genotypes <- as.character(ec$genotypes)
rownames(ec) <- NULL
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) cut(x, breaks = 4))
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) factor(as.numeric(x)))

head(ec)

core <- rownames(dactylis_CC)

quant <- c("X2", "X3", "X4", "X5", "X8")
qual <- c("X1", "X6", "X7")

#####
# EvaluateCore
#####

iqr.evaluate.core(data = ec, names = "genotypes",
                  quantitative = quant, selected = core)
```

levene.evaluate.core *Levene's Test*

Description

Test for of variances of the entire collection (EC) and core set (CS) for quantitative traits by Levene's test (Levene 1960).

Usage

```
levene.evaluate.core(data, names, quantitative, selected)
```

Arguments

data	The data as a data frame object. The data frame should possess one row per individual and columns with the individual names and multiple trait/character data.
names	Name of column with the individual names as a character string
quantitative	Name of columns with the quantitative traits as a character vector.
selected	Character vector with the names of individuals selected in core collection and present in the names column.

Value

A data frame with the following columns

Trait	The quantitative trait.
EC_V	The variance of the EC.
CS_V	The variance of the CS.
EC_CV	The coefficient of variance of the EC.
CS_CV	The coefficient of variance of the CS.
Levene_Fvalue	The test statistic.
Levene_pvalue	The p value for the test statistic.
Levene_significance	The significance of the test statistic (*: $p \leq 0.01$; **: $p \leq 0.05$; ns: $p > 0.05$).

References

Levene H (1960). "Robust tests for equality of variances." In Olkin I, Ghurye SG, Hoeffding W, Madow WG, Mann HB (eds.), *Contribution to Probability and Statistics: Essays in Honor of Harold Hotelling*, 278–292. Stanford University Press, Palo Alto, CA.

See Also

[leveneTest](#)

Examples

```
#####
# Use data from R package ccChooser
#####

library(ccChooser)
data("dactylis_CC")
data("dactylis_EC")

ec <- cbind(genotypes = rownames(dactylis_EC), dactylis_EC[, -1])
ec$genotypes <- as.character(ec$genotypes)
rownames(ec) <- NULL
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) cut(x, breaks = 4))
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) factor(as.numeric(x)))

head(ec)

core <- rownames(dactylis_CC)

quant <- c("X2", "X3", "X4", "X5", "X8")
qual <- c("X1", "X6", "X7")

#####
# EvaluateCore
#####

levene.evaluate.core(data = ec, names = "genotypes",
                    quantitative = quant, selected = core)
```

pca.evaluate.core *Principal Component Analysis*

Description

Compute Principal Component Analysis Statistics (Mardia et al. 1979) to compare the probability distributions of quantitative traits between entire collection (EC) and core set (CS).

Usage

```
pca.evaluate.core(
  data,
  names,
  quantitative,
  selected,
  center = TRUE,
  scale = TRUE,
  npc.plot = 6
)
```

Arguments

data	The data as a data frame object. The data frame should possess one row per individual and columns with the individual names and multiple trait/character data.
names	Name of column with the individual names as a character string
quantitative	Name of columns with the quantitative traits as a character vector.
selected	Character vector with the names of individuals selected in core collection and present in the names column.
center	either a logical value or numeric-alike vector of length equal to the number of columns of x, where 'numeric-alike' means that <code>as.numeric(.)</code> will be applied successfully if <code>is.numeric(.)</code> is not true.
scale	either a logical value or a numeric-alike vector of length equal to the number of columns of x.
npc.plot	The number of principal components for which eigen values are to be plotted. The default value is 6.

Value

A list with the following components.

EC PC Importance

A data frame of importance of principal components for EC

EC PC Loadings A data frame with eigen vectors of principal components for EC

CS PC Importance

A data frame of importance of principal components for CS

CS PC Loadings A data frame with eigen vectors of principal components for CS

Scree Plot The scree plot of principal components for EC and CS as a ggplot object.

PC Loadings Plot
A plot of the eigen vector values of principal components for EC and CS as specified by npc.plot as a ggplot2 object.

References

Mardia KV, Kent JT, Bibby JM (1979). *Multivariate analysis*. Academic Press, London; New York. ISBN 0-12-471250-9 978-0-12-471250-8 0-12-471252-5 978-0-12-471252-2.

See Also

[prcomp](#)

Examples

```
#####
# Use data from R package ccChooser
#####

library(ccChooser)
data("dactylis_CC")
data("dactylis_EC")

ec <- cbind(genotypes = rownames(dactylis_EC), dactylis_EC[, -1])
ec$genotypes <- as.character(ec$genotypes)
rownames(ec) <- NULL
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) cut(x, breaks = 4))
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) factor(as.numeric(x)))

head(ec)

core <- rownames(dactylis_CC)

quant <- c("X2", "X3", "X4", "X5", "X8")
qual <- c("X1", "X6", "X7")

#####
# EvaluateCore
#####

pca.evaluate.core(data = ec, names = "genotypes",
                  quantitative = quant, selected = core,
                  center = TRUE, scale = TRUE, npc.plot = 4)
```

Description

Compute Kullback-Leibler (Kullback and Leibler 1951), Kolmogorov-Smirnov (Kolmogorov 1933; Smirnov 1948) and Anderson-Darling distances (Anderson and Darling 1952) between the probability distributions of collection (EC) and core set (CS) for quantitative traits.

Usage

```
pdfdist.evaluate.core(data, names, quantitative, selected)
```

Arguments

data	The data as a data frame object. The data frame should possess one row per individual and columns with the individual names and multiple trait/character data.
names	Name of column with the individual names as a character string
quantitative	Name of columns with the quantitative traits as a character vector.
selected	Character vector with the names of individuals selected in core collection and present in the names column.

Value

A data frame with the following columns.

Trait	The quantitative trait.
KL_Distance	The Kullback-Leibler distance (Kullback and Leibler 1951) between EC and CS.
KS_Distance	The Kolmogorov-Smirnov distance (Kolmogorov 1933; Smirnov 1948) between EC and CS.
KS_pvalue	The p value of the Kolmogorov-Smirnov distance.
AD_Distance	Anderson-Darling distance (Anderson and Darling 1952) between EC and CS.
AD_pvalue	The p value of the Anderson-Darling distance.
KS_significance	The significance of the Kolmogorov-Smirnov distance (*: $p \leq 0.01$; **: $p \leq 0.05$; ns: $p > 0.05$).
AD_pvalue	The significance of the Anderson-Darling distance (*: $p \leq 0.01$; **: $p \leq 0.05$; ns: $p > 0.05$).

See Also

[KL.plugin](#), [ks.test](#), [ad.test](#)

Examples

```
#####
# Use data from R package ccChooser
#####

library(ccChooser)
data("dactylis_CC")
data("dactylis_EC")
```

```

ec <- cbind(genotypes = rownames(dactylis_EC), dactylis_EC[, -1])
ec$genotypes <- as.character(ec$genotypes)
rownames(ec) <- NULL
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) cut(x, breaks = 4))
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) factor(as.numeric(x)))

head(ec)

core <- rownames(dactylis_CC)

quant <- c("X2", "X3", "X4", "X5", "X8")
qual <- c("X1", "X6", "X7")

#####
# EvaluateCore
#####

pdfdist.evaluate.core(data = ec, names = "genotypes",
                      quantitative = quant, selected = core)

```

percentdiff.evaluate.core

Percentage Difference of Means and Variances

Description

Compute the following differences between the entire collection (EC) and core set (CS).

- Percentage of significant differences of mean ($MD\%_{Hu}$) (Hu et al. 2000)
- Percentage of significant differences of variance ($VD\%_{Hu}$) (Hu et al. 2000)
- Average of absolute differences between means ($MD\%_{Kim}$) (Kim et al. 2007)
- Average of absolute differences between variances ($VD\%_{Kim}$) (Kim et al. 2007)
- Percentage difference between the mean squared Euclidean distance among accessions ($\bar{d}D\%$) (Studnicki et al. 2013)

Usage

```
percentdiff.evaluate.core(data, names, quantitative, selected, alpha = 0.05)
```

Arguments

data	The data as a data frame object. The data frame should possess one row per individual and columns with the individual names and multiple trait/character data.
names	Name of column with the individual names as a character string
quantitative	Name of columns with the quantitative traits as a character vector.
selected	Character vector with the names of individuals selected in core collection and present in the names column.
alpha	Type I error probability (Significance level) of difference.


```

head(ec)

core <- rownames(dactylis_CC)

quant <- c("X2", "X3", "X4", "X5", "X8")
qual <- c("X1", "X6", "X7")

#####
# EvaluateCore
#####

percentdiff.evaluate.core(data = ec, names = "genotypes",
                          quantitative = quant, selected = core)

```

qq.evaluate.core *Quantile-Quantile Plots*

Description

Plot Quantile-Quantile (QQ) plots (Wilk and Gnanadesikan 1968) to graphically compare the probability distributions of quantitative traits between entire collection (EC) and core set (CS).

Usage

```
qq.evaluate.core(data, names, quantitative, selected)
```

Arguments

data	The data as a data frame object. The data frame should possess one row per individual and columns with the individual names and multiple trait/character data.
names	Name of column with the individual names as a character string
quantitative	Name of columns with the quantitative traits as a character vector.
selected	Character vector with the names of individuals selected in core collection and present in the names column.

Value

A list with the ggplot objects of QQ plots of CS vs EC for each trait specified as quantitative.

References

Wilk MB, Gnanadesikan R (1968). "Probability plotting methods for the analysis for the analysis of data." *Biometrika*, **55**(1), 1–17.

See Also

[qqplot](#)

Examples

```
#####
# Use data from R package ccChooser
#####

library(ccChooser)
data("dactylis_CC")
data("dactylis_EC")

ec <- cbind(genotypes = rownames(dactylis_EC), dactylis_EC[, -1])
ec$genotypes <- as.character(ec$genotypes)
rownames(ec) <- NULL
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) cut(x, breaks = 4))
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) factor(as.numeric(x)))

head(ec)

core <- rownames(dactylis_CC)

quant <- c("X2", "X3", "X4", "X5", "X8")
qual <- c("X1", "X6", "X7")

#####
# EvaluateCore
#####

qq.evaluate.core(data = ec, names = "genotypes",
                 quantitative = quant, selected = core)
```

shannon.evaluate.core *Shannon-Weaver Diversity Index*

Description

Compute the Shannon-Weaver Diversity Index (H'), Maximum diversity (H'_{max}) and Shannon Equitability Index (E_H) (Shannon and Weaver 1949) to compare the phenotypic diversity for qualitative traits between entire collection (EC) and core set (CS).

Usage

```
shannon.evaluate.core(data, names, qualitative, selected)
```

Arguments

data	The data as a data frame object. The data frame should possess one row per individual and columns with the individual names and multiple trait/character data.
names	Name of column with the individual names as a character string
qualitative	Name of columns with the qualitative traits as a character vector.
selected	Character vector with the names of individuals selected in core collection and present in the names column.


```

ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) factor(as.numeric(x)))
head(ec)

core <- rownames(dactylis_CC)

quant <- c("X2", "X3", "X4", "X5", "X8")
qual <- c("X1", "X6", "X7")

#####
# EvaluateCore
#####

shannon.evaluate.core(data = ec, names = "genotypes",
                     qualitative = qual, selected = core)

```

signtest.evaluate.core

Sign Test

Description

Test difference between means and variances of entire collection (EC) and core set (CS) for quantitative traits by Sign test (+ versus -) (Basigalup et al. 1995; Tai and Miller 2001).

Usage

```
signtest.evaluate.core(data, names, quantitative, selected)
```

Arguments

data	The data as a data frame object. The data frame should possess one row per individual and columns with the individual names and multiple trait/character data.
names	Name of column with the individual names as a character string
quantitative	Name of columns with the quantitative traits as a character vector.
selected	Character vector with the names of individuals selected in core collection and present in the names column.

Details

The test statistic for Sign test (χ^2) is computed as follows.

$$\chi^2 = \frac{(N_1 - N_2)^2}{N_1 + N_2}$$

Where, where N_1 is the number of variables for which the mean or variance of the CS is greater than the mean or variance of the EC (number of + signs); N_2 is the number of variables for which the mean or variance of the CS is less than the mean or variance of the EC (number of - signs). The value of χ^2 is compared with a Chi-square distribution with 1 degree of freedom.

Value

A data frame with the following components.

Comparison	The comparison measure.
ChiSq	The test statistic (χ^2).
p.value	The p value for the test statistic.
significance	The significance of the test statistic (*: $p \leq 0.01$; **: $p \leq 0.05$; ns: $p > 0.05$).

References

Basigalup DH, Barnes DK, Stucker RE (1995). "Development of a core collection for perennial *Medicago* plant introductions." *Crop Science*, **35**(4), 1163–1168.

Tai PYP, Miller JD (2001). "A Core Collection for *Saccharum spontaneum* L. from the World Collection of Sugarcane." *Crop Science*, **41**(3), 879–885.

Examples

```
#####
# Use data from R package ccChooser
#####

library(ccChooser)
data("dactylis_CC")
data("dactylis_EC")

ec <- cbind(genotypes = rownames(dactylis_EC), dactylis_EC[, -1])
ec$genotypes <- as.character(ec$genotypes)
rownames(ec) <- NULL
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) cut(x, breaks = 4))
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) factor(as.numeric(x)))

head(ec)

core <- rownames(dactylis_CC)

quant <- c("X2", "X3", "X4", "X5", "X8")
qual <- c("X1", "X6", "X7")

#####
# EvaluateCore
#####

signtest.evaluate.core(data = ec, names = "genotypes",
                      quantitative = quant, selected = core)
```

 snk.evaluate.core *Student-Newman-Keuls Test*

Description

Test difference between means of entire collection (EC) and core set (CS) for quantitative traits by Newman-Keuls or Student-Newman-Keuls test (Newman 1939; Keuls 1952).

Usage

```
snk.evaluate.core(data, names, quantitative, selected)
```

Arguments

data	The data as a data frame object. The data frame should possess one row per individual and columns with the individual names and multiple trait/character data.
names	Name of column with the individual names as a character string
quantitative	Name of columns with the quantitative traits as a character vector.
selected	Character vector with the names of individuals selected in core collection and present in the names column.

Value

A data frame with the following components.

Trait	The quantitative trait.
EC_Min	The minimum value of the trait in EC.
EC_Max	The maximum value of the trait in EC.
EC_Mean	The mean value of the trait in EC.
EC_SE	The standard error of the trait in EC.
CS_Min	The minimum value of the trait in CS.
CS_Max	The maximum value of the trait in CS.
CS_Mean	The mean value of the trait in CS.
CS_SE	The standard error of the trait in CS.
SNK_pvalue	The p value of the Student-Newman-Keuls test for equality of means of EC and CS.
SNK_significance	The significance of the Student-Newman-Keuls test for equality of means of EC and CS.

References

Keuls M (1952). "The use of the „studentized range" in connection with an analysis of variance." *Euphytica*, **1**(2), 112–122.

Newman D (1939). "The distribution of range in samples from a normal population, expressed in terms of an independent estimate of standard deviation." *Biometrika*, **31**(1-2), 20–30.

See Also[SNK.test](#)**Examples**

```
#####
# Use data from R package ccChooser
#####

library(ccChooser)
data("dactylis_CC")
data("dactylis_EC")

ec <- cbind(genotypes = rownames(dactylis_EC), dactylis_EC[, -1])
ec$genotypes <- as.character(ec$genotypes)
rownames(ec) <- NULL
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) cut(x, breaks = 4))
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) factor(as.numeric(x)))

head(ec)

core <- rownames(dactylis_CC)

quant <- c("X2", "X3", "X4", "X5", "X8")
qual <- c("X1", "X6", "X7")

#####
# EvaluateCore
#####

snk.evaluate.core(data = ec, names = "genotypes",
                  quantitative = quant, selected = core)
```

ttest.evaluate.core *Student's t Test*

Description

Test difference between means of entire collection (EC) and core set (CS) for quantitative traits by Student's t test (Student 1908).

Usage

```
ttest.evaluate.core(data, names, quantitative, selected)
```

Arguments

data The data as a data frame object. The data frame should possess one row per individual and columns with the individual names and multiple trait/character data.

names	Name of column with the individual names as a character string
quantitative	Name of columns with the quantitative traits as a character vector.
selected	Character vector with the names of individuals selected in core collection and present in the names column.

Value

Trait	The quantitative trait.
EC_Min	The minimum value of the trait in EC.
EC_Max	The maximum value of the trait in EC.
EC_Mean	The mean value of the trait in EC.
EC_SE	The standard error of the trait in EC.
CS_Min	The minimum value of the trait in CS.
CS_Max	The maximum value of the trait in CS.
CS_Mean	The mean value of the trait in CS.
CS_SE	The standard error of the trait in CS.
ttest_pvalue	The p value of the Student's t test for equality of means of EC and CS.
ttest_significance	The significance of the Student's t test for equality of means of EC and CS.

References

Student (1908). "The probable error of a mean." *Biometrika*, **6**(1), 1–25.

See Also

[t.test](#)

Examples

```
#####
# Use data from R package ccChooser
#####

library(ccChooser)
data("dactylis_CC")
data("dactylis_EC")

ec <- cbind(genotypes = rownames(dactylis_EC), dactylis_EC[, -1])
ec$genotypes <- as.character(ec$genotypes)
rownames(ec) <- NULL
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) cut(x, breaks = 4))
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) factor(as.numeric(x)))

head(ec)

core <- rownames(dactylis_CC)

quant <- c("X2", "X3", "X4", "X5", "X8")
qual <- c("X1", "X6", "X7")
```

```
#####
# EvaluateCore
#####

ttest.evaluate.core(data = ec, names = "genotypes",
                    quantitative = quant, selected = core)
```

vr.evaluate.core *Variable Rate of Coefficient of Variation*

Description

Compute the Variable Rate of Coefficient of Variation (VR) (Hu et al. 2000) to compare quantitative traits of the entire collection (EC) and core set (CS).

Usage

```
vr.evaluate.core(data, names, quantitative, selected)
```

Arguments

data	The data as a data frame object. The data frame should possess one row per individual and columns with the individual names and multiple trait/character data.
names	Name of column with the individual names as a character string
quantitative	Name of columns with the quantitative traits as a character vector.
selected	Character vector with the names of individuals selected in core collection and present in the names column.

Details

The Variable Rate of Coefficient of Variation (VR) is computed as follows.

$$VR = \left(\frac{1}{n} \sum_{i=1}^n \frac{CV_{CS_i}}{CV_{EC_i}} \right) \times 100$$

Where, CV_{CS_i} is the coefficients of variation for the i th trait in the CS, CV_{EC_i} is the coefficients of variation for the i th trait in the EC and n is the total number of traits

Value

The VR value.

References

Hu J, Zhu J, Xu HM (2000). "Methods of constructing core collections by stepwise clustering with three sampling strategies based on the genotypic values of crops." *Theoretical and Applied Genetics*, **101**(1), 264–268.

Examples

```
#####
# Use data from R package ccChooser
#####

library(ccChooser)
data("dactylis_CC")
data("dactylis_EC")

ec <- cbind(genotypes = rownames(dactylis_EC), dactylis_EC[, -1])
ec$genotypes <- as.character(ec$genotypes)
rownames(ec) <- NULL
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) cut(x, breaks = 4))
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) factor(as.numeric(x)))

head(ec)

core <- rownames(dactylis_CC)

quant <- c("X2", "X3", "X4", "X5", "X8")
qual <- c("X1", "X6", "X7")

#####
# EvaluateCore
#####

vr.evaluate.core(data = ec, names = "genotypes",
                 quantitative = quant, selected = core)
```

wilcox.evaluate.core *Wilcoxon Rank Sum Test*

Description

Compare the medians of quantitative traits between entire collection (EC) and core set (CS) by Wilcoxon rank sum test or Mann-Whitney-Wilcoxon test or Mann-Whitney U test (Wilcoxon 1945; Mann and Whitney 1947).

Usage

```
wilcox.evaluate.core(data, names, quantitative, selected)
```

Arguments

data	The data as a data frame object. The data frame should possess one row per individual and columns with the individual names and multiple trait/character data.
names	Name of column with the individual names as a character string
quantitative	Name of columns with the quantitative traits as a character vector.
selected	Character vector with the names of individuals selected in core collection and present in the names column.

Value

Trait	The quantitative trait.
EC_Med	The median value of the trait in EC.
CS_Med	The median value of the trait in CS.
Wilcox_pvalue	The p value of the Wilcoxon test for equality of medians of EC and CS.
Wilcox_significance	The significance of the Wilcoxon test for equality of medians of EC and CS.

References

Mann HB, Whitney DR (1947). "On a test of whether one of two random variables is stochastically larger than the other." *The Annals of Mathematical Statistics*, **18**(1), 50–60.

Wilcoxon F (1945). "Individual comparisons by ranking methods." *Biometrics Bulletin*, **1**(6), 80.

See Also

[wilcox.test](#)

Examples

```
#####
# Use data from R package ccChooser
#####

library(ccChooser)
data("dactylis_CC")
data("dactylis_EC")

ec <- cbind(genotypes = rownames(dactylis_EC), dactylis_EC[, -1])
ec$genotypes <- as.character(ec$genotypes)
rownames(ec) <- NULL
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) cut(x, breaks = 4))
ec[, c("X1", "X6", "X7")] <- lapply(ec[, c("X1", "X6", "X7")],
                                   function(x) factor(as.numeric(x)))

head(ec)

core <- rownames(dactylis_CC)

quant <- c("X2", "X3", "X4", "X5", "X8")
qual <- c("X1", "X6", "X7")

#####
# EvaluateCore
#####

wilcox.evaluate.core(data = ec, names = "genotypes",
                    quantitative = quant, selected = core)
```

Index

ad.test, [20](#)
as.numeric, [18](#)

bar.evaluate.core, [2](#)
barplot, [3](#)
box.evaluate.core, [3](#)
boxplot, [4](#)

chisq.test, [6](#)
chisquare.evaluate.core, [5](#)
cor, [7](#)
cor_pmat, [7](#)
corr.evaluate.core, [6](#)
coverage.evaluate.core, [8](#)
cr.evaluate.core, [9](#)

dist.evaluate.core, [11](#)

evaluateCore, [12](#)

freqdist.evaluate.core, [13](#)

geom_bar, [3](#)
geom_boxplot, [4](#)
geom_histogram, [14](#)
ggcorrplot, [7](#)

hist, [14](#)

IQR, [15](#)
iqr.evaluate.core, [15](#)
is.numeric, [18](#)

KL.plugin, [20](#)
ks.test, [20](#)

levene.evaluate.core, [16](#)
leveneTest, [17](#)

mantel, [7](#)

pca.evaluate.core, [18](#)
pdfdist.evaluate.core, [19](#)
percentdiff.evaluate.core, [21](#)
prcomp, [19](#)

qq.evaluate.core, [23](#)
qqplot, [23](#)

shannon, [25](#)
shannon.evaluate.core, [24](#)
signtest.evaluate.core, [26](#)
snk.evaluate.core, [22, 28](#)
SNK.test, [29](#)

t.test, [30](#)
ttest.evaluate.core, [29](#)

vr.evaluate.core, [31](#)

wilcox.evaluate.core, [32](#)
wilcox.test, [10, 33](#)