

Package ‘FIESTAutils’

August 7, 2022

Type Package

Title Utility Functions for Forest Inventory Estimation and Analysis

Version 1.1.3

Date 2022-08-06

Description A set of tools for data wrangling, spatial data analysis, statistical modeling (including direct, model-assisted, photo-based, and small area tools), and USDA Forest Service data base tools. These tools are aimed to help Foresters, Analysts, and Scientists extract and perform analyses on USDA Forest Service data.

Depends R (>= 3.5.0)

Imports data.table, DBI, graphics, hbsae, JoSAE, mase, methods, nlme, Rcpp, RColorBrewer, rgdal, RPostgreSQL, RSQLite, sae, sf, sp, sqldf, stats, units, utils, xml2, largeList

Suggests knitr

License GPL-3

Copyright See file COPYRIGHTS for details.

URL <https://github.com/USDAForestService/FIESTAutils>

BugReports <https://github.com/USDAForestService/FIESTAutils/issues>

Encoding UTF-8

LazyData true

LinkingTo Rcpp

RoxygenNote 7.2.0

NeedsCompilation yes

Author Tracey Frescino [aut],
Chris Toney [aut],
Grayson White [aut, cre]

Maintainer Grayson White <graysonwhite13@gmail.com>

Repository CRAN

Date/Publication 2022-08-07 03:40:02 UTC

R topics documented:

datExportData	2
DBtestPostgreSQL	3
DBtestSQLite	4
DEFAULT_NODATA	5
GDT_NAMES	5
kindcd3old	5
multest_options	6
rasterToVRT	7
Rcpp_CmbTable-class	8
Rcpp_RunningStats-class	9
ref_codes	9
ref_diacl2in	10
ref_domain	10
ref_estvar	10
ref_statecd	11
savedata_options	11
spMakeSpatial_options	13
strata_options	14
stunitco	15
table_options	16
title_options	18
unit_options	20
Index	21

datExportData	<i>Spatial - Exports a data frame object.</i>
---------------	---

Description

Exports a data frame object to a specified output.

Usage

```
datExportData(
  dfobj,
  create_dsn = FALSE,
  index.unique = NULL,
  index = NULL,
  savedata_opts = savedata_options()
)
```

Arguments

dfobj	Data.frame class R object. Data frame object to export.
create_dsn	Boolean.
index.unique	String. Name of variable(s) in dfobj to make unique index.
index	String. Name of variable(s) in dfobj to make (non-unique) index.
savedata_opts	List. See help(savedata_options()) for a list of options.

Details

Wrapper for sf::st_write function.

Value

An sf spatial object is written to the out_dsn.

Note

If out_fmt='shp':

The ESRI shapefile driver truncates variable names to 10 characters or less. Variable names are changed before export using an internal function (trunc10shp). Name changes are output to the outfolder, 'outshpnm'_newnames.csv.

If sf object has more than 1 record, it cannot be exported to a shapefile.

Author(s)

Tracey S. Frescino

DBtestPostgreSQL *Database - Test a SQLite database table.*

Description

Checks a SQLite database.

Usage

```
DBtestPostgreSQL(dbname, dbconnopen = TRUE)
```

Arguments

dbname	String. Name of PostgreSQL database.
dbconnopen	Logical. If TRUE, the dbconn connection is not closed.

Value

An S4 object that inherits from DBIConnection via the DBI package. For more information, see 'help(DBI::dbConnect)'.

Author(s)

Tracey S. Frescino

DBtestSQLite

*Database - Checks access to a SQLite database.***Description**

Checks a SQLite database.

Usage

```
DBtestSQLite(
  SQLitefn = NULL,
  gpkg = FALSE,
  dbconnopen = FALSE,
  outfolder = NULL,
  showlist = TRUE,
  returnpath = TRUE,
  createnew = TRUE,
  stopifnull = FALSE,
  overwrite = TRUE
)
```

Arguments

SQLitefn	String. Name of SQLite database (*.sqlite).
gpkg	Logical. If TRUE, Sqlite geopackage database.
dbconnopen	Logical. If TRUE, the dbconn connection is not closed.
outfolder	String. Optional. Name of output folder. If NULL, export to working directory.
showlist	Logical. If TRUE, shows list of tables in database.
returnpath	Logical. If TRUE, returns full path to SQLite file name. If FALSE, returns SQLitefn.
createnew	If TRUE, creates new SQLite database.
stopifnull	Logical. If TRUE, stops if SQLite database doesn't exist.
overwrite	Logical. If TRUE, overwrites data.

Value

Character string containing the path to the SQLite database of interest.

Author(s)

Tracey S. Frescino

DEFAULT_NODATA	<i>Reference tables - NODATA Values.</i>
----------------	--

Description

List of NODATA Values based on data type.

Format

A list of 6 components.

Source

gdal values.

GDT_NAMES	<i>Reference tables - gdal data types.</i>
-----------	--

Description

Table with gdal data type names.

Format

A vector of 12 data type values.

Source

gdal values.

kindcd3old	<i>Reference table - List of RMRS plots that have fallen out of inventory because they were not found or they were in the wrong place.</i>
------------	--

Description

Table with variable codes (VALUE) and descriptions (MEANING).

Format

A dataframe

Source

```
FIA query. SELECT bp.STATECD, bp.COUNTYCD, bp.PLOT_FIADB NEW_PLOT, bp.START_DATE
NEW_START_DATE, bp_old.COUNTYCD OLD_COUNTYCD, bp_old.PLOT_FIADB OLD_PLOT,
bp_old.END_DATE OLD_END_DATE, p.CN FROM fs_nims_rmrs.NIMS_BASE_PLOT bp JOIN
fs_nims_rmrs.NIMS_BASE_PLOT bp_old on (bp.PREV_NBP_CN=bp_old.CN) JOIN fs_nims_rmrs.NIMS_PLOT_RMRS
p on(p.NBP_CN=bp_old.CN) WHERE p.KINDCD = 1 ORDER BY bp.STATECD, bp.COUNTYCD,
bp_old.PLOT_FIADB"
```

multest_options	<i>Multest output options.</i>
-----------------	--------------------------------

Description

Returns a list of user-supplied parameters and parameter values for outputting multest with custom aesthetics.

Usage

```
multest_options(
  multest_fmt = "csv",
  multest_outfolder = NULL,
  multest_dsn = NULL,
  multest_layer = NULL,
  multest.append = FALSE,
  multest.AOIonly = FALSE,
  ...
)
```

Arguments

multest_fmt	String. Format for multest output tables ('csv', 'sqlite', 'gpkg').
multest_outfolder	String. Outfolder for multest. If NULL, same as outfolder.
multest_dsn	String. Name of database if multest_fmt = c('sqlite', 'gpkg').
multest_layer	String. Name of database layer if multest_fmt = c('sqlite', 'gpkg').
multest.append	Logical. If TRUE, appends multest dataframe to output.
multest.AOIonly	Logical. If TRUE, appends multest dataframe (AOI=1) to output.
...	For extensibility.

Details

If no parameters, an empty list is returned.

Value

A list of user-supplied parameters and parameter values for outputting multest.

Author(s)

Grayson W. White

Examples

```
multest_options(multest.append = TRUE)
```

rasterToVRT

Write a GDAL virtual raster file (VRT)

Description

Write a GDAL VRT file for a source raster with options for repositioning and and resampling the source data at a different pixel resolution

Usage

```
rasterToVRT(
  srcfile,
  relativeToVRT = 0,
  vrtfile = tempfile("tmprast", fileext = ".vrt"),
  resolution = NULL,
  subwindow = NULL,
  align = TRUE,
  resampling = "nearest"
)
```

Arguments

srcfile	Source raster file name.
relativeToVRT	Integer. Should srcfile be interpreted as relative to the .vrt file (value is 1) or not relative to the .vrt file (value is 0)? If value is 1, the .vrt file is assumed to be in the same directory as srcfile and basename(srcfile) is used in .vrt.
vrtfile	Output VRT file name.
resolution	A numeric vector of length two, with xres, yres. The pixel size must be expressed in georeferenced units. Both must be positive values. The source pixel size is used if resolution is not specified.

subwindow	A numeric vector of length four, with xmin, ymin, xmax and ymax values (e.g., <code>sp::bbox</code> or <code>sf::st_bbox</code>). Selects a subwindow of the source raster with corners given in georeferenced coordinates (in the source CRS). If not given, the upper left corner of the VRT will be the same as source, and the VRT extent will be the same or larger than source depending on resolution.
align	Logical scalar. If TRUE, the upper left corner of the VRT extent will be set to the upper left corner of the source pixel that contains subwindow xmin, ymax. The VRT will be pixel-aligned with source if the VRT resolution is the same as the source pixel size, otherwise VRT extent will be the minimum rectangle that contains subwindow for the given pixel size. If FALSE, the VRT upper left corner be exactly subwindow xmin, ymax, and the VRT extent will be the minimum rectangle that contains subwindow for the given pixel size. If subwindow is not given, the source window is the source raster extent in which case align=FALSE has no effect.
resampling	The resampling method to use if xsize, ysize of the VRT is different from the size of the underlying source rectangle (in number of pixels). The values allowed are nearest, bilinear, cubic, cubicspline, lanczos, average and mode.

Details

`rasterToVRT` is useful for virtually clipping a raster to a subwindow, or virtually resampling at a different pixel resolution. The output VRT file will have the same coordinate system as the source raster.

Rcpp_CmbTable-class *Class "Rcpp_CmbTable"*

Description

C++ program to combine raster files.

Extends

Class "[C++Object](#)", directly.

All reference classes extend and inherit methods from "[envRefClass](#)".

Author(s)

Chris Toney

Rcpp_RunningStats-class
Class "Rcpp_RunningStats"

Description

C++ program to calculate mean and variance on a data stream.

Extends

Class "[C++Object](#)", directly.

All reference classes extend and inherit methods from "[envRefClass](#)".

Author(s)

Chris Toney

ref_codes	<i>Reference tables - Code definitions.</i>
-----------	---

Description

Table with variable codes (VALUE) and descriptions (MEANING).

Format

A dataframe with 7 columns, VARIABLE, VALUE, MEANING, COLORHEX, GROUP, GROUPNM, GROUPHEX.

Source

FIA look-up tables.

References

O'Connell, B.M.; LaPoint, E.B.; Turner, J.A.; Ridley, T.; Boyer, D.; Wilson, A.M.; Waddell, K.L.; Christensen, G.; Conkling, B.L. 2012. The Forest Inventory and Analysis Database: Database Description and Users Manual Version 5.1.2 for Phase 2. U.S. Department of Agriculture. (http://fia.fs.fed.us/library/database-documentation/current/ver5-2012/FIADB_user_manual_5-1-2_p2_07_2012.pdf)

ref_diacl2in	<i>Reference table - diameter 2-inch class codes (DIA).</i>
--------------	---

Description

Table with min (MIN), max (MAX), and 2-inch class diameter codes (MEANING).

Format

A dataframe with 3 columns, MIN, MAX, and MEANING.

Source

Imported from comma-delimited file.

References

O'Connell, B.M.; LaPoint, E.B.; Turner, J.A.; Ridley, T.; Boyer, D.; Wilson, A.M.; Waddell, K.L.; Christensen, G.; Conkling, B.L. 2012. The Forest Inventory and Analysis Database: Database Description and Users Manual Version 5.1.2 for Phase 2. U.S. Department of Agriculture. (http://fia.fs.fed.us/library/database-documentation/current/ver5-2012/FIADB_user_manual_5-1-2_p2_07_2012.pdf)

ref_domain	<i>Reference table - for generating tables.</i>
------------	---

Description

Table with row/column domain (VARNM) and their pretty names for table output (TABLENM).

Format

A dataframe with 2 columns, VARNM and TABLENM.

Source

FIA look-up table.

ref_estvar	<i>Reference table - for generating estimates</i>
------------	---

Description

Data frame with variable names and descriptions

Format

A data frame to use a reference for estimation variables and filters.

ref_statecd	<i>Reference table - state codes (STATECD).</i>
-------------	---

Description

Table with state codes (VALUE), name (MEANING), abbreviation (ABBR), and UNIT.

Format

A dataframe with 4 columns, VALUE, MEANING, ABBR, UNIT.

Source

Imported from comma-delimited file.

References

O'Connell, B.M.; LaPoint, E.B.; Turner, J.A.; Ridley, T.; Boyer, D.; Wilson, A.M.; Waddell, K.L.; Christensen, G.; Conkling, B.L. 2012. The Forest Inventory and Analysis Database: Database Description and Users Manual Version 5.1.2 for Phase 2. U.S. Department of Agriculture. (http://fia.fs.fed.us/library/database-documentation/current/ver5-2012/FIADB_user_manual_5-1-2_p2_07_2012.pdf)

savadata_options	<i>Data saving options.</i>
------------------	-----------------------------

Description

Returns a list of user-supplied parameters and parameter values for saving data.

Usage

```
savadata_options(
  outfolder = NULL,
  out_fmt = "csv",
  outsp_fmt = "shp",
  outobj_fmt = "rds",
  out_dsn = NULL,
  out_layer = "outdat",
  outfn.pre = NULL,
  outfn.date = FALSE,
  addtitle = TRUE,
  raw_fmt = "csv",
  raw_dsn = NULL,
  overwrite_dsn = FALSE,
  overwrite_layer = TRUE,
  append_layer = FALSE,
```

```

    add_layer = TRUE,
    layer.pre = NULL,
    ...
)

```

Arguments

outfolder	String. The outfolder to write files to. If NULL, files are written to working directory, or if gui=TRUE, a window to browse.
out_fmt	String. Format for output tables ('csv', 'sqlite', 'gpkg', 'gdb').
outsp_fmt	String. Format for output spatial ('shp', 'sqlite', 'gpkg', 'gdb').
outobj_fmt	String. Format for output spatial ('rda', 'rds', 'llo').
out_dsn	String. Data source name for output. If extension is not included, out_fmt is used. Use full path if outfolder=NULL.
out_layer	outlayer.
outfn.pre	String. If savedata=TRUE, prefix for output files. If rawdata=TRUE, prefix for rawdata files (if raw_fmt = 'csv') or raw_dsn (if raw_fmt != 'csv').
outfn.date	Logical. If TRUE, add current date to out_dsn.
addtitle	Logical. If TRUE and savedata=TRUE, adds title to outfile.
raw_fmt	String. Format for output rawdata tables ('sqlite', 'gpkg', 'csv', 'gdb').
raw_dsn	String. Data source name for rawdata output. If extension is not included, out_fmt is used. Use full path if outfolder=NULL.
overwrite_dsn	Logical. If TRUE, overwrites raw_dsn, if exists.
overwrite_layer	Logical. If TRUE, overwrites the output. If rawdata=TRUE, overwrites out_layer in rawdata folder (if raw_fmt = 'csv') or out_layers in raw_dsn (if raw_fmt != 'csv').
append_layer	Logical. If TRUE, and appends data to existing *.csv files (if *_fmt = 'csv') or *_dsn layers (if *_fmt != 'csv').
add_layer	Logical. If TRUE, adds layer to an existing out_dsn (if out_fmt != c('csv', 'shp')).
layer.pre	Layer prefix.
...	For extensibility.

Details

If no parameters, an empty list is returned.

Value

A list of user-supplied parameters and parameter values for saving data.

Author(s)

Grayson W. White

Examples

```
savedata_options(outfolder = "path", overwrite_dsn = FALSE)
```

spMakeSpatial_options *Make SpatialPoints options*

Description

Returns a list of user-supplied parameters and parameter values for making SpatialPoints.

Usage

```
spMakeSpatial_options(
  xvar = NULL,
  yvar = NULL,
  xy.crs = 4269,
  prj = NULL,
  datum = NULL,
  zone = NULL,
  zones = FALSE,
  aea.param = "USGS",
  ...
)
```

Arguments

xvar	String. Name of variable in xyplt defining x coordinate.
yvar	String. Name of variable in xyplt defining y coordinate.
xy.crs	PROJ.4 String or CRS object or Integer EPSG code defining Coordinate Reference System. (e.g., EPSG:4269-Geodetic coordinate system for North America, NAD83).
prj	String. Projection, or coordinate system of the X/Y coordinates ("longlat", "utm", "aea"). If other, include PROJ.4 string in prj4str.
datum	String. Datum of projection ("WGS84", "NAD83", "NAD27").
zone	Integer. If prj="utm", the UTM zone.
zones	Logical. If prj="utm", if the UTM zone is in the Southern hemisphere.
aea.param	String. If prj="aea", the associated lat/lon parameters (USGS: " +lat_1=29.5 +lat_2=45.5 +lat_0=23 +lon_0=-96 +x_0=0 +y_0=0"). If other, include PROJ.4 string in prj4str.
...	For extensibility.

Details

If no parameters, an empty list is returned.

Value

A list of user-supplied parameters and parameter values for strata.

Author(s)

Grayson W. White

Examples

```
spMakeSpatial_options()
```

strata_options	<i>Strata options.</i>
----------------	------------------------

Description

Returns a list of user-supplied parameters and parameter values for strata.

Usage

```
strata_options(  
  getwt = FALSE,  
  getwtvar = "P1POINTCNT",  
  strwtvar = "strwt",  
  stratcombine = TRUE,  
  minplotnum.strat = 2,  
  pivot = FALSE,  
  nonresp = FALSE,  
  ...  
)
```

Arguments

getwt	Logical. If TRUE, calculates strata weights from stratlut getwtvar. If FALSE, strwtvar variable must be in stratlut.
getwtvar	String. If getwt=TRUE, name of variable in stratlut to calculate weights (Default = 'P1POINTCNT').
strwtvar	String. If getwt=FALSE, name of variable in stratlut with calculated weights (Default = 'strwt').
stratcombine	Logical. If TRUE, and strata=TRUE, automatically combines strata categories if less than minplotnum.strat plots in any one stratum. See notes for more info.

<code>minplotnum.strat</code>	Integer. Minimum number of plots for a stratum within an estimation unit.
<code>pivot</code>	Logical. If TRUE, pivot stratalut.
<code>nonresp</code>	Logical. If TRUE, uses Westfall variance methods.
<code>...</code>	For extendibility.

Details

If no parameters, an empty list is returned.

Value

A list of user-supplied parameters and parameter values for strata.

Author(s)

Grayson W. White

Examples

```
strata_options(getwt = FALSE)
```

<code>stunitco</code>	<i>SpatialPolygonsDataFrame with FIA state, unit, county codes and names</i>
-----------------------	--

Description

Polygon feature class with state and county boundaries defined by Census Bureau, including Federal Information Processing Standards (FIPS) codes. The FIA Survey Unit code and name attributes (UNITCD, UNITNM) were appended to dataset, with joining columns of STATECD and COUNTYCD.

Format

A `SpatialPolygonsDataFrame` with 3233 features and 8 attributes
 RS - FIA Research Station name
 RSCD - FIA Research Station code
 STATECD - FIPS state code
 STATENM - FIPS state name
 STATEAB - FIPS state abbreviation
 UNITCD - FIA survey unit code
 UNITNM - FIA survey unit name
 COUNTYCD - FIPS county code
 COUNTYNM - FIPS county name

Details

Derived from cb_2018_us_county_5m. STATEFP was converted to numeric and named STATECD
 COUNTYFP was converted to numeric and named COUNTYCD
 Lookup table for FIA Research Station (REF_RESEARCH_STATION) was downloaded from FIA DataMart on 20191105 (FI-ADB_1.6.1.00) and joined by STATECD. A lookup table for UNITCD was created from plot data using unique STATECD, COUNTYCD, UNITCD and joined to table.

Converted to simple feature

Transformed CRS from longlat(EPSTG:4269) to Albers (EPSTG:5070)

Saved to R object, with compression='xz'

Source

Downloaded from the United States Census Bureau on 2019 November 3, format Esri Shapefile (<https://www.census.gov/geographies/mapping-files/time-series/geo/carto-boundary-file.html>) Projection: Geographic (GCS_North_American_1983) EPSTG: 4269

table_options	<i>Table aesthetics and output options.</i>
---------------	---

Description

Returns a list of user-supplied parameters and parameter values for outputting tables with custom aesthetics.

Usage

```
table_options(
  row.FIAname = FALSE,
  col.FIAname = FALSE,
  row.orderby = NULL,
  col.orderby = NULL,
  row.add0 = FALSE,
  col.add0 = FALSE,
  rowlut = NULL,
  collut = NULL,
  rawonly = FALSE,
  raw.keep0 = FALSE,
  rowgrp = FALSE,
  rowgrpnm = NULL,
  rowgrpord = NULL,
  totals = TRUE,
  allin1 = FALSE,
  metric = FALSE,
  estround = 1,
  pseround = 2,
  estnull = "--",
```



```

    psnull = "--",
    divideby = NULL,
    ...
)

```

Arguments

row.FIAname	Logical. If TRUE, retrieves default FIA reference names for rowvar located in ref_codes data frame. Names are only available for certain variables (Check <code>sort(unique(ref_codes\$VARIABLE))</code> for available names. If row.FIAname = TRUE and rowvar is in ref_codes, the rowvar name is used for the output table, and the rowvar code is used to sort.
col.FIAname	Logical. If TRUE, retrieves default FIA reference names for colvar located in ref_codes data frame. Names are only available for certain variables. Check: <code>sort(unique(ref_codes\$VARIABLE))</code> for available names. If col.FIAname = TRUE and rowvar is in ref_codes, the colvar name is used for the output table, and the colvar code is used to sort.
row.orderby	String. Optional. Name of variable to sort table rows. Both the rowvar and row.orderby variables must be included in the same input data.frame. if NULL, and row.FIAname=FALSE or rowvar is not in ref_codes, the rows are ordered by rowvar.
col.orderby	String. Optional. Name of variable to sort table columns. Both the colvar and col.orderby variables must be included in the same input data.frame. if NULL, and col.FIAname=FALSE or colvar is not in ref_codes, the columns are ordered by colvar.
row.add0	Logical. If TRUE, include rows with 0 values to the output table.
col.add0	Logical. If TRUE, include columns with 0 values to the output table.
rowlut	Data frame. A lookup table with variable codes and code names to include as rows of output table (See notes for more information and format).
collut	Data frame. A lookup table with variable codes and code names to include as columns of output table (See notes for more information and format).
rawonly	Logical. If TRUE, only rawdata are output. If dataset includes many estimation units, and only raw data tables are desired, it is more efficient to output raw data only.
raw.keep0	Logical. If TRUE, keep 0 values in raw data tables.
rowgrp	Logical. If TRUE, appends row groups to first column of table. Only available if group category exists in ref_codes table or defined in rowgrpnm (e.g., FORTYPGRPCD, OWNGRPCD).
rowgrpnm	String. Name of variable for grouping rowvar. Variable must be included in same input table as rowvar.
rowgrpord	String. Name of variable to sort row group variable. Variable must be included in same input table as rowgrpnm.
totals	Logical. If TRUE, returns total estimate (mean * AREAUSED).
allin1	Logical. If TRUE, both estimates and percent sample error are output in one table as: estimates (percent sample error).

metric	Logical. If TRUE, output if returned in metric units.
estround	Integer. Number of decimal places for estimates.
pseround	Integer. Number of decimal places for percent sampling error.
estnull	Number or character. The number or symbol to use to indicate 'not sampled' for estimate.
psenull	Number or character. The number or symbol to use to indicate 'not sampled' for percent standard error.
divideby	String. Conversion number for output ('hundred', 'thousand', 'million').
...	For extensibility.

Details

If no parameters, an empty list is returned.

Value

A list of user-supplied parameters and parameter values for outputting tables with custom aesthetics.

Author(s)

Grayson W. White

Examples

```
table_options(row.FIAname = TRUE, col.FIAname = TRUE)
```

title_options	<i>Title output options.</i>
---------------	------------------------------

Description

Returns a list of user-supplied parameters and parameter values for outputting title with custom aesthetics.

Usage

```
title_options(
  title.main = NULL,
  title.ref = NULL,
  title.rowvar = NULL,
  title.colvar = NULL,
  title.unitvar = NULL,
  title.estvar = NULL,
  title.estvarn = NULL,
```

```

    title.filter = NULL,
    title.units = "acres",
    ...
)

```

Arguments

title.main	String. TITLE, if savedata=TRUE and/or returntitle=TRUE: the complete title used for table. If title.main=NULL, the title.* parameters are used to generate title string. Note: if title.ref is not NULL, it is added to title.main.
title.ref	String. TITLE, if savedata=TRUE and/or returntitle=TRUE: the ending text of the table title (e.g., Nevada, 2004-2005). If NULL, = "".
title.rowvar	String. TITLE, if savedata=TRUE and/or returntitle=TRUE: pretty name for the row domain variable. If NULL, = rowvar.
title.colvar	String. TITLE, if savedata=TRUE and/or returntitle=TRUE: pretty name for the column domain variable. If NULL, = colvar.
title.unitvar	String. TITLE, if savedata=TRUE and/or returntitle=TRUE: pretty name for the estimation unit variable. If NULL, = unitvar.
title.estvar	String. TITLE: if savedata=TRUE and/or returntitle=TRUE: pretty name for the estimate variable. If NULL, title.estvar = estvar.name.
title.estvarn	String. TITLE: if savedata=TRUE and/or returntitle=TRUE: pretty name for the estimate variable. If NULL, title.estvar = estvar.name.
title.filter	String. TITLE, if savedata=TRUE and/or returntitle=TRUE: pretty name for filter(s). If title.filter=NULL, a default is generated from cfilter. If title.filter="", no title.filter is used.
title.units	String.
...	For extendibility.

Details

If no parameters, an empty list is returned.

Value

A list of user-supplied parameters and parameter values for outputting titles with custom aesthetics.

Author(s)

Grayson W. White

Examples

```
title_options(title.main = "My fancy title", title.estvar = "Estimate title")
```

unit_options	<i>Unit options.</i>
--------------	----------------------

Description

Returns a list of user-supplied parameters and parameter values for unit.

Usage

```
unit_options(
  unitvar2 = NULL,
  areaunits = "acres",
  minplotnum.unit = 10,
  unit.action = "keep",
  npixelvar = "npixels",
  ...
)
```

Arguments

unitvar2	String. Name of a second level estimation unit variable in unitarea and cond or pltassgn with assignment for each plot (e.g., 'STATECD').
areaunits	String. Units of areavar in unitarea ('acres', 'hectares').
minplotnum.unit	Integer. Minimum number of plots for estimation unit.
unit.action	String. What to do if number of plots in an estimation unit is less than minplotnum.unit ('keep', 'remove' 'combine'). If unit.action='combine', combines estimation unit to the following estimation unit, ordered in unitzonal or stratalut.
npixelvar	String. Name of variable in unitlut defining number of pixels by estimation unit.
...	For extensibility.

Details

If no parameters, an empty list is returned.

Value

A list of user-supplied parameters and parameter values for strata.

Author(s)

Grayson W. White

Examples

```
unit_options()
```

Index

* classes

Rcpp_CmbTable-class, 8
Rcpp_RunningStats-class, 9

* datasets

DEFAULT_NODATA, 5
GDT_NAMES, 5
kindcd3old, 5
ref_codes, 9
ref_diacl2in, 10
ref_domain, 10
ref_estvar, 10
ref_statecd, 11
stunitco, 15

* data

datExportData, 2
DBtestPostgreSQL, 3
DBtestSQLite, 4

* options

multest_options, 6
savedata_options, 11
spMakeSpatial_options, 13
strata_options, 14
table_options, 16
title_options, 18
unit_options, 20

C++Object, 8, 9

datExportData, 2
DBtestPostgreSQL, 3
DBtestSQLite, 4
DEFAULT_NODATA, 5

envRefClass, 8, 9

GDT_NAMES, 5

kindcd3old, 5

multest_options, 6

rasterToVRT, 7

Rcpp_CmbTable-class, 8
Rcpp_RunningStats-class, 9
ref_codes, 9
ref_diacl2in, 10
ref_domain, 10
ref_estvar, 10
ref_statecd, 11

savedata_options, 11
spMakeSpatial_options, 13
strata_options, 14
stunitco, 15

table_options, 16
title_options, 18

unit_options, 20