

Package ‘gdalcubes’

January 19, 2023

Title Earth Observation Data Cubes from Satellite Image Collections

Version 0.6.3

Date 2023-01-19

Description Processing collections of Earth observation images as on-demand multispectral, multitemporal raster data cubes. Users define cubes by spatiotemporal extent, resolution, and spatial reference system and let 'gdalcubes' automatically apply cropping, reprojection, and resampling using the 'Geospatial Data Abstraction Library' ('GDAL'). Implemented functions on data cubes include reduction over space and time, applying arithmetic expressions on pixel band values, moving window aggregates over time, filtering by space, time, bands, and predicates on pixel values, exporting data cubes as 'netCDF' or 'GeoTIFF' files, plotting, and extraction from spatial and or spatiotemporal features. All computational parts are implemented in C++, linking to the 'GDAL', 'netCDF', 'CURL', and 'SQLite' libraries. See Appel and Pebesma (2019) <[doi:10.3390/data4030092](https://doi.org/10.3390/data4030092)> for further details.

Depends R (>= 3.4)

Imports Rcpp, jsonlite, ncdf4

License MIT + file LICENSE

URL https://github.com/appelmar/gdalcubes_R

BugReports https://github.com/appelmar/gdalcubes_R/issues/

Encoding UTF-8

RoxygenNote 7.2.2

LinkingTo Rcpp

Suggests knitr, magrittr, rmarkdown, stars, av, gifski, sf, tinytest, lubridate

VignetteBuilder knitr

Copyright file inst/COPYRIGHTS

NeedsCompilation yes

SystemRequirements C++11, GDAL (>= 2.0.1), PROJ (>= 4.8.0), netcdf, sqlite3

Author Marius Appel [aut, cre] (<<https://orcid.org/0000-0001-5281-3896>>),
 Edzer Pebesma [ctb] (<<https://orcid.org/0000-0001-8049-7069>>),
 Roger Bivand [ctb],
 Jeroen Ooms [ctb] (<<https://orcid.org/0000-0002-4035-0289>>),
 Lewis Van Winkle [cph],
 Ole Christian Eidheim [cph],
 Howard Hinnant [cph],
 Adrian Colomitchi [cph],
 Florian Dang [cph],
 Paul Thompson [cph],
 Tomasz Kamiński [cph],
 Dropbox, Inc. [cph]

Maintainer Marius Appel <marius.appel@uni-muenster.de>

Repository CRAN

Date/Publication 2023-01-19 11:30:03 UTC

R topics documented:

.copy_cube	4
add_collection_format	4
add_images	5
aggregate_space	6
aggregate_time	7
animate	8
apply_pixel	10
apply_pixel.array	11
apply_pixel.cube	12
apply_time	13
apply_time.array	15
apply_time.cube	16
as_array	17
as_json	18
bands	19
chunk_apply	20
collection_formats	21
create_image_collection	22
crop	24
cube_view	25
dim.cube	27
dimensions	28
dimension_bounds	29
dimension_values	30
extent	30
extract_geom	31
fill_time	33
filter_geom	34
filter_pixel	36

gdalcubes	37
gdalcubes_gdalformats	37
gdalcubes_gdalversion	38
gdalcubes_gdal_has_geos	38
gdalcubes_options	38
gdalcubes_selection	40
gdalcubes_set_gdal_config	42
gdalcubes_version	43
image_collection	43
image_mask	44
join_bands	45
json_cube	46
memsize	47
names.cube	48
nbands	49
ncdf_cube	49
nt	50
nx	51
ny	52
pack_minmax	53
plot.cube	54
print.cube	56
print.cube_view	57
print.image_collection	57
proj4	58
raster_cube	59
read_chunk_as_array	60
reduce_space	61
reduce_space.array	62
reduce_space.cube	63
reduce_time	64
reduce_time.array	65
reduce_time.cube	66
rename_bands	68
select_bands	69
select_time	70
size	71
slice_space	72
slice_time	73
srs	74
stack_cube	75
stac_image_collection	77
st_as_stars.cube	78
window_time	79
window_time.cube	80
write_chunk_from_array	81
write_ncdf	82
write_tif	84

Index**86**

<code>.copy_cube</code>	<i>Create a data cube proxy object copy</i>
-------------------------	---

Description

Copy a data cube proxy object without copying any data

Usage

```
.copy_cube(cube)
```

Arguments

<code>cube</code>	source data cube proxy object
-------------------	-------------------------------

Details

This internal function copies the complete processing chain / graph of a data cube but does not copy any data. It is used internally to avoid in-place modification for operations with potential side effects on source data cubes.

Value

copied data cube proxy object

<code>add_collection_format</code>	<i>Download and install an image collection format from a URL</i>
------------------------------------	---

Description

Download and install an image collection format from a URL

Usage

```
add_collection_format(url, name = NULL)
```

Arguments

<code>url</code>	URL pointing to the collection format JSON file
<code>name</code>	optional name used to refer to the collection format

Details

By default, the collection format name will be derived from the basename of the URL.

Examples

```
add_collection_format(
    "https://raw.githubusercontent.com/appeymar/gdalcubes/dev/formats/Sentinel1_IW_GRD.json")
```

add_images	<i>Add images to an existing image collection</i>
------------	---

Description

This function adds provided files or GDAL dataset identifiers and to an existing image collection by extracting datetime, image identifiers, and band information according to the collection's format.

Usage

```
add_images(
    image_collection,
    files,
    unroll_archives = TRUE,
    out_file = "",
    quiet = FALSE
)
```

Arguments

image_collection	image_collection object or path to an existing collection file
files	character vector with paths to image files on disk or any GDAL dataset identifiers (including virtual file systems and higher level drivers or GDAL sub-datasets)
unroll_archives	automatically convert .zip, .tar archives and .gz compressed files to GDAL virtual file system dataset identifiers (e.g. by prepending /vsizip/) and add contained files to the list of considered files
out_file	path to output file, an empty string (the default) will update the collection in-place, whereas images will be added to a new copy of the image collection at the given location otherwise.
quiet	logical; if TRUE, do not print resulting image collection if return value is not assigned to a variable

Value

image collection proxy object, which can be used to create a data cube using [raster_cube](#)

Examples

```
L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                      ".TIF", recursive = TRUE, full.names = TRUE)
L8_col = create_image_collection(L8_files[1:12], "L8_L1TP")
add_images(L8_col, L8_files[13:24])
```

aggregate_space	<i>Spatial aggregation of data cubes</i>
-----------------	--

Description

Create a proxy data cube, which applies an aggregation function to reduce the spatial resolution.

Usage

```
aggregate_space(cube, dx, dy, method = "mean", fact = NULL)
```

Arguments

cube	source data cube
dx	numeric value; new spatial resolution in x direction
dy	numeric value; new spatial resolution in y direction
method	aggregation method, one of "mean", "min", "max", "median", "count", "sum", "prod", "var", and "sd"
fact	simple integer factor defining how many cells (per axis) become aggregated to a single new cell, can be used instead of dx and dy

Details

This function reduces the spatial resolution of a data cube by applying an aggregation function to smaller blocks of pixels.

The size of the cube may be expanded automatically in all directions if the original extent is not divisible by the new size of pixels.

Notice that if boundaries of the target cube do not align with the boundaries of the input cube (for example, if aggregating from 10m to 15m spatial resolution), pixels of the input cube will contribute to the output pixel that contains its center coordinate. If the center coordinate is exactly on a boundary, the input pixel will contribute to the right / bottom pixel of the output cube.

Note

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}
L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
  srs="EPSG:32618", dx = 500, dy=500, dt="P3M", aggregation = "median")
L8.cube = raster_cube(L8.col, v, mask=image_mask("BQA", bits=4, values=16))
L8.rgb = select_bands(L8.cube, c("B02", "B03", "B04"))
L8.5km = aggregate_space(L8.rgb, 5000,5000, "mean")
L8.5km

plot(L8.5km, rgb=3:1, zlim=c(5000,12000))
```

 aggregate_time

Aggregate data cube time series to lower temporal resolution

Description

Create a proxy data cube, which applies an aggregation function over pixel time series to lower temporal resolution.

Usage

```
aggregate_time(cube, dt, method = "mean", fact = NULL)
```

Arguments

cube	source data cube
dt	character; new temporal resolution, datetime period string, e.g. "P1M"
method	aggregation method, one of "mean", "min", "max", "median", "count", "sum", "prod", "var", and "sd"
fact	simple integer factor defining how many cells become aggregated to a single new cell, can be used instead of dt

Details

This function can be used to aggregate time series to lower resolution or to regularize a data cube with irregular (labeled) time axis. It is possible to change the unit of the temporal resolution (e.g. to create monthly composites from daily images). The size of the cube may be expanded automatically if the original temporal extent is not divisible by the new temporal size of pixels.

Note

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}
L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P3M", aggregation = "median")
L8.cube = raster_cube(L8.col, v, mask=image_mask("BQA", bits=4, values=16))
L8.rgb = select_bands(L8.cube, c("B02", "B03", "B04"))
L8.two_monthly = aggregate_time(L8.rgb, "P6M", "min")
L8.two_monthly

plot(L8.two_monthly, rgb=3:1, zlim=c(5000,12000))
```

animate

Animate a data cube as an image time series

Description

This function can animate data cube time series as mp4 videos or animated GIFs. Depending on the desired output format, either the `av` or the `gifski` package is needed to create mp4 and GIF animations respectively.

Usage

```
animate(
  x,
  ...,
  fps = 1,
  loop = TRUE,
  width = 800,
  height = 800,
  save_as = tempfile(fileext = ".gif"),
  preview = interactive()
)
```


Arguments

x	a data cube proxy object (class cube)
...	parameters passed to plot.cube
fps	frames per second of the animation
loop	how many iterations, TRUE = infinite
width	width (in pixels) of the animation
height	height (in pixels) of the animation
save_as	character path where the animation shall be stored, must end with ".mp4" or ".gif"
preview	logical; preview the animation

Details

Animations can be created for single band data cubes or RGB plots of multi-band data cubes (by providing the argument `rgb`) only.

Value

character; path pointing to the the created file

See Also

[plot.cube](#)

Examples

```
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P16D")

animate(select_bands(raster_cube(L8.col, v), c("B02", "B03", "B04")), rgb=3:1,
  zlim=c(0,20000), fps=1, loop=1)

animate(select_bands(raster_cube(L8.col, v), c("B05")), col=terrain.colors, key.pos=1)
```

 apply_pixel

Apply a function over (multi-band) pixels

Description

This generic function applies a function on pixels of a data cube, an R array, or other classes if implemented.

Usage

```
apply_pixel(x, ...)
```

Arguments

x	input data
...	additional arguments passed to method implementations

Value

return value and type depend on the class of x

See Also

[apply_pixel.cube](#)
[apply_pixel.array](#)

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")

L8.col = image_collection(file.path(tempdir(), "L8.db"))
apply_pixel(raster_cube(L8.col, v), "(B05-B04)/(B05+B04)", "NDVI")

d <- c(4,16,128,128)
x <- array(rnorm(prod(d)), d)
y <- apply_pixel(x, function(v) {
```

```
v[1] + v[2] + v[3] - v[4]
})
```

apply_pixel.array	<i>Apply a function over pixels in a four-dimensional (band, time, y, x) array</i>
-------------------	--

Description

Apply a function over pixels in a four-dimensional (band, time, y, x) array

Usage

```
## S3 method for class 'array'
apply_pixel(x, FUN, ...)
```

Arguments

x	four-dimensional input array with dimensions band, time, y, x (in this order)
FUN	function that receives a vector of band values in a one-dimensional array
...	further arguments passed to FUN

Details

FUN is expected to produce a numeric vector (or scalar) where elements are interpreted as new bands in the result.

Note

This is a helper function that uses the same dimension ordering as gdalcubes. It can be used to simplify the application of R functions e.g. over time series in a data cube.

Examples

```
d <- c(4,16,32,32)
x <- array(rnorm(prod(d)), d)
y <- apply_pixel(x, function(v) {
  v[1] + v[2] + v[3] - v[4]
})
dim(y)
```

apply_pixel.cube	<i>Apply arithmetic expressions over all pixels of a data cube</i>
------------------	--

Description

Create a proxy data cube, which applies arithmetic expressions over all pixels of a data cube. Expressions may access band values by name.

Usage

```
## S3 method for class 'cube'
apply_pixel(x, expr, names = NULL, keep_bands = FALSE, ..., FUN)
```

Arguments

x	source data cube
expr	character vector with one or more arithmetic expressions (see Details)
names	optional character vector with the same length as expr to specify band names for the output cube
keep_bands	logical; keep bands of input data cube, defaults to FALSE, i.e. original bands will be dropped
...	not used
FUN	user-defined R function that is applied on all pixels (see Details)

Details

The function can either apply simple arithmetic C expressions given as a character vector (expr argument), or apply a custom R reducer function if FUN is provided.

In the former case, gdalcubes uses the [tinyexpr library](#) to evaluate expressions in C / C++, you can look at the [library documentation](#) to see what kind of expressions you can execute. Pixel band values can be accessed by name.

FUN receives values of the bands from one pixel as a (named) vector and should return a numeric vector with identical length for all pixels. Elements of the result vectors will be interpreted as bands in the result data cube.

Value

a proxy data cube object

Note

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

Examples

```

# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

# 1. Apply a C expression
L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
L8.cube = raster_cube(L8.col, v)
L8.cube = select_bands(L8.cube, c("B04", "B05"))
L8.ndvi = apply_pixel(L8.cube, "(B05-B04)/(B05+B04)", "NDVI")
L8.ndvi

plot(L8.ndvi)

# 2. Apply a user defined R function
L8.ndvi.noisy = apply_pixel(L8.cube, names="NDVI_noisy",
                           FUN=function(x) {
                             rnorm(1, 0, 0.1) + (x["B05"]-x["B04"])/(x["B05"]+x["B04"])
                           })
L8.ndvi.noisy

plot(L8.ndvi.noisy)

```

 apply_time

Apply a function over (multi-band) pixel time series

Description

This generic function applies a function on pixel time series of a data cube, an R array, or other classes if implemented. The resulting object is expected to have the same spatial and temporal shape as the input, i.e., no reduction is performed.

Usage

```
apply_time(x, ...)
```

Arguments

x input data
 ... additional arguments passed to method implementations

Value

return value and type depend on the class of x

See Also

[apply_time.cube](#)
[apply_time.array](#)

Examples

```
# 1. input is data cube
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-01", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
L8.cube = raster_cube(L8.col, v)
L8.cube = select_bands(L8.cube, c("B04", "B05"))
L8.ndvi = apply_pixel(L8.cube, "(B05-B04)/(B05+B04)", "NDVI")

# Apply a user defined R function
apply_time(L8.ndvi, names="NDVI_residuals",
           FUN=function(x) {
             y = x["NDVI",]
             if (sum(is.finite(y)) < 3) {
               return(rep(NA,ncol(x)))
             }
             t = 1:ncol(x)
             return(predict(lm(y ~ t)) - x["NDVI",]))

# 2. input is array
d <- c(4,16,32,32)
x <- array(rnorm(prod(d)), d)
z <- apply_time(x, function(v) {
  y = matrix(NA, ncol=ncol(v), nrow=2)
  y[1,] = (v[1,] + v[2,]) / 2
  y[2,] = (v[3,] + v[4,]) / 2
  y
})
```

```
dim(z)
```

apply_time.array	<i>Apply a function over pixel time series in a four-dimensional (band, time, y, x) array</i>
------------------	---

Description

Apply a function over pixel time series in a four-dimensional (band, time, y, x) array

Usage

```
## S3 method for class 'array'
apply_time(x, FUN, ...)
```

Arguments

x	four-dimensional input array with dimensions band, time, y, x (in this order)
FUN	function that receives a vector of band values in a one-dimensional array
...	further arguments passed to FUN

Details

FUN is expected to produce a matrix (or vector if result has only one band) where rows are interpreted as new bands and columns represent time.

Note

This is a helper function that uses the same dimension ordering as gdalcubes. It can be used to simplify the application of R functions e.g. over time series in a data cube.

Examples

```
d <- c(4,16,32,32)
x <- array(rnorm(prod(d)), d)
z <- apply_time(x, function(v) {
  y = matrix(NA, ncol=ncol(v), nrow=2)
  y[1,] = (v[1,] + v[2,]) / 2
  y[2,] = (v[3,] + v[4,]) / 2
  y
})
dim(z)
```

apply_time.cube	<i>Apply a user-defined R function over (multi-band) pixel time series</i>
-----------------	--

Description

Create a proxy data cube, which applies a user-defined R function over all pixel time series of a data cube. In contrast to `reduce_time`, the time dimension is not reduced, i.e., resulting time series must have identical length as the input data cube but may contain a different number of bands / variables. Example uses of this function may include time series decompositions, cumulative sums / products, smoothing, sophisticated NA filling, or similar.

Usage

```
## S3 method for class 'cube'
apply_time(x, names = NULL, keep_bands = FALSE, FUN, ...)
```

Arguments

x	source data cube
names	optional character vector to specify band names for the output cube
keep_bands	logical; keep bands of input data cube, defaults to FALSE, i.e., original bands will be dropped
FUN	user-defined R function that is applied on all pixel time series (see Details)
...	not used

Details

FUN receives a single (multi-band) pixel time series as a matrix with rows corresponding to bands and columns corresponding to time. In general, the function must return a matrix with the same number of columns. If the result contains only a single band, it may alternatively return a vector with length identical to the length of the input time series (number of columns of the input).

Value

a proxy data cube object

Note

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

Examples

```

# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-06"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
L8.cube = raster_cube(L8.col, v)
L8.cube = select_bands(L8.cube, c("B04", "B05"))
L8.ndvi = apply_pixel(L8.cube, "(B05-B04)/(B05+B04)", "NDVI")

# Apply a user defined R function
L8.ndvi.resid = apply_time(L8.ndvi, names="NDVI_residuals",
  FUN=function(x) {
    y = x["NDVI",]
    if (sum(is.finite(y)) < 3) {
      return(rep(NA, ncol(x)))
    }
    t = 1:ncol(x)
    return(predict(lm(y ~ t)) - x["NDVI",])
  })
L8.ndvi.resid

plot(L8.ndvi.resid)

```

as_array

*Convert a data cube to an in-memory R array***Description**

Convert a data cube to an in-memory R array

Usage

```
as_array(x)
```

Arguments

x data cube

Value

Four dimensional array with dimensions band, t, y, x

Note

Depending on the data cube size, this function may require substantial amounts of main memory, i.e. it makes sense for small data cubes only.

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-04", t1="2018-05"),
  srs="EPSG:32618", nx = 100, ny=100, dt="P1M")
x = as_array(select_bands(raster_cube(L8.col, v), c("B04", "B05")))
dim(x)
dimnames(x)
```

as_json

Query data cube properties

Description

gdalcubes internally uses a graph to serialize data cubes (including chained operations on cubes). This function derives a JSON representation, which can be used to save data cube objects without pixel data to disk.

Usage

```
as_json(obj, file = NULL)
```

Arguments

obj	a data cube proxy object (class cube)
file	optional output file

Value

If file is NULL, the function returns a JSON string representing a graph that can be used to recreate the same chain of gdalcubes operations even in a different R sessions.

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-04"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
cat(as_json(select_bands(raster_cube(L8.col, v), c("B04", "B05"))))
```

bands

*Query data cube properties***Description**

Query data cube properties

Usage

```
bands(obj)
```

Arguments

obj a data cube proxy object (class cube)

Value

A data.frame with rows representing the bands and columns representing properties of a band (name, type, scale, offset, unit)

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}
```

```
L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                        bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
             srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
bands(raster_cube(L8.col, v))
```

chunk_apply

Apply an R function on chunks of a data cube

Description

Apply an R function on chunks of a data cube

Usage

```
chunk_apply(cube, f)
```

Arguments

cube	source data cube
f	R function to apply over all chunks

Details

This function internally creates a gdalcubes stream data cube, which streams data of a chunk to a new R process. For reading data, the function typically calls `x <- read_chunk_as_array()` which then results in a 4 dimensional (band, time, y, x) array. Similarly `write_chunk_from_array(x)` will write a result array as a chunk in the resulting data cube. The chunk size of the input cube is important to control how the function will be exposed to the data cube. For example, if you want to apply an R function over complete pixel time series, you must define the chunk size argument in [raster_cube](#) to make sure that chunk contain the correct parts of the data.

Value

a proxy data cube object

Note

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")

L8.cube = raster_cube(L8.col, v)
L8.cube = select_bands(L8.cube, c("B04", "B05"))
f <- function() {
  x <- read_chunk_as_array()
  out <- reduce_time(x, function(x) {
    cor(x[1,], x[2,], use="na.or.complete", method = "kendall")
  })
  write_chunk_from_array(out)
}
L8.cor = chunk_apply(L8.cube, f)
```

collection_formats *List predefined image collection formats*

Description

gdalcubes comes with some predefined collection formats e.g. to scan Sentinel 2 data. This function lists available formats including brief descriptions.

Usage

```
collection_formats(print = TRUE)
```

Arguments

print	logical; should available formats and their descriptions be printed nicely, defaults to TRUE
-------	--

Details

Image collection formats define how individual files / GDAL datasets relate to an image collection, i.e., which bands they contain, to which image they belong, and how to derive acquisition date/time. They are described as a set of regular expressions in a JSON file and used by gdalcubes to extract this information from the paths and/or filenames.

Value

data.frame with columns name and description where the former describes the unique identifier that can be used in `create_image_collection` and the latter gives a brief description of the format.

Examples

```
collection_formats()
```

```
create_image_collection
```

Create an image collection from a set of GDAL datasets or files

Description

This function iterates over files or GDAL dataset identifiers and extracts datetime, image identifiers, and band information according to a given collection format.

Usage

```
create_image_collection(
  files,
  format = NULL,
  out_file = tempfile(fileext = ".sqlite"),
  date_time = NULL,
  band_names = NULL,
  use_subdatasets = FALSE,
  unroll_archives = TRUE,
  quiet = FALSE,
  one_band_per_file = NULL
)
```

Arguments

<code>files</code>	character vector with paths to image files on disk or any GDAL dataset identifiers (including virtual file systems and higher level drivers or GDAL sub-datasets)
<code>format</code>	collection format, can be either a name to use predefined formats (as output from collection_formats) or a path to a custom JSON format description file
<code>out_file</code>	optional name of the output SQLite database file, defaults to a temporary file
<code>date_time</code>	vector with date/ time for files; can be of class character, Date, or POSIXct (argument is only applicable for image collections without collection format)
<code>band_names</code>	character vector with band names, length must match the number of bands in provided files (argument is only applicable for image collections without collection format)

use_subdatasets	logical; use GDAL subdatasets of provided files (argument is only applicable for image collections without collection format)
unroll_archives	automatically convert .zip, .tar archives and .gz compressed files to GDAL virtual file system dataset identifiers (e.g. by prepending /vsizip/) and add contained files to the list of considered files
quiet	logical; if TRUE, do not print resulting image collection if return value is not assigned to a variable
one_band_per_file	logical; if TRUE, assume that band_names are given for all files (argument is only applicable for image collections without collection format, see Details)

Details

An image collection is a simple index (a SQLite database) containing references to existing image files / GDAL dataset identifiers.

Collections can be created in two different ways: First, if a collection format is specified (argument `format`), date/time, bands, and metadata are automatically extracted from provided files. This is the most general approach but requires a collection format for the specific dataset.

Second, image collections can sometimes be created without collection format by manually specifying date/time of images (argument `date_time`) and names of bands (argument `band_names`). This is possible if either each image file contains *all* bands of the collection or only a single band. In the former case `band_names` simply contains the names of the bands or can be NULL to use default names. In the latter case (image files contain a single band only), the lengths of `band_names` and `date_time` must be identical. By default, the function assumes one band per file if `length(band_names) == length(files)`. In the unlikely situation that this is not desired, it can be explicitly set using `one_band_per_file`.

Value

image collection proxy object, which can be used to create a data cube using [raster_cube](#)

Examples

```
# 1. create image collection using a collection format
L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                      ".TIF", recursive = TRUE, full.names = TRUE)
x = create_image_collection(L8_files, "L8_L1TP")
x

# 2. create image collection without format for a single band
L8_files_B4 <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        "_B4.TIF", recursive = TRUE, full.names = TRUE)
d = as.Date(substr(basename(L8_files_B4), 18, 25), "%Y%m%d")
y = create_image_collection(L8_files_B4, date_time = d, band_names = "B4")
y
```

```
# 3. create image collection without format for all bands
d = as.Date(substr(basename(L8_files), 18, 25), "%Y%m%d")
fname = basename(tools::file_path_sans_ext(L8_files))
b = substr(fname, 27, nchar(fname))
z = create_image_collection(L8_files, date_time = d, band_names = b)
z
```

crop

Crop data cube extent by space and/or time

Description

Create a proxy data cube, which crops a data cube by a spatial and/or temporal extent.

Usage

```
crop(cube, extent = NULL, iextent = NULL, snap = "near")
```

Arguments

cube	source data cube
extent	list with numeric items left, right, top, bottom, and character items t0 and t1, or a subset thereof, see examples
iextent	list with length-two integer items named x, y, and t, defining the lower and upper boundaries as integer coordinates, see examples
snap	one of 'near', 'in', or 'out'; ignored if using iextent

Details

The new extent can be specified by spatial coordinates and datetime values (using the `extent` argument), or as zero-based integer indexes (using the `iextent` argument). In the former case, `extent` expects a list with numeric items left, right, top, bottom, t0, and t1, or a subset thereof. In the latter case, `iextent` is expected as a list with length-two integer vectors x, y, and t as items, defining the lower and upper cell indexes per dimension.

Notice that it is possible to crop only selected boundaries (e.g., only the right boundary) as missing boundaries in the `extent` or NA / NULL values in the `iextent` arguments are considered as "no change". It is, however, not possible to mix arguments `extent` and `iextent`.

If `extent` is given, the `snap` argument can be used to define what happens if the new boundary falls within a data cube cell.

Note

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}
L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P3M", aggregation = "median")
L8.cube = raster_cube(L8.col, v, mask=image_mask("BQA", bits=4, values=16))
L8.rgb = select_bands(L8.cube, c("B02", "B03", "B04"))

# crop by integer indexes
L8.cropped = crop(L8.rgb, iextent = list(x=c(0,400), y=c(0,400), t=c(1,1)))

# crop by spatiotemporal coordinates
L8.cropped = crop(L8.rgb, extent = list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-06"), snap = "in")
L8.cropped

L8.cropped = crop(L8.rgb, extent = list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-06"), snap = "near")
L8.cropped

plot(L8.cropped, rgb = 3:1, zlim=c(5000,10000))
```

cube_view

Create or update a spatiotemporal data cube view

Description

Data cube views define the shape of a cube, i.e., the spatiotemporal extent, resolution, and spatial reference system (srs). They are used to access image collections as on-demand data cubes. The data cube will filter images based on the view's extent, read image data at the defined resolution, and warp / reproject images to the target srs automatically.

Usage

```
cube_view(
  view,
  extent,
  srs,
  nx,
```

```

    ny,
    nt,
    dx,
    dy,
    dt,
    aggregation,
    resampling,
    keep.asp = TRUE
)

```

Arguments

view	if provided, update this cube_view object instead of creating a new data cube view where fields that are already set will be overwritten
extent	spatiotemporal extent as a list e.g. from extent or an image collection object, see Details
srs	target spatial reference system as a string; can be a proj4 definition, WKT, or in the form "EPSG:XXXX"
nx	number of pixels in x-direction (longitude / easting)
ny	number of pixels in y-direction (latitude / northing)
nt	number of pixels in t-direction
dx	size of pixels in x-direction (longitude / easting)
dy	size of pixels in y-direction (latitude / northing)
dt	size of pixels in time-direction, expressed as ISO8601 period string (only 1 number and unit is allowed) such as "P16D"
aggregation	aggregation method as string, defining how to deal with pixels containing data from multiple images, can be "min", "max", "mean", "median", or "first"
resampling	resampling method used in gdalwarp when images are read, can be "near", "bilinear", "bicubic" or others as supported by gdalwarp (see https://gdal.org/programs/gdalwarp.html)
keep.asp	if TRUE, derive ny or dy automatically from nx or dx (or vice versa) based on the aspect ratio of the spatial extent

Details

The extent argument expects a simple list with elements left, right, bottom, top, t0 (start date/time), t1 (end date/time) or an image collection object. In the latter case, the [extent](#) function is automatically called on the image collection object to get the full spatiotemporal extent of the collection. In the former case, datetimes are expressed as ISO8601 datetime strings.

The function can be used in two different ways. First, it can create data cube views from scratch by defining the extent, the spatial reference system, and for each dimension either the cell size (dx, dy, dt) or the total number of cells (nx, ny, nt). Second, the function can update an existing data cube view by overwriting specific fields. In this case, the extent or some elements of the extent may be missing.

In some cases, the extent of the view is automatically extended if the provided resolution would end within a pixel. For example, if the spatial extent covers an area of 1km x 1km and $dx = dy = 300m$, the extent would be enlarged to 1.2 km x 1.2km. The alignment will be reported to the user in a diagnostic message.

Value

A list with data cube view properties

Examples

```
L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                      ".TIF", recursive = TRUE, full.names = TRUE)
L8.col = create_image_collection(L8_files, "L8_L1TP")

# 1. Create a new data cube view specification
v = cube_view(extent=extent(L8.col,"EPSG:4326"), srs="EPSG:4326", dt="P1M",
              nx=1000, ny=500, aggregation = "mean", resampling="bilinear")
v

# 2. overwrite parts of an existing data cube view
vnew = cube_view(v, dt="P1M")
```

dim.cube	<i>Query data cube properties</i>
----------	-----------------------------------

Description

Query data cube properties

Usage

```
## S3 method for class 'cube'
dim(x)
```

Arguments

x a data cube proxy object (class cube)

Value

size of a data cube (number of cells) as integer vector in the order t, y, x

See Also

[size](#)

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
dim(raster_cube(L8.col, v))
```

dimensions

Query data cube properties

Description

Query data cube properties

Usage

```
dimensions(obj)
```

Arguments

obj a data cube proxy object (class cube)

Details

Elements of the returned list represent individual dimensions with properties such as dimension boundaries, names, and chunk size stored as inner lists

Value

Dimension information as a list

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}
```

```
L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                        bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
             srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
dimension_bounds(raster_cube(L8.col, v))
```

dimension_bounds *Query coordinate bounds for all dimensions of a data cube*

Description

Dimension values give the coordinates bounds the spatial and temporal axes of a data cube.

Usage

```
dimension_bounds(obj, datetime_unit = NULL)
```

Arguments

obj a data cube proxy (class cube)

datetime_unit unit used to format values in the datetime dimension, one of "Y", "m", "d", "H", "M", "S", defaults to the unit of the cube.

Value

list with elements t,y,x, each a list with two elements, start and end

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                       ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                        bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
             srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
dimension_bounds(raster_cube(L8.col, v))
```

dimension_values *Query coordinate values for all dimensions of a data cube*

Description

Dimension values give the coordinates along the spatial and temporal axes of a data cube.

Usage

```
dimension_values(obj, datetime_unit = NULL)
```

Arguments

`obj` a data cube proxy (class `cube`), or a data cube view object

`datetime_unit` unit used to format values in the datetime dimension, one of "Y", "m", "d", "H", "M", "S", defaults to the unit of the cube.

Value

list with elements t,y,x

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
dimension_values(raster_cube(L8.col, v))
```

extent *Derive the spatiotemporal extent of an image collection*

Description

Derive the spatiotemporal extent of an image collection

Usage

```
extent(x, srs = "EPSG:4326")
```

Arguments

x image collection proxy object
 srs target spatial reference system

Value

a list with elements left, right, bottom, top, t0 (start date/time), and t1 (end date/time)

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
extent(L8.col, "EPSG:32618")
cube_view(extent=extent(L8.col, "EPSG:32618"),
          srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
```

 extract_geom

Extract values from a data cube by spatial or spatiotemporal features

Description

Extract pixel values of a data cube from a set of spatial or spatiotemporal features. Applications include the extraction of full time series at irregular points, extraction from spatiotemporal points, extraction of pixel values in polygons, and computing summary statistics over polygons.

Usage

```
extract_geom(
  cube,
  sf,
  datetime = NULL,
  time_column = NULL,
  FUN = NULL,
  ...,
  reduce_time = FALSE
)
```

Arguments

cube	source data cube to extract values from
sf	object of class sf, see sf package
datetime	Date, POSIXt, or character vector containing per feature time information; length must be identical to the number of features in sf
time_column	name of the column in sf containing per feature time information
FUN	optional function to compute per feature summary statistics
...	additional arguments passed to FUN
reduce_time	logical; if TRUE, time is ignored when FUN is applied

Details

The geometry in sf can be of any simple feature type supported by GDAL, including POINTS, LINES, POLYGONS, MULTI*, and more. If no time information is provided in one of the arguments datetime or time_column, the full time series of pixels with regard to the features are returned.

Notice that feature identifiers in the FID column typically correspond to the row names / numbers of the provided sf object. This can be used to combine the output with the original geometries, e.g., using [merge\(\)](#).

Pixels with missing values are automatically dropped from the result. It is hence not guaranteed that the result will contain rows for all input features.

Features are automatically reprojected if the coordinate reference system differs from the data cube.

Extracted values can be aggregated by features by providing a summary function. If reduce_time is FALSE (the default), the values are grouped by feature and time, i.e., the result will contain unique combinations of FID and time. To ignore time and produce a single value per feature, reduce_time can be set to TRUE.

Value

A data.frame with columns FID, time, and data cube bands / variables, see Details

Examples

```
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}
L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(srs="EPSG:32618", dy=1000, dx=1000, dt="P1M",
              aggregation = "median", resampling = "bilinear",
              extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931,
                          t0="2018-01-01", t1="2018-04-30"))
L8.cube = raster_cube(L8.col, v)
L8.cube = select_bands(L8.cube, c("B04", "B05"))
```



```

L8.ndvi = apply_pixel(L8.cube, "(B05-B04)/(B05+B04)", "NDVI")
L8.ndvi

if (gdalcubes_gdal_has_geos()) {
  if (requireNamespace("sf", quietly = TRUE)) {

    x = runif(20, v$space$left, v$space$right)
    y = runif(20, v$space$bottom, v$space$top)
    t = sample(seq(as.Date("2018-01-01"), as.Date("2018-04-30"), by = 1), 20, replace = TRUE)
    df = sf::st_as_sf(data.frame(x = x, y = y), coords = c("x", "y"), crs = v$space$srs)

    # spatiotemporal points
    extract_geom(L8.ndvi, df, datetime = t)

    # time series at spatial points
    extract_geom(L8.ndvi, df)

    # summary statistics over polygons
    x = sf::st_read(system.file("nycd.gpkg", package = "gdalcubes"))
    zstats = extract_geom(L8.ndvi, x, FUN=median, reduce_time = TRUE)
    zstats
    # combine with original sf object
    x$FID = rownames(x)
    x = merge(x, zstats, by = "FID")
    x
    # plot(x["NDVI"])
  }
}

```

fill_time

Fill NA data cube pixels by simple time series interpolation

Description

Create a proxy data cube, which fills NA pixels of a data cube by nearest neighbor or linear time series interpolation.

Usage

```
fill_time(cube, method = "near")
```

Arguments

cube	source data cube
method	interpolation method, can be "near" (nearest neighbor), "linear" (linear interpolation), "lof" (last observation carried forward), or "nocb" (next observation carried backward)

Details

Please notice that completely empty (NA) time series will not be filled, i.e. the result cube might still contain NA values.

Value

a proxy data cube object

Note

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}
L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P3M", aggregation = "median")
L8.cube = raster_cube(L8.col, v, mask=image_mask("BQA", bits=4, values=16))
L8.rgb = select_bands(L8.cube, c("B02", "B03", "B04"))
L8.filled = fill_time(L8.rgb, "linear")
L8.filled

plot(L8.filled, rgb=3:1, zlim=c(5000,12000))
```

 filter_geom

Filter data cube pixels by a polygon

Description

Create a proxy data cube, which filters pixels by a spatial (multi)polygon For all pixels whose center is within the polygon, the original

Usage

```
filter_geom(cube, geom, srs = NULL)
```

Arguments

cube	source data cube
geom	either a WKT string, or an sfc or sfg object (sf package)
srs	string identifier of the polygon's coordinate reference system understandable for GDAL

Details

The resulting data cube will not be cropped but pixels outside of the polygon will be set to NAN.

If geom is provided as an sfc object with length > 1, geometries will be combined with `sf::st_combine()` before.

The geometry is automatically transformed to the data cube's spatial reference system if needed.

Value

a proxy data cube object

Note

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-01", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
L8.cube = raster_cube(L8.col, v)
L8.cube = select_bands(L8.cube, c("B04", "B05"))
L8.ndvi = apply_pixel(L8.cube, "(B05-B04)/(B05+B04)", "NDVI")
WKT = gsub(pattern='\\n',replacement="",x =
  "Polygon ((-74.3541 40.9254,
             -73.9813 41.2467,
             -73.9997 41.4400,
             -74.5362 41.1795,
             -74.6286 40.9137,
             -74.3541 40.9254))")
L8.ndvi.filtered = filter_geom(L8.ndvi, WKT, "EPSG:4326")
L8.ndvi.filtered

plot(L8.ndvi.filtered)
```

 filter_pixel

Filter data cube pixels by a user-defined predicate on band values

Description

Create a proxy data cube, which evaluates a predicate over all pixels of a data cube. For all pixels that fulfill the predicate, the original band values are returned. Other pixels are simply filled with NaNs. The predicate may access band values by name.

Usage

```
filter_pixel(cube, pred)
```

Arguments

cube	source data cube
pred	predicate to be evaluated over all pixels

Details

gdalcubes uses and extends the [tinyexpr library](#) to evaluate expressions in C / C++, you can look at the [library documentation](#) to see what kind of expressions you can execute. Pixel band values can be accessed by name.

Value

a proxy data cube object

Note

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-01", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
```

```
L8.cube = raster_cube(L8.col, v)
L8.cube = select_bands(L8.cube, c("B04", "B05"))
L8.ndvi = apply_pixel(L8.cube, "(B05-B04)/(B05+B04)", "NDVI")
L8.ndvi.filtered = filter_pixel(L8.ndvi, "NDVI > 0.5")
L8.ndvi.filtered

plot(L8.ndvi.filtered)
```

gdalcubes

gdalcubes: Earth Observation Data Cubes from Satellite Image Collections

Description

Processing collections of Earth observation images as on-demand multispectral, multitemporal raster data cubes. Users define cubes by spatiotemporal extent, resolution, and spatial reference system and let 'gdalcubes' automatically apply cropping, reprojection, and resampling using the 'Geospatial Data Abstraction Library' ('GDAL'). Implemented functions on data cubes include reduction over space and time, applying arithmetic expressions on pixel band values, moving window aggregates over time, filtering by space, time, bands, and predicates on pixel values, exporting data cubes as 'netCDF' or 'GeoTIFF' files, plotting, and extraction from spatial and or spatiotemporal features. All computational parts are implemented in C++, linking to the 'GDAL', 'netCDF', 'CURL', and 'SQLite' libraries. See Appel and Pebesma (2019) <doi:10.3390/data4030092> for further details.

gdalcubes_gdalformats *Get available GDAL drivers*

Description

Get available GDAL drivers

Usage

```
gdalcubes_gdalformats()
```

Examples

```
gdalcubes_gdalformats()
```

gdalcubes_gdalversion *Get the GDAL version used by gdalcubes*

Description

Get the GDAL version used by gdalcubes

Usage

```
gdalcubes_gdalversion()
```

Examples

```
gdalcubes_gdalversion()
```

gdalcubes_gdal_has_geos
Check if GDAL was built with GEOS

Description

Check if GDAL was built with GEOS

Usage

```
gdalcubes_gdal_has_geos()
```

Examples

```
gdalcubes_gdal_has_geos()
```

gdalcubes_options *Set or read global options of the gdalcubes package*

Description

Set global package options to change the default behavior of gdalcubes. These include how many parallel processes are used to process data cubes, how created netCDF files are compressed, and whether or not debug messages should be printed.

Usage

```
gdalcubes_options(
  ...,
  parallel,
  ncdf_compression_level,
  debug,
  cache,
  ncdf_write_bounds,
  use_overview_images,
  show_progress,
  default_chunksize,
  streaming_dir,
  log_file,
  threads
)
```

Arguments

...	not used
parallel	number of parallel workers used to process data cubes or TRUE to use the number of available cores automatically
ncdf_compression_level	integer; compression level for created netCDF files, 0=no compression, 1=fast compression, 9=small compression
debug	logical; print debug messages
cache	logical; TRUE if temporary data cubes should be cached to support fast reprocessing of the same cubes
ncdf_write_bounds	logical; write dimension bounds as additional variables in netCDF files
use_overview_images	logical; if FALSE, all images are read on original resolution and existing overviews will be ignored
show_progress	logical; if TRUE, a progress bar will be shown for actual computations
default_chunksize	length-three vector with chunk size in t, y, x directions or a function taking a data cube size and returning a suggested chunk size
streaming_dir	directory where temporary binary files for process streaming will be written to
log_file	character, if empty string or NULL, diagnostic messages will be printed to the console, otherwise to the provided file
threads	number of threads used to process data cubes (deprecated)

Details

Data cubes can be processed in parallel where the number of chunks in a cube is distributed among parallel worker processes. The actual number of used workers can be lower if a data cube as less

chunks. If `parallel` is `TRUE`, the number of available cores is used. Setting `parallel = FALSE` can be used to disable parallel processing. Notice that since version 0.6.0, separate processes are being used instead of parallel threads to avoid possible R session crashes due to some multithreading issues.

Caching has no effect on disk or memory consumption, it simply tries to reuse existing temporary files where possible. For example, changing only parameters to `plot` will void reprocessing the same data cube if `cache` is `TRUE`.

The streaming directory can be used to control the performance of user-defined functions, if disk IO is a bottleneck. Ideally, this can be set to a directory on a shared memory device.

Passing no arguments will return the current options as a list.

Examples

```
gdalcubes_options(parallel=4) # set the number
gdalcubes_options() # print current options
gdalcubes_options(parallel=FALSE) # reset
```

gdalcubes_selection *Subsetting data cubes*

Description

Subset data cube dimensions and bands / variables.

Usage

```
## S3 method for class 'cube'
x$name

## S3 method for class 'cube'
x[ib = TRUE, it = TRUE, iy = TRUE, ix = TRUE, ...]
```

Arguments

<code>x</code>	source data cube
<code>name</code>	character; name of selected band
<code>ib</code>	first selector (optional), object of type character, list, Date, POSIXt, numeric, st_bbox , or st_sfc , see Details and examples
<code>it</code>	second selector (optional), see <code>ib</code>
<code>iy</code>	third selector (optional), see <code>ib</code>
<code>ix</code>	fourth selector (optional), see <code>ib</code>
<code>...</code>	further arguments, not used

Details

The `[]` operator allows for flexible subsetting of data cubes by date, datetime, bounding box, spatial points, and band names. Depending on the arguments, it supports slicing (selecting one element of a dimension), cropping (selecting a subinterval of a dimension) and combinations thereof (e.g., selecting a spatial window and a temporal slice). Dimension subsets can be specified by integer indexes or coordinates / datetime values. Arguments are matched by type and order. For example, if the first argument is a length-two vector of type `Date`, the function will understand to subset the time dimension. Otherwise, arguments are treated in the order band, time, y, x.

Note

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}
L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P3M", aggregation = "median")
L8.cube = raster_cube(L8.col, v, mask=image_mask("BQA", bits=4, values=16))
L8.red = L8.cube$B04

plot(L8.red)

v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-01-01", t1="2018-12-31"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1D", aggregation = "median")
L8.cube = raster_cube(L8.col, v, mask=image_mask("BQA", bits=4, values=16))

L8.cube[c("B05", "B04")] # select bands
L8.cube[as.Date(c("2018-01-10", "2018-01-20"))] # crop by time
L8.cube[as.Date("2018-01-10")] # slice by time
L8.cube["B05", "2018-01-10"] # select bands and slice by time
L8.cube["B05", c("2018-01-10", "2018-01-17")] # select bands and crop by time
L8.cube[, c("2018-01-10", "2018-01-17")] # crop by time

# crop by space (coordinates and integer indexes respectively)
L8.cube[list(left=388941.2 + 1e5, right=766552.4 - 1e5, bottom=4345299 + 1e5, top=4744931 - 1e5)]
L8.cube[, , c(1,100), c(1,100)]

L8.cube[, c(1,2), , ] # crop by time (integer indexes)
```

```
# subset by spatial point or bounding box
if (requireNamespace("sf", quietly = TRUE)) {
  s = sf::st_sfc(sf::st_point(c(500000, 4500000)), crs = "EPSG:32618")
  L8.cube[s]

  bbox = sf::st_bbox(c(xmin = 388941.2 + 1e5, xmax = 766552.4 - 1e5,
                        ymax = 4744931 - 1e5, ymin = 4345299 + 1e5), crs = sf::st_crs(32618))
  L8.cube[bbox]
}
```

gdalcubes_set_gdal_config

Set GDAL config options

Description

Set GDAL config options

Usage

```
gdalcubes_set_gdal_config(key, value)
```

Arguments

key	name of a GDAL config option to be set
value	value

Details

Details and a list of possible options can be found at <https://gdal.org/user/configoptions.html>.

Examples

```
gdalcubes_set_gdal_config("GDAL_NUM_THREADS", "ALL_CPUS")
```

gdalcubes_version	<i>Query gdalcubes version information</i>
-------------------	--

Description

Query gdalcubes version information

Usage

```
gdalcubes_version()
```

Value

List with gdalcubes library version information

Examples

```
gdalcubes_version()
```

image_collection	<i>Load an existing image collection from a file</i>
------------------	--

Description

This function will load an image collection from an SQLite file. Image collection files index and reference existing imagery. To create a collection from files on disk, use [create_image_collection](#).

Usage

```
image_collection(path)
```

Arguments

path path to an existing image collection file

Value

an image collection proxy object, which can be used to create a data cube using [raster_cube](#)

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
L8.col
```

image_mask

Create a mask for images in a raster data cube

Description

Create an image mask based on a band and provided values to filter pixels of images read by [raster_cube](#)

Usage

```
image_mask(
  band,
  min = NULL,
  max = NULL,
  values = NULL,
  bits = NULL,
  invert = FALSE
)
```

Arguments

band	name of the mask band
min	minimum value, values between min and max will be masked
max	maximum value, values between min and max will be masked
values	numeric vector; specific values that will be masked.
bits	for bitmasks, extract the given bits (integer vector) with a bitwise AND before filtering the mask values, bit indexes are zero-based
invert	logical; invert mask

Details

Values of the selected mask band can be based on a range (by passing min and max) or on a set of values (by passing values). By default pixels with mask values contained in the range or in the values are masked out, i.e. set to NA. Setting invert = TRUE will invert the masking behavior. Passing values will override min and max.

Note

Notice that masks are applied per image while reading images as a raster cube. They can be useful to eliminate e.g. cloudy pixels before applying the temporal aggregation to merge multiple values for the same data cube pixel.

Examples

```
image_mask("SCL", values = c(3,8,9)) # Sentinel 2 L2A: mask cloud and cloud shadows
image_mask("BQA", bits=4, values=16) # Landsat 8: mask clouds
image_mask("B10", min = 8000, max=65000)
```

join_bands	<i>Join bands of two identically shaped data cubes</i>
------------	--

Description

Create a proxy data cube, which joins the bands of two identically shaped data cubes. The resulting cube will have bands from both input cubes.

Usage

```
join_bands(cube_list, cube_names = NULL)
```

Arguments

cube_list	a list with two or more source data cubes
cube_names	list or character vector with optional name prefixes for bands in the output data cube (see Details)

Details

The number of provided cube_names must match the number of provided input cubes. If no cube_names are provided, bands of the output cube will adopt original names from the input cubes (without any prefix). If any two of the input bands have identical names, prefixes default prefixes ("X1", "X2", ...) will be used.

Value

proxy data cube object

Note

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

Examples

```

# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-05"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")

L8.cube = raster_cube(L8.col, v)
L8.cube.b04 = select_bands(raster_cube(L8.col, v), c("B04"))
L8.cube.b05 = select_bands(raster_cube(L8.col, v), c("B05"))
join_bands(list(L8.cube.b04,L8.cube.b05))

plot(join_bands(list(L8.cube.b04,L8.cube.b05)))

```

json_cube*Read a data cube from a json description file*

Description

Read a data cube from a json description file

Usage

```
json_cube(json, path = NULL)
```

Arguments

json	length-one character vector with a valid json data cube description
path	source data cube proxy object

Details

Data cubes can be stored as JSON description files. These files do not store any data but the recipe how a data cube is constructed, i.e., the chain (or graph) of processes involved.

Since data cube objects (as returned from `raster_cube`) cannot be saved with normal R methods, the combination of `as_json` and `json_cube` provides a cheap way to save virtual data cube objects across several R sessions, as in the examples.

Value

data cube proxy object

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
cube = raster_cube(L8.col, v)

# save
fname = tempfile()
as_json(cube, fname)

# load
json_cube(path = fname)
```

memsize

Query data cube properties

Description

Query data cube properties

Usage

```
memsize(obj, unit = "MiB")
```

Arguments

obj	a data cube proxy object (class cube)
unit	Unit of data size, can be "B", "KB", "KiB", "MB", "MiB", "GB", "GiB", "TB", "TiB", "PB", "PiB"

Value

Total data size of data cube values expressed in the given unit

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
memsize(raster_cube(L8.col, v))
```

names.cube

*Query data cube properties***Description**

Query data cube properties

Usage

```
## S3 method for class 'cube'
names(x)
```

Arguments

x a data cube proxy object (class cube)

Value

Band names as character vector

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
names(raster_cube(L8.col, v))
```

nbands	<i>Query data cube properties</i>
--------	-----------------------------------

Description

Query data cube properties

Usage

```
nbands(obj)
```

Arguments

obj a data cube proxy object (class cube)

Value

Number of bands

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
nbands(raster_cube(L8.col, v))
```

ncdf_cube	<i>Read a data cube from an existing netCDF file</i>
-----------	--

Description

Create a proxy data cube from a netCDF file that has been created using [write_ncdf](#). This function does not read cubes from arbitrary netCDF files and can be used e.g., to load intermediate results and/or plotting existing netCDF cubes on disk without doing the data cube creation from image collections.

Usage

```
ncdf_cube(path, chunking = NULL, auto_unpack = TRUE)
```

Arguments

path	path to an existing netCDF file
chunking	custom chunk sizes to read from the netCDF file; defaults to using chunk sizes from the netCDF file
auto_unpack	logical; automatically apply offset and scale when reading data values

Value

a proxy data cube object

Note

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")

ncfile = write_ncdf(select_bands(raster_cube(L8.col, v), c("B02", "B03", "B04")))
ncdf_cube(ncfile)
```

 nt

Query data cube properties

Description

Query data cube properties

Usage

nt(obj)

Arguments

obj a data cube proxy object (class cube)

Value

Number of pixels in the time dimension

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
nt(raster_cube(L8.col, v))
```

 nx

Query data cube properties

Description

Query data cube properties

Usage

nx(obj)

Arguments

obj a data cube proxy object (class cube)

Value

Number of pixels in the x dimension

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
nx(raster_cube(L8.col, v))
```

ny

*Query data cube properties***Description**

Query data cube properties

Usage

```
ny(obj)
```

Arguments

obj a data cube proxy object (class cube)

Value

Number of pixels in the y dimension

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
ny(raster_cube(L8.col, v))
```

pack_minmax	<i>Helper function to define packed data exports by min / max values</i>
-------------	--

Description

This function can be used to define packed exports in `write_ncdf` and `write_tif`. It will generate scale and offset values with maximum precision (unless `simplify=TRUE`).

Usage

```
pack_minmax(type = "int16", min, max, simplify = FALSE)
```

Arguments

type	target data type of packed values (one of "uint8", "uint16", "uint32", "int16", or "int32")
min	numeric; minimum value(s) of original values, will be packed to the 2nd lowest value of the target data type
max	numeric; maximum value(s) in original scale, will be packed to the highest value of the target data type
simplify	logical; round resulting scale and offset to power of 10 values

Details

Nodata values will be mapped to the lowest value of the target data type.

Arguments `min` and `max` must have length 1 or length equal to the number of bands of the data cube to be exported. In the former case, the same values are used for all bands of the exported target cube, whereas the latter case allows to use different ranges for different bands.

Note

Using `simplify=TRUE` will round scale values to the next smaller power of 10.

Examples

```
ndvi_packing = pack_minmax(type="int16", min=-1, max=1)
ndvi_packing
```

plot.cube

Plot a gdalcubes data cube

Description

Plot a gdalcubes data cube

Usage

```
## S3 method for class 'cube'
plot(
  x,
  y,
  ...,
  nbreaks = 11,
  breaks = NULL,
  col = grey(1:(nbreaks - 1)/nbreaks),
  key.pos = NULL,
  bands = NULL,
  t = NULL,
  rgb = NULL,
  zlim = NULL,
  gamma = 1,
  periods.in.title = TRUE,
  join.timeseries = FALSE,
  axes = TRUE,
  ncol = NULL,
  nrow = NULL,
  downsample = TRUE,
  na.color = "#AAAAAA"
)
```

Arguments

x	a data cube proxy object (class cube)
y	__not used__
...	further arguments passed to image.default
nbreaks	number of breaks, should be one more than the number of colors given
breaks	actual breaks used to assign colors to values; if missing, the function subsamples values and uses equally sized intervals between min and max or zlim[0] and zlim[1] if defined
col	color definition, can be a character vector with nbreaks - 1 elements or a function such as heat.colors
key.pos	position for the legend, 1 (bottom), 2 (left), 3 (top), or 4 (right). If NULL (the default), do not plot a legend.

bands	integer vector with band numbers to plot (this must be band numbers, not band names)
t	integer vector with time indexes to plot (this must be time indexes, not date / time)
rgb	bands used to assign RGB color channels, vector of length 3 (this must be band numbers, not band names)
zlim	vector of length 2, defining the minimum and maximum values to either derive breaks, or define black and white values in RGB plots
gamma	gamma correction value, used for RGB plots only
periods.in.title	logical value, if TRUE, the title of plots includes the datetime period length as ISO 8601 string
join.timeseries	logical, for pure time-series plots, shall time series of multiple bands be plotted in a single plot (with different colors)?
axes	logical, if TRUE, plots include axes
ncol	number of columns for arranging plots with layout(), see Details
nrow	number of rows for arranging plots with layout(), see Details
downsample	length-one integer or logical value used to select only every i-th pixel (in space only) for faster plots; by default (TRUE), downsampling will be determined automatically based on the resolution of the graphics device; set to FALSE to avoid downsampling.
na.color	color used to plot NA pixels

Details

The style of the plot depends on provided parameters and on the shape of the cube, i.e., whether it is a pure time series and whether it contains multiple bands or not. Multi-band, multi-temporal images will be arranged with layout() such that bands are represented by columns and time is represented by rows. Time series plots can be combined to a single plot by setting join.timeseries = TRUE. The layout can be controlled with ncol and nrow, which define the number of rows and columns in the plot layout. Typically, only one of ncol and nrow is provided. For multi-band, multi-temporal plots, the actual number of rows or columns can be less if the input cube has less bands or time slices.

The downsample argument is used to speed-up plotting if the cube has much more pixels than the graphics device. If set to a scalar integer value > 1, the value is used to skip pixels in the spatial dimensions. For example, setting downsample = 4 means that every fourth pixel is used in the spatial dimensions. If TRUE (the default) downsample is derived automatically based on the sizes of the cube and the graphics device. If 1 or FALSE, no additional downsampling is performed. Notice that downsampling is only used for plotting. The size of the data cube (and hence the computation time to process the data cube) is not modified.

Note

If caching is enabled for the package (see [gdalcubes_options](#)), repeated calls of plot for the same data cube will not reevaluate the cube. Instead, the temporary result file will be reused, if possible. Some parts of the function have been copied from the stars package (c) Edzer Pebesma

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")

plot(select_bands(raster_cube(L8.col, v), c("B02", "B03", "B04")), rgb=3:1)

L8.cube = select_bands(raster_cube(L8.col, v), c("B04", "B05"))
L8.ndvi = apply_pixel(L8.cube, "(B05-B04)/(B05+B04)", "NDVI")
plot(reduce_time(L8.ndvi, "median(NDVI)"), key.pos=1, zlim=c(0,1))
```

print.cube

Print data cube information

Description

Prints information about the dimensions and bands of a data cube.

Usage

```
## S3 method for class 'cube'
print(x, ...)
```

Arguments

```
x          Object of class "cube"
...        Further arguments passed to the generic print function
```

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
```



```
v = cube_view(extent=list(left=388941.2, right=766552.4,
                        bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
             srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
print(raster_cube(L8.col, v))
```

print.cube_view *Print data cube view information*

Description

Prints information about a data cube view, including its dimensions, spatial reference, aggregation method, and resampling method.

Usage

```
## S3 method for class 'cube_view'
print(x, ...)
```

Arguments

x Object of class "cube_view"
... Further arguments passed to the generic print function

Examples

```
v = cube_view(extent=list(left=388941.2, right=766552.4,
                        bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
             srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
print(v)
```

print.image_collection *Print image collection information*

Description

Prints information about images in an image collection.

Usage

```
## S3 method for class 'image_collection'
print(x, ..., n = 6)
```

Arguments

x	Object of class "image_collection"
...	Further arguments passed to the generic print function
n	Number of images for which details are printed

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
print(L8.col)
```

proj4

Query data cube properties

Description

Query data cube properties

Usage

```
proj4(obj)
```

Arguments

obj	a data cube proxy object (class cube)
-----	---------------------------------------

Value

The spatial reference system expressed as proj4 string

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
```

```
v = cube_view(extent=list(left=388941.2, right=766552.4,
                        bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
             srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
proj4(raster_cube(L8.col, v))
```

raster_cube	<i>Create a data cube from an image collection</i>
-------------	--

Description

Create a proxy data cube, which loads data from a given image collection according to a data cube view

Usage

```
raster_cube(
  image_collection,
  view,
  mask = NULL,
  chunking = .pkgenv$default_chunksize
)
```

Arguments

image_collection	Source image collection as from <code>image_collection</code> or <code>create_image_collection</code>
view	A data cube view defining the shape (spatiotemporal extent, resolution, and spatial reference), if missing, a default overview is used
mask	mask pixels of images based on band values, see image_mask
chunking	length-3 vector or a function returning a vector of length 3, defining the size of data cube chunks in the order time, y, x.

Details

The following steps will be performed when the data cube is requested to read data of a chunk:

1. Find images from the input collection that intersect with the spatiotemporal extent of the chunk
2. For all resulting images, apply `gdalwarp` to reproject, resize, and resample to an in-memory GDAL dataset
3. Read the resulting data to the chunk buffer and optionally apply a mask on the result
4. Update pixel-wise aggregator (as defined in the data cube view) to combine values of multiple images within the same data cube pixels

If chunking is provided as a function, it must accept exactly three arguments for the total size of the cube in t, y, and x axes (in this order).

Value

A proxy data cube object

Note

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
raster_cube(L8.col, v)

# using a mask on the Landsat quality bit band to filter out clouds
raster_cube(L8.col, v, mask=image_mask("BQA", bits=4, values=16))
```

read_chunk_as_array *Read chunk data of a data cube from stdin or a file*

Description

This function can be used within function passed to [chunk_apply](#) in order to read a data cube chunk as a four-dimensional R array. It works only for R processes, which have been started from the gdalcubes C++ library. The resulting array has dimensions band, time, y, x (in this order).

Usage

```
read_chunk_as_array(with.dimnames = TRUE)
```

Arguments

`with.dimnames` if TRUE, the resulting array will contain dimnames with coordinates, datetime, and band names

Value

four-dimensional array

Note

Call this function **ONLY** from a function passed to `chunk_apply`.

This function only works in R sessions started from gdalcubes streaming.

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
L8.cube = raster_cube(L8.col, v)
L8.cube = select_bands(L8.cube, c("B04", "B05"))
f <- function() {
  x <- read_chunk_as_array()
  out <- reduce_time(x, function(x) {
    cor(x[1,], x[2,], use="na.or.complete", method = "kendall")
  })
  write_chunk_from_array(out)
}
L8.cor = chunk_apply(L8.cube, f)
plot(L8.cor, zlim=c(0,1), key.pos=1)
```

 reduce_space

Reduce multidimensional data over space

Description

This generic function applies a reducer function over a data cube, an R array, or other classes if implemented.

Usage

```
reduce_space(x, ...)
```

Arguments

`x` object to be reduced
`...` further arguments passed to specific implementations

Value

return value and type depend on the class of x

See Also

[reduce_space.cube](#)

[reduce_space.array](#)

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
reduce_space(raster_cube(L8.col, v) , "median(B02)")

d <- c(4,16,32,32)
x <- array(rnorm(prod(d)), d)
y <- reduce_space(x, function(v) {
  apply(v, 1, mean)
})
```

reduce_space.array	<i>Apply a function over space and bands in a four-dimensional (band, time, y, x) array and reduce spatial dimensions</i>
--------------------	---

Description

Apply a function over space and bands in a four-dimensional (band, time, y, x) array and reduce spatial dimensions

Usage

```
## S3 method for class 'array'
reduce_space(x, FUN, ...)
```

Arguments

x	four-dimensional input array with dimensions band, time, y, x (in this order)
FUN	function which receives one spatial slice in a three-dimensional array with dimensions bands, y, x as input
...	further arguments passed to FUN

Details

FUN is expected to produce a numeric vector (or scalar) where elements are interpreted as new bands in the result.

Note

This is a helper function that uses the same dimension ordering as gdalcubes streaming. It can be used to simplify the application of R functions e.g. over spatial slices in a data cube.

Examples

```
d <- c(4,16,32,32)
x <- array(rnorm(prod(d)), d)
# reduce individual bands over spatial slices
y <- reduce_space(x, function(v) {
  apply(v, 1, mean)
})
dim(y)
```

reduce_space.cube	<i>Reduce a data cube over spatial (x,y or lat,lon) dimensions</i>
-------------------	--

Description

Create a proxy data cube, which applies one or more reducer functions to selected bands over spatial slices of a data cube

Usage

```
## S3 method for class 'cube'
reduce_space(x, expr, ..., FUN, names = NULL)
```

Arguments

x	source data cube
expr	either a single string, or a vector of strings defining which reducers will be applied over which bands of the input cube
...	optional additional expressions (if expr is not a vector)
FUN	a user-defined R function applied over pixel time series (see Details)
names	character vector; if FUN is provided, names can be used to define the number and name of output bands

Details

Notice that expressions have a very simple format: the reducer is followed by the name of a band in parantheses. You cannot add more complex functions or arguments.

Possible reducers currently are "min", "max", "sum", "prod", "count", "mean", "median", "var", "sd".

Value

proxy data cube object

Note

Implemented reducers will ignore any NAN values (as na.rm=TRUE does).

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")

L8.cube = raster_cube(L8.col, v)
L8.b02 = select_bands(L8.cube, c("B02"))
L8.b02.median = reduce_space(L8.b02, "median(B02)")
L8.b02.median

plot(L8.b02.median)
```

reduce_time

Reduce multidimensional data over time

Description

This generic function applies a reducer function over a data cube, an R array, or other classes if implemented.

Usage

```
reduce_time(x, ...)
```

Arguments

```
x          object to be reduced
...        further arguments passed to specific implementations
```

Value

return value and type depend on the class of x

See Also

[reduce_time.cube](#)
[reduce_time.array](#)

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8-L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-01", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
reduce_time(raster_cube(L8.col, v) , "median(B02)", "median(B03)", "median(B04)")

d <- c(4,16,32,32)
x <- array(rnorm(prod(d)), d)
y <- reduce_time(x, function(v) {
  apply(v, 1, mean)
})
```

reduce_time.array	<i>Apply a function over time and bands in a four-dimensional (band, time, y, x) array and reduce time dimension</i>
-------------------	--

Description

Apply a function over time and bands in a four-dimensional (band, time, y, x) array and reduce time dimension

Usage

```
## S3 method for class 'array'
reduce_time(x, FUN, ...)
```

Arguments

x	four-dimensional input array with dimensions band, time, y, x (in this order)
FUN	function which receives one time series in a two-dimensional array with dimensions bands, time as input
...	further arguments passed to FUN

Details

FUN is expected to produce a numeric vector (or scalar) where elements are interpreted as new bands in the result.

Note

This is a helper function that uses the same dimension ordering as `gdalcubes` streaming. It can be used to simplify the application of R functions e.g. over time series in a data cube.

Examples

```
d <- c(4,16,32,32)
x <- array(rnorm(prod(d)), d)
# reduce individual bands over pixel time series
y <- reduce_time(x, function(v) {
  apply(v, 1, mean)
})
dim(y)
```

```
reduce_time.cube
```

Reduce a data cube over the time dimension

Description

Create a proxy data cube, which applies one or more reducer functions to selected bands over pixel time series of a data cube

Usage

```
## S3 method for class 'cube'
reduce_time(x, expr, ..., FUN, names = NULL)
```

Arguments

x	source data cube
expr	either a single string, or a vector of strings defining which reducers will be applied over which bands of the input cube
...	optional additional expressions (if expr is not a vector)
FUN	a user-defined R function applied over pixel time series (see Details)
names	character vector; if FUN is provided, names can be used to define the number and name of output bands

Details

The function can either apply a built-in reducer if `expr` is given, or apply a custom R reducer function if `FUN` is provided.

In the former case, notice that expressions have a very simple format: the reducer is followed by the name of a band in parentheses. You cannot add more complex functions or arguments. Possible reducers currently are "min", "max", "sum", "prod", "count", "mean", "median", "var", "sd", "which_min", and "which_max".

User-defined R reducer functions receive a two-dimensional array as input where rows correspond to the band and columns represent the time dimension. For example, one row is the time series of a specific band. `FUN` should always return a numeric vector with the same number of elements, which will be interpreted as bands in the result cube. Notice that it is recommended to specify the names of the output bands as a character vector. If names are missing, the number and names of output bands is tried to be derived automatically, which may fail in some cases.

Value

proxy data cube object

Note

Implemented reducers will ignore any NAN values (as `na.rm=TRUE` does)

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-01", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
```

```

L8.cube = raster_cube(L8.col, v)
L8.rgb = select_bands(L8.cube, c("B02", "B03", "B04"))
L8.rgb.median = reduce_time(L8.rgb, "median(B02)", "median(B03)", "median(B04)")
L8.rgb.median

plot(L8.rgb.median, rgb=3:1)

# user defined reducer calculating interquartile ranges
L8.rgb.iqr = reduce_time(L8.rgb, names=c("iqr_R", "iqr_G", "iqr_B"), FUN = function(x) {
  c(diff(quantile(x[["B04"],],c(0.25,0.75), na.rm=TRUE)),
    diff(quantile(x[["B03"],],c(0.25,0.75), na.rm=TRUE)),
    diff(quantile(x[["B02"],],c(0.25,0.75), na.rm=TRUE)))
})
L8.rgb.iqr

plot(L8.rgb.iqr, key.pos=1)

```

 rename_bands

Rename bands of a data cube

Description

Create a proxy data cube, which renames specific bands of a data cube.

Usage

```
rename_bands(cube, ...)
```

Arguments

cube	source data cube
...	named arguments with bands that will be renamed, see Details

Details

The result data cube always contains the same number of bands. No subsetting is done if only names for some of the bands are provided. In this case, only provided bands are renamed whereas other bands keep their original name. Variable arguments must be named by the old band name and the new names must be provided as simple character values (see example).

Value

proxy data cube object

Note

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-04", t1="2018-07"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
L8.cube = raster_cube(L8.col, v)
L8.rgb = select_bands(L8.cube, c("B02", "B03", "B04"))
L8.rgb
L8.rgb = rename_bands(L8.cube, B02 = "blue", B03 = "green", B04 = "red")
L8.rgb
```

 select_bands

Select bands of a data cube

Description

Create a proxy data cube, which selects specific bands of a data cube. The resulting cube will drop any other bands.

Usage

```
select_bands(cube, bands)
```

Arguments

cube	source data cube
bands	character vector with band names

Value

proxy data cube object

Note

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

For performance reasons, `select_bands` should always be called directly on a cube created with `raster_cube` and drop all unneeded bands. This allows to reduce RasterIO and warp operations in GDAL.

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-04", t1="2018-07"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
L8.cube = raster_cube(L8.col, v)
L8.rgb = select_bands(L8.cube, c("B02", "B03", "B04"))
L8.rgb

plot(L8.rgb, rgb=3:1)
```

 select_time

Select time slices of a data cube

Description

Create a proxy data cube, which selects specific time slices of a data cube. The time dimension of the resulting cube will be irregular / labeled.

Usage

```
select_time(cube, t)
```

Arguments

cube	source data cube
t	character vector with date/time

Value

proxy data cube object

Note

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                        bottom=4345299, top=4744931, t0="2018-04", t1="2018-07"),
             srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
L8.cube = raster_cube(L8.col, v)
L8.rgb = select_bands(L8.cube, c("B02", "B03", "B04"))
L8.rgb = select_time(L8.rgb, c("2018-04", "2018-07"))
L8.rgb

plot(L8.rgb, rgb=3:1)
```

size

Query data cube properties

Description

Query data cube properties

Usage

```
size(obj)
```

Arguments

obj a data cube proxy object (class cube)

Value

size of a data cube (number of cells) as integer vector in the order t, y, x

See Also

[dim.cube](#)

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
size(raster_cube(L8.col, v))
```

 slice_space

Extract a single time series (spatial slice) from a data cube

Description

Create a proxy data cube, which extracts a time series from a data cube defined by spatial coordinates or integer x and y indexes.

Usage

```
slice_space(cube, loc = NULL, i = NULL)
```

Arguments

cube	source data cube
loc	numeric length-two vector; spatial coordinates (x, y) of the time series, expressed in the coordinate reference system of the source data cube
i	integer length-2 vector; indexes (x,y) of the time slice (zero-based)

Details

Either loc or i must be non-NULL. If both arguments are provided, integer indexes i are ignored.

Note

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}
L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P3M", aggregation = "median")
L8.cube = raster_cube(L8.col, v, mask=image_mask("BQA", bits=4, values=16))
L8.rgb = select_bands(L8.cube, c("B02", "B03", "B04"))
L8.ts = slice_space(L8.rgb, loc = c(5e05, 4400000))
L8.ts

plot(L8.ts, join.timeseries = TRUE)
```

 slice_time

Extract a single time slice from a data cube

Description

Create a proxy data cube, which extracts a time slice from a data cube defined by label (datetime string) or integer index.

Usage

```
slice_time(cube, datetime = NULL, it = NULL)
```

Arguments

cube	source data cube
datetime	character; datetime string of the time slice
it	integer; index of the time slice (zero-based)

Details

Either datetime or it must be non-NULL. If both arguments are provided, the integer index it is ignored.

Note

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}
L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M", aggregation = "median")
L8.cube = raster_cube(L8.col, v, mask=image_mask("BQA", bits=4, values=16))
L8.rgb = select_bands(L8.cube, c("B02", "B03", "B04"))
L8.slice = slice_time(L8.rgb, "2018-03")
L8.slice

plot(L8.slice, rgb=3:1, zlim=c(5000,12000))
```

srs

*Query data cube properties***Description**

Query data cube properties

Usage

```
srs(obj)
```

Arguments

obj a data cube proxy object (class cube)

Value

The spatial reference system expressed as a string readable by GDAL

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
```

```

}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                        bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
             srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
srs(raster_cube(L8.col, v))

```

stack_cube	<i>Create a data cube from a set of images with the same spatial extent and spatial reference system</i>
------------	--

Description

Create a spatiotemporal data cube directly from images with identical spatial extent and spatial reference system, similar to a raster stack with an additional dimension supporting both, time and multiple bands / variables.

Usage

```

stack_cube(
  x,
  datetime_values,
  bands = NULL,
  band_names = NULL,
  chunking = c(1, 256, 256),
  dx = NULL,
  dy = NULL
)

```

Arguments

x	character vector where items point to image files
datetime_values	vector of type character, Date, or POSIXct with recording date of images
bands	optional character vector defining the band or spectral band of each item in x, if files relate to different spectral bands or variables
band_names	name of bands, only used if bands is NULL, i.e., if all files contain the same spectral band(s) / variable(s)
chunking	vector of length 3 defining the size of data cube chunks in the order time, y, x.
dx	optional target pixel size in x direction, by default (NULL) the original or highest resolution of images is used
dy	optional target pixel size in y direction, by default (NULL) the original or highest resolution of images is used

Details

This function creates a four-dimensional (space, time, bands / variables) raster data cube from a set of provided files without the need to create an image collection before. This is possible if all images have the same spatial extent and spatial reference system and can be used for two different file organizations:

1. If all image files share the same bands / variables, the bands argument can be ignored (default NULL) can names of the bands can be specified using the band_names argument.
2. If image files represent different band / variable (e.g. individual files for red, green, and blue channels), the bands argument must be used to define the corresponding band / variable. Notice that in this case all files are expected to represent exactly one variable / band at one point in datetime. It is not possible to combine files with different numbers of variables / bands. If image files for different bands have different pixel sizes, the smallest size is used by default.

Notice that to avoid opening all image files in advance, no automatic check whether all images share the spatial extent and spatial reference system is performed.

Value

A proxy data cube object

Note

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

Examples

```
# toy example, repeating the same image as a daily time series
L8_file_nir <-
system.file("L8NY18/LC08_L1TP_014032_20181122_20181129_01_T1/LC08_L1TP_014032_20181122_B5.TIF",
            package = "gdalcubes")
files = rep(L8_file_nir, 10)
datetime = as.Date("2018-11-22") + 1:10
stack_cube(files, datetime, band_names = "B05")

# using a second band from different files
L8_file_red <-
system.file("L8NY18/LC08_L1TP_014032_20181122_20181129_01_T1/LC08_L1TP_014032_20181122_B4.TIF",
            package = "gdalcubes")
files = rep(c(L8_file_nir, L8_file_red), each = 10)
datetime = rep(as.Date("2018-11-22") + 1:10, 2)
bands = rep(c("B5", "B4"), each = 10)
stack_cube(files, datetime, bands = bands)
```

stac_image_collection *Create an image collection from a STAC feature collection*

Description

This function creates an image collection from a STAC API collection response. It does not need to read any image data. Additionally, bands can be filtered and asset links can be transformed to make them readable for GDAL.

Usage

```
stac_image_collection(
  s,
  out_file = tempfile(fileext = ".sqlite"),
  asset_names = NULL,
  asset_regex = NULL,
  url_fun = .default_url_fun,
  property_filter = NULL,
  skip_image_metadata = FALSE,
  srs = NULL,
  srs_overwrite = FALSE,
  duration = c("center", "start")
)
```

Arguments

s	STAC feature collection
out_file	optional name of the output SQLite database file, defaults to a temporary file
asset_names	character vector with names of assets (e.g., bands) to be used, other assets will be ignored. By default (NULL), all asset names with "eo:bands" attributes will be used
asset_regex	length 1 character defining a regular expression asset names must match to be considered
url_fun	optional function to modify URLs of assets, e.g, to add /vsicurl/ to URLs (the default)
property_filter	optional function to filter STAC items (images) by their properties; see Details
skip_image_metadata	logical, if TRUE per-image metadata (STAC item properties) will not be added to the image collection
srs	character spatial reference system of images used either for images without corresponding STAC property only or for all images
srs_overwrite	logical, if FALSE, use srs only for images with unknown srs (missing STAC metadata)
duration	character, if images represent time intervals, use either the "start" or "center" of time intervals

Details

The `property_filter` argument can be used to filter images by metadata such as cloud coverage. The function receives all properties of a STAC item (image) as input list and is expected to produce a single logical value, where an image will be ignored if the function returns `FALSE`.

Note

Currently, `bbox` results are expected to be WGS84 coordinates, even if `bbox-crs` is given in the STAC response.

<code>st_as_stars.cube</code>	<i>Coerce gdalcubes object into a stars object</i>
-------------------------------	--

Description

The function materializes a data cube as a temporary netCDF file and loads the file with the stars package.

Usage

```
st_as_stars.cube(.x, ...)
```

Arguments

<code>.x</code>	data cube object to coerce
<code>...</code>	not used

Value

stars object

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-04"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
if(require("stars"))
  st_as_stars(select_bands(raster_cube(L8.col, v), c("B04", "B05")))
```

window_time	<i>Apply a moving window operation over time</i>
-------------	--

Description

This generic function applies a reducer function over a moving window over the time dimension of a data cube, an R array, or other classes if implemented.

Usage

```
window_time(x, ...)
```

Arguments

x	object to be reduced
...	further arguments passed to specific implementations

Value

value and type depend on the class of x

See Also

[window_time.cube](#)

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-07"),
  srs="EPSG:32618", nx = 400, dt="P1M")
L8.cube = raster_cube(L8.col, v)
L8.nir = select_bands(L8.cube, c("B05"))
window_time(L8.nir, window = c(2,2), "min(B05)")
window_time(L8.nir, kernel=c(-1,1), window=c(1,0))

plot(window_time(L8.nir, kernel=c(-1,1), window=c(1,0)), key.pos=1)
```

window_time.cube	<i>Apply a moving window function over the time dimension of a data cube</i>
------------------	--

Description

Create a proxy data cube, which applies one or more moving window functions to selected bands over pixel time series of a data cube. The function can either use a predefined aggregation function or apply a custom convolution kernel.

Usage

```
## S3 method for class 'cube'
window_time(x, expr, ..., kernel, window)
```

Arguments

x	source data cube
expr	either a single string, or a vector of strings defining which reducers will be applied over which bands of the input cube
...	optional additional expressions (if expr is not a vector)
kernel	numeric vector with elements of the kernel
window	integer vector with two elements defining the size of the window before and after a cell, the total size of the window is window[1] + 1 + window[2]

Details

The function either applies a kernel convolution (if the kernel argument is provided) or a general reducer function over moving temporal windows. In the former case, the kernel convolution will be applied over all bands of the input cube, i.e., the output cube will have the same number of bands as the input cubes. If a kernel is given and the window argument is missing, the window will be symmetric to the center pixel with the size of the provided kernel. For general reducer functions, the window argument must be provided and several expressions can be used to create multiple bands in the output cube.

Notice that expressions have a very simple format: the reducer is followed by the name of a band in parentheses. You cannot add more complex functions or arguments.

Possible reducers currently are "min", "max", "sum", "prod", "count", "mean", "median".

Value

proxy data cube object

Note

Implemented reducers will ignore any NAN values (as na.rm=TRUE does).

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

Examples

```

# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-01", t1="2018-07"),
              srs="EPSG:32618", nx = 400, dt="P1M")

L8.cube = raster_cube(L8.col, v)
L8.nir = select_bands(L8.cube, c("B05"))
L8.nir.min = window_time(L8.nir, window = c(2,2), "min(B05)")
L8.nir.min

L8.nir.kernel = window_time(L8.nir, kernel=c(-1,1), window=c(1,0))
L8.nir.kernel

```

```
write_chunk_from_array
```

Write chunk data of a cube to stdout or a file

Description

This function can be used within function passed to [chunk_apply](#) in order to pass four-dimensional R arrays as a data cube chunk to the gdalcubes C++ library. It works only for R processes, which have been started from the gdalcubes C++ library. The input array must have dimensions band, time, y, x (in this order).

Usage

```
write_chunk_from_array(v)
```

Arguments

`v` four-dimensional array with dimensions band, time, y, and x

Note

Call this function ONLY from a function passed to [chunk_apply](#).

This function only works in R sessions started from gdalcubes streaming.

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")

L8.cube = raster_cube(L8.col, v)
L8.cube = select_bands(L8.cube, c("B04", "B05"))
f <- function() {
  x <- read_chunk_as_array()
  out <- reduce_time(x, function(x) {
    cor(x[1,], x[2,], use="na.or.complete", method = "kendall")
  })
  write_chunk_from_array(out)
}
L8.cor = chunk_apply(L8.cube, f)
plot(L8.cor, zlim=c(0,1), key.pos=1)
```

write_ncdf

Export a data cube as netCDF file(s)

Description

This function will read chunks of a data cube and write them to a single (the default) or multiple (if chunked = TRUE) netCDF file(s). The resulting file(s) uses the enhanced netCDF-4 format, supporting chunking and compression.

Usage

```
write_ncdf(
  x,
  fname = tempfile(pattern = "gdalcubes", fileext = ".nc"),
  overwrite = FALSE,
  write_json_descr = FALSE,
  with_VRT = FALSE,
  pack = NULL,
  chunked = FALSE
)
```

Arguments

x	a data cube proxy object (class cube)
fname	output file name
overwrite	logical; overwrite output file if it already exists
write_json_descr	logical; write a JSON description of x as additional file
with_VRT	logical; write additional VRT datasets (one per time slice)
pack	reduce output file size by packing values (see Details), defaults to no packing
chunked	logical; if TRUE, write one netCDF file per chunk; defaults to FALSE

Details

The resulting netCDF file(s) contain three dimensions (t, y, x) and bands as variables.

If `write_json_descr` is TRUE, the function will write an addition file with the same name as the NetCDF file but ".json" suffix. This file includes a serialized description of the input data cube, including all chained data cube operations.

To reduce the size of created files, values can be packed by applying a scale factor and an offset value and using a smaller integer data type for storage (only supported if `chunked = TRUE`). The `pack` argument can be either NULL (the default), or a list with elements `type`, `scale`, `offset`, and `nodata`. `type` can be any of "uint8", "uint16", "uint32", "int16", or "int32". `scale`, `offset`, and `nodata` must be numeric vectors with length one or length equal to the number of data cube bands (to use different values for different bands). The helper function [pack_minmax](#) can be used to derive offset and scale values with maximum precision from minimum and maximum data values on original scale.

If `chunked = TRUE`, names of the produced files will start with name (with removed extension), followed by an underscore and the internal integer chunk number.

Value

returns (invisibly) the path of the created netCDF file(s)

Note

Packing is currently ignored if `chunked = TRUE`

See Also

[gdalcubes_options](#)

[pack_minmax](#)

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
```

```

        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-04", t1="2018-04"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
write_ncdf(select_bands(raster_cube(L8.col, v), c("B04", "B05")), fname=tempfile(fileext = ".nc"))

```

write_tif

Export a data cube as a collection of GeoTIFF files

Description

This function will time slices of a data cube as GeoTIFF files in a given directory.

Usage

```

write_tif(
  x,
  dir = tempfile(pattern = ""),
  prefix = basename(tempfile(pattern = "cube_")),
  overviews = FALSE,
  COG = FALSE,
  rsmpl_overview = "nearest",
  creation_options = NULL,
  write_json_descr = FALSE,
  pack = NULL
)

```

Arguments

x	a data cube proxy object (class cube)
dir	destination directory
prefix	output file name
overviews	logical; generate overview images
COG	logical; create cloud-optimized GeoTIFF files (forces overviews=TRUE)
rsmpl_overview	resampling method for overviews (image pyramid) generation (see https://gdal.org/programs/gdaladdo.html for available methods)
creation_options	additional creation options for resulting GeoTIFF files, e.g. to define compression (see https://gdal.org/drivers/raster/gtiff.html#creation-options)
write_json_descr	logical; write a JSON description of x as additional file
pack	reduce output file size by packing values (see Details), defaults to no packing

Details

If `write_json_descr` is `TRUE`, the function will write an additional file with name according to prefix (if not missing) or simply `cube.json`. This file includes a serialized description of the input data cube, including all chained data cube operations.

Additional GDAL creation options for resulting GeoTIFF files must be passed as a named list of simple strings, where element names refer to the key. For example, `creation_options = list("COMPRESS" = "DEFLATE", "ZLEVEL" = "5")` would enable deflate compression at level 5.

To reduce the size of created files, values can be packed by applying a scale factor and an offset value and using a smaller integer data type for storage. The `pack` argument can be either `NULL` (the default), or a list with elements `type`, `scale`, `offset`, and `nodata`. `type` can be any of `"uint8"`, `"uint16"`, `"uint32"`, `"int16"`, or `"int32"`. `scale`, `offset`, and `nodata` must be numeric vectors with length one or length equal to the number of data cube bands (to use different values for different bands). The helper function `pack_minmax` can be used to derive offset and scale values with maximum precision from minimum and maximum data values on original scale.

If `overviews=TRUE`, the numbers of pixels are halved until the longer spatial dimensions counts less than 256 pixels. Setting `COG=TRUE` automatically sets `overviews=TRUE`.

Value

returns (invisibly) a vector of paths pointing to the created GeoTIFF files

See Also

[pack_minmax](#)

Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"), quiet = TRUE)
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-04"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
write_tif(select_bands(raster_cube(L8.col, v), c("B04", "B05")), dir=tempdir())
```

Index

.copy_cube, 4
[.cube (gdalcubes_selection), 40
\$.cube (gdalcubes_selection), 40

add_collection_format, 4
add_images, 5
aggregate_space, 6
aggregate_time, 7
animate, 8
apply_pixel, 10
apply_pixel.array, 10, 11
apply_pixel.cube, 10, 12
apply_time, 13
apply_time.array, 14, 15
apply_time.cube, 14, 16
as_array, 17
as_json, 18, 46

bands, 19

chunk_apply, 20, 60, 61, 81
collection_formats, 21, 22
create_image_collection, 22, 43
crop, 24
cube_view, 25

dim.cube, 27, 71
dimension_bounds, 29
dimension_values, 30
dimensions, 28

extent, 26, 30
extract_geom, 31

fill_time, 33
filter_geom, 34
filter_pixel, 36

gdalcubes, 37
gdalcubes_gdal_has_geos, 38
gdalcubes_gdalformats, 37
gdalcubes_gdalversion, 38
gdalcubes_options, 38, 55, 83
gdalcubes_selection, 40
gdalcubes_set_gdal_config, 42
gdalcubes_version, 43

image_collection, 43
image_mask, 44, 59

join_bands, 45
json_cube, 46, 46

memsize, 47
merge(), 32

names.cube, 48
nbands, 49
ncdf_cube, 49
nt, 50
nx, 51
ny, 52

pack_minmax, 53, 83, 85
plot.cube, 9, 54
print.cube, 56
print.cube_view, 57
print.image_collection, 57
proj4, 58

raster_cube, 5, 20, 23, 43, 44, 46, 59, 70
read_chunk_as_array, 60
reduce_space, 61
reduce_space.array, 62, 62
reduce_space.cube, 62, 63
reduce_time, 16, 64
reduce_time.array, 65, 65
reduce_time.cube, 65, 66
rename_bands, 68

select_bands, 69
select_time, 70

sf package, [32](#)
size, [27](#), [71](#)
slice_space, [72](#)
slice_time, [73](#)
srs, [74](#)
st_as_stars.cube, [78](#)
st_bbox, [40](#)
st_sfc, [40](#)
stac_image_collection, [77](#)
stack_cube, [75](#)

window_time, [79](#)
window_time.cube, [79](#), [80](#)
write_chunk_from_array, [81](#)
write_ncdf, [49](#), [53](#), [82](#)
write_tif, [53](#), [84](#)