

# Package ‘rmarchingcubes’

June 17, 2021

**Type** Package

**Title** Calculate 3D Contour Meshes Using the Marching Cubes Algorithm

**Version** 0.1.3

**Date** 2021-06-14

**Author** S. H. Wilks <sw463@cam.ac.uk> [aut, cre],  
Thomas Lewiner <lewiner@gmail.com> [aut]

**Maintainer** S. H. Wilks <sw463@cam.ac.uk>

**Description** A port of the C++ routine for applying the marching cubes algorithm written by Thomas Lewiner et al. (2012) <[doi:10.1080/10867651.2003.10487582](https://doi.org/10.1080/10867651.2003.10487582)> into an R package. The package supplies the `contour3d()` function, which takes a 3-dimensional array of voxel data and calculates the vertices, vertex normals, and faces for a 3d mesh representing the contour(s) at a given level.

**URL** <https://github.com/shwilks/rmarchingcubes>

**BugReports** <https://github.com/shwilks/rmarchingcubes/issues>

**Language** en-US

**License** MIT + file LICENSE

**Imports** Rcpp (>= 1.0.5)

**LinkingTo** Rcpp, RcppArmadillo

**RoxygenNote** 7.1.1

**Suggests** rmarkdown, knitr, testthat (>= 3.0.0)

**Config/testthat/edition** 3

**VignetteBuilder** knitr

**NeedsCompilation** yes

**Repository** CRAN

**Date/Publication** 2021-06-16 22:30:07 UTC

## R topics documented:

contour3d . . . . . 2

**Index** . . . . . 3

---

`contour3d`*Compute Isosurface, a Three Dimension Contour*

---

**Description**

Computes a 3D contours or isosurface by the marching cubes algorithm.

**Usage**

```
contour3d(griddata, level, x, y, z)
```

**Arguments**

<code>griddata</code>	A three dimensional array from which to calculate the contour
<code>level</code>	The level at which to construct the contour surface
<code>x, y, z</code>	locations of grid planes at which values in <code>griddata</code> are measured

**Value**

Returns a list with coordinates of each surface vertex, indices of the vertices that make up each triangle, and surface normals at each vertex

# Index

contour3d, [2](#)