

Package ‘sfdep’

August 15, 2022

Title Spatial Dependence for Simple Features

Version 0.2.0

Description An interface to 'spdep' to integrate with 'sf' objects and the 'tidyverse'.

License GPL-3

URL <https://sfdep.josiahparry.com>,

<https://github.com/josiahparry/sfdep>

Suggests broom, dbscan, dplyr, ggplot2, knitr, magrittr, patchwork, purrr, pracma, rmarkdown, sfnetworks, stringr, testthat (>= 3.0.0), tibble, tidyr, vctrs, yaml, zoo, Kendall, readr

Config/testthat/edition 3

Encoding UTF-8

RoxygenNote 7.2.1

Imports sf, cli, spdep, stats, rlang

Depends R (>= 3.5.0)

LazyData true

VignetteBuilder knitr

NeedsCompilation no

Author Josiah Parry [aut, cre] (<<https://orcid.org/0000-0001-9910-865X>>)

Maintainer Josiah Parry <josiah.parry@gmail.com>

Repository CRAN

Date/Publication 2022-08-15 13:30:02 UTC

R topics documented:

active	3
as_sf	4
center_mean	5
complete_spacetime_cube	6
cond_permute_nb	7

critical_threshold	8
ellipse	8
emerging_hotspot_analysis	9
find_xj	11
global_c	12
global_colocation	13
global_c_perm	14
global_c_test	15
global_g_test	16
global_jc_perm	16
global_moran	18
global_moran_bv	18
global_moran_perm	19
global_moran_test	20
guerry	21
include_self	22
is_spacetime_cube	23
local_c	24
local_colocation	26
local_g	27
local_gstar	28
local_jc_bv	29
local_jc_uni	30
local_moran	31
local_moran_bv	32
losh	33
nb_match_test	34
nb_union	35
pairwise_colocation	36
pct_nonzero	37
recreate_listw	38
set_col	38
spacetime	39
spatial_gini	41
spt_update	42
std_dev_ellipse	42
std_distance	43
st_as_edges	44
st_as_graph	45
st_as_nodes	46
st_block_nb	47
st_cardinalties	48
st_complete_nb	48
st_contiguity	49
st_dist_band	50
st_inverse_distance	50
st_kernel_weights	51
st_knn	52

st_lag	53
st_nb_apply	54
st_nb_dists	55
st_nb_lag	56
st_nb_lag_cumul	57
st_weights	57
szero	58
tidyverse	59
wt_as_matrix	59

Index**61**

active	<i>Activate spacetime context</i>
--------	-----------------------------------

Description

From a [spacetime](#) object, activate either the data or geometry contexts. The active object will then become available for manipulation.

Usage

```
active(x)
```

```
activate(x, what = NULL)
```

Arguments

x	a spacetime object
what	default NULL. Determines which context to activate. Valid argument values are "geometry" and "data". If left null, returns x.

Details

A [spacetime](#) object contains both a data frame and an sf object. The data frame represents geographies over one or more time periods and the sf object contains the geographic information for those locations.

Examples

```
df_fp <- system.file("extdata", "bos-ecometric.csv", package = "sfdep")
geo_fp <- system.file("extdata", "bos-ecometric.geojson", package = "sfdep")

# read in data
df <- readr::read_csv(df_fp, col_types = "ccidD")
geo <- sf::read_sf(geo_fp)

# Create spacetime object called `bos`
bos <- spacetime(df, geo,
```

```

        .loc_col = ".region_id",
        .time_col = "time_period")

active(bos)
activate(bos, "geometry")

```

as_sf

Cast between spacetime and sf classes

Description

Cast between spacetime and sf classes
 Convert sf object to spacetime

Usage

```

as_sf(x, ...)

as_spacetime(x, .loc_col, .time_col, ...)

## S3 method for class 'sf'
as_spacetime(x, .loc_col, .time_col, ...)

```

Arguments

x for `st_as_sf()` a spacetime object. For `as_spacetime()` an sf object.
 ... arguments passed to merge.
 .loc_col the quoted name of the column containing unique location identifiers.
 .time_col the quoted name of the column containing time periods.

Examples

```

if (FALSE) {
df_fp <- system.file("extdata", "bos-ecometric.csv", package = "sfdep")
geo_fp <- system.file("extdata", "bos-ecometric.geojson", package = "sfdep")

# read in data
df <- readr::read_csv(df_fp, col_types = "ccidD")
geo <- sf::read_sf(geo_fp)

# Create spacetime object called `bos`
bos <- spacetime(df, geo,
                .loc_col = ".region_id",
                .time_col = "time_period")

as_sf(bos)
as_spacetime(as_sf(bos), ".region_id", "year")

```

```
}
```

center_mean	<i>Calculate Center Mean Point</i>
-------------	------------------------------------

Description

Given an sfc object containing points, calculate a measure of central tendency.

Usage

```
center_mean(geometry, weights = NULL)

center_median(geometry)

euclidean_median(geometry, tolerance = 1e-09)
```

Arguments

geometry	an sfc object. If a polygon, uses sf::st_point_on_surface() .
weights	an optional vector of weights to apply to the coordinates before calculation.
tolerance	a tolerance level to terminate the process. This is passed to pracma::geo_median() .

Details

- `center_mean()` calculates the mean center of a point pattern
- `euclidean_median()` calculates the euclidean median center of a point pattern using the `pracma` package
- `center_median()` calculates the median center it is recommended to use the euclidean median over the this function.

See Also

Other point-pattern: [std_distance\(\)](#)
Other point-pattern: [std_distance\(\)](#)

Examples

```
# Make a grid to sample from
grd <- sf::st_make_grid(n = c(1, 1), cellsize = c(100, 100), offset = c(0,0))

# sample 100 points
pnts <- sf::st_sample(grd, 100)

cm <- center_mean(pnts)
```

```
em <- euclidean_median(pnts)
cmcd <- center_median(pnts)

plot(pnts)
plot(cm, col = "red", add = TRUE)
plot(em, col = "blue", add = TRUE)
plot(cmcd, col = "green", add = TRUE)
```

complete_spacetime_cube

Convert spacetime object to spacetime cube

Description

Given a spacetime object, convert it to a spacetime cube. A spacetime cube ensures that there is a regular time-series for each geometry present.

Usage

```
complete_spacetime_cube(x, ...)
```

Arguments

x	a spacetime object.
...	unused

Details

If observations are missing for a time period and location combination, columns will be populated with NAs.

See [is_spacetime_cube\(\)](#) for more details on spacetime cubes.

Examples

```
df_fp <- system.file("extdata", "bos-ecometric.csv", package = "sfdep")
geo_fp <- system.file("extdata", "bos-ecometric.geojson", package = "sfdep")

# read in data
df <- readr::read_csv(df_fp, col_types = "ccidD")
geo <- sf::read_sf(geo_fp)

# Create spacetime object called `bos`
bos <- spacetime(df, geo,
                .loc_col = ".region_id",
                .time_col = "time_period")

# create a sample of data
set.seed(0)
sample_index <- sample(1:nrow(bos), nrow(bos) * 0.95)
```

```
incomplete_spt <- bos[sample_index,]  
  
# check to see if is spacetime cube  
is_spacetime_cube(incomplete_spt)  
  
# complete it again  
complete_spacetime_cube(incomplete_spt)
```

cond_permute_nb	<i>Conditional permutation of neighbors</i>
-----------------	---

Description

Creates a conditional permutation of neighbors list holding *i* fixed and shuffling it's neighbors.

Usage

```
cond_permute_nb(nb, seed = NULL)
```

Arguments

nb	a neighbor list.
seed	default null. A value to pass to <code>set.seed()</code> for reproducibility.

Value

A list of class `nb` where each element contains a random sample of neighbors excluding the observed region.

Examples

```
nb <- st_contiguity(guerry)  
nb[1:5]  
# conditionally permute neighbors  
perm_nb <- cond_permute_nb(nb)  
perm_nb[1:5]
```

`critical_threshold` *Identify critical threshold*

Description

Identifies the minimum distance in which each observation will have at least one neighbor.

Usage

```
critical_threshold(geometry, k = 1)
```

Arguments

<code>geometry</code>	an sf geometry column
<code>k</code>	the minimum number of neighbors to check for

Value

a numeric scalar value.

Examples

```
critical_threshold(sf::st_geometry(guerry))
```

`ellipse` *Create an Ellipse*

Description

Generate an ellipse from center coordinates, major and minor axis radii, and angle rotation.

Usage

```
ellipse(x = 0, y = 0, sx = 2, sy = 1, rotation = 0, n = 100)
```

```
st_ellipse(geometry, sx, sy, rotation = 0, n = 100)
```

Arguments

<code>x</code>	longitude of center point
<code>y</code>	latitude of center point
<code>sx</code>	radius of major axis
<code>sy</code>	radius of minor axis
<code>rotation</code>	the degree of rotation of the ellipse
<code>n</code>	the number of coordinates to generate for the ellipse
<code>geometry</code>	an sf ST_POINT geometry. Can be sfg, sfc, or sf object

Details

`ellipse()` returns a matrix of point locations defining the ellipse. `st_ellipse()` returns an sf object with LINE geography of the ellipse. Increasing `n` increases the number of points generated to define the ellipse shape.

`ellipse()` function is adapted from `ggVennDiagram`.

Examples

```
ellipse(n = 10)
st_ellipse(sf::st_point(c(0, 0)), sx = 10, sy = 10)
```

emerging_hotspot_analysis

Emerging Hot Spot Analysis

Description

Emerging Hot Spot Analysis identifies trends in spatial clustering over a period of time. Emerging hot spot analysis combines the Getis-Ord G_i^* statistic with the Mann-Kendall trend test to determine if there is a temporal trend associated with local clustering of hot and cold spots.

Usage

```
emerging_hotspot_analysis(  
  x,  
  .var,  
  k = 1,  
  include_gi = FALSE,  
  nb_col = NULL,  
  wt_col = NULL,  
  nsim = 199,  
  threshold = 0.01,  
  ...  
)
```

Arguments

<code>x</code>	a spacetime object and must be a spacetime cube see details for more.
<code>.var</code>	a numeric vector in the spacetime cube with no missing values.
<code>k</code>	default 1. The number of time lags to include in the neighborhood for calculating the local G_i^* . See details for more.
<code>include_gi</code>	default FALSE. If TRUE, includes the local G_i^* calculations in the attribute <code>gi_star</code> .
<code>nb_col</code>	Optional. Default NULL. The name of the column in the geometry context of <code>x</code> containing spatial neighbors. If NULL, Queen's contiguity neighbors are identified.

wt_col	Optional. Default NULL. The name of the column in the geometry context of x containing spatial weights. If NULL, row standardized weights are used.
nsim	default 199. The number of simulations to run in calculating the simulated p-value for the local G_i^* .
threshold	default 0.01. The significance threshold to use.
...	unused.

Details

How Emerging Hot Spot Analysis Works:

Emerging Hot Spot Analysis is a somewhat simple process. It works by first calculating the G_i^* statistic for each location in each time period (time-slice). Next, for each location across all time-periods, the Mann-Kendall trend test is done to identify any temporal trend in G_i^* values over all time periods. Additionally, each location is classified into one of seventeen categories based on [ESRI's emerging hot spot classification criteria](#).

The Mann-Kendall trend test is done using `Kendall::MannKendall()`. `Kendall` is not installed with `sfdep` and should be installed prior to use.

Using your own neighbors and weights:

If you would like to use your own neighbors and weights, they must be created in the geometry context of a spatetime object. The arguments `nb_col` and `wt_col` must both be populated in order to use your own neighbor and weights definitions.

Time lagged neighbors:

In addition to identifying neighbors in space, emerging hotspot analysis also incorporates the same observations from k periods ago-called a time lag. If the time lag k is 1 and the unit of time is month, the neighbors for the calculation of G_i^* would include the spatial neighbors' values at time t and the same spatial neighbors' values at time $t-1$. If $k = 2$, it would include t , $t-1$, and $t-2$.

Missing values:

Presently, there is no method of missing value handling. If there are missing values, the emerging hot spot analysis will fail. Be sure to fill or omit time-slices with missing values *prior* to using emerging hot spot analysis.

Value

Returns a data.frame.

See Also

[How Emerging Hot Spot Analysis works](#), [Emerging Hot Spot Analysis \(Space Time Pattern Mining\)](#), and the video [Spatial Data Mining II: A Deep Dive into Space-Time Analysis](#) by ESRI.

Examples

```
if (FALSE) {  
  
  df_fp <- system.file("extdata", "bos-ecometric.csv", package = "sfdep")  
  geo_fp <- system.file("extdata", "bos-ecometric.geojson", package = "sfdep")  
  
  # read in data  
  df <- readr::read_csv(df_fp, col_types = "ccidD")  
  geo <- sf::read_sf(geo_fp)  
  
  # Create spacetime object called `bos`  
  bos <- spacetime(df, geo,  
                  .loc_col = ".region_id",  
                  .time_col = "time_period")  
  
  # conduct EHSA  
  ehsa <- emerging_hotspot_analysis(  
    x = bos,  
    .var = "value",  
    k = 1,  
    nsim = 99  
  )  
  
  ehsa  
}
```

find_xj

Identify xj values

Description

Find xj values given a numeric vector, x, and neighbors list, nb.

Usage

```
find_xj(x, nb)
```

Arguments

x	a vector of any class
nb	a nb object e.g. created by st_contiguity() or st_knn()

Value

A list of length x where each element is a numeric vector with the same length as the corresponding element in nb.

Examples

```
nb <- st_contiguity(sf::st_geometry(guerry))
xj <- find_xj(guerry$crime_prop, nb)
xj[1:3]
```

`global_c`*Compute Geary's C*

Description

Compute Geary's C

Usage

```
global_c(x, nb, wt, allow_zero = NULL)
```

Arguments

<code>x</code>	A numeric vector.
<code>nb</code>	a neighbor list object for example as created by <code>st_contiguity()</code> .
<code>wt</code>	a weights list as created by <code>st_weights()</code> .
<code>allow_zero</code>	If TRUE, assigns zero as lagged value to zone without neighbors.

Value

a list with two names elements C and K returning the value of Geary's C and sample kurtosis respectively.

See Also

Other `global_c`: [global_c_perm\(\)](#), [global_c_test\(\)](#)

Examples

```
nb <- guerry_nb$nb
wt <- guerry_nb$wt
x <- guerry_nb$crime_pers
global_c(x, nb, wt)
```

global_colocation	<i>Global Colocation Quotient</i>
-------------------	-----------------------------------

Description

Calculate the Global Colocation Quotient (CLQ) for a categorical variable using simulation based significance testing.

Usage

```
global_colocation(A, nb, nsim = 99)
```

Arguments

A	a character or factor vector.
nb	a neighbors list e.g. created by <code>st_knn()</code> or <code>st_contiguity()</code>
nsim	default 99. An integer representing how many simulations to run for calculating the simulated p-values.

Details

Definition:

The CLQ is defined as $CLQ_{Global} = \frac{\sum_{A \in X} C_{A \rightarrow A}}{\sum_{A \in X} N_A \left(\frac{N_A - 1}{N - 1} \right)}$. The numerator identifies the observed proportion of same-category neighbors while the denominator contains the *expected* proportion of same-category neighbors under the assumption of no spatial association. Thus the CLQ is just a ratio of observed to expected.

Inference:

Inference is done using conditional permutation as suggested by Anselin 1995 where a number of replicates are created. The observed values are compared to the replicates and a the simulated p-value is the proportion of cases where the observed is more extreme as compared to replicate. The simulated p-value returns the lower p-value of either tail.

Interpretation:

Given that the CLQ is a ratio of the observed to expected, we interpret values larger than one to mean that there is more colocation than to be expected under the null hypothesis of no spatial association. When the value is smaller than 0, we interpret it to mean that there is less colocation than expected under the null.

Value

A list of two elements CLQ and p_sim containing the observed colocation quotient and the simulated p-value respectively.

References

Leslie, T.F. and Kronenfeld, B.J. (2011), The Colocation Quotient: A New Measure of Spatial Association Between Categorical Subsets of Points. *Geographical Analysis*, 43: 306-326. doi: [10.1111/j.15384632.2011.00821.x](https://doi.org/10.1111/j.15384632.2011.00821.x)

Examples

```
A <- guerry$main_city
nb <- st_contiguity(sf::st_geometry(guerry))
global_colocation(A, nb, 49)
```

global_c_perm	<i>Global C Permutation Test</i>
---------------	----------------------------------

Description

Global C Permutation Test

Usage

```
global_c_perm(
  x,
  nb,
  wt,
  nsim = 499,
  alternative = "greater",
  allow_zero = NULL,
  ...
)
```

Arguments

<code>x</code>	A numeric vector.
<code>nb</code>	a neighbor list object for example as created by <code>st_contiguity()</code> .
<code>wt</code>	a weights list as created by <code>st_weights()</code> .
<code>nsim</code>	number of simulations to run.
<code>alternative</code>	default "two.sided". Should be one of "greater", "less", or "two.sided" to specify the alternative hypothesis.
<code>allow_zero</code>	If TRUE, assigns zero as lagged value to zone without neighbors.
<code>...</code>	additional arguments passed to <code>spdep::geary.mc()</code> .

Value

an object of classes `htest` and `mc.sim`

See Also

Other global_c: [global_c_test\(\)](#), [global_c\(\)](#)

Examples

```
geo <- sf::st_geometry(guerry)
nb <- st_contiguity(geo)
wt <- st_weights(nb)
x <- guerry$crime_pers
global_c_perm(x, nb, wt)
```

global_c_test	<i>Global C Test</i>
---------------	----------------------

Description

Global C Test

Usage

```
global_c_test(x, nb, wt, randomization = TRUE, allow_zero = NULL, ...)
```

Arguments

x	A numeric vector.
nb	a neighbor list object for example as created by st_contiguity() .
wt	a weights list as created by st_weights() .
randomization	default TRUE. Calculate variance based on randomization. If FALSE, under the assumption of normality.
allow_zero	If TRUE, assigns zero as lagged value to zone without neighbors.
...	additional arguments passed to spdep::moran.mc()

Value

an htest object

See Also

Other global_c: [global_c_perm\(\)](#), [global_c\(\)](#)

Examples

```
geo <- sf::st_geometry(guerry)
nb <- st_contiguity(geo)
wt <- st_weights(nb)
x <- guerry$crime_pers
global_c_test(x, nb, wt)
```

global_g_test	<i>Getis-Ord Global G</i>
---------------	---------------------------

Description

Getis-Ord Global G

Usage

```
global_g_test(x, nb, wt, alternative = "greater", allow_zero = NULL, ...)
```

Arguments

x	A numeric vector.
nb	a neighbor list object for example as created by <code>st_contiguity()</code> .
wt	a weights list as created by <code>st_weights()</code> .
alternative	default "two.sided". Should be one of "greater", "less", or "two.sided" to specify the alternative hypothesis.
allow_zero	If TRUE, assigns zero as lagged value to zone without neighbors.
...	additional methods passed to <code>spdep::globalG.test()</code> .

Value

an htest object

Examples

```
geo <- sf::st_geometry(guerry)
nb <- st_contiguity(geo)
wt <- st_weights(nb, style = "B")
x <- guerry$crime_pers
global_g_test(x, nb, wt)
```

global_jc_perm	<i>Global Join Counts</i>
----------------	---------------------------

Description

Calculate global join count measure for a categorical variable.

Usage

```
global_jc_perm(
  fx,
  nb,
  wt,
  alternative = "greater",
  nsim = 499,
  allow_zero = FALSE,
  ...
)

global_jc_test(fx, nb, wt, alternative = "greater", allow_zero = NULL, ...)

tally_jc(fx, nb, wt, allow_zero = TRUE, ...)
```

Arguments

fx	a factor or character vector of the same length as nb.
nb	a neighbor list object for example as created by <code>st_contiguity()</code> .
wt	a weights list as created by <code>st_weights()</code> .
alternative	default "two.sided". Should be one of "greater", "less", or "two.sided" to specify the alternative hypothesis.
nsim	number of simulations to run.
allow_zero	If TRUE, assigns zero as lagged value to zone without neighbors.
...	additional arguments passed to methods

Details

- `global_jc_perm()` implements the monte-carlo based join count using `spdep::joincount.mc()`
- `global_jc_test()` implements the traditional BB join count statistic using `spdep::joincount.test()`
- `tally_jc()` calculated join counts for a variable `fx` and returns a `data.frame` using `spdep::joincount.multi()`

Value

an object of class `jclist` which is a list where each element is of class `hctest` and `mc.sim`.

Examples

```
geo <- sf::st_geometry(guerry)
nb <- st_contiguity(geo)
wt <- st_weights(nb, style = "B")
fx <- guerry$region
global_jc_perm(fx, nb, wt)

global_jc_test(fx, nb, wt)

tally_jc(fx, nb, wt)
```

global_moran	<i>Calculate Global Moran's I</i>
--------------	-----------------------------------

Description

Calculate Global Moran's I

Usage

```
global_moran(x, nb, wt, na_ok = FALSE, ...)
```

Arguments

x	A numeric vector.
nb	a neighbor list object for example as created by <code>st_contiguity()</code> .
wt	a weights list as created by <code>st_weights()</code> .
na_ok	default FALSE. If FALSE presence or NA or Inf results in an error.
...	additional arguments passed to <code>spdep::moran()</code> .

Value

an htest object

See Also

Other global_moran: `global_moran_bv()`, `global_moran_perm()`, `global_moran_test()`, `local_moran_bv()`

Examples

```
nb <- guerry_nb$nb
wt <- guerry_nb$wt
x <- guerry_nb$crime_pers
moran <- global_moran(x, nb, wt)
```

global_moran_bv	<i>Compute the Global Bivariate Moran's I</i>
-----------------	---

Description

Given two continuous numeric variables, calculate the bivariate Moran's I. See details for more.

Usage

```
global_moran_bv(x, y, nb, wt, nsim = 99)
```

Arguments

x	a numeric vector of same length as nb.
y	a numeric vector of same length as nb.
nb	a neighbor list object for example as created by <code>st_contiguity()</code> .
wt	a weights list as created by <code>st_weights()</code> .
nsim	the number of simulations to run.

Details

The Global Bivariate Moran is defined as

$$I_B = \frac{\sum_i (\sum_j w_{ij} y_j \times x_i)}{\sum_i x_i^2}$$

It is important to note that this is a measure of autocorrelation of X with the spatial lag of Y. As such, the resultant measure may overestimate the amount of spatial autocorrelation which may be a product of the inherent correlation of X and Y.

Value

a named list with two elements `Ib` and `p_sim` containing the bivariate Moran's I and simulated p-value respectively.

References

[Global Spatial Autocorrelation \(2\): Bivariate, Differential and EB Rate Moran Scatter Plot, Luc Anselin](#)

See Also

Other `global_moran`: `global_moran_perm()`, `global_moran_test()`, `global_moran()`, `local_moran_bv()`

Examples

```
x <- guerry_nb$crime_pers
y <- guerry_nb$wealth
nb <- guerry_nb$nb
wt <- guerry_nb$wt
global_moran_bv(x, y, nb, wt)
```

`global_moran_perm` *Global Moran Permutation Test*

Description

Global Moran Permutation Test

Usage

```
global_moran_perm(x, nb, wt, alternative = "two.sided", nsim = 499, ...)
```

Arguments

x	A numeric vector.
nb	a neighbor list object for example as created by <code>st_contiguity()</code> .
wt	a weights list as created by <code>st_weights()</code> .
alternative	default "two.sided". Should be one of "greater", "less", or "two.sided" to specify the alternative hypothesis.
nsim	number of simulations to run.
...	additional arguments passed to <code>spdep::moran.mc()</code>

Value

an object of classes `htest`, and `mc.sim`.

See Also

Other `global_moran`: [global_moran_bv\(\)](#), [global_moran_test\(\)](#), [global_moran\(\)](#), [local_moran_bv\(\)](#)

Examples

```
nb <- guerry_nb$nb
wt <- guerry_nb$wt
x <- guerry_nb$crime_pers
moran <- global_moran_perm(x, nb, wt)
broom::tidy(moran)
```

global_moran_test	<i>Global Moran Test</i>
-------------------	--------------------------

Description

Global Moran Test

Usage

```
global_moran_test(
  x,
  nb,
  wt,
  alternative = "greater",
  randomization = TRUE,
  ...
)
```

Arguments

<code>x</code>	A numeric vector.
<code>nb</code>	a neighbor list object for example as created by <code>st_contiguity()</code> .
<code>wt</code>	a weights list as created by <code>st_weights()</code> .
<code>alternative</code>	default "two.sided". Should be one of "greater", "less", or "two.sided" to specify the alternative hypothesis.
<code>randomization</code>	default TRUE. Calculate variance based on randomization. If FALSE, under the assumption of normality.
<code>...</code>	additional arguments passed to <code>spdep::moran.mc()</code>

Value

an object of class `hstest`

See Also

Other `global_moran`: `global_moran_bv()`, `global_moran_perm()`, `global_moran()`, `local_moran_bv()`

Examples

```
nb <- guerry_nb$nb
wt <- guerry_nb$wt
x <- guerry_nb$crime_pers
global_moran_test(x, nb, wt)
```

guerry

"Essay on the Moral Statistics of France" data set.

Description

This dataset has been widely used to demonstrate geospatial methods and techniques. As such it is useful for inclusion to this R package for the purposes of example. The dataset in this package is modified from Guerry by [Michael Friendly](#).

Usage

guerry

guerry_nb

Format

An object of class `sf` (inherits from `tbl_df`, `tbl`, `data.frame`) with 85 rows and 27 columns.

`guerry` an `sf` object with 85 observations and 27 variables. `guerry_nb` has 2 additional variables created by `sfdep`.

Details

guerry and guerry_nb objects are sf class objects. These are polygons of the boundaries of France (excluding Corsica) as they were in 1830.

Source

Guerry::gfrance85

include_self	<i>Includes self in neighbor list</i>
--------------	---------------------------------------

Description

Includes observed region in list of own neighbors. For some neighbor lists, it is important to include the *i*th observation (or self) in the neighbors list, particularly for kernel weights.

Usage

```
include_self(nb)
remove_self(nb)
```

Arguments

nb an object of class nb e.g. made by `st_contiguity()`

Value

An object of class nb.

Examples

```
nb <- st_contiguity(guerry)
self_included <- include_self(nb)
self_included
remove_self(self_included)
```

is_spacetime_cube	<i>Test if a spacetime object is a spacetime cube</i>
-------------------	---

Description

Given an object with class `spacetime`, determine if it is a *spacetime cube*. If the time-series is irregular a warning is emitted (see `validate_spacetime()` for more on the restrictions on the time column).

Usage

```
is_spacetime_cube(x, ...)
```

Arguments

x	a spacetime object
...	unused

Details

A spacetime object is a spacetime cube when it contains a regular time-series representation of each geometry. That is, only one observation for at each time period per geography is present.

The number of rows in a spacetime cube is the number of geographies multiplied by the number of time periods. For example if there are 10 locations and 20 time periods, the number of rows must be 200.

Validation

`is_spacetime_cube()` runs a number of checks that to ensure that the provided object is in fact a spacetime cube. It checks that:

- the number of rows is equal to the number of locations multiplied by the number of time periods
- each time period has an equal number of observations
- each location has an equal number of observations
- each combination of time period and location has only one observation
- that the time-series is regular

Examples

```
df_fp <- system.file("extdata", "bos-ecometric.csv", package = "sfdep")
geo_fp <- system.file("extdata", "bos-ecometric.geojson", package = "sfdep")

# read in data
df <- readr::read_csv(df_fp, col_types = "ccidD")
geo <- sf::read_sf(geo_fp)
```

```
# Create spacetime object called `bos`
bos <- spacetime(df, geo,
                .loc_col = ".region_id",
                .time_col = "time_period")

is_spacetime_cube(bos)
is_spacetime_cube(bos[round(runif(1000, 0, nrow(bos))),])
is_spacetime_cube(guerry)
```

local_c

Compute Local Geary statistic

Description

The Local Geary is a local adaptation of Geary's C statistic of spatial autocorrelation. The Local Geary uses squared differences to measure dissimilarity unlike the Local Moran. Low values of the Local Geary indicate positive spatial autocorrelation and large refers to negative spatial autocorrelation. Inference for the Local Geary is based on a permutation approach which compares the observed value to the reference distribution under spatial randomness. The Local Geary creates a pseudo p-value. This is not an analytical p-value and is based on the number of permutations and as such should be used with care.

Usage

```
local_c(x, nb, wt, ...)
```

```
local_c_perm(x, nb, wt, nsim = 499, alternative = "two.sided", ...)
```

Arguments

x	a numeric vector, or list of numeric vectors of equal length.
nb	a neighbor list
wt	a weights list
...	other arguments passed to <code>spdep::localC_perm()</code> , e.g. <code>zero.policy = TRUE</code> to allow for zones without neighbors.
nsim	The number of simulations used to generate reference distribution.
alternative	A character defining the alternative hypothesis. Must be one of "two.sided", "less" or "greater".

Details

Overview:

The Local Geary can be extended to a multivariate context. When `x` is a numeric vector, the univariate Local Geary will be calculated. To calculate the multivariate Local Moran provide either a list or a matrix. When `x` is a list, each element must be a numeric vector of the same length and of the same length as the neighbours in `listw`. In the case that `x` is a matrix the number of rows must be the same as the length of the neighbours in `listw`.

While not required in the univariate context, the standardized Local Geary is calculated. The multivariate Local Geary is *always* standardized.

The univariate Local Geary is calculated as $c_i = \sum_j w_{ij}(x_i - x_j)^2$ and the multivariate Local Geary is calculated as $c_{k,i} = \sum_{v=1}^k c_{v,i}$ as described in Anselin (2019).

Implementation:

These functions are based on the implementations of the local Geary statistic in the development version of `spdep`. They are based on `spdep::localC` and `spdep::localC_perm`.

`spdep::localC_perm` and thus `local_c_perm` utilize a conditional permutation approach to approximate a reference distribution where each observation `i` is held fixed, randomly samples neighbors, and calculated the local C statistic for that tuple (`ci`). This is repeated `nsim` times. From the simulations 3 different types of p-values are calculated—all of which have their potential flaws. So be *extra judicious* with using p-values to make conclusions.

- `p_ci`: utilizes the sample mean and standard deviation. The p-value is then calculated using `pnorm()`—assuming a normal distribution which isn't always true.
- `p_ci_sim`: uses the rank of the observed statistic.
- `p_folded_sim`: follows the `pysal` implementation where p-values are in the range of $[0, 0.5]$. This excludes 1/2 of all p-values and should be used with caution.

Value

a `data.frame` with columns

- `ci`: Local Geary statistic
- `e_ci`: expected value of the Local Geary based on permutations
- `z_ci`: standard deviation based on permutations
- `var_ci`: variance based on permutations
- `p_ci`: p-value based on permutation sample standard deviation and means
- `p_ci_sim`: p-value based on rank of observed statistic
- `p_folded_sim`: p-value based on the implementation of `Pysal` which always assumes a two-sided test taking the minimum possible p-value
- `skewness`: sample skewness
- `kurtosis`: sample kurtosis

Author(s)

Josiah Parry, <josiah.parry@gmail.com>

References

- Anselin, L. (1995), Local Indicators of Spatial Association—LISA. *Geographical Analysis*, 27: 93-115. doi: [10.1111/j.15384632.1995.tb00338.x](https://doi.org/10.1111/j.15384632.1995.tb00338.x)
- Anselin, L. (2019), A Local Indicator of Multivariate Spatial Association: Extending Geary's *c*. *Geogr Anal*, 51: 133-150. doi: [10.1111/gean.12164](https://doi.org/10.1111/gean.12164)

Examples

```
g <- dplyr::transmute(guerry,
  nb = st_contiguity(geometry),
  wt = st_weights(nb),
  geary = local_c_perm(
    x = list(crime_pers, literacy), nb, wt)
)

tidyr::unnest(g, geary)
```

local_colocation	<i>Local indicator of Colocation Quotient</i>
------------------	---

Description

The local indicator of the colocation quotient (LCLQ) is a Local Indicator of Spatial Association (LISA) that evaluates if a given observation's subcategory in A is colocated with subcategories in B. Like the CLQ, the LCLQ provides insight into the asymmetric relationships between subcategories of A and B (where B can also equal A) but at the local level.

The LCLQ is defined using Gaussian kernel weights and an adaptive bandwidth (see [st_kernel_weights\(\)](#)). However, any type of weights list can be used. Kernel weights are used to introduce a decay into the calculation of the CLQ. This ensures that points nearer to the focal point have more influence than those that are more distant.

Usage

```
local_colocation(A, B, nb, wt, nsim)
```

Arguments

A	a character or factor vector.
B	a character or factor vector.
nb	a neighbors list e.g. created by st_knn() or st_contiguity()
wt	a weights list. Recommended that it is a Gaussian kernel weights list using an adaptive bandwidth e.g. created by st_kernel_weights(nb, geometry, "gaussian", addaptive = TRUE) that does not include the self.
nsim	default 99. An integer representing how many simulations to run for calculating the simulated p-values.

Details

The LCLQ is defined as $LCLQ_{A_i \rightarrow B} = \frac{N_{A_i \rightarrow B}}{N_B / (N - 1)}$ where $N_{A_i \rightarrow B} = \sum_{j=1}^N (j \neq i) \left(\frac{w_{ij} f_{ij}}{\sum_{j=1}^N (j \neq i) w_{ij}} \right)$.

And the weights matrix, w_{ij} , uses adaptive bandwidth Gaussian kernel weights.

LCLQ is only calculated for those subcategories which are present in the neighbor list. If a subcategory is not present, then the resultant LCLQ and simulated p-value will be NA.

Value

a data frame with as many rows as observations in A and two times as many columns as unique values in B. Columns contain each unique value of B as well as the simulated p-value for each value of B.

References

Fahui Wang, Yujie Hu, Shuai Wang & Xiaojuan Li (2017) Local Indicator of Colocation Quotient with a Statistical Significance Test: Examining Spatial Association of Crime and Facilities, The Professional Geographer, 69:1, 22-31, doi: [10.1080/00330124.2016.1157498](https://doi.org/10.1080/00330124.2016.1157498)

Examples

```
if (FALSE) {
  A <- guerry$main_city
  B <- guerry$region
  geo <- sf::st_geometry(guerry)
  nb <- st_knn(geo, 5)
  wt <- st_kernel_weights(nb, geo, "gaussian", adaptive = TRUE)
  res <- local_colocation(A, B, nb, wt, 49)
  tail(res)
}
```

local_g	<i>Local G</i>
---------	----------------

Description

Calculate the local Geary statistic for a given variable.

Usage

```
local_g(x, nb, wt, alternative = "two.sided", ...)
```

```
local_g_perm(x, nb, wt, nsim = 499, alternative = "two.sided", ...)
```

Arguments

<code>x</code>	A numeric vector.
<code>nb</code>	a neighbor list object for example as created by <code>st_contiguity()</code> .
<code>wt</code>	a weights list as created by <code>st_weights()</code> .
<code>alternative</code>	default "two.sided". Should be one of "greater", "less", or "two.sided" to specify the alternative hypothesis.
<code>...</code>	methods passed to <code>spdep::localG()</code> or <code>spdep::localG_perm()</code>
<code>nsim</code>	The number of simulations to run.

Value

a data.frame with columns:

- gi: the observed statistic
- e_gi: the permutation sample mean
- var_gi: the permutation sample variance
- p_value: the p-value using sample mean and standard deviation
- p_folded_sim: p-value based on the implementation of Pysal which always assumes a two-sided test taking the minimum possible p-value
- skewness: sample skewness
- kurtosis: sample kurtosis

Examples

```
x <- guerry$crime_pers
nb <- st_contiguity(guerry)
wt <- st_weights(nb)

res <- local_g_perm(x, nb, wt)

head(res)
```

local_gstar

*Local G**

Description

Calculate the local G_i^* statistic.

Usage

```
local_gstar(x, nb, wt, alternative = "two.sided", ...)
```

```
local_gstar_perm(x, nb, wt, nsim = 499, alternative = "two.sided", ...)
```

Arguments

x	A numeric vector.
nb	a neighbor list object for example as created by <code>st_contiguity()</code> .
wt	a weights list as created by <code>st_weights()</code> .
alternative	default "two.sided". Should be one of "greater", "less", or "two.sided" to specify the alternative hypothesis.
...	methods passed to <code>spdep::localG()</code> or <code>spdep::localG_perm()</code>
nsim	The number of simulations to run.

Value

a data.frame with columns:

- gi: the observed statistic
- e_gi: the permutation sample mean
- var_gi: the permutation sample variance
- p_value: the p-value using sample mean and standard deviation
- p_folded_sim: p-value based on the implementation of Pysal which always assumes a two-sided test taking the minimum possible p-value
- skewness: sample skewness
- kurtosis: sample kurtosis

Examples

```
nb <- st_contiguity(guerry)
wt <- st_weights(nb)
x <- guerry$crime_pers

res <- local_gstar_perm(x, nb, wt)
head(res)

res <- local_gstar(x, nb, wt)
head(res)
```

local_jc_bv	<i>Bivariate local join count</i>
-------------	-----------------------------------

Description

Bivariate local join count

Usage

```
local_jc_bv(x, z, nb, wt, nsim = 499)
```

Arguments

x	a binary variable either numeric or logical
z	a binary variable either numeric or logical
nb	a neighbors list object.
wt	default st_weights(nb, style = "B"). A binary weights list as created by st_weights(nb, style = "B").
nsim	the number of conditional permutation simulations

Value

a data.frame with two columns join_count and p_sim and number of rows equal to the length of arguments x, z, nb, and wt.

Examples

```
x <- as.integer(guerry$infants > 23574)
z <- as.integer(guerry$donations > 10973)
nb <- st_contiguity(guerry)
wt <- st_weights(nb, style = "B")
local_jc_bv(x, z, nb, wt)
```

 local_jc_uni

Compute local univariate join count

Description

The univariate local join count statistic is used to identify clusters of rarely occurring binary variables. The binary variable of interest should occur less than half of the time.

Usage

```
local_jc_uni(
  x,
  nb,
  wt = st_weights(nb, style = "B"),
  nsim = 499,
  alternative = "two.sided"
)
```

Arguments

x	a binary variable either numeric or logical
nb	a neighbors list object.
wt	default st_weights(nb, style = "B"). A binary weights list as created by st_weights(nb, style = "B").
nsim	the number of conditional permutation simulations
alternative	default "greater". One of "less" or "greater".

Details

The local join count statistic requires a binary weights list which can be generated with st_weights(nb, style = "B"). Additionally, ensure that the binary variable of interest is rarely occurring in no more than half of observations.

P-values are estimated using a conditional permutation approach. This creates a reference distribution from which the observed statistic is compared. For more see [Geoda Glossary](#).

Value

a data.frame with two columns `join_count` and `p_sim` and number of rows equal to the length of arguments `x`, `nb`, and `wt`.

Examples

```
res <- dplyr::transmute(
  guerry,
  top_crime = crime_prop > 9000,
  nb = st_contiguity(geometry),
  wt = st_weights(nb, style = "B"),
  jc = local_jc_uni(top_crime, nb, wt))
tidyr::unnest(res, jc)
```

 local_moran

Calculate the Local Moran's I Statistic

Description

Moran's I is calculated for each polygon based on the neighbor and weight lists.

Usage

```
local_moran(x, nb, wt, alternative = "two.sided", nsim = 499, ...)
```

Arguments

<code>x</code>	A numeric vector.
<code>nb</code>	a neighbor list object for example as created by <code>st_contiguity()</code> .
<code>wt</code>	a weights list as created by <code>st_weights()</code> .
<code>alternative</code>	default "two.sided". Should be one of "greater", "less", or "two.sided" to specify the alternative hypothesis.
<code>nsim</code>	The number of simulations to run.
<code>...</code>	See <code>?spdep::localmoran_perm()</code> for more options.

Details

`local_moran()` calls `spdep::localmoran_perm()` and calculates the Moran I for each polygon. As well as provide simulated p-values.

Value

a data.frame containing the columns `ii`, `eii`, `var_ii`, `z_ii`, `p_ii`, `p_ii_sim`, and `p_folded_sim`. For more details please see `spdep::localmoran_perm()`.

See Also

Other stats: [st_lag\(\)](#)

Examples

```
library(magrittr)
lisa <- guerry %>%
  dplyr::mutate(nb = st_contiguity(geometry),
               wt = st_weights(nb),
               moran = local_moran(crime_pers, nb, wt))

# unnest the dataframe column
tidyr::unnest(lisa, moran)
```

 local_moran_bv

 Compute the Local Bivariate Moran's I Statistic

Description

Given two continuous numeric variables, calculate the bivariate Local Moran's I.

Usage

```
local_moran_bv(x, y, nb, wt, nsim = 499)
```

Arguments

x	a numeric vector of same length as nb.
y	a numeric vector of same length as nb.
nb	a neighbor list object for example as created by <code>st_contiguity()</code> .
wt	a weights list as created by <code>st_weights()</code> .
nsim	the number of simulations to run.

Details

The Bivariate Local Moran, like its global counterpart, evaluates the value of x at observation i with its spatial neighbors' value of y. The value of

$$I_i^B$$

is just $x_i * W_{yi}$. Or, in simpler words the local bivariate Moran is the result of multiplying x by the spatial lag of y. Formally it is defined as

$$I_i^B = cx_i \sum_j w_{ij} y_j$$

Value

a data.frame containing two columns `Ib` and `p_sim` containing the local bivariate Moran's I and simulated p-values respectively.

References

[Local Spatial Autocorrelation \(3\): Multivariate Local Spatial Autocorrelation, Luc Anselin](#)

See Also

Other global_moran: [global_moran_bv\(\)](#), [global_moran_perm\(\)](#), [global_moran_test\(\)](#), [global_moran\(\)](#)

Examples

```
x <- guerry_nb$crime_pers
y <- guerry_nb$wealth
nb <- guerry_nb$nb
wt <- guerry_nb$wt
local_moran_bv(x, y, nb, wt)
```

Iosh

Local spatial heteroscedacity

Description

Local spatial heteroscedacity

Usage

```
losh(x, nb, wt, a = 2, ...)
```

```
losh_perm(x, nb, wt, a = 2, nsim = 499, ...)
```

Arguments

x	a numeric vector.
nb	a neighbor list for example created by st_contiguity()
wt	a weights list for example created by st_weights()
a	the exponent applied to the local residuals
...	methods passed to spdep::LOSH
nsim	number of simulations to run

Value

a data.frame with columns

- hi: the observed statistic
- e_hi: the sample average
- var_hi: the sample variance
- z_hi the approximately Chi-square distributed test statistic
- x_bar_i: the local spatially weight mean for observation i
- ei: residuals

Examples

```
nb <- st_contiguity(guerry)
wt <- st_weights(nb)
x <- guerry$crime_pers
losh(x, nb, wt)
losh(x, nb, wt, var_hi = FALSE)
losh_perm(x, nb, wt, nsim = 49)
```

nb_match_test	<i>Local Neighbor Match Test</i>
---------------	----------------------------------

Description

Implements the Local Neighbor Match Test as described in *Tobler's Law in a Multivariate World* (Anselin and Li, 2020).

Usage

```
nb_match_test(
  x,
  nb,
  wt = st_weights(nb),
  k = 10,
  nsim = 499,
  scale = TRUE,
  .method = "euclidian",
  .p = 2
)
```

Arguments

x	a numeric vector or a list of numeric vectors of equal length.
nb	a neighbor list object for example as created by <code>st_contiguity()</code> .
wt	a weights list as created by <code>st_weights()</code> .
k	the number of neighbors to identify in attribute space. Should be the same as number of neighbors provided in <code>st_knn</code> .
nsim	the number of simulations to run for calculating the simulated p-value.
scale	default TRUE. Whether x should be scaled or not. Note that measures should be standardized.
.method	default "euclidian". The distance measure passed to <code>stats::dist()</code> .
.p	default 2. The power of Minkowski distance passed to the p argument in <code>stats::dist()</code> .

Value

a `data.frame` with columns

- `n_shared` (integer): the number of shared neighbors between geographic and attribute space
- `nb_matches` (list): matched neighbor indexes. Each element is an integer vector of same length as the *i*th observation of `n_shared`
- `knn_nb` (list): the neighbors in attribute space
- `probability` (numeric): the geometric probability of observing the number of matches
- `p_sim` (numeric): a folded simulated p-value

Examples

```
library(magrittr)
guerry %>%
  dplyr::transmute(nb = st_knn(geometry, k = 10),
                  nmt = nb_match_test(list(crime_pers, literacy, suicides),
                                     nb, nsim = 999)) %>%
  tidyr::unnest(nmt)
```

 nb_union

Set Operations

Description

Perform set operations element-wise on two lists of equal length.

Usage

```
nb_union(x, y)
```

```
nb_intersect(x, y)
```

```
nb_setdiff(x, y)
```

Arguments

`x` list of class `nb`

`y` list of class `nb`

Details

- `nb_union()` returns the union of elements in each element of `x` and `y`
- `nb_intersect()` returns the intersection of elements in each element of `x` and `y`
- `nb_setdiff()` returns the intersection of elements in each element of `x` and `y`

Value

A list of class nb

Examples

```
nb <- st_contiguity(guerry$geometry)
nb_knn <- st_knn(guerry$geometry, k = 3)
nb_setdiff(nb, nb_knn)
nb_union(nb, nb_knn)
nb_intersect(nb, nb_knn)
```

pairwise_colocation *Pairwise Colocation Quotient*

Description

Calculate the pairwise colocation quotient (CLQ) for two categorical variables using conditional permutation.

Usage

```
pairwise_colocation(A, B, nb, nsim = 99)
```

Arguments

A	a character or factor vector.
B	a character or factor vector.
nb	a neighbors list e.g. created by <code>st_knn()</code> or <code>st_contiguity()</code>
nsim	default 99. An integer representing how many simulations to run for calculating the simulated p-values.

Details**Intuition:**

The pairwise CLQ is used to test if there is a spatial directional association between subcategories of two vectors A and B. Compared to the cross-K metric and the join count statistic, the pairwise CLQ can elucidate the presence of an asymmetric relationship between subcategories of A and B. A and B can either be separate categorical vectors or the same categorical vector.

"The null hypothesis for a CLQ-based analysis is 'given the clustering of the joint population, there is no spatial association between pairs of categorical subsets.'"

Definition:

The pairwise colocation quotient is defined as "the ratio of observed to expected proportions of B among A's nearest neighbors. Formally this is given by $CLQ_{A \rightarrow B} = \frac{C_{A \rightarrow B}/N_A}{N'_B/(N-1)}$ " where

$$C_{A \rightarrow B} = \sum_{i=1}^{N_A} \sum_{j=1}^v \frac{B_{ij}(1,0)}{v}.$$

Inference:

Inference is done using conditional permutation as suggested by Anselin 1995 where a number of replicates are created. The observed values are compared to the replicates and a the simulated p-value is the proportion of cases where the observed is more extreme as compared to replicate. The simulated p-value returns the lower p-value of either tail.

Interpretation:

Given that the CLQ is a ratio of the observed to expected, we interpret values larger than one to mean that there is more colocation than to be expected under the null hypothesis of no spatial association. When the value is smaller than 0, we interpret it to mean that there is less colocation than expected under the null.

Value

A matrix where the rownames are the unique values of A and the column names are the unique values of B and their simulated p-values in the form of $p_{sim\{B\}}$.

Examples

```
A <- guerry$main_city
B <- guerry$region
nb <- st_knn(sf::st_geometry(guerry), 5)
pairwise_colocation(B, A, nb)
pairwise_colocation(B, B, nb, 199)
```

pct_nonzero	<i>Percent Non-zero Neighbors</i>
-------------	-----------------------------------

Description

Calculate the percentage of non-zero neighbors in a neighbor list.

Usage

```
pct_nonzero(nb)
```

Arguments

nb a neighbor list object

Value

a scalar double

Examples

```
nb <- st_contiguity(guerry)
pct_nonzero(nb)
```

recreate_listw	<i>Create a listw object from a neighbors and weight list</i>
----------------	---

Description

Given a neighbor and weight list, create a listw object.

Usage

```
recreate_listw(nb, wt)
```

Arguments

nb	a neighbor list object for example as created by <code>st_contiguity()</code> .
wt	a weights list as created by <code>st_weights()</code> .

Examples

```
recreate_listw(guerry_nb$nb, guerry_nb$wt)
```

set_col	<i>Set columns from geometry to data</i>
---------	--

Description

Set a column from the geometry context of a spacetime object to the data context.

Usage

```
set_col(x, .from_geo, .to_data = .from_geo)
```

```
set_wts(x, .wt_col = "wt")
```

```
set_nbs(x, .nb_col = "nb")
```

Arguments

x	a spacetime object
.from_geo	the name of the column in the geometry context
.to_data	the name of the new variable to create in the data context
.wt_col	the name of the weights column in the geometry context
.nb_col	the name of neighbor column in the geometry context

Details

These functions will reorder the spacetime object to ensure that it is ordered correctly based on the location time columns in the geometry context defined by the `loc_col` and `time_col` attributes respectively.

`set_wts()` and `set_nbs()` create a new column in the data context with the same name as the column in the geometry context. If a different name is desired use `set_col()`

Value

A spacetime object with an active data context and a new column from the geometry context.

Examples

```
df_fp <- system.file("extdata", "bos-ecometric.csv", package = "sfdep")
geo_fp <- system.file("extdata", "bos-ecometric.geojson", package = "sfdep")

# read in data
df <- readr::read_csv(df_fp, col_types = "ccidD")
geo <- sf::read_sf(geo_fp)

# Create spacetime object called `bos`
bos <- spacetime(df, geo,
                .loc_col = ".region_id",
                .time_col = "time_period")
bos <- activate(bos, "geometry")
bos$nb <- st_contiguity(bos)
bos$wt <- st_weights(bos$nb)
bos$card <- st_cardinalities(bos$nb)

set_nbs(bos)
set_wts(bos)
set_col(bos, "card")
set_col(bos, "card", "cardinalities")
```

spacetime

Construct a spacetime object

Description

A spacetime object is a collection of a linked data frame and an sf objects. It can be thought of as geography linked to a table that represents those geographies over one or more time periods.

Usage

```
spacetime(.data, .geometry, .loc_col, .time_col, active = "data")
```

```
new_spacetime(.data, .geometry, .loc_col, .time_col, active = "data")
```

```

validate_spacetime(.data, .geometry, .loc_col, .time_col)

is_spacetime(x, ...)

is.spacetime(x, ...)

```

Arguments

<code>.data</code>	an object with base class <code>data.frame</code> containing location and time identifiers <code>.loc_col</code> and <code>.time_col</code> respectively.
<code>.geometry</code>	an <code>sf</code> object with columns <code>.loc_col</code> and <code>.time_col</code>
<code>.loc_col</code>	the quoted name of the column containing unique location identifiers. Must be present in both <code>.data</code> and <code>.geometry</code> .
<code>.time_col</code>	the quoted name of the column containing time periods must be present <code>.data</code> . See details for more
<code>active</code>	default "data". The object to make active. See activate() for more.
<code>x</code>	an object to test
<code>...</code>	unused

Details

Create a spacetime representation of vector data from a `data.frame` and an `sf` object with `spacetime()`. `.time_col` must be able to be sorted. As such, `.time_col` cannot be a character vector. It must have a base type of `(typeof())` either `double` or `integer`—the case in dates or factors respectively. An edge case exists with `POSIXlt` class objects as these can be sorted appropriately but have a base type of `list`.

[spacetime\(\)](#) is a wrapper around [new_spacetime\(\)](#). Spacetimes are validated before creation with [validate_spacetime\(\)](#).

Check if an object is a spacetime object with [is_spacetime\(\)](#) or [is.spacetime\(\)](#).

Validation

`validate_spacetime()` checks both `.data` and `.geometry` to ensure that the constructed spacetime object meets minimum requirements.:

- `.data` inherits the `data.frame` class
- `.geometry` is an `sf` object
- ensures that `.time_col` is of the proper class
- ensures there are no missing geometries in `.geometry`
- checks for duplicate geometries
- ensures `.loc_col` are the same type in `.data` and `.geometry`
- lastly informs of missing values in additional columns in `.data`

Examples

```
df_fp <- system.file("extdata", "bos-ecometric.csv", package = "sfdep")
geo_fp <- system.file("extdata", "bos-ecometric.geojson", package = "sfdep")

# read in data
df <- readr::read_csv(df_fp, col_types = "ccidD")
geo <- sf::read_sf(geo_fp)

bos <- spacetime(df, geo, ".region_id", "year")
is_spacetime(bos)
bos
```

spatial_gini

Spatial Gini Index

Description

Calculates the spatial Gini index for a given numeric vector and neighbor list. Based on the formula provided Rey and Smith (2013).

Usage

```
spatial_gini(x, nb)
```

Arguments

x a numeric vector without missing values
nb a neighbor list, for example created with `st_contiguity()`

Details

The Gini index is a global measure of inequality based on the Lorenz curve. It ranges between 0 and 1 where 0 is perfect equality and 1 is perfect inequality.

The spatial Gini index decomposes the Gini coefficient based on spatial neighbors.

Value

A data frame with columns:

- G: the Gini index
- NBG: the neighbor composition of the Gini coefficient
- NG: the non-neighbor composition of the Gini coefficient
- SG: the Spatial Gini which is equal to $NG * \frac{1}{G}$

References

doi: [10.1007/s120760120086z](https://doi.org/10.1007/s120760120086z)

Examples

```
nb <- st_contiguity(guerry)
x <- guerry$wealth
spatial_gini(x, nb)
```

spt_update	<i>Update spacetime attributes</i>
------------	------------------------------------

Description

Update's a spacetime object's number of locations and time periods. A spacetime object's attributes are sticky and will not change if subsetted for example by using `dplyr::filter()` or `dplyr::slice()`. Update the locations and times of a spacetime object.

Usage

```
spt_update(x, ...)
```

Arguments

x	a spacetime object
...	unused

std_dev_ellipse	<i>Calculation Standard Deviation Ellipse</i>
-----------------	---

Description

From an sf object containing points, calculate the standard deviational ellipse.

Usage

```
std_dev_ellipse(geometry)
```

Arguments

geometry	an sfc object. If a polygon, uses <code>sf::st_point_on_surface()</code> .
----------	--

Details

The bulk of this function is derived from the archived CRAN package `aspace` version 3.2.0.

Value

An sf object with three columns

- sx: major axis radius in CRS units,
- sy: minor axis radius in CRS units,
- theta: degree rotation of the ellipse.

sf object's geometry is the center mean point.

Examples

```
#' # Make a grid to sample from
grd <- sf::st_make_grid(n = c(1, 1), cellsize = c(100, 100), offset = c(0,0))

# sample 100 points
pnts <- sf::st_sample(grd, 100)
std_dev_ellipse(pnts)
```

std_distance	<i>Calculate standard distance</i>
--------------	------------------------------------

Description

The standard distance of a point pattern is a measure of central tendency. Standard distance measures distance away from the mean center of the point pattern similar to standard deviations.

Usage

```
std_distance(geometry)
```

Arguments

geometry an sfc object. If a polygon, uses [sf::st_point_on_surface\(\)](#).

See Also

Other point-pattern: [center_mean\(\)](#)

Examples

```
# Make a grid to sample from
grd <- sf::st_make_grid(n = c(1, 1), cellsize = c(100, 100), offset = c(0,0))

# sample 100 points
pnts <- sf::st_sample(grd, 100)

# plot points
plot(pnts)
```

```
# calculate standard distance
std_distance(pnts)
```

st_as_edges	<i>Convert to an edge lines object</i>
-------------	--

Description

Given geometry and neighbor and weights lists, create an edge list sf object.

Usage

```
st_as_edges(x, nb, wt)

## S3 method for class 'sf'
st_as_edges(x, nb, wt)

## S3 method for class 'sfc'
st_as_edges(x, nb, wt)
```

Arguments

x	object of class sf or sfc.
nb	a neighbor list. If x is class sf, the unquote named of the column. If x is class sfc, an object of class nb as created from st_contiguity().
wt	optional. A weights list as generated by st_weights(). . If x is class sf, the unquote named of the column. If x is class sfc, the weights list itself.

Details

Creating an edge list creates a column for each i position and j between an observation and their neighbors. You can recreate these values by expanding the nb and wt list columns.

```
library(magrittr)
guerry_nb %>%
  tibble::as_tibble() %>%
  dplyr::select(nb, wt) %>%
  dplyr::mutate(i = dplyr::row_number(), .before = 1) %>%
  tidyr::unnest(c(nb, wt))
#> # A tibble: 420 x 3
#>   i     nb     wt
#>   <int> <int> <dbl>
#> 1     1     36 0.25
#> 2     1     37 0.25
#> 3     1     67 0.25
#> 4     1     69 0.25
#> 5     2      7 0.167
```

```
#> 6      2      49 0.167
#> 7      2      57 0.167
#> 8      2      58 0.167
#> 9      2      73 0.167
#> 10     2      76 0.167
#> # ... with 410 more rows
#> # i Use `print(n = ...)` to see more rows
```

Value

Returns an sf object with edges represented as a LINESTRING.

- from: node index. This is the row position of x.
- to: node index. This is the neighbor value stored in nb.
- i: node index. This is the row position of x.
- j: node index. This is the neighbor value stored in nb.
- wt: the weight value of j stored in wt.

Examples

```
library(magrittr)
guerry %>%
  dplyr::mutate(nb = st_contiguity(geometry),
               wt = st_weights(nb)) %>%
  st_as_edges(nb, wt)
```

st_as_graph	<i>Create an sfnetwork</i>
-------------	----------------------------

Description

Given an sf or sfc object and neighbor and weights lists, create an sfnetwork object.

Usage

```
st_as_graph(x, nb, wt)

## S3 method for class 'sf'
st_as_graph(x, nb, wt)

## S3 method for class 'sfc'
st_as_graph(x, nb, wt)
```

Arguments

x	object of class sf or sfc.
nb	a neighbor list. If x is class sf, the unquote named of the column. If x is class sfc, an object of class nb as created from st_contiguity().
wt	optional. A weights list as generated by st_weights(). . If x is class sf, the unquote named of the column. If x is class sfc, the weights list itself.

See Also

[st_as_nodes\(\)](#) and [st_as_edges\(\)](#)

Examples

```
library(magrittr)

guerry_nb %>%
  st_as_graph(nb, wt)
```

st_as_nodes	<i>Convert to a node point object</i>
-------------	---------------------------------------

Description

Given geometry and a neighbor list, creates an sf object to be used as nodes in an `sfnetworks::sfnetwork()`. If the provided geometry is a polygon, `sf::st_point_on_surface()` will be used to create the node point.

Usage

```
st_as_nodes(x, nb)

## S3 method for class 'sf'
st_as_nodes(x, nb)

## S3 method for class 'sfc'
st_as_nodes(x, nb)
```

Arguments

x	object of class sf or sfc.
nb	a neighbor list. If x is class sf, the unquote named of the column. If x is class sfc, an object of class nb as created from st_contiguity().

Details

`st_as_node()` adds a row i based on the attribute "region.id" in the nb object. If the nb object is created with `sfdep`, then the values will always be row indexes.

Value

An object of class sf with POINT geometry.

Examples

```
library(magrittr)
guerry %>%
  dplyr::transmute(nb = st_contiguity(geometry)) %>%
  st_as_nodes(nb)
```

st_block_nb

Create Block Contiguity for Spatial Regimes

Description

libpysal write that "block contiguity structures are relevant when defining neighbor relations based on membership in a regime. For example, all counties belonging to the same state could be defined as neighbors, in an analysis of all counties in the US."

Source: [libpysal](#)

Usage

```
st_block_nb(regime, id = 1:length(regime), diag = FALSE)
```

Arguments

regime	a column identifying which spatial regime each element of id belongs
id	a column identifying unique observations
diag	default FALSE. If TRUE, includes diagonal element / the self.

Value

An object of class nb. When diag = TRUE the attribute self.included = TRUE.

Examples

```
id <- guerry$code_dept
regime <- guerry$region
st_block_nb(regime, id)
```

st_cardinalties	<i>Calculate neighbor cardinalities</i>
-----------------	---

Description

Identify the cardinality of a neighbor object. Utilizes `spdep::card()` for objects with class `nb`, otherwise returns `lengths(nb)`.

Usage

```
st_cardinalties(nb)
```

Arguments

`nb` A neighbor list object as created by `st_neighbors()`.

Value

an integer vector with the same length as `nb`.

See Also

Other other: [st_nb_lag_cumul\(\)](#), [st_nb_lag\(\)](#)

Examples

```
nb <- st_contiguity(sf::st_geometry(guerry))
st_cardinalties(nb)
```

st_complete_nb	<i>Create Neighbors as Complete Graph</i>
----------------	---

Description

Create a neighbors list where every element is related to every other element. This creates a complete graph.

Usage

```
st_complete_nb(n_elements, diag = FALSE)
```

Arguments

`n_elements` the number of observations to create a neighbors list for
`diag` default FALSE. If TRUE, includes diagonal element / the self.

Value

A neighbors list representing a complete graph.

Examples

```
st_complete_nb(5)
```

st_contiguity	<i>Identify polygon neighbors</i>
---------------	-----------------------------------

Description

Given an sf geometry of type POLYGON or MULTIPOLYGON identify contiguity based neighbors.

Usage

```
st_contiguity(x, queen = TRUE, ...)
```

Arguments

x	an sf or sfc object.
queen	default TRUE. For more see <code>?spdep::poly2nb</code>
...	additional arguments passed to <code>spdep::poly2nb()</code>

Details

Utilizes `spdep::poly2nb()`

Value

a list of class nb

See Also

Other neighbors: `st_dist_band()`, `st_knn()`

Examples

```
# on basic polygons
geo <- sf::st_geometry(guerry)
st_contiguity(geo)

# in a pipe
library(magrittr)
guerry %>%
  dplyr::mutate(nb = st_contiguity(geometry), .before = 1)
```

st_dist_band	<i>Neighbors from a distance band</i>
--------------	---------------------------------------

Description

Creates neighbors based on a distance band. By default, creates a distance band with the maximum distance of k-nearest neighbors where k = 1 (the critical threshold) to ensure that there are no regions that are missing neighbors.

Usage

```
st_dist_band(geometry, lower = 0, upper = critical_threshold(geometry), ...)
```

Arguments

geometry	An sf or sfc object.
lower	The lower threshold of the distance band. It is recommended to keep this as 0.
upper	The upper threshold of the distance band. By default is set to a critical threshold using <code>critical_threshold()</code> ensuring that each region has a minimum of one neighbor.
...	Passed to <code>spdep::dnearneigh()</code> .

Value

a list of class nb

See Also

Other neighbors: [st_contiguity\(\)](#), [st_knn\(\)](#)

Examples

```
geo <- sf::st_geometry(guerry)
st_dist_band(geo, upper = critical_threshold(geo))
```

st_inverse_distance	<i>Calculate inverse distance weights</i>
---------------------	---

Description

From a neighbor list and sf geometry column, calculate inverse distance weight.

Usage

```
st_inverse_distance(nb, geometry, scale = 100, alpha = 1)
```

Arguments

nb	a neighbors list object e.g. created by <code>st_knn()</code> or <code>st_contiguity()</code>
geometry	sf geometry
scale	default 100. a value to scale distances by before exponentiating by alpha
alpha	default 1. Set to 2 for gravity weights.

Details

The inverse distance formula is $w_{ij} = 1/d_{ij}^\alpha$

Value

a list where each element is a numeric vector

See Also

Other weights: `st_kernel_weights()`, `st_nb_dists()`, `st_weights()`

Examples

```
geo <- sf::st_geometry(guerry)
nb <- st_contiguity(geo)
wts <- st_inverse_distance(nb, geo)
head(wts, 3)
wts <- st_inverse_distance(nb, geo, scale = 10000)
head(wts, 3)
```

st_kernel_weights *Calculate Kernel Weights*

Description

Create a weights list using a kernel function.

Usage

```
st_kernel_weights(
  nb,
  geometry,
  kernel = "uniform",
  threshold = critical_threshold(geometry),
  adaptive = FALSE,
  self_kernel = FALSE
)
```

Arguments

nb	an object of class nb e.g. created by st_contiguity() or st_knn() .
geometry	the geometry an sf object.
kernel	One of "uniform", "gaussian", "triangular", "epanechnikov", or "quartic". See kernels for more.
threshold	a scaling threshold to be used in calculating
adaptive	default FALSE. If TRUE uses the maximum neighbor distance for each region as the threshold. Suppresses the threshold argument.
self_kernel	default FALSE. If TRUE applies the kernel function to the observed region.

Details

By default `st_kernel_weight()` utilizes a critical threshold of the maximum neighbor distance using `critical_threshold()`. If desired, the critical threshold can be specified manually. The threshold will be passed to the underlying kernel.

Value

a list where each element is a numeric vector.

See Also

Other weights: [st_inverse_distance\(\)](#), [st_nb_dists\(\)](#), [st_weights\(\)](#)

Examples

```
geometry <- sf::st_geometry(guerry)
nb <- st_contiguity(geometry)
nb <- include_self(nb)
res <- st_kernel_weights(nb, geometry)
head(res, 3)
```

st_knn

Calculate K-Nearest Neighbors

Description

Identifies the k nearest neighbors for given point geometry. If polygon geometry is provided, the centroids of the polygon will be used and a warning will be emitted.

Usage

```
st_knn(x, k = 1, symmetric = FALSE, ...)
```

Arguments

x	an sf or sfc object.
k	number of nearest neighbours to be returned
symmetric	default FALSE. Whether to force output of neighbours to be symmetric.
...	additional arguments to be passed to knearneigh().

Details

This function utilizes `spdep::knearneigh()` and `spdep::knn2nb()`.

Value

a list of class nb

See Also

Other neighbors: `st_contiguity()`, `st_dist_band()`

Examples

```
st_knn(sf::st_geometry(guerry), k = 8)
```

st_lag	<i>Calculate spatial lag</i>
--------	------------------------------

Description

Calculates the spatial lag of a numeric variable given a neighbor and weights list.

Usage

```
st_lag(x, nb, wt, na_ok = FALSE, allow_zero = NULL, ...)
```

Arguments

x	A numeric vector
nb	A neighbor list object as created by <code>st_neighbors()</code> .
wt	A weights list as created by <code>st_weights()</code> .
na_ok	Default FALSE. If, TRUE missing values return a lagged NA.
allow_zero	If TRUE, assigns zero as lagged value to zone without neighbors.
...	See <code>?spdep::lag.listw</code> for more.

Value

a numeric vector with same length as x

See Also

Other stats: [local_moran\(\)](#)

Examples

```
geo <- sf::st_geometry(guerry)
nb <- st_contiguity(geo)
wt <- st_weights(nb)

st_lag(guerry$crime_pers, nb, wt)
```

st_nb_apply

Apply a function to neighbors

Description

Sometimes one may want to create custom lag variables or create some other neighborhood level metric that may not be defined yet. This `st_nb_apply()` enables you to apply a function to each observation's (xi) neighbors (xij).

Usage

```
st_nb_apply(x, nb, wt, .f, suffix = "dbl", ...)
```

Arguments

x	A vector that will be used for neighbor xij values.
nb	A neighbor list object as created by <code>st_neighbors()</code> .
wt	A weights list as created by <code>st_weights()</code> .
.f	A function definition. There are three default objects that can be used inside of the function definition: <ul style="list-style-type: none"> • <code>.xij</code>: neighbor values of x for the ith observation. This is simply the subset of x based on the corresponding nb list values for each element. • <code>.nb</code>: neighbor positions. • <code>.wt</code>: neighbor weights value. If any of these three function arguments are omitted from <code>.f</code> , dots (<code>...</code>) must be supplied.
suffix	The map variant to use. Options are "dbl", "int", "lgl", "chr", "list".
...	arguments to pass to <code>.f</code>

Details

The below example calculates the spatial lag using `st_nb_apply()` and `st_lag()` to illustrate how we can apply functions to neighbors.

Currently questioning the use case. `find_xj()` is now exported and may negate the need for this function.

Value

a vector or list of with same length as x.

Examples

```
library(magrittr)
guerry %>%
  dplyr::transmute(
    nb = st_contiguity(geometry),
    wt = st_weights(nb),
    lag_apply = st_nb_apply(
      crime_pers, nb, wt,
      .f = function(.xij, .wt, ...) sum(.xij *.wt)
    ),
    lag = st_lag(crime_pers, nb, wt)
  )
```

 st_nb_dists

Calculate neighbor distances

Description

From an nb list and point geometry, return a list of distances for each observation's neighbors list.

Usage

```
st_nb_dists(x, nb, longlat = NULL)
```

Arguments

x	an object of class <code>sfc</code> .
nb	a neighbor list for example created by <code>st_contiguity()</code>
longlat	TRUE if point coordinates are longitude-latitude decimal degrees, in which case distances are measured in kilometers. See <code>?spdep::nbdists()</code> for more.

Details

Utilizes `spdep::nbdists()` for distance calculation.

Value

a list where each element is a numeric vector.

See Also

Other weights: `st_inverse_distance()`, `st_kernel_weights()`, `st_weights()`

Examples

```
geo <- sf::st_geometry(guerry)
nb <- st_contiguity(geo)
dists <- st_nb_dists(geo, nb)

head(dists)
```

`st_nb_lag`*Pure Higher Order Neighbors*

Description

Identify higher order neighbors from a neighbor list. order must be greater than 1. When order equals 2 then the neighbors of the neighbors list is returned and so forth. See [Anselin's slides](#) for an example.

Usage

```
st_nb_lag(nb, order)
```

Arguments

nb	A neighbor list object as created by <code>st_contiguity()</code> .
order	The order of neighbors.

Details

Utilizes `spdep::nblag()`

Value

a list of class nb

See Also

Other other: `st_cardinalties()`, `st_nb_lag_cumul()`

Examples

```
nb <- st_contiguity(sf::st_geometry(guerry))
st_nb_lag(nb, 3)
```

st_nb_lag_cumul	<i>Encompassing Higher Order Neighbors</i>
-----------------	--

Description

Creates an encompassing neighbor list of the order specified. For example, if the order is 2 the result contains both 1st and 2nd order neighbors.

Usage

```
st_nb_lag_cumul(nb, order)
```

Arguments

nb	A neighbor list object as created by <code>st_contiguity()</code> .
order	The order of neighbors.

Details

Utilizes `spdep::nblag_cumul()`

Value

a list of class nb

See Also

Other other: `st_cardinalties()`, `st_nb_lag()`

Examples

```
nb <- st_contiguity(sf::st_geometry(guerry))
st_nb_lag_cumul(nb, 3)
```

st_weights	<i>Calculate spatial weights</i>
------------	----------------------------------

Description

Calculate polygon spatial weights from a nb list. See `spdep::nb2listw()` for further details.

Usage

```
st_weights(nb, style = "W", allow_zero = NULL, ...)
```

Arguments

<code>nb</code>	A neighbor list object as created by <code>st_neighbors()</code> .
<code>style</code>	Default "W" for row standardized weights. This value can also be "B", "C", "U", "minmax", and "S". See <code>spdep::nb2listw()</code> for details.
<code>allow_zero</code>	If TRUE, assigns zero as lagged value to zone without neighbors.
<code>...</code>	additional arguments passed to <code>spdep::nb2listw()</code> .

Details

Under the hood, `st_weights()` creates a `listw` object and then extracts the weights elements from it as the `neighbours` element is already—presumably—already existent in the neighbors list you've already created. `listw` objects are recreated using `recreate_listw()` when calculating other statistics.

Value

a list where each element is a numeric vector

See Also

Other weights: `st_inverse_distance()`, `st_kernel_weights()`, `st_nb_dists()`

Examples

```
library(magrittr)
guerry %>%
  dplyr::mutate(nb = st_contiguity(geometry),
               wt = st_weights(nb),
               .before = 1)

# using geometry column directly
nb <- st_contiguity(guerry$geometry)
wt <- st_weights(nb)
wt[1:3]
```

szero

Global sum of weights

Description

Calculate the global sum of weights

Usage

```
szero(wt)
```

Arguments

`wt` a weights list—i.e. created by `st_weights()`

Value

a scalar double

Examples

```
nb <- st_contiguity(guerry)
wt <- st_weights(nb)
szero(wt)
```

tidyverse

tidyverse methods for spacetime objects

Description

dplyr methods for spacetime objects.

Usage

```
group_by.spacetime(.data, ...)
```

```
mutate.spacetime(.data, ...)
```

Arguments

`.data` a data frame

`...` additional arguments

`wt_as_matrix`

Convert neighbor or weights list to matrix

Description

Given a nb list or weights list, convert them to a matrix.

Usage

```
wt_as_matrix(nb, wt)
```

```
nb_as_matrix(nb)
```

Arguments

nb a neighbor list—i.e. as created by `st_contiguity()`.
wt a weights list—i.e. as created by `st_weights()`

Value

Returns a $n \times n$ matrix

Examples

```
# make a grid
g <- sf::st_make_grid(
  cellsize = c(10, 10),
  offset = c(0, 0),
  n = c(2, 2)
)

# create neighbors
nb <- st_contiguity(g)

# cast to matrix
nb_as_matrix(nb)

# create weights
wt <- st_weights(nb)

# cast as matrix
wt_as_matrix(nb, wt)
```

Index

- * **datasets**
 - guerry, 21
- * **global_c**
 - global_c, 12
 - global_c_perm, 14
 - global_c_test, 15
- * **global_moran**
 - global_moran, 18
 - global_moran_bv, 18
 - global_moran_perm, 19
 - global_moran_test, 20
 - local_moran_bv, 32
- * **neighbors**
 - st_contiguity, 49
 - st_dist_band, 50
 - st_knn, 52
- * **other**
 - st_cardinalities, 48
 - st_nb_lag, 56
 - st_nb_lag_cumul, 57
- * **point-pattern**
 - center_mean, 5
 - std_distance, 43
- * **stats**
 - local_moran, 31
 - st_lag, 53
- * **weights**
 - st_inverse_distance, 50
 - st_kernel_weights, 51
 - st_nb_dists, 55
 - st_weights, 57
- activate (active), 3
- activate(), 40
- active, 3
- as_sf, 4
- as_spacetime (as_sf), 4
- as_spacetime(), 4
- center_mean, 5, 43
- center_median (center_mean), 5
- complete_spacetime_cube, 6
- cond_permute_nb, 7
- critical_threshold, 8
- critical_threshold(), 50
- dplyr::filter(), 42
- dplyr::slice(), 42
- ellipse, 8
- ellipse(), 9
- emerging_hotspot_analysis, 9
- euclidean_median (center_mean), 5
- find_xj, 11
- find_xj(), 54
- global_c, 12, 15
- global_c_perm, 12, 14, 15
- global_c_test, 12, 15, 15
- global_colocation, 13
- global_g_test, 16
- global_jc_perm, 16
- global_jc_test (global_jc_perm), 16
- global_moran, 18, 19–21, 33
- global_moran_bv, 18, 18, 20, 21, 33
- global_moran_perm, 18, 19, 19, 21, 33
- global_moran_test, 18–20, 20, 33
- group_by.spacetime (tidyverse), 59
- guerry, 21
- guerry_nb (guerry), 21
- include_self, 22
- is.spacetime (spacetime), 39
- is.spacetime(), 40
- is_spacetime (spacetime), 39
- is_spacetime(), 40
- is_spacetime_cube, 23
- is_spacetime_cube(), 6
- Kendall::MannKendall(), 10

kernels, 52
 local_c, 24
 local_c_perm, 25
 local_c_perm(local_c), 24
 local_colocation, 26
 local_g, 27
 local_g_perm(local_g), 27
 local_gstar, 28
 local_gstar_perm(local_gstar), 28
 local_jc_bv, 29
 local_jc_uni, 30
 local_moran, 31, 54
 local_moran(), 31
 local_moran_bv, 18–21, 32
 losh, 33
 losh_perm(losch), 33

 mutate.spacetime(tidyverse), 59

 nb_as_matrix(wt_as_matrix), 59
 nb_intersect(nb_union), 35
 nb_match_test, 34
 nb_setdiff(nb_union), 35
 nb_union, 35
 new_spacetime(spacetime), 39
 new_spacetime(), 40

 pairwise_colocation, 36
 pct_nonzero, 37
 pracma::geo_median(), 5

 recreate_listw, 38
 recreate_listw(), 58
 remove_self(include_self), 22

 set_col, 38
 set_col(), 39
 set_nbs(set_col), 38
 set_nbs(), 39
 set_wts(set_col), 38
 set_wts(), 39
 sf::st_point_on_surface(), 5, 42, 43, 46
 sfnetworks::sfnetwork(), 46
 spacetime, 3, 39
 spacetime(), 40
 spatial_gini, 41
 spdep::geary.mc(), 14
 spdep::globalG.test(), 16
 spdep::knearest(), 53
 spdep::knn2nb(), 53
 spdep::localC, 25
 spdep::localC_perm, 25
 spdep::localC_perm(), 24
 spdep::localG(), 27, 28
 spdep::localG_perm(), 27, 28
 spdep::localmoran_perm(), 31
 spdep::LOSH, 33
 spdep::moran(), 18
 spdep::moran.mc(), 15, 20, 21
 spdep::nb2listw(), 57, 58
 spdep::nblag(), 56
 spdep::nblag_cumul(), 57
 spdep::poly2nb(), 49
 spt_update, 42
 st_as_edges, 44
 st_as_edges(), 46
 st_as_graph, 45
 st_as_nodes, 46
 st_as_nodes(), 46
 st_as_sf(), 4
 st_block_nb, 47
 st_cardinalties, 48, 56, 57
 st_complete_nb, 48
 st_contiguity, 49, 50, 53
 st_contiguity(), 11, 13, 22, 26, 33, 36, 41, 51, 52, 55
 st_dist_band, 49, 50, 53
 st_ellipse(ellipse), 8
 st_ellipse(), 9
 st_inverse_distance, 50, 52, 55, 58
 st_kernel_weights, 51, 51, 55, 58
 st_kernel_weights(), 26
 st_knn, 34, 49, 50, 52
 st_knn(), 11, 13, 26, 36, 51, 52
 st_lag, 32, 53
 st_lag(), 54
 st_nb_apply, 54
 st_nb_apply(), 54
 st_nb_dists, 51, 52, 55, 58
 st_nb_lag, 48, 56, 57
 st_nb_lag_cumul, 48, 56, 57
 st_weights, 51, 52, 55, 57
 st_weights(), 33, 58
 stats::dist(), 34
 std_dev_ellipse, 42
 std_distance, 5, 43
 szero, 58

tally_jc (global_jc_perm), 16
tidyverse, 59

validate_spacetime (spacetime), 39
validate_spacetime(), 23, 40

wt_as_matrix, 59