

Package ‘starter’

November 24, 2021

Title Starter Kit for New Projects

Version 0.1.8

Description Get started with new projects by dropping a skeleton of a new project into a new or existing directory, initialise git repositories, and create reproducible environments with the 'renv' package. The package allows for dynamically named files, folders, file content, as well as the functionality to drop individual template files into existing projects.

License AGPL (>= 3)

URL <https://github.com/ddsjoberg/starter>,
<https://www.danieldsjoberg.com/starter/index.html>

BugReports <https://github.com/ddsjoberg/starter/issues>

Depends R (>= 3.4)

Imports dplyr (>= 1.0.7), fs (>= 1.5.0), gert (>= 1.4.1), glue (>= 1.4.2), here (>= 1.0.1), purrr (>= 0.3.4), R.utils (>= 2.11.0), readr (>= 2.0.1), renv (>= 0.14.0), rlang (>= 0.4.11), stringr (>= 1.4.0), tibble (>= 3.1.4), usethis (>= 2.0.1)

Suggests covr (>= 3.5.1), knitr (>= 1.34), pkgdown (>= 1.6.1), rmarkdown (>= 2.11), spelling (>= 2.2), testthat (>= 3.0.4)

VignetteBuilder knitr

Config/testthat/edition 3

Encoding UTF-8

Language en-US

RoxygenNote 7.1.2

NeedsCompilation no

Author Daniel D. Sjoberg [aut, cre] (<<https://orcid.org/0000-0003-0862-2018>>)

Maintainer Daniel D. Sjoberg <danield.sjoberg@gmail.com>

Repository CRAN

Date/Publication 2021-11-23 23:20:02 UTC

R topics documented:

create_project	2
create_symlink	3
use_project_file	4

Index	6
--------------	----------

create_project	<i>Start a new project</i>
----------------	----------------------------

Description

Creates a directory with the essential files for a new project. The function can be used on existing project directories as well. Existing files will *not* be overwritten; rather, the user will be prompted whether to replace the existing file with the template file.

Usage

```
create_project(
  path,
  path_data = NULL,
  template = "default",
  git = TRUE,
  renv = TRUE,
  symlink = git,
  overwrite = NA,
  open = interactive()
)
```

Arguments

path	A path. If it exists, it is used. If it does not exist, it is created.
path_data	A path. The directory where the secure data exist. Default is NULL. When supplied, a symbolic link to data folder will be created.
template	A project template. See vignette for details.
git	Logical indicating whether to create Git repository. Default is TRUE. When NA, user will be prompted whether to initialise Git repo.
renv	Logical indicating whether to add renv to a project. Default is TRUE. When NA user is asked interactively for preference.
symlink	Logical indicating whether to place a symbolic link to the location in path_data=. Default is to place the symbolic link if the project is a git repository.
overwrite	Logical indicating whether to overwrite existing files if they exist. Options are TRUE, FALSE, and NA (aka ask interactively). Default is NA
open	Logical indicating whether to open new project in fresh RStudio session

Value

NULL, places project template in new or existing directory

Personalized Template

Users can create a personalized project template. Check out the [vignette](#) for step by step instructions.

Author(s)

Daniel D. Sjoberg

See Also

[use_project_file\(\)](#)

[Vignette for create_project\(\)](#)

Examples

```
# specifying project folder location (folder does not yet exist)
project_path <- fs::path(tempdir(), "My Project Folder")

# creating folder where secure data would be stored (typically will be a network drive)
secure_data_path <- fs::path(tempdir(), "secure_data")
fs::dir_create(secure_data_path)

# creating new project folder
create_project(project_path, path_data = secure_data_path)
```

create_symlink

Establish symbolic link between folders

Description

The `starter_symlink()` function is an OS agnostic function that creates symbolic links between two folders. The function is, at its core, a wrapper for the `R.utils::createLink()` function with opinionated defaults. The function must be called in an environment where the working directory is known (e.g. using `*.Rproj`, `setwd()`, etc.).

Usage

```
create_symlink(to, name = "secure_data", ...)
```

Arguments

to	target file or directory to which the shortcut should point to.
name	symbolic link folder name. Default folder name is "secure_data"
...	Arguments passed on to R.utils::createLink

Details

A symbolic link is a special kind of file that points to another file/folder. A symbolic link does not contain the data in the target file. It simply points to another entry somewhere in the file system. This allows symbolic links to link to directories or files on remote network locations. Depending on your operating system, a link may not establish if the originating path is a network drive.

Value

NULL, Places the path or pathname to the link.

Author(s)

Daniel D. Sjoberg

See Also

[R.utils::createLink\(\)](#)

Examples

```
# only run fn interactively, will place symbolic link in current working dir
if (interactive()) {
  # Using `starter_symlink()` to establish a symbolic link to a
  # mapped networked data folder.
  # The default name of the symlink folder is 'secure_data'
  create_symlink("0:/Outcomes/Project Folder/Data")
}
```

use_project_file	<i>Write a template file</i>
------------------	------------------------------

Description

Rather than using `create_project()` to start a new project folder, you may use `use_project_file()` to write a single file from any project template. The functions `use_project_gitignore()` and `use_project_readme()` are shortcuts for `use_project_file("gitignore")` and `use_project_file("readme")`.

Usage

```
use_project_file(  
  name = NULL,  
  filename = NULL,  
  template = NULL,  
  open = interactive()  
)  
  
use_project_gitignore(filename = NULL, template = NULL)  
  
use_project_readme(filename = NULL, template = NULL)
```

Arguments

name	Name of file to write. Not sure of the files available to you? Run the function without specifying a name, and all files available within the template will print.
filename	Optional argument to specify the name of the file to be written. Paths/filename is relative to project base (e.g. here: :here())
template	A project template. See vignette for details.
open	If TRUE, opens the new file.

Value

NULL, places single template file in current working directory

See Also

[create_project\(\)](#)
[Vignette for create_project\(\)](#)

Examples

```
# only run fn interactively, will place files in current working dir  
if (interactive()) {  
  # create gitignore file  
  use_project_file("gitignore")  
  use_project_gitignore()  
  
  # create README.md file  
  use_project_file("readme")  
  use_project_readme()  
}
```

Index

`create_project`, [2](#)
`create_project()`, [5](#)
`create_symlink`, [3](#)

`R.utils::createLink`, [4](#)
`R.utils::createLink()`, [4](#)

`use_project_file`, [4](#)
`use_project_file()`, [3](#)
`use_project_gitignore`
 (`use_project_file`), [4](#)
`use_project_readme` (`use_project_file`), [4](#)